

Network Working Group
Request for Comments: 3456
Category: Standards Track

B. Patel
Intel Corp
B. Aboba
Microsoft
S. Kelly
Airespace
V. Gupta
Sun Microsystems, Inc.
January 2003

Dynamic Host Configuration Protocol (DHCPv4)
Configuration of IPsec Tunnel Mode

Status of this Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Copyright (C) The Internet Society (2003). All Rights Reserved.

Abstract

This memo explores the requirements for host configuration in IPsec tunnel mode, and describes how the Dynamic Host Configuration Protocol (DHCPv4) may be leveraged for configuration. In many remote access scenarios, a mechanism for making the remote host appear to be present on the local corporate network is quite useful. This may be accomplished by assigning the host a "virtual" address from the corporate network, and then tunneling traffic via IPsec from the host's ISP-assigned address to the corporate security gateway. In IPv4, DHCP provides for such remote host configuration.

Table of Contents

1. Introduction.....	2
1.1 Terminology.....	2
1.2 Requirements Language.....	3
2. IPsec tunnel mode configuration requirements.....	3
2.1 DHCP configuration evaluation.....	3
2.2 Summary.....	4
3. Scenario overview.....	4
3.1 Configuration walk-through.....	5
4. Detailed description.....	6
4.1 DHCPDISCOVER message processing.....	6
4.2 DHCP Relay behavior.....	9
4.3 DHCPREQUEST message processing.....	10
4.4 DHCPACK message processing.....	10
4.5 Configuration policy.....	11
5. Security Considerations.....	11
6. IANA Considerations.....	12
7. Intellectual Property Statement.....	12
8. References.....	13
8.1 Normative References.....	13
8.2 Informative References.....	13
9. Acknowledgments.....	14
Appendix - IKECFG evaluation.....	15
Authors' Addresses.....	17
Full Copyright Statement	18

1. Introduction

In many remote access scenarios, a mechanism for making the remote host appear to be present on the local corporate network is quite useful. This may be accomplished by assigning the host a "virtual" address from the corporate network, and then tunneling traffic via IPsec from the host's ISP-assigned address to the corporate security gateway. In IPv4, Dynamic Host Configuration Protocol (DHCP) [3] provides for such remote host configuration. This document explores the requirements for host configuration in IPsec tunnel mode, and describes how DHCPv4 may be leveraged for configuration.

1.1. Terminology

This document uses the following terms:

DHCP client

A DHCP client or "client" is an Internet host using DHCP to obtain configuration parameters such as a network address.

DHCP server

A DHCP server or "server" is an Internet host that returns configuration parameters to DHCP clients.

1.2. Requirements language

In this document, the key words "MAY", "MUST", "MUST NOT", "optional", "recommended", "SHOULD", and "SHOULD NOT", are to be interpreted as described in [1].

2. IPsec tunnel mode configuration requirements

As described in [21], the configuration requirements of a host with an IPsec tunnel mode interface include the need to obtain an IPv4 address and other configuration parameters appropriate to the class of host. In addition to meeting the basic requirements [21], the following additional capabilities may be desirable:

- a. integration with existing IPv4 address management facilities
- b. support for address pool management
- c. reconfiguration when required
- d. support for fail-over
- e. maintaining security and simplicity in the IKE implementation.
- f. authentication where required

2.1. DHCP configuration evaluation

Leveraging DHCP for configuration of IPsec tunnel mode meets the basic requirements described in [21]. It also provides the additional capabilities described above.

Basic configuration

In IPv4, leveraging DHCPv4 [3] for the configuration of IPsec tunnel mode satisfies the basic requirements described in [21]. Since the required configuration parameters described in [21] are a subset of those already supported in DHCPv4 options [4], no new DHCPv4 options are required, and no modifications to DHCPv4 [3] are required.

Address management integration

Since DHCPv4 is widely deployed for address management today, reuse of DHCPv4 for IPsec tunnel mode address management enables compatibility and integration with existing addressing implementations and IPv4 address management software.

Address pool management

As described in [18], DHCPv4 implementations support conditional behavior so that the address and configuration parameters assigned can be dependent on parameters included in the DHCPDISCOVER. This makes it possible for the security gateway to ensure that the remote host receives an IP address assignment from the appropriate address pool, such as via the User Class option, described in [16].

Reconfiguration

DHCP supports the concept of configuration leases, and there is a proposal for handling forced reconfiguration [14].

Fail-over support

When leveraging DHCPv4, configuration and addressing state is kept on the DHCP server, not within the IKE implementation. As a result, the loss of a tunnel server does not result in the loss of configuration and addressing state, thus making it easier to support fail-over [12].

Security and simplicity

Leveraging DHCPv4 also makes it easier to maintain security in the IKE implementation since no IKE modifications are required to support configuration.

Authentication

Where DHCPv4 authentication [5] is required, this can be supported on an IPsec tunnel mode interface as it would be on any other interface.

2.2. Summary

As described, DHCPv4 [3] meets the IPsec tunnel mode configuration requirements [21], as well as providing additional capabilities. As described in the Appendix, IKECFG [13] does not meet the basic requirements, nor does it provide the additional capabilities. As a result, DHCPv4 is the superior alternative for IPsec tunnel mode configuration.

3. Scenario overview

IPsec [2], [6]-[9] is a protocol suite defined to secure communication at the network layer between communicating peers. Among many applications enabled by IPsec, a useful application is to connect a remote host to a corporate intranet via a security gateway, using IPsec tunnel mode. This host is then configured in such a manner so as to provide it with a virtual presence on the internal network. This is accomplished in the following manner:

3.1. Configuration walk-through

The configuration of the intranet interface of the IPsec tunnel mode host is accomplished in the following steps:

- a. The remote host establishes an IKE security association with the security gateway in a main mode or aggressive mode exchange. This IKE SA then serves to secure additional quick mode IPsec SAs.
- b. The remote host establishes a DHCP SA with the IPsec tunnel mode server in a quick mode exchange. The DHCP SA is an IPsec tunnel mode SA established to protect initial DHCPv4 traffic between the security gateway and the remote host. The DHCP SA MUST only be used for DHCP traffic. The details of how this SA is set up are described in Section 4.1.
- c. DHCP messages are sent back and forth between the remote host and the DHCPv4 server. The traffic is protected between the remote host and the security gateway using the DHCP SA established in step b. After the DHCP conversation completes, the remote host's intranet interface obtains an IP address as well as other configuration parameters.
- d. The remote host MAY request deletion of the DHCP SA since future DHCP messages will be carried over a new IPsec tunnel. Alternatively, the remote host and the security gateway MAY continue to use the same SA for all subsequent traffic by adding temporary SPD selectors in the same manner as is provided for name ID types in [2].
- e. If a new IPsec tunnel is required, the remote host establishes a tunnel mode SA to the security gateway in a quick mode exchange. In this case, the new address assigned via DHCPv4 SHOULD be used in the quick mode ID.

At the end of the last step, the remote host is ready to communicate with the intranet using an IPsec tunnel. All the IP traffic (including future DHCPv4 messages) between the remote host and the intranet are now tunneled over this IPsec tunnel mode SA.

Since the security parameters used for different SAs are based on the unique requirements of the remote host and the security gateway, they are not described in this document. The mechanisms described here work best when the VPN is implemented using a virtual interface.

4. Detailed description

This section provides details relating to the messages exchanged during the setup and teardown of the DHCP SAs.

4.1. DHCPDISCOVER message processing

The events begin with the remote host intranet interface generating a DHCPDISCOVER message. Details are described below:

FIELD	OCTETS	DESCRIPTION
op	1	Message op code / message type. 1 = BOOTREQUEST, 2 = BOOTREPLY
htype	1	Hardware address type. Set to value 31, signifying an IPsec tunnel mode virtual interface.
hlen	1	Hardware address length
hops	1	Client sets to zero, optionally used by relay agents when booting via a relay agent.
xid	4	Transaction ID, a random number chosen by the client, used by the client and server to associate messages and responses between a client and a server.
secs	2	Filled in by client, seconds elapsed since client began address acquisition or renewal process.
flags	2	Flags. Broadcast bit MUST be set to zero.
ciaddr	4	Client IP address; only filled in if client is in BOUND, RENEW or REBINDING state.
yiaddr	4	'your' (client) IP address.
siaddr	4	IP address of next server to use in bootstrap; returned in DHCPOFFER, DHCPACK by server.
giaddr	4	Security gateway interface IPv4 address, used in booting via a relay agent.
chaddr	16	Client hardware address. Should be unique.
sname	64	Optional server host name, null terminated string.
file	128	Boot file name, null terminated string; "generic" name or null in DHCPDISCOVER, fully qualified directory-path name in DHCPOFFER.
options	var	Optional parameters field.

Table 1: Description of fields in the DHCP message

The htype value is set to the value 31, signifying a virtual IPsec tunnel mode interface, in order to enable the DHCP server to differentiate VPN from non-VPN requests. The chaddr field of the DHCPDISCOVER MUST include an identifier unique to the virtual subnet. The client MUST use the same chaddr field in all subsequent messages within the same DHCPv4 exchange. In addition, the chaddr SHOULD be

persistent between reboots so that the DHCP server will be able to re-assign the same address if desired.

The hlen and chaddr fields SHOULD be determined as follows:

- a. If one or more LAN interfaces are available, the hlen and chaddr fields SHOULD be determined from the active LAN interface with the lowest interface number. If no active LAN interface is available, then the parameters SHOULD be determined from the LAN interface with the lowest interface number. This enables the chaddr to be persistent between reboots, as long as the LAN interface hardware is not removed.
- b. If there is no LAN interface, the chaddr field SHOULD be determined by concatenating x'4000', the IPv4 address of the interface supplying network connectivity, and an additional octet. The x'4000' value indicates a locally administered unicast MAC address, thus guaranteeing that the constructed chaddr value will not conflict with a globally assigned value.

The additional octet (which MAY represent an interface number) SHOULD be persistent between reboots, so that the chaddr value will be persistent across reboots if the assigned IPv4 address remains consistent.

If the above prescription is followed, then the chaddr will always be unique on the virtual subnet provided that the remote host only brings up a single tunnel to the security gateway. Where a LAN interface is available, the chaddr will be globally unique. When a non-LAN interface is available and a unique Internet address is assigned to the remote host, the chaddr will also be globally unique. Where a private IP address [22] is assigned to a non-LAN interface, it will not be globally unique. However, in this case packets will not be routed back and forth between the remote host and the security gateway unless the external network and corporate network have a consistent addressing plan. In this case the private IP address assigned to the remote host will be unique on the virtual subnet.

For use in DHCPv4 configuration of IPsec tunnel mode, the client-identifier option MUST be included, MUST be unique within the virtual subnet and SHOULD be persistent across reboots. Possibilities include:

- a. The htype/chaddr combination. If assigned as described above, this will be unique on the virtual subnet. It will be persistent across reboots for a LAN interface. If a non-LAN interface is used, it may not be persistent across reboots if the assigned IP address changes.

- b. The machine FQDN concatenated with an interface number. Assuming that the machine FQDN does not conflict with that of another machine, this will be unique on the virtual subnet as well as persistent across reboots.
- c. The user NAI concatenated with an interface number. Assuming that the user is only connected to the VPN at one location, this will be unique on the subnet as well as persistent across reboots.

In order to deliver the DHCPDISCOVER packet from the intranet interface to the security gateway, an IKE Phase 1 SA is established between the Internet interface and the security gateway. A phase 2 (quick mode) DHCP SA tunnel mode SA is then established. The key lifetime for the DHCP SA SHOULD be on the order of minutes since it will only be temporary. The remote host SHOULD use an IDci payload of 0.0.0.0/UDP/port 68 in the quick mode exchange. The security gateway will use an IDcr payload of its own Internet address/UDP/port 67. The DHCP SA is established as a tunnel mode SA with filters set as follows:

From remote host to security gateway: Any to Any, destination: UDP port 67

From security gateway to remote host: Any to Any, destination: UDP port 68

Note that these filters will work not only for a client without configuration, but also with a client that has previously obtained a configuration lease, and is attempting to renew it. In the latter case, the DHCP SA will initially be used to send a DHCPREQUEST rather than a DHCPDISCOVER message. The initial DHCPv4 message (DHCPDISCOVER or DHCPREQUEST) is then tunneled to the security gateway using the tunnel mode SA. Note that since the DHCPDISCOVER packet has a broadcast address destination, the IPsec implementations on both the remote host and the security gateway must be capable of handling this.

4.2. DHCP Relay behavior

While other configurations are possible, typically the DHCPv4 server will not reside on the same machine as the security gateway, which will act as a DHCPv4 relay, inserting its address in the "giaddr" field. In this case, the security gateway relays packets between the client and the DHCPv4 server, but does not request or renew addresses on the client's behalf. While acting as a DHCP Relay, the security gateway MAY implement DHCP Relay load balancing as described in [19].

Since DHCP Relays are stateless, the security gateway SHOULD insert appropriate information in the DHCP message prior to forwarding to one or more DHCP servers. This enables the security gateway to route the corresponding DHCPOFFER message(s) back to the remote host on the correct IPsec tunnel, without having to keep state gleaned from the DISCOVER, such as a table of the xid, chaddr and tunnel.

If the security gateway maintains a separate subnet for each IPsec tunnel, then this can be accomplished by inserting the appropriate interface address in the giaddr field. Alternatively, the security gateway can utilize the DHCP Relay Agent Information Option [17]. In this case, the virtual port number of the tunnel is inserted in the Agent Circuit ID Sub-option (sub-option code 1).

To learn the internal IP address of the client in order to route packets to it, the security gateway will typically snoop the yiaddr field within the DHCPACK and plumb a corresponding route as part of DHCP Relay processing.

Where allocating a separate subnet for each tunnel is not feasible, and the DHCP server does not support the Relay Agent Information Option, stateless Relay Agent behavior will not be possible. In such cases, implementations MAY devise a mapping between the xid, chaddr, and tunnel in order to route the DHCP server response to the appropriate tunnel endpoint. Note that this is particularly undesirable in large VPN servers where the resulting state will be substantial.

4.3. DHCPREQUEST message processing

After the Internet interface has received the DHCPOFFER message, it forwards this to the intranet interface after IPsec processing. The intranet interface then responds by creating a DHCPREQUEST message, which is tunneled to security gateway using the DHCP SA.

4.4. DHCPACK message processing

The DHCPv4 server then replies with a DHCPACK or DHCPNAK message, which is forwarded down the DHCP SA by the security gateway. The remote host Internet interface then forwards the DHCPACK or DHCPNAK message to the intranet interface after IPsec processing.

After processing of the DHCPACK, the intranet interface is configured and the Internet interface can establish a new IPsec tunnel mode SA to the security gateway. The remote host may now delete the DHCP tunnel mode SA. All future DHCP messages sent by the client, including DHCPREQUEST, DHCPINFORM, DHCPDECLINE, and DHCPRELEASE messages will use the newly established VPN SA. Similarly, all DHCP

messages subsequently sent by the DHCPv4 server will be forwarded by the security gateway (acting as a DHCP Relay) using the IPsec tunnel mode SA, including DHCPOFFER, DHCPACK, and DHCPNAK messages.

It SHOULD be possible to configure the remote host to forward all Internet-bound traffic through the tunnel. While this adds overhead to round-trips between the remote host and the Internet, it provides some added security in return for this, in that the corporate security gateway may now filter traffic as it would if the remote host were physically located on the corporate network.

4.5. Configuration policy

Several mechanisms can be used to enable remote hosts to be assigned different configurations. For example, clients may use the User Class Option [16] to request various configuration profiles. The DHCPv4 server may also take a number of other variables into account, including the htype/chaddr; the host name option; the client-identifier option; the DHCP Relay Agent Information option [17]; the vendor-class-identifier option; the vendor-specific information option; or the subnet selection option [15].

Conditional configuration of clients, described in [18], can be used to solve a number of problems, including assignment of options based on the client operating system; assignment of groups of clients to address ranges subsequently used to determine quality of service; allocation of special address ranges for remote hosts; assignment of static routes to clients [20], etc. As noted in the security considerations, these mechanisms, while useful, do not enhance security since they can be evaded by a remote host choosing its own IP address.

5. Security Considerations

This protocol is secured using IPsec, and as a result the DHCP packets flowing between the remote host and the security gateway are authenticated and integrity protected.

However, since the security gateway acts as a DHCP Relay, no protection is afforded the DHCP packets in the portion of the path between the security gateway and the DHCP server, unless DHCP authentication is used.

Note that authenticated DHCP cannot be used as an access control mechanism. This is because a remote host can always set its own IP address and thus evade any security measures based on DHCP authentication.

As a result, the assigned address MUST NOT be depended upon for security. Instead, the security gateway can use other techniques such as instantiating packet filters or quick mode selectors on a per-tunnel basis.

As described in [17], a number of issues arise when forwarding DHCP client requests from untrusted sources. These include DHCP exhaustion attacks, and spoofing of the client identifier option or client MAC address. These issues can be partially addressed through use of the DHCP Relay Information Option [17].

6. IANA Considerations

This document requires that an htype value be allocated for use with IPsec tunnel mode, as described in section 4.1. Note that DHCP relies on the arp-parameters registry for definition of both the hrd parameter in ARP and the htype parameter in BOOTP/DHCP. As a result, an assignment in the arp-parameters registry is required, even though IPsec-DHCP will never use that parameter for ARP purposes, since conceptually BOOTP/DHCP and ARP share the arp-parameters registry.

This document does not create any new number spaces for IANA administration.

7. Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in BCP-11. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

8. References

8.1 Normative References

- [1] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [2] Atkinson, R. and S. Kent, "Security Architecture for the Internet Protocol", RFC 2401, November 1998.
- [3] Droms, R., "Dynamic Host Configuration Protocol", RFC 2131, March 1997.
- [4] Alexander, S. and R. Droms, "DHCP Options and BOOTP Vendor Extensions", RFC 2132, March 1997.
- [5] Droms, R. and W. Arbaugh, "Authentication for DHCP Messages", RFC 3118, June 2001.
- [6] Kent, S. and R. Atkinson, "IP Authentication Header", RFC 2402, November 1998.
- [7] Kent, S. and R. Atkinson, "IP Encapsulating Security Payload (ESP)", RFC 2406, November 1998.
- [8] Piper, D., "The Internet IP Security Domain of Interpretation of ISAKMP", RFC 2407, November 1998.
- [9] Harkins, D. and D. Carrel, "The Internet Key Exchange (IKE)", RFC 2409, November 1998.

8.2 Informative References

- [10] McGregor, G., "The PPP Internet Protocol Control Protocol (IPCP)", RFC 1332, May 1992.
- [11] Cobb, S., "PPP Internet Protocol Control Protocol Extensions for Name Server Addresses", RFC 1877, December 1995.
- [12] Droms, R., Kinnear, K., Stapp, M., Volz, B., Gonczi, S., Rabil, G., Dooley, M. and A. Kapur, "DHCP Failover Protocol", Work in Progress.
- [13] Dukes, D. and R. Pereira, "The ISAKMP Configuration Method", Work in Progress.
- [14] T'Joens, Y., Hublet, C. and P. De Schrijver, "DHCP reconfigure extension", RFC 3203, December 2001.

- [15] Waters, G., "The IPv4 Subnet Selection Option for DHCP", RFC 3011, November 2000.
- [16] Stump, G., Droms, R., Gu, Y., Vyaghrapuri, R., Demirtjis, A., Beser, B. and J. Privat, "The User Class Option for DHCP", RFC 3004, November 2000.
- [17] Patrick, M., "DHCP Relay Agent Information Option", RFC 3046, January 2001.
- [18] Droms, R., and Lemon, T., The DHCP Handbook, Macmillan, Indianapolis, Indiana, 1999.
- [19] Volz, B., Gonczi, S., Lemon, T. and R. Stevens, "DHC Load Balancing Algorithm", RFC 3074, February 2001.
- [20] Lemon, T., Cheshire, S. and B. Volz, "The Classless Static Route Option for Dynamic Host Configuration Protocol (DHCP)", RFC 3442, December 2002.
- [21] Kelly, S. and S. Ramamoorthi, "Requirements for IPsec Remote Access Scenarios", RFC 3457, January 2003.
- [22] Rekhter, Y., Moskowitz, B., Karrenberg, D., G. de Groot, and E. Lear, "Address Allocation for Private Internets", BCP 5, RFC 1918, February 1996.
- [23] Atkinson, R., "Key Exchange Delegation Record for the DNS", RFC 2230, November 1997.
- [24] Gulbrandsen, A., Vixie, P. and L. Esibov, "A DNS RR for specifying the location of services (DNS SRV)", RFC 2782, February 2000.

9. Acknowledgments

This document has been enriched by comments from John Richardson and Prakash Iyer of Intel, Gurdeep Pall and Peter Ford of Microsoft.

Appendix - IKECFG evaluation

Alternatives to DHCPv4, such as ISAKMP CFG, described in [13], do not meet the basic requirements described in [21], nor do they provide the additional capabilities of DHCPv4.

Basic configuration

While ISAKMP CFG can provide for IP address assignment as well as configuration of a few additional parameters such as the DNS server and WINS server addresses, the rich configuration facilities of DHCPv4 are not supported. Past experience with similar configuration mechanisms within PPP IPCP [11] has taught us that it is not viable merely to support minimal configuration. Eventually, either much of the functionality embodied in the DHCPv4 options [4] is duplicated or support for DHCPINFORM [3] will be required.

Address management integration

Since IKECFG is not integrated with existing IP address management facilities, it is difficult to integrate it with policy management services that may be dependent on the user to IP address binding.

Address pool management

IKECFG does not provide a mechanism for the remote host to indicate a preference for a particular address pool. This makes it difficult to support address pool management.

Reconfiguration

IKECFG does not support the concept of configuration leases or reconfiguration.

Fail-over support

Since IKECFG creates a separate pool of address state, it complicates the provisioning of network utility-class reliability, both in the IP address management system and in the security gateways themselves.

Security and simplicity

As past history with PPP IPCP demonstrates, once it is decided to provide non-integrated address management and configuration facilities within IKE, it will be difficult to limit the duplication of effort to address assignment. Instead, it will be tempting to also duplicate the configuration, authentication and fail-over facilities of DHCPv4. This duplication will greatly increase the scope of work, eventually compromising the security of IKE.

Authentication

While IKECFG can support mutual authentication of the IPsec tunnel endpoints, it is difficult to integrate IKECFG with DHCPv4 authentication [5]. This is because the security gateway will not typically have access to the client credentials necessary to issue an DHCPv4 authentication option on the client's behalf.

As a result, security gateways implementing IKECFG typically request allocation of an IP address on their own behalf, and then assign this to the client via IKECFG. Since IKECFG does not support the concept of an address lease, the security gateway will need to do the renewal itself. This complicates the renewal process.

Since RFC 2131 [3] assumes that a DHCPREQUEST will not contain a filled in giaddr field when generated during RENEWING state, the DHCPACK will be sent directly to the client, which will not be expecting it. As a result, it is either necessary for the security gateway to add special code to avoid forwarding such packets, or to wait until REBINDING state. Since [3] does not specify that the giaddr field cannot be filled in when in the REBINDING state, the security gateway may put its own address in the giaddr field when in REBINDING state, thereby ensuring that it can receive the renewal response without treating it as a special case.

Authors' Addresses

Baiju V. Patel
Intel Corp
2511 NE 25th Ave
Hillsboro, OR 97124

Phone: +1 503 712 2303
EMail: baiju.v.patel@intel.com

Bernard Aboba
Microsoft Corporation
One Microsoft Way
Redmond, WA 98052

Phone: +1 425 706 6605
EMail: bernarda@microsoft.com

Scott Kelly
Airespace
110 Nortech Pkwy
San Jose CA 95134 USA

Phone: +1 (408) 941-0500
EMail: scott@hyperthought.com

Vipul Gupta
Sun Microsystems, Inc.
MS UMTV29-235
2600 Casey Avenue
Mountain View, CA 94303

Phone: +1 650 336 1681
EMail: vipul.gupta@sun.com

Full Copyright Statement

Copyright (C) The Internet Society (2003). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.

