

IDR Working Group
Internet-Draft
Obsoletes: 4360 (if approved)
Intended status: Standards Track
Expires: 2 March 2026

S. Sangli
Juniper Networks
N. Kao, Ed.
Individual Contributor
29 August 2025

BGP Extended Communities Attribute
draft-chairs-idr-rfc4360-bis-01

Abstract

This document describes the "extended community" BGP-4 attribute. This attribute provides a mechanism for labeling information carried in BGP-4. These labels can be used to control the distribution of this information, or for other applications.

This document obsoletes [RFC4360].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 2 March 2026.

Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Table of Contents

1. Introduction	2
1.1. Requirements Language	3
2. BGP Extended Communities Attribute	3
3. Defined BGP Extended Community Types	5
3.1. Two-Octet AS Specific Extended Community	5
3.2. IPv4 Address Specific Extended Community	5
3.3. Opaque Extended Community	6
4. Route Target Community	7
5. Route Origin Community	7
6. Operations	8
7. Error Handling	9
8. IANA Considerations	9
9. Security Considerations	11
10. Contributors	11
11. Acknowledgements	11
12. References	12
12.1. Normative References	12
12.2. Informative References	13
Authors' Addresses	13

1. Introduction

The Extended Community Attribute provides a mechanism for labeling information carried in BGP-4 [BGP-4]. It provides two important enhancements over the existing BGP Community Attribute [RFC1997]:

- * An extended range, ensuring that communities can be assigned for a plethora of uses, without fear of overlap.
- * The addition of a Type field provides structure for the community space.

The addition of structure allows the usage of policy based on the application for which the community value will be used. For example, one can filter out all communities of a particular type, or allow only certain values for a particular type of community. It also allows one to specify whether a particular community is transitive or non-transitive across an Autonomous System (AS) boundary. Without structure, this can only be accomplished by explicitly enumerating all community values that will be denied or allowed and passed to BGP speakers in neighboring ASes based on the transitive property.

1.1. Requirements Language


The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

2. BGP Extended Communities Attribute

The Extended Communities Attribute is a transitive optional BGP attribute, with the Type Code 16. The attribute consists of a set of "extended communities". All routes with the Extended Communities attribute belong to the communities listed in the attribute.

Each Extended Community is encoded as an 8-octet quantity, as follows:

- Type Field : 1 or 2 octets
- Value Field : Remaining octets



(*) Present for Extended types only, used for the Value field otherwise.

Type Field:

Two classes of Type Field are introduced: Regular type and Extended type.

The size of Type Field for Regular types is 1 octet, and the size of the Type Field for Extended types is 2 octets.

The value of the high-order octet of the Type Field determines if an extended community is a Regular type or an Extended type. The class of a type (Regular or Extended) is not encoded in the structure of the type itself. The class of a type is specified in the document that defines the type and the IANA registry.

The high-order octet of the Type Field is as shown below:

```

0 1 2 3 4 5 6 7
+---+---+---+---+
| I | T |         |
+---+---+---+---+

```

I - IANA authority bit

Value 0: IANA-assignable type using the "First Come First Serve" policy

Value 1: Part of this Type Field space is for IANA assignable types using either the Standard Action or the Early IANA Allocation policy. The rest of this Type Field space is for Experimental use.

T - Transitive bit

Value 0: The community is transitive across ASes

Value 1: The community is non-transitive across ASes

Remaining 6 bits:

Indicates the structure of the community

Value Field:

The encoding of the Value Field is dependent on the "type" of the community as specified by the Type Field.

Two extended communities are declared equal only when all 8 octets of the community are equal.

The two members in the tuple <Type, Value> should be enumerated to specify any community value. The remaining octets of the community interpreted based on the value of the Type field.

3. Defined BGP Extended Community Types

This section introduces a few extended types and defines the format of the Value Field for those types. The types introduced here provide "templates", where each template is identified by the high-order octet of the extended community Type field, and the lower-order octet (sub-type) is used to indicate a particular type of extended community.

3.1. Two-Octet AS Specific Extended Community

This is an extended type with Type Field composed of 2 octets and Value Field composed of 6 octets.

0										1										2										3									
0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1								
0x00 or 0x40										Sub-Type										Global Administrator																			
										Local Administrator																													

The value of the high-order octet of this extended type is either 0x00 or 0x40. The low-order octet of this extended type is used to indicate sub-types.

The Value Field consists of two sub-fields:

Global Administrator sub-field: 2 octets

This sub-field contains an Autonomous System number assigned by IANA.

Local Administrator sub-field: 4 octets

The organization identified by Autonomous System number in the Global Administrator sub-field can encode any information in this sub-field. The format and meaning of the value encoded in this sub-field should be defined by the sub-type of the community.

3.2. IPv4 Address Specific Extended Community

This is an extended type with Type Field composed of 2 octets and Value Field composed of 6 octets.

```

      0               1               2               3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+-----+-----+-----+-----+-----+-----+-----+-----+
| 0x01 or 0x41 | Sub-Type | Global Administrator |
+-----+-----+-----+-----+-----+-----+-----+-----+
| Global Administrator (cont.) | Local Administrator |
+-----+-----+-----+-----+-----+-----+-----+-----+

```

The value of the high-order octet of this extended type is either 0x01 or 0x41. The low-order octet of this extended type is used to indicate sub-types.

The Value field consists of two sub-fields:

Global Administrator sub-field: 4 octets

This sub-field contains an IPv4 unicast address assigned by one of the Internet registries.

Local Administrator sub-field: 2 octets

The organization that has been assigned the IPv4 address in the Global Administrator sub-field can encode any information in this sub-field. The format and meaning of this value encoded in this sub-field should be defined by the sub-type of the community.

3.3. Opaque Extended Community

This is an extended type with Type Field composed of 2 octets and Value Field composed of 6 octets.

```

      0               1               2               3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+-----+-----+-----+-----+-----+-----+-----+-----+
| 0x03 or 0x43 | Sub-Type | Value |
+-----+-----+-----+-----+-----+-----+-----+-----+
| Value (cont.) |
+-----+-----+-----+-----+-----+-----+-----+-----+

```

The value of the high-order octet of this extended type is either 0x03 or 0x43. The low-order octet of this extended type is used to indicate sub-types.

This is a generic community of extended type. The value of the sub-type that should define the Value Field is to be assigned by IANA.

4. Route Target Community

The Route Target Community identifies one or more routers that may receive a set of routes (that carry this Community) carried by BGP. This is transitive across the Autonomous System boundary.

The Route Target Community is of an extended type.

The value of the high-order octet of the Type field for the Route Target Community can be 0x00 (as defined in Section 3.1), 0x01 (as defined in Section 3.2), or 0x02 (as defined in [RFC5668]). The value of the low-order octet of the Type field for this community is 0x02.

When the value of the high-order octet of the Type field is 0x00 or 0x02, the Local Administrator sub-field contains a number from a numbering space that is administered by the organization to which the Autonomous System number carried in the Global Administrator sub-field has been assigned by an appropriate authority.

When the value of the high-order octet of the Type field is 0x01, the Local Administrator sub-field contains a number from a numbering space that is administered by the organization to which the IP address carried in the Global Administrator sub-field has been assigned by an appropriate authority.

One possible use of the Route Target Community is specified in [RFC4364].

5. Route Origin Community

The Route Origin Community identifies one or more routers that inject a set of routes (that carry this Community) into BGP. This is transitive across the Autonomous System boundary.

The Route Origin Community is of an extended type.

The value of the high-order octet of the Type field for the Route Origin Community can be 0x00 (as defined in Section 3.1), 0x01 (as defined in Section 3.2), or 0x02 (as defined in [RFC5668]). The value of the low-order octet of the Type field for this community is 0x03.

When the value of the high-order octet of the Type field is 0x00 or 0x02, the Local Administrator sub-field contains a number from a numbering space that is administered by the organization to which the Autonomous System number carried in the Global Administrator sub-field has been assigned by an appropriate authority.

When the value of the high-order octet of the Type field is 0x01, the Local Administrator sub-field contains a number from a numbering space that is administered by the organization to which the IP address carried in the Global Administrator sub-field has been assigned by an appropriate authority.

One possible use of the Route Origin Community is specified in [RFC4364].

6. Operations

A BGP speaker may use the Extended Communities attribute to control which routing information it accepts or distributes to its peers.

The Extended Community attribute **MUST NOT** be used to modify the BGP best path selection algorithm in a way that leads to forwarding loops.

A BGP speaker receiving a route that doesn't have the Extended Communities attribute **MAY** append this attribute to the route when propagating it to its peers.

A BGP speaker receiving a route with the Extended Communities attribute **MAY** modify this attribute according to the local policy.

By default if a range of routes is to be aggregated and the resultant aggregates path attributes do not carry the `ATOMIC_AGGREGATE` attribute, then the resulting aggregate should have an Extended Communities path attribute that contains the set union of all the Extended Communities from all of the aggregated routes. The default behavior could be overridden via local configuration, in which case handling the Extended Communities attribute in the presence of route aggregation becomes a matter of the local policy of the BGP speaker that performs the aggregation.

A route may carry both the BGP Communities attribute, as defined in [RFC1997]), and the Extended BGP Communities attribute. In this case, the BGP Communities attribute is handled as specified in [RFC1997], and the Extended BGP Communities attribute is handled as specified in this document.

If a route has non-transitive extended communities, those communities SHOULD NOT be propagated across an Autonomous System boundary and SHOULD be removed from the route. However, non-transitive extended communities SHOULD NOT be removed when advertising the route within the same BGP AS Confederation(as defined in [RFC5065]). As part of configuration or BGP protocol extensions, BGP speakers MAY attach non-transitive extended communities to routes advertised across Autonomous System boundaries.

By default, when a BGP speaker receives routes with non-transitive extended communities across Autonomous System or Confederation Member-AS boundaries, it MUST NOT remove these extended communities. This default behavior MAY be configurable. The BGP speaker SHOULD also allow local policies to match against or remove these extended communities.

7. Error Handling

[RFC7606], Section 7.14, defines the error handling procedure for the Extended Community attribute.

8. IANA Considerations

All the BGP Extended Communities contain a Type field. The IANA has created a registry entitled, "BGP Extended Communities Type". The IANA will maintain this registry.

The Type could be either regular or extended. For a regular Type the IANA allocates an 8-bit value; for an extended Type the IANA allocates a 16-bit value.

The value allocated for a regular Type MUST NOT be reused as the value of the high-order octet when allocating an extended Type. The value of the high-order octet allocated for an extended Type MUST NOT be reused when allocating a regular Type.

The Type field indicates where the Extended Community is transitive or not. Future requests for assignment of a Type value must specify whether the Type value is intended for a transitive or a non-transitive Extended Community.

Future assignment are to be made using either the Standards Action process defined in [RFC8126], the Early IANA Allocation process defined in [RFC7120], or the "First Come First Served" policy defined in [RFC8126].

The following table summarizes the ranges for the assignment of Types:

Type	Standard Action	First Come
-----	Early IANA Allocation	First Served
-----	-----	-----
regular, transitive	0x90-0xbf	0x00-x3f
regular, non-transitive	0xd0-0xff	0x40-0x7f
extended, transitive	0x9000-0xbfff	0x0000-0x3fff
extended, non-transitive	0xd000-0xffff	0x4000-0x7fff

Assignments consist of a name and the value.

The Type values 0x80-0x8f and 0xc0-0xcf for regular Types, and 0x8000-0x8fff and 0xc000-0xcfff for extended Types are for Experimental use as defined in [RFC3692].

This document defines a class of extended communities called two-octet AS specific extended community for which the IANA is to create and maintain a registry entitled "Two-octet AS Specific Extended Community". All the communities in this class are of extended Types. Future assignment are to be made using the "First Come First Served" policy defined in [RFC8126]. The Type values for the transitive communities of the two-octet AS specific extended community class are 0x0000-0x00ff, and for the non-transitive communities of that class are 0x4000-0x40ff. Assignments consist of a name and the value.

This document makes the following assignments for the two-octet AS specific extended community:

Name	Type Value
----	-----
two-octet AS specific Route Target	0x0002
two-octet AS specific Route Origin	0x0003

This document defines a class of extended communities called IPv4 address specific extended community for which the IANA is to create and maintain a registry entitled "IPv4 Address Specific Extended Community". All the communities in this class are of extended Types. Future assignment are to be made using the "First Come First Served" policy defined in [RFC8126]. The Type values for the transitive communities of the IPv4 Address specific extended community class are 0x0100-0x01ff, and for the non-transitive communities of that class are 0x4100-0x41ff. Assignments consist of a name and the value.

This document makes the following assignments for the IPv4 address specific extended community:

Name	Type Value
----	-----
IPv4 address specific Route Target	0x0102
IPv4 address specific Route Origin	0x0103

This document defines a class of extended communities called opaque extended community for which the IANA is to create and maintain a registry entitled "Opaque Extended Community". All the communities in this class are of extended Types. Future assignment are to be made using the "First Come First Served" policy defined in [RFC8126]. The Type values for the transitive communities of the opaque extended community class are 0x0300-0x03ff, and for the non-transitive communities of that class are 0x4300-0x43ff. Assignments consist of a name and the value.

When requesting an allocation from more than one registry defined above, one may ask for allocating the same Type value from these registries. If possible, the IANA should accommodate such requests.

9. Security Considerations

This extension to BGP has similar security implications as BGP Communities [RFC1997].

This extension to BGP does not change the underlying security issues. Specifically, an operator who is relying on the information carried in BGP must have a transitive trust relationship back to the source of the information. Specifying the mechanism(s) to provide such a relationship is beyond the scope of this document.

10. Contributors

Dan Tappan and Yakov Rekhter were the authors of [RFC4360] and, therefore, are contributing authors of this document.

11. Acknowledgements

We wish to thank John Hawkinson, Jeffrey Haas, Bruno Rijsman, Bill Fenner, and Alex Zinin for their suggestions and feedback on the original [RFC4360].

We thank Yakov Rekhter and Alfred Hoenes for pointing out several errors in [RFC4360].

We also wish to thank Bruno Decraene, Laurent Vanbever, and Pierre Francois for pointing out inconsistencies regarding the procedures for originating non-transitive extended communities in [I-D.decraene-idr-rfc4360-clarification].

We also thank Jeffrey Haas for his suggestions and feedback on this document.

12. References

12.1. Normative References

- [RFC1997] Chandra, R., Traina, P., and T. Li, "BGP Communities Attribute", RFC 1997, DOI 10.17487/RFC1997, August 1996, <<https://www.rfc-editor.org/info/rfc1997>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3692] Narten, T., "Assigning Experimental and Testing Numbers Considered Useful", BCP 82, RFC 3692, DOI 10.17487/RFC3692, January 2004, <<https://www.rfc-editor.org/info/rfc3692>>.
- [BGP-4] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", RFC 4271, DOI 10.17487/RFC4271, January 2006, <<https://www.rfc-editor.org/info/rfc4271>>.
- [RFC5065] Traina, P., McPherson, D., and J. Scudder, "Autonomous System Confederations for BGP", RFC 5065, DOI 10.17487/RFC5065, August 2007, <<https://www.rfc-editor.org/info/rfc5065>>.
- [RFC4360] Sangli, S., Tappan, D., and Y. Rekhter, "BGP Extended Communities Attribute", RFC 4360, DOI 10.17487/RFC4360, February 2006, <<https://www.rfc-editor.org/info/rfc4360>>.
- [RFC5668] Rekhter, Y., Sangli, S., and D. Tappan, "4-Octet AS Specific BGP Extended Community", RFC 5668, DOI 10.17487/RFC5668, October 2009, <<https://www.rfc-editor.org/info/rfc5668>>.
- [RFC7120] Cotton, M., "Early IANA Allocation of Standards Track Code Points", BCP 100, RFC 7120, DOI 10.17487/RFC7120, January 2014, <<https://www.rfc-editor.org/info/rfc7120>>.
- [RFC7606] Chen, E., Ed., Scudder, J., Ed., Mohapatra, P., and K. Patel, "Revised Error Handling for BGP UPDATE Messages", RFC 7606, DOI 10.17487/RFC7606, August 2015, <<https://www.rfc-editor.org/info/rfc7606>>.

- [RFC8126] Cotton, M., Leiba, B., and T. Narten, "Guidelines for Writing an IANA Considerations Section in RFCs", BCP 26, RFC 8126, DOI 10.17487/RFC8126, June 2017, <<https://www.rfc-editor.org/info/rfc8126>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

12.2. Informative References

- [RFC4364] Rosen, E. and Y. Rekhter, "BGP/MPLS IP Virtual Private Networks (VPNs)", RFC 4364, DOI 10.17487/RFC4364, February 2006, <<https://www.rfc-editor.org/info/rfc4364>>.
- [I-D.dekraene-idr-rfc4360-clarification] Dekraene, B., Vanbever, L., and P. Francois, "RFC 4360 Clarification Request", Work in Progress, Internet-Draft, draft-dekraene-idr-rfc4360-clarification-00, 19 October 2009, <<https://datatracker.ietf.org/doc/html/draft-dekraene-idr-rfc4360-clarification-00>>.

Authors' Addresses

Srihari Sangli
Juniper Networks
Exora Business Park
Bangalore, KA 560103
India
Email: ssangli@juniper.net

Nat Kao (editor)
Individual Contributor
Email: pyxislx@gmail.com