

MPLS Working Group
Internet-Draft
Intended status: Standards Track
Expires: 3 September 2025

W. Cheng
China Mobile
X. Min
ZTE Corp.
R. Gandhi
Cisco Systems, Inc.
G. Mirsky
Ericsson
G. Fioccola
Huawei
2 March 2025

MNA for Performance Measurement with Alternate Marking Method
draft-cx-mpls-mna-inband-pm-06

Abstract

MPLS Network Action (MNA) is used to indicate action for Label Switched Paths (LSPs) and/or MPLS packets, and to transfer data needed for the action.

This document defines MNA encoding for MPLS performance measurement with alternate marking method, which performs flow-based packet loss, delay, and jitter measurements on MPLS live traffic.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 3 September 2025.

Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	2
1.1. Terminology	2
2. MPLS Network Action for Flow-based PM	3
3. Security Considerations	4
4. IANA Considerations	4
5. Acknowledgements	4
6. References	4
6.1. Normative References	4
6.2. Informative References	5
Authors' Addresses	5

1. Introduction

MPLS Network Action (MNA) [I-D.ietf-mpls-mna-fwk] is used to indicate action for Label Switched Paths (LSPs) and/or MPLS packets, and to transfer data needed for the action. [I-D.ietf-mpls-mna-hdr] defines the MNA sub-stack solution for carrying Network Action Indicators and Ancillary Data in the label stack.

As specified in [RFC9714], Flow-ID Label, L bit and D bit are used for MPLS flow identification and flow-based performance measurement with alternate marking method [RFC9341], which can be an applicable MNA usecase [I-D.ietf-mpls-mna-usecases].

This document defines MNA encoding for MPLS performance measurement with alternate marking method, which performs flow-based packet loss, delay, and jitter measurements on MPLS live traffic. The proposed MNA encoding is compliant with the MNA sub-stack solution specified in [I-D.ietf-mpls-mna-hdr] and reuses the data fields specified in [RFC9714].

1.1. Terminology

This document makes use of the terms defined in [RFC9714] and [I-D.ietf-mpls-mna-hdr].

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

2. MPLS Network Action for Flow-based PM

The MNA format for performance measurement with alternate marking method is illustrated as below:

```

      0               1               2               3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+-----+-----+-----+-----+-----+-----+-----+-----+
| Opcode=PMAMM |                               Flow-ID                               |S|U|FID|L|D|NAL=0|
+-----+-----+-----+-----+-----+-----+-----+-----+

```

Figure 1: MNA for Alternate Marking

The description of MNA for Alternate Marking is as follows:

- * Opcode: Performance Measurement with Alternate Marking Method (PMAMM) Action.
- * Network Action Indication: The PMAMM Action indication is Opcode TBA1.
- * Scope: The PMAMM Action is valid in all scopes.
- * In-Stack Data: The PMAMM Action carries 20 bits of ancillary data. The most significant 18 bits of ancillary data is the Flow-ID Value, immediately followed by L bit and D bit. The three fields Flow-ID Value, L bit, and D bit have semantics consistent with the Flow-ID Label, L bit and D bit defined in [RFC9714], except that the Flow-ID Value is an 18-bit value while the Flow-ID Label is a 20-bit value. While the Flow-ID Label has some restrictions to avoid collisions with the reserved label space (0-15) [RFC3032], those restrictions are not necessary for the Flow-ID Value and do not apply. The forwarding node in the scope of PMAMM Action SHOULD execute the flow-based performance measurement by using the Flow-ID Value, L bit and D bit.
- * Label Stack Entry (LSE) Format: Format C as defined in [I-D.ietf-mpls-mna-hdr]. There is no additional data. The Network Action Length (NAL) field MUST be set to zero.
- * Post-Stack Data: None.

3. Security Considerations

Security issues discussed in [RFC9341], [RFC9714], and [I-D.ietf-mpls-mna-hdr] apply to this document.

4. IANA Considerations

This document requests that IANA allocates a codepoint (TBA1) from the MPLS "HBH and Select In-Stack MPLS Network Action Indicator Opcodes" from the "IETF Review" range and the same codepoint from the MPLS "I2E In-Stack MPLS Network Action Indicator Opcodes" from the "IETF Review" range for the Performance Measurement with Alternate Marking Method Action. Note that both the "HBH and Select In-Stack MPLS Network Action Indicator Opcodes" and the "I2E In-Stack MPLS Network Action Indicator Opcodes" will be created based on the request from [I-D.ietf-mpls-mna-hdr]. Specifically, this document requests the following allocation from IANA.

MNA Opcode	Description	Scope
-----	-----	-----
TBA1	PM with Alternate Marking Method	HBH, Select, or I2E

5. Acknowledgements

The authors would like to acknowledge Loa Andersson for his careful review and helpful comments.

6. References

6.1. Normative References

- [I-D.ietf-mpls-mna-hdr]
Rajamanickam, J., Gandhi, R., Zigler, R., Song, H., and K. Kompella, "MPLS Network Action (MNA) Sub-Stack Solution", Work in Progress, Internet-Draft, draft-ietf-mpls-mna-hdr-11, 17 February 2025, <<https://datatracker.ietf.org/doc/html/draft-ietf-mpls-mna-hdr-11>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3032] Rosen, E., Tappan, D., Fedorkow, G., Rekhter, Y., Farinacci, D., Li, T., and A. Conta, "MPLS Label Stack Encoding", RFC 3032, DOI 10.17487/RFC3032, January 2001, <<https://www.rfc-editor.org/info/rfc3032>>.

- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC9341] Fioccola, G., Ed., Cociglio, M., Mirsky, G., Mizrahi, T., and T. Zhou, "Alternate-Marking Method", RFC 9341, DOI 10.17487/RFC9341, December 2022, <<https://www.rfc-editor.org/info/rfc9341>>.
- [RFC9714] Cheng, W., Ed., Min, X., Ed., Zhou, T., Dai, J., and Y. Peleg, "Encapsulation for MPLS Performance Measurement with the Alternate-Marking Method", RFC 9714, DOI 10.17487/RFC9714, February 2025, <<https://www.rfc-editor.org/info/rfc9714>>.

6.2. Informative References

- [I-D.ietf-mpls-mna-fwk]
Andersson, L., Bryant, S., Bocci, M., and T. Li, "MPLS Network Actions (MNA) Framework", Work in Progress, Internet-Draft, draft-ietf-mpls-mna-fwk-15, 27 December 2024, <<https://datatracker.ietf.org/doc/html/draft-ietf-mpls-mna-fwk-15>>.
- [I-D.ietf-mpls-mna-usecases]
Saad, T., Makhijani, K., Song, H., and G. Mirsky, "Use Cases for MPLS Network Action Indicators and MPLS Ancillary Data", Work in Progress, Internet-Draft, draft-ietf-mpls-mna-usecases-15, 23 September 2024, <<https://datatracker.ietf.org/doc/html/draft-ietf-mpls-mna-usecases-15>>.

Authors' Addresses

Weiqiang Cheng
China Mobile
Beijing
China
Email: chengweiqiang@chinamobile.com

Xiao Min
ZTE Corp.
Nanjing
China
Email: xiao.min2@zte.com.cn

Rakesh Gandhi
Cisco Systems, Inc.
Canada
Email: rgandhi@cisco.com

Greg Mirsky
Ericsson
United States of America
Email: gregimirsky@gmail.com

Giuseppe Fioccola
Huawei
Italy
Email: giuseppe.fioccola@huawei.com