

BIER Working Group
Internet-Draft
Intended status: Informational
Expires: 17 April 2026

G. Mirsky, Ed.
Ericsson
N. Kumar
Oracle
M. Chen
Huawei Technologies
S. Pallagatti, Ed.
VMware
14 October 2025

Operations, Administration and Maintenance (OAM) Requirements for Bit
Index Explicit Replication (BIER) Layer
draft-ietf-bier-oam-requirements-19

Abstract

This document specifies a list of functional requirements for Operations, Administration, and Maintenance mechanisms, protocols, and tools that support operations in the Bit Index Explicit Replication layer of a network.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 17 April 2026.

Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights

and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	2
1.1. Conventions used in this document	2
1.1.1. Terminology	2
1.1.2. Requirements Language	3
1.1.3. Acronyms	3
2. Requirements	4
3. IANA Considerations	5
4. Security Considerations	5
5. Acknowledgements	6
6. Normative References	6
7. Informative References	6
Contributors' Addresses	8
Authors' Addresses	8

1. Introduction

[RFC8279] specifies a Bit Index Explicit Replication (BIER) architecture and how it supports forwarding of multicast data packets.

This document lists the Operations, Administration, and Maintenance (OAM) requirements for the BIER layer see Section 4.2 of [RFC8279]) of the multicast domain. The list can further be used for gap analysis of available OAM tools to identify possible enhancements of existing or whether new OAM tools are required to support proactive and on-demand path monitoring and service validation.

1.1. Conventions used in this document

1.1.1. Terminology

The reader is expected to be familiar with [RFC7799], particularly definitions of Active, Passive, and Hybrid measurement methods and metrics.

The term "BIER OAM" is used in this document interchangeably with a more extended version, "set of OAM protocols, methods, and tools for BIER layer".

Downstream - is the direction from the ingress toward the egress endpoints of a multicast distribution tree.

- * In-band OAM is an active OAM or hybrid OAM method [RFC7799] in which OAM packets traverse the same set of links and interfaces, and receive the same QoS treatment, as the monitored BIER flow (traffic flows in [RFC7011]).
- * Out-of-band OAM refers to an active OAM method in which the path traversed through the BIER domain is not topologically identical to that of the monitored BIER flow, or in which the OAM test packets receive different QoS treatment, or both.
- * OAM session is a communication established between network nodes to perform OAM functions like fault detection, performance monitoring, and localization [RFC7276]. These sessions can be proactive (continuous, persistent configuration) or on-demand (manual, temporary diagnostics).

1.1.2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

The requirements language is used in Section 2 and applies to implementations of BIER OAM conformant to the listed requirements.

1.1.3. Acronyms

BFD: Bidirectional Forwarding Detection [RFC8562]

BFR: Bit-Forwarding Router [RFC8279]

BFER: Bit-Forwarding Egress Router [RFC8279]

BIER: Bit Index Explicit Replication [RFC8279]

OAM: Operations, Administration, and Maintenance [RFC6291]

p2mp: Point-to-Multipoint [RFC8562]

RDI: Remote Defect Indication

STAMP: Simple Two-way Active Measurement Protocol [RFC8762]

2. Requirements

This section lists the requirements for OAM of the BIER layer:

1. The listed requirements MUST be supported with any routing underlay [RFC8279] over which the BIER layer can be realized.
2. It MUST be possible to initialize a BIER OAM session from any Bit-Forwarding Router (BFR) of the given BIER domain.
3. It SHOULD be possible to initialize a BIER OAM session from a centralized controller.
4. BIER OAM MUST support proactive and on-demand OAM monitoring and measurement methods.
5. BIER OAM MUST support downstream path continuity check. Bidirectional Forwarding Detection (BFD) [RFC8562] is an example of a protocol that monitors the continuity of a multicast distribution tree.
6. BIER OAM MUST support downstream performance measurement. Simple Two-way Active Measurement Protocol (STAMP) [RFC8762] is an example of a protocol that supports measurement of performance metrics, e.g., packet loss ratio, delay, and delay variation.
7. BIER OAM packets in the forward direction (i.e., from the ingress toward the egress endpoint(s) of the OAM test session) MUST be transmitted in-band, as defined in Section 1.1.1.
8. BIER OAM MUST support bi-directional OAM methods. Such methods MAY combine in-band monitoring or measurement in the forward direction with out-of-band notification, as defined in Section 1.1.1, in the reverse direction (i.e., from the egress toward the ingress endpoint of the OAM test session, as in Point-to-Multipoint (p2mp) BFD with active tail [RFC9780]).
9. BIER OAM MUST support the ability of any BFR in the given BIER domain to monitor BFER availability proactively. The p2mp BFD with active tail support [RFC9780] is an example of a protocol that provides notifications about the loss of connectivity in a multicast distribution tree.
10. BIER OAM MUST support Path Maximum Transmission Unit discovery [RFC1191].

11. BIER OAM MUST support Remote Defect Indication (RDI) [RFC6428] notification of the source of continuity checking BFR by Bit-Forwarding Egress Routers (BFERs). The Diagnostic field in p2mp BFD with active tail support, as described in Section 5 of [RFC9780], is an example of the RDI mechanism.
12. BIER OAM MUST support active and passive performance measurement methods [RFC7799].
13. BIER OAM MUST support downstream performance measurement method(s) that (together) calculate performance metrics, e.g., throughput, loss, delay, and delay variation metrics [RFC6374]. STAMP ([RFC8762] and [RFC8972]) is an example of an active performance measurement method of performance metrics that may be applied in a BIER domain. The Alternate Marking Method, described in [RFC9341] and [RFC9342], is an example of a hybrid measurement method ([RFC7799]) that may be applied in a BIER domain.
14. BIER OAM MUST support defect notification mechanism(s), like Alarm Indication Signal [RFC6427].
15. BIER OAM MUST support a way for any BFR in the given BIER domain to originate a fault management message addressed to any subset of BFRs within the domain. [RFC6427] provides an example of a Fault Management messaging mechanism.
16. BIER OAM MUST support methods to enable the survivability of a BIER layer. Protection switching and restoration are examples of survivability methods.

3. IANA Considerations

This document does not propose any IANA consideration. This section may be removed.

4. Security Considerations

This document lists the OAM requirement for a BIER-enabled domain and thus inherits security considerations discussed in [RFC8279] and [RFC8296]. Another general security aspect results from using active OAM protocols, according to the [RFC7799], in a multicast network.

Active OAM protocols inject specially constructed test packets, and some active OAM protocols are based on the echo request/reply principle. In the multicast network, test packets are replicated as data packets, thus creating a possible amplification effect of multiple echo responses being transmitted to the sender of the echo

request. Thus, an implementation of BIER OAM MUST protect the control plane from spoofed replies. Also, an implementation of BIER OAM MUST provide control of the number of BIER OAM messages sent to the control plane.

5. Acknowledgements

The authors would like to thank the comments and suggestions from Gunter van de Velde that helped improve this document.

6. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

7. Informative References

- [RFC1191] Mogul, J. and S. Deering, "Path MTU discovery", RFC 1191, DOI 10.17487/RFC1191, November 1990, <<https://www.rfc-editor.org/info/rfc1191>>.
- [RFC6291] Andersson, L., van Helvoort, H., Bonica, R., Romascanu, D., and S. Mansfield, "Guidelines for the Use of the "OAM" Acronym in the IETF", BCP 161, RFC 6291, DOI 10.17487/RFC6291, June 2011, <<https://www.rfc-editor.org/info/rfc6291>>.
- [RFC6374] Frost, D. and S. Bryant, "Packet Loss and Delay Measurement for MPLS Networks", RFC 6374, DOI 10.17487/RFC6374, September 2011, <<https://www.rfc-editor.org/info/rfc6374>>.
- [RFC6427] Swallow, G., Ed., Fulignoli, A., Ed., Vigoureux, M., Ed., Boutros, S., and D. Ward, "MPLS Fault Management Operations, Administration, and Maintenance (OAM)", RFC 6427, DOI 10.17487/RFC6427, November 2011, <<https://www.rfc-editor.org/info/rfc6427>>.

- [RFC6428] Allan, D., Ed., Swallow, G., Ed., and J. Drake, Ed., "Proactive Connectivity Verification, Continuity Check, and Remote Defect Indication for the MPLS Transport Profile", RFC 6428, DOI 10.17487/RFC6428, November 2011, <<https://www.rfc-editor.org/info/rfc6428>>.
- [RFC7011] Claise, B., Ed., Trammell, B., Ed., and P. Aitken, "Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of Flow Information", STD 77, RFC 7011, DOI 10.17487/RFC7011, September 2013, <<https://www.rfc-editor.org/info/rfc7011>>.
- [RFC7276] Mizrahi, T., Sprecher, N., Bellagamba, E., and Y. Weingarten, "An Overview of Operations, Administration, and Maintenance (OAM) Tools", RFC 7276, DOI 10.17487/RFC7276, June 2014, <<https://www.rfc-editor.org/info/rfc7276>>.
- [RFC7799] Morton, A., "Active and Passive Metrics and Methods (with Hybrid Types In-Between)", RFC 7799, DOI 10.17487/RFC7799, May 2016, <<https://www.rfc-editor.org/info/rfc7799>>.
- [RFC8279] Wijnands, IJ., Ed., Rosen, E., Ed., Dolganow, A., Przygienda, T., and S. Aldrin, "Multicast Using Bit Index Explicit Replication (BIER)", RFC 8279, DOI 10.17487/RFC8279, November 2017, <<https://www.rfc-editor.org/info/rfc8279>>.
- [RFC8296] Wijnands, IJ., Ed., Rosen, E., Ed., Dolganow, A., Tantsura, J., Aldrin, S., and I. Meilik, "Encapsulation for Bit Index Explicit Replication (BIER) in MPLS and Non-MPLS Networks", RFC 8296, DOI 10.17487/RFC8296, January 2018, <<https://www.rfc-editor.org/info/rfc8296>>.
- [RFC8562] Katz, D., Ward, D., Pallagatti, S., Ed., and G. Mirsky, Ed., "Bidirectional Forwarding Detection (BFD) for Multipoint Networks", RFC 8562, DOI 10.17487/RFC8562, April 2019, <<https://www.rfc-editor.org/info/rfc8562>>.
- [RFC8762] Mirsky, G., Jun, G., Nydell, H., and R. Foote, "Simple Two-Way Active Measurement Protocol", RFC 8762, DOI 10.17487/RFC8762, March 2020, <<https://www.rfc-editor.org/info/rfc8762>>.

- [RFC8972] Mirsky, G., Min, X., Nydell, H., Foote, R., Masputra, A., and E. Ruffini, "Simple Two-Way Active Measurement Protocol Optional Extensions", RFC 8972, DOI 10.17487/RFC8972, January 2021, <<https://www.rfc-editor.org/info/rfc8972>>.
- [RFC9341] Fioccola, G., Ed., Cociglio, M., Mirsky, G., Mizrahi, T., and T. Zhou, "Alternate-Marking Method", RFC 9341, DOI 10.17487/RFC9341, December 2022, <<https://www.rfc-editor.org/info/rfc9341>>.
- [RFC9342] Fioccola, G., Ed., Cociglio, M., Sapio, A., Sisto, R., and T. Zhou, "Clustered Alternate-Marking Method", RFC 9342, DOI 10.17487/RFC9342, December 2022, <<https://www.rfc-editor.org/info/rfc9342>>.
- [RFC9780] Mirsky, G., Mishra, G., and D. Eastlake 3rd, "Bidirectional Forwarding Detection (BFD) for Multipoint Networks over Point-to-Multipoint MPLS Label Switched Paths (LSPs)", RFC 9780, DOI 10.17487/RFC9780, May 2025, <<https://www.rfc-editor.org/info/rfc9780>>.

Contributors' Addresses

Erik Nordmark
Email: nordmark@acm.org

Sam Aldrin
Google
Email: aldrin.ietf@gmail.com

Lianshu Zheng
Email: veronique_cheng@hotmail.com

Nobo Akiya
Email: nobo.akiya.dev@gmail.com

Authors' Addresses

Greg Mirsky (editor)
Ericsson
Email: gregimirsky@gmail.com

Nagendra Kumar
Oracle
Email: nagendrakumar.nainar@gmail.com

Mach Chen
Huawei Technologies
Email: mach.chen@huawei.com

Santosh Pallagatti (editor)
VMware
Email: santosh.pallagatti@gmail.com