

Global Routing Operations
Internet-Draft
Obsoletes: 7454 (if approved)
Intended status: Best Current Practice
Expires: 17 October 2025

T. Fiebig
MPI-INF
N. Hilliard
INEX
15 April 2025

Updated BGP Operations and Security
draft-ietf-grow-bgpsecupd-08

Abstract

The Border Gateway Protocol (BGP) is a critical component in the Internet to exchange routing information between network domains. Due to this central nature, it is important to understand the security and reliability requirements that can and should be ensured to prevent accidental or intentional routing disturbances.

Previously, security considerations for BGP have been described in RFC7454 / BCP194. Since the publications of RFC7454 / BCP194, several developments and changes in operational practice took place that warrant an update of these best current practices. This document replaces RFC7454 / BCP194, focusing on the overall goals, and providing a less implementation centric set of best practices.

To this end, the document describes the security requirements and goals when operating BGP for exchanging routing information with other networks. The document explicitly does not focus on specific technical implementations and requirements. Operators are advised to consult documentation and contemporary informational documents concerning methods to ensure that these properties are sufficiently ensured in their network.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 17 October 2025.

Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	2
1.1. Requirements Language	3
2. Scope of the Document	3
3. Protection of the BGP Speaker and Session	3
3.1. BGP Session Protection	3
3.2. BGP Speaker Management Interface Protection	4
4. NLRI Filtering	4
4.1. Importing NLRI	4
4.2. Originating and Redistributing NLRI	5
4.3. Altering NLRI	5
5. IANA Considerations	5
6. Security Considerations	6
7. References	6
7.1. Normative References	6
7.2. Informative References	7
Acknowledgements	7
Authors' Addresses	8

1. Introduction

The Border Gateway Protocol (BGP), specified in [RFC4271], is the protocol used in the Internet to exchange routing information between network domains. BGP does not directly include mechanisms that control whether the routes exchanged conform to the various guidelines defined by the Internet community. Furthermore, the BGP protocol itself, by its design, does not have any direct way to protect itself against threats to confidentiality, integrity, and availability. This document summarizes security properties and requirements when operating BGP for securing the infrastructure as well as for security considerations regarding the exchanged routing

information.

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

2. Scope of the Document

The guidelines defined in this document are intended for BGP when used to exchange generic Internet routing information within the DFZ. It specifically does not cover other uses of BGP, e.g., when using BGP for NLRI exchange in a data-center context. This document does not specify how the outlined requirements and properties can be technically realized at a specific point in time. Instead, operators are advised to consult applicable documentation and contemporary informational documents describing implementation specifics.

3. Protection of the BGP Speaker and Session

The BGP speaker, i.e., the host running BGP to exchange routing information, needs to be protected from external attempts to taint integrity or availability of the BGP session and host alike.

3.1. BGP Session Protection

To protect a BGP speaker on the network layer, an operator MUST ensure the following properties using technical or organizational measures:

- * Prevent off-path attackers from injecting BGP messages into existing sessions.
- * Prevent off-path attackers from interrupting existing sessions.
- * Prevent off-path attackers from preventing the establishment of new sessions.
- * Prevent remote systems from overwhelming the BGP speaker by sending large volumes of unsolicited packets or BGP messages.
- * Ensure that unstable sessions do not threaten the availability of BGP speakers within the network.

3.2. BGP Speaker Management Interface Protection

In addition to the control plane / exchange of BGP protocol messages, the management plane of BGP speakers must be appropriately secured. Hence, operators MUST ensure that:

- * No unauthorized third-parties can obtain access or connect to the management interface of a BGP speaker in a way that allows tainting confidentiality, integrity, or availability.
- * External activity towards the management interface do not interfere with the integrity or availability of BGP sessions.

4. NLRI Filtering

The purpose of BGP is exchanging routing information, i.e., NLRI. Importing or exporting incorrect or malicious NLRI is a security risk for networks themselves, but may also form a threat for connected and/or remote networks. As such, operators MUST ensure the following properties when importing or exporting routing information from their neighbors.

4.1. Importing NLRI

When importing NLRI from a neighbor, an operator MUST ensure that all imported NLRI conform to the following properties by implementing technical or organizational measures:

- * The AS originating NLRI for a prefix MUST be globally authorized to originate that prefix. Operators MAY deviate from this for default routes (::/0 and 0.0.0.0/0), if they granted the specific neighbor permission to announce default routes towards them.
- * All ASes left of the originating AS in the AS_PATH MUST be authorized to advertise the NLRI to the AS directly to their left, and the neighbor from which an NLRI is received MUST be authorized to advertise it to the importing AS.
- * The AS_PATH MUST NOT contain AS numbers reserved for private [RFC6996] or special-use cases, except for those AS numbers explicitly dedicated to a special-use that requires their presence in the global routing table [IANAASNSpec].
- * The number of NLRI received from a neighbor MUST NOT exceed the resources of the local router.

4.2. Originating and Redistributing NLRI

When originating NLRI or redistributing NLRI received from a neighbor, an operator MUST ensure that all NLRI they export conform to the following properties by implementing technical or organizational measures:

- * The redistributing AS MUST be authorized to redistribute NLRI for the specific prefix when received from the AS directly to its right in the AS_PATH. Additionally, each AS in the AS_PATH not originating the prefix MUST be authorized to redistribute the prefix when receiving it from the next AS to its right.
- * The AS originating NLRI for a prefix MUST be globally authorized to originate that prefix. Operators MAY deviate from this for default routes (::/0 and 0.0.0.0/0), if they originate the default route and the specific neighbor granted them permission to announce default routes towards them.
- * The AS_PATH MUST NOT contain AS numbers reserved for private [RFC6996] or special-use cases, except for those AS numbers explicitly dedicated to a special-use that requires their presence in the global routing table [IANAASNSpec].

4.3. Altering NLRI

When processing NLRI, an operator MUST ensure that basic properties of these NLRI are not altered:

- * An operator MUST NOT change or remove immutable transitive BGP attributes, e.g., ORIGIN as per [RFC4271]. If an attribute is unknown to the operator it must be considered immutable. In selected cases, if a specific attribute is known to be malicious, an operator MAY either temporarily remove that specific attribute from NLRI when importing them or filter NLRI carrying the attribute.
- * NLRI carried on BGP MUST NOT be enriched with transitive attributes subject to change independent of the underlying NLRI, e.g., encoding RPKI validation state in transitive attributes [I-D.ietf-sidrops-avoid-rpki-state-in-bgp].

5. IANA Considerations

This document does not require any IANA actions.

6. Security Considerations

This document is entirely about BGP operational security. It lists requirements and properties operators MUST ensure using technical or organizational measures when operating BGP routers in the DFZ.

However, it does not detail how the outlined properties and security requirements can be implemented and enforced in practice. This is a conscious choice given that available techniques and methods to ensure these properties will change over time, while the underlying principles remain the same.

Instead, readers MAY refer to the most recent non expired draft of [I-D.ietf-grow-routing-ops-sec-inform] for an updated list of currently available technology to ensure the above principles, and the most recent non expired draft of [I-D.ietf-grow-routing-ops-terms] for information on currently used terms and definitions in the context of global routing operations. Readers MUST NOT rely on expired versions of these I-Ds. If no most recent non-expired version of either I-D is available, the document MUST be considered to be non-existent.

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", RFC 4271, DOI 10.17487/RFC4271, January 2006, <<https://www.rfc-editor.org/info/rfc4271>>.
- [RFC6996] Mitchell, J., "Autonomous System (AS) Reservation for Private Use", BCP 6, RFC 6996, DOI 10.17487/RFC6996, July 2013, <<https://www.rfc-editor.org/info/rfc6996>>.
- [IANAASNSpec] IANA, "Special-Purpose Autonomous System (AS) Numbers", <<https://www.iana.org/assignments/iana-as-numbers-special-registry/iana-as-numbers-special-registry.xhtml>>.

7.2. Informative References

[RFC7454] Durand, J., Pepelnjak, I., and G. Doering, "BGP Operations and Security", BCP 194, RFC 7454, DOI 10.17487/RFC7454, February 2015, <<https://www.rfc-editor.org/info/rfc7454>>.

[I-D.ietf-grow-routing-ops-sec-inform]
Fiebig, T., "Current Options for Securing Global Routing", Work in Progress, Internet-Draft, draft-ietf-grow-routing-ops-sec-inform, 9 April 2025, <<https://datatracker.ietf.org/doc/draft-ietf-grow-routing-ops-sec-inform/>>.

[I-D.ietf-grow-routing-ops-terms]
Fiebig, T., "Currently Used Terminology in Global Routing Operations", Work in Progress, Internet-Draft, draft-ietf-grow-routing-ops-terms, 9 April 2025, <<https://datatracker.ietf.org/doc/draft-ietf-grow-routing-ops-terms/>>.

[I-D.ietf-sidrops-avoid-rpki-state-in-bgp]
Snijders, J., Fiebig, T., and M. A. Stucchi, "Guidance to Avoid Carrying RPKI Validation States in Transitive BGP Path Attributes", Work in Progress, Internet-Draft, draft-ietf-sidrops-avoid-rpki-state-in-bgp, 3 October 2024, <<https://datatracker.ietf.org/doc/draft-ietf-sidrops-avoid-rpki-state-in-bgp/>>.

Acknowledgements

This document has been originally based on [RFC7454] and we thank the original authors for their work.

We thank the following people for reviewing this draft and suggesting changes:

- * Gert Doerring
- * Jeff Haas
- * Geng Nan
- * Martin Pels
- * Job Snijders
- * Berislav Todorovic

- * Martin Pels
- * Wolfgang Tremmel
- * Ben Maddison
- * Mohamed Boucadair

Authors' Addresses

Tobias Fiebig
Max-Planck-Institut fuer Informatik
Campus E14
66123 Saarbruecken
Germany
Phone: +49 681 9325 3527
Email: tfiebig@mpi-inf.mpg.de

Nick Hilliard
Internet Neutral Exchange Association
4027 Kingswood Road
Citywest, Dublin
D24 AX96
Ireland
Phone: +353 1 433 205 2
Email: nick@inex.ie