

IDR
Internet-Draft
Intended status: Standards Track
Expires: 30 November 2026

C. Lin
New H3C Technologies
W. Cheng
China Mobile
Y. Liu
ZTE
K. Talaulikar
Cisco Systems
M. Chen
New H3C Technologies
29 May 2026

BGP SR Policy Extensions for Segment List Identifier
draft-ietf-idr-sr-policy-seglist-id-10

Abstract

Segment Routing (SR) is a source routing paradigm that explicitly indicates the forwarding path for packets at the ingress node. An SR Policy is a set of candidate paths, each consisting of one or more segment lists. This document defines extensions to BGP SR Policy to specify the identifier of a segment list.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 30 November 2026.

Copyright Notice

Copyright (c) 2026 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	2
1.1. Requirements Language	3
2. Segment List Identifier in SR Policy	3
2.1. Segment List ID Sub-TLV	5
3. Security Considerations	6
4. Implementation Status	6
4.1. New H3C Technologies	7
4.2. ZTE Corp	8
5. IANA Considerations	8
6. Acknowledgments	8
7. References	8
7.1. Normative References	8
7.2. Informative References	9
Appendix A. Cross WG Information	10
A.1. Spring WG	10
A.2. PCE WG	10
A.3. SRv6OPS	11
Authors' Addresses	11

1. Introduction

Segment routing (SR) [RFC8402] is a source routing paradigm that explicitly indicates the forwarding path for packets at the ingress node. The ingress node steers packets into a specific path according to the Segment Routing Policy (SR Policy) as defined in [RFC9256]. In order to distribute SR policies to the headend, [RFC9830] specifies a mechanism by using BGP.

However, there is no identifier for segment lists in BGP SR Policy, which may cause inconvenience for other mechanisms to designate segment lists distributed by BGP.

Consider a scenario where a network controller distributes SR policies to the headend nodes, which need to collect traffic forwarding statistics per segment list. When a headend node reports each statistic to the controller, it needs to specify the segment list to which the statistic belongs. Due to the lack of an

identifier, the headend node usually reports all SIDs in the associated segment list along with the statistic, and then the controller needs to compare the SIDs one by one to recognize which segment list it is. The advertisement of all SIDs in the segment list consumes a lot of octets, and the comparison of SIDs can be complicated.

Consider a second example where a network controller distributes SR policies using BGP, and then uses NETCONF to set some configurations of the segment lists that are not suitable to be carried in BGP. The controller needs to specify which segment list these configurations belong to when it issues them. In this case, a simple identifier of the segment list can also be helpful.

An identifier of a segment list may also serve as a user-friendly attribute for debugging and troubleshooting purposes, such as displaying an invalid segment list when its associated BFD session is down.

Section 5.7.4 of [RFC9857] defines an SR Segment List Identifier sub-TLV for reporting the identifier associated with a specific SID list. This document defines extensions to BGP SR Policy to specify the identifier of an SR Segment List.

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

2. Segment List Identifier in SR Policy

As defined in [RFC9830], the SR policy encoding structure is as follows:

SR Policy SAFI NLRI: <Distinguisher, Policy-Color, Endpoint>

Attributes:

- Tunnel Encapsulation Attribute (23)
 - Tunnel Type: SR Policy (15)
 - Binding SID
 - SRv6 Binding SID
 - Preference
 - Priority
 - Policy Name
 - Policy Candidate Path Name
 - Explicit NULL Label Policy (ENLP)
 - Segment List
 - Weight
 - Segment
 - Segment
 - ...
- ...

Figure 1: SR Policy Encoding

SR policy with segment list identifier is expressed as below:

SR Policy SAFI NLRI: <Distinguisher, Policy-Color, Endpoint>

Attributes:

- Tunnel Encapsulation Attribute (23)
 - Tunnel Type: SR Policy (15)
 - Binding SID
 - SRv6 Binding SID
 - Preference
 - Priority
 - Policy Name
 - Policy Candidate Path Name
 - Explicit NULL Label Policy (ENLP)
 - Segment List
 - Weight
 - Segment List Identifier
 - Segment
 - Segment
 - ...
- ...

Figure 2: SR policy with segment list identifier Encoding

The segment list identifier can be advertised using the Segment List ID sub-TLV, as defined in Section 2.1.

2.1. Segment List ID Sub-TLV

The Segment List ID sub-TLV is defined in the BGP Tunnel Encapsulation Attribute [RFC9012]. The Segment List ID sub-TLV can be carried in the BGP Tunnel Encapsulation Attribute with the tunnel type set to SR Policy.

The Segment List ID sub-TLV specifies the identifier of the segment list by a 4-octet number. The Segment List ID is unique within the context of a Candidate Path.

The Segment List ID sub-TLV is an optional sub-TLV. Only a single instance of this sub-TLV is advertised for a given segment list. If multiple instances are present, then the first valid one (i.e., not determined to be malformed as per Section 2.4 of [RFC9830]) is used and the rest are ignored.

The Segment List ID sub-TLV has the following format:




Figure 3: Segment List ID sub-TLV

where:

- * Type: 19.
- * Length: 6.
- * Flags: 1 octet of flags. None are defined at this stage. Flags SHOULD be set to zero on transmission and MUST be ignored on receipt.
- * RESERVED: 1 octet of reserved bits. SHOULD be set to zero on transmission and MUST be ignored on receipt.
- * Segment List ID: 4 octets which carry a 32-bit unsigned non-zero number that serves as the identifier associated with the segment list. A value of 0 indicates that there is no identifier associated with the Segment List. The scope of this identifier is the SR Policy Candidate path.

The validation of an SR Policy NLRI with the Segment List ID sub-TLV in the BGP tunnel encapsulation attribute [RFC9012] follows the procedures in Section 4.2 of [RFC9830].

The Segment List ID sub-TLV is considered malformed if its format does not match the above description. If its format is considered malformed, the associated BGP SR Policy NLRI is considered malformed and the "treat-as-withdraw" strategy of [RFC7606] MUST be applied.

3. Security Considerations

The protocol extensions defined in this document do not affect the base BGP security model. The security requirements and mechanisms described in [RFC9830] also apply to this document. SR operates within a trusted SR domain [RFC8402] and its security considerations also apply to BGP sessions when carrying SR Policy information.

The Segment List ID sub-TLV is an optional sub-TLV that specifies an identifier associated with a segment list. The scope of this identifier is the SR Policy Candidate Path. The Segment List ID uniquely identifies a segment list within an SR Policy Candidate Path.

The Segment List ID is assigned by a controller, distributed via BGP, and used as an identifier for the segment list. Since this identifier may expose mission-critical or commercially sensitive network information, it introduces a confidentiality risk.

Network operators MUST ensure that only trusted nodes (including both routers and controller applications) within the SR domain are permitted to receive this information.

4. Implementation Status

[Note to the RFC Editor - remove this section before publication, as well as remove the reference to [RFC7942].]

This section records the status of known implementations of the protocol defined by this specification at the time of posting of this Internet-Draft, and is based on a proposal described in [RFC7942]. The description of implementations in this section is intended to assist the IETF in its decision processes in progressing drafts to RFCs. Please note that the listing of any individual implementation here does not imply endorsement by the IETF. Furthermore, no effort has been spent to verify the information presented here that was supplied by IETF contributors. This is not intended as, and must not be construed to be, a catalog of available implementations or their features. Readers are advised to note that other implementations may exist.

According to [RFC7942], "this will allow reviewers and working groups to assign due consideration to documents that have the benefit of running code, which may serve as evidence of valuable experimentation and feedback that have made the implemented protocols more mature. It is up to the individual working groups to use this information as they see fit".

4.1. New H3C Technologies

- * Organization: New H3C Technologies.
- * Implementation: H3C CR16000, CR19000 series routers implementation.
- * Description: All sections including all the "MUST" and "SHOULD" clauses have been implemented in above-mentioned New H3C Products(running Version 7.1.099 and above).
- * Maturity Level: Product
- * Coverage: All sections.
- * Version: Draft-03
- * Licensing: N/A
- * Implementation experience: Nothing specific.
- * Contact: linchangwang.04414@h3c.com
- * Last updated: February 10, 2025

4.2. ZTE Corp

- * Organization: ZTE Corporation
- * Implementation: ZTE's ZXR10 core router
- * Description: The implementation in lab has been completed. The commercial implementation is under development.
- * Maturity Level: Product
- * Coverage: All
- * Version: Draft-03
- * Licensing: N/A
- * Implementation experience: Nothing specific.
- * Contact: feng.jun99@zte.com.cn
- * Last updated: February 6, 2025

5. IANA Considerations

This document defines a new Sub-TLV in the registry "SR Policy Segment List Sub-TLVs" [RFC9830]:

Value	Description	Reference
19	Segment List ID sub-TLV	This document

6. Acknowledgments

The authors would like to thank Susan Hares, Hao Li, Haiyang Zhang, Yisong Liu, Ran Chen, Libin Liu, Lancheng Qin and Xinxin Yi for their review and discussion of this document.

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

- [RFC7606] Chen, E., Ed., Scudder, J., Ed., Mohapatra, P., and K. Patel, "Revised Error Handling for BGP UPDATE Messages", RFC 7606, DOI 10.17487/RFC7606, August 2015, <<https://www.rfc-editor.org/info/rfc7606>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8402] Filsfils, C., Ed., Previdi, S., Ed., Ginsberg, L., Decraene, B., Litkowski, S., and R. Shakir, "Segment Routing Architecture", RFC 8402, DOI 10.17487/RFC8402, July 2018, <<https://www.rfc-editor.org/info/rfc8402>>.
- [RFC9012] Patel, K., Van de Velde, G., Sangli, S., and J. Scudder, "The BGP Tunnel Encapsulation Attribute", RFC 9012, DOI 10.17487/RFC9012, April 2021, <<https://www.rfc-editor.org/info/rfc9012>>.
- [RFC9256] Filsfils, C., Talaulikar, K., Ed., Voyer, D., Bogdanov, A., and P. Mattes, "Segment Routing Policy Architecture", RFC 9256, DOI 10.17487/RFC9256, July 2022, <<https://www.rfc-editor.org/info/rfc9256>>.
- [RFC9830] Previdi, S., Filsfils, C., Talaulikar, K., Ed., Mattes, P., and D. Jain, "Advertising Segment Routing Policies in BGP", RFC 9830, DOI 10.17487/RFC9830, September 2025, <<https://www.rfc-editor.org/info/rfc9830>>.

7.2. Informative References

- [RFC7942] Sheffer, Y. and A. Farrel, "Improving Awareness of Running Code: The Implementation Status Section", BCP 205, RFC 7942, DOI 10.17487/RFC7942, July 2016, <<https://www.rfc-editor.org/info/rfc7942>>.
- [RFC9857] Previdi, S., Talaulikar, K., Ed., Dong, J., Gredler, H., and J. Tantsura, "Advertisement of Segment Routing Policies Using BGP - Link State", RFC 9857, DOI 10.17487/RFC9857, October 2025, <<https://www.rfc-editor.org/info/rfc9857>>.

[I-D.ietf-pce-multipath]

Koldychev, M. and S. Sidor, "Path Computation Element Communication Protocol (PCEP) Extensions for Signaling Multipath Information", Work in Progress, Internet-Draft, draft-ietf-pce-multipath-25, 13 May 2026, <<https://datatracker.ietf.org/doc/html/draft-ietf-pce-multipath-25>>.

Appendix A. Cross WG Information

This section describes cross-working group information for the IETF review process. This section will be removed by the RFC Editor before publication. The RFC Editor will also remove the references to [I-D.ietf-pce-multipath].

A.1. Spring WG

[RFC9256] details SR Policy architecture, but does not define any identifier for a Segment List. The Segment List ID was introduced in BGP-LS (Section 5.7.4 of [RFC9857]) and PCEP (Section 4.2 of [I-D.ietf-pce-multipath]). Note that the names are different due to the objects/TLVs in respective protocols but the semantics are identical.

A Segment List belongs to a Candidate Path. Note that the Segment List is meant to realize the objectives of a specific Candidate Path. Therefore, the segment list ID is scoped under the candidate path hierarchy. The segment list ID is a 32-bit non-zero number that serves as the identifier associated with a segment list. Currently, in BGP-LS and PCEP extensions, the segment list ID is scoped under the candidate path.

This document defines extensions to BGP SR Policy to specify the identifier of an SR Segment List. The definition of the segment list ID in this document is consistent with the specification of segment list ID in BGP-LS and PCEP extensions.

A.2. PCE WG

The BGP extension in this document for the identifier of segment list also could be implemented via PCEP according to Section 4.2 of [I-D.ietf-pce-multipath]. The Path ID uniquely identifies a Path within the context of an LSP. Path IDs MUST be unique across all these path types within the same LSP. In this document, Path IDs correspond to the identifier of a segment list under CP.

Sections 4.3 and 4.4 of [I-D.ietf-pce-multipath] describe the usage of Path IDs in load-balancing and multiple paths for protection scenarios, respectively. Additionally, Appendix A of [I-D.ietf-pce-multipath] specifies how Path IDs are encapsulated within the PCEP protocol.

A.3. SRv6OPS

This document is unrelated to SRv6OPS and only relates to BGP-TE extensions.

Authors' Addresses

Changwang Lin
New H3C Technologies
8 Yongjia North Road
Beijing
Haidian District, 100094
China
Email: linchangwang.04414@h3c.com

Weiqiang Cheng
China Mobile
32 Xuanwumen West Street
Beijing
Xicheng District, 100053
China
Email: chengweiqiang@chinamobile.com

Yao Liu
ZTE
China
Email: liu.yao71@zte.com.cn

Ketan Talaulikar
Cisco Systems
India
Email: ketant.ietf@gmail.com

Mengxiao Chen
New H3C Technologies
China
Email: chen.mengxiao@h3c.com