

Internet
Internet-Draft
Intended status: Standards Track
Expires: 7 January 2026

Y. Qu
Futurewei Technologies
A. Lindem
M. Joshi
Arrcus, Inc.
6 July 2025

YANG Model for IS-IS Application-Specific Link Attributes and Flexible
Algorithm
draft-ietf-lsr-isis-flex-algo-yang-00

Abstract

This document defines a YANG data model to support IS-IS Application-Specific Link Attributes and Flexible Algorithm.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 7 January 2026.

Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Overview	2
1.1. Requirements Language	2
2. YANG Module for IS-IS Application-Specific Link Attributes	2
3. YANG Module for IS-IS Flexible Algorithm	13
4. Security Considerations	25
5. IANA Considerations	25
6. Acknowledgements	26
7. Normative References	26
Appendix A. Example IS-IS Flex-Algo Configuration	28
Appendix B. Example IS-IS Flex-Algo Configuration (JSON)	29
Authors' Addresses	30

1. Overview

This document defines two YANG [RFC7950] data modules. The first module is to provide support for configuration and operational state for IS-IS Application-Specific Link Attributes as defined in [RFC9479], and the second module is to support IS-IS Flexible Algorithm as defined in [RFC9350]. Both modules are augmenting the IETF IS-IS YANG model [RFC9130].

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119.

2. YANG Module for IS-IS Application-Specific Link Attributes

This document defined a YANG module for IS-IS Application-Specific Link Attributes as defined in [RFC9479].

```

module: ietf-isis-link-attr
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis:
      +--rw isis-link-attr-op
        +--rw (link-attr-op-mode)
          +--:(legacy)
            | +--rw legacy?          empty
          +--:(transition)
            | +--rw transition?      empty
          +--:(app-specific)
            +--rw app-specific?      empty
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:interfaces
      /isis:interface:

```

```

+--rw isis-asla
  +--rw interface-asla* [app-id]
    +--rw app-id                uint16
    +--rw unidirectional-link-delay?  uint32
    +--rw metric-type?              uint8
    +--rw metric?                  uint32
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/isis:isis/isis:database
  /isis:levels/isis:lsp/isis:extended-is-neighbor
  /isis:neighbor/isis:instances/isis:instance:
+--ro asla-sub-tlvs
  +--ro asla-sub-tlv* []
    +--ro l-flag?          boolean
    +--ro sabm-length?      uint8
    +--ro r-flag?          boolean
    +--ro udabm-length?     uint8
    +--ro sabm
    | +--ro sabm-bits*      identityref
    +--ro udabm
    +--ro unknown-tlvs
      +--ro unknown-tlv* []
        +--ro type?        uint16
        +--ro length?      uint16
        +--ro value?       yang:hex-string
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/isis:isis/isis:database
  /isis:levels/isis:lsp/isis:mt-is-neighbor/isis:neighbor
  /isis:instances/isis:instance:
+--ro asla-sub-tlvs
  +--ro asla-sub-tlv* []
    +--ro l-flag?          boolean
    +--ro sabm-length?      uint8
    +--ro r-flag?          boolean
    +--ro udabm-length?     uint8
    +--ro sabm
    | +--ro sabm-bits*      identityref
    +--ro udabm
    +--ro unknown-tlvs
      +--ro unknown-tlv* []
        +--ro type?        uint16
        +--ro length?      uint16
        +--ro value?       yang:hex-string
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/isis:isis/isis:database
  /isis:levels/isis:lsp:
+--ro application-specific-srlg-tlv
  +--ro as-srlg-tlv* []
    +--ro neighbor-system-id?  isis:system-id

```

```

+--ro pseudo-node-id?      uint8
+--ro l-flag?               boolean
+--ro sabm-length?         uint8
+--ro r-flag?               boolean
+--ro udabm-length?        uint8
+--ro sabm
| +--ro sabm-bits*         identityref
+--ro udabm
+--ro length-of-sub-tlvs?   uint8
+--ro link-id-sub-tlvs
| +--ro link-local-remote-ids
| | +--ro link-local-id?   union
| | +--ro link-remote-id?  union
| +--ro ipv4-interface-addr
| | +--ro ipv4-int-addr?   inet:ipv4-address
| +--ro ipv4-neighbor-addr
| | +--ro ipv4-neighbor-addr?  inet:ipv4-address
| +--ro ipv6-interface-addr
| | +--ro ipv6-int-addr?   inet:ipv6-address
| +--ro ipv6-neighbor-addr
| | +--ro ipv6-neighbor-addr?  inet:ipv6-address
+--ro srlgs
   +--ro srlg*             uint32

```

```

<CODE BEGINS> file "ietf-isis-link-attr@2025-07-06.yang"
module ietf-isis-link-attr {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-isis-link-attr";

  prefix isis-link-attr;

  import ietf-inet-types {
    prefix inet;
    reference
      "RFC 6991 - Common YANG Data Types";
  }

  import ietf-routing {
    prefix rt;
    reference
      "RFC 8349: A YANG Data Model for Routing
      Management (NMDA Version)";
  }

  import ietf-isis {
    prefix isis;
    reference
      "RFC 9130: YANG Data Model for the IS-IS Protocol";
  }

```

```
}

organization
  "IETF LSR - Link State Routing Working Group";

contact
  "WG Web:    <https://datatracker.ietf.org/wg/lsr>
  WG List:    <mailto:lsr@ietf.org>

  Author:     Yingzhen Qu
               <mailto:yingzhen.ietf@gmail.com>
  Author:     Acee Lindem
               <mailto:acee.ietf@gmail.com>
  Author:     Stephane Litkowski
               <mailto:slitkows.ietf@gmail.com>
  Author:     Madhavi Joshi
               <madhavi@arrcus.com>
  ";

description
  "This YANG module defines the configuration and operational
  state for IS-IS application specific link attributes feature as
  defined in RFC 9479.

  This YANG model conforms to the Network Management
  Datastore Architecture (NMDA) as described in RFC 8342.

  Copyright (c) 2025 IETF Trust and the persons identified as
  authors of the code. All rights reserved.

  Redistribution and use in source and binary forms, with or
  without modification, is permitted pursuant to, and subject to
  the license terms contained in, the Revised BSD License set
  forth in Section 4.c of the IETF Trust's Legal Provisions
  Relating to IETF Documents
  (http://trustee.ietf.org/license-info).

  This version of this YANG module is part of RFC XXXX;
  see the RFC itself for full legal notices.

  The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL
  NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED',
  'MAY', and 'OPTIONAL' in this document are to be interpreted as
  described in BCP 14 (RFC 2119) (RFC 8174) when, and only when,
  they appear in all capitals, as shown here."

reference "RFC XXXX";
```

```
revision 2025-07-06 {
  description
    "Initial version";
  reference
    "RFC XXXX: A YANG Data Model for IS-IS Application-Specific
    Link Attributes.";
}

identity sabm-bit {
  description
    "Base identity for sabm bits.";
  reference
    "RFC 8919: IS-IS Application-Specific Link Attributes";
}

identity rsvp-te-bit {
  base sabm-bit;
  description
    "R bit, RSVP-TE.";
}

identity sr-policy-bit {
  base sabm-bit;
  description
    "S bit, Segment Routing Policy.";
}

identity lfa-bit {
  base sabm-bit;
  description
    "F bit, Loop Free Alternate (LFA). Includes all LFA types.";
}

identity flex-algo-bit {
  base sabm-bit;
  description
    "X bit, flexible algorithm.";
  reference
    "RFC 9350: IGP Flexible Algorithm, Section 12.";
}

grouping application-identifier-bit-mask {
  description
    "Identification of the set of applications associated with
    link attribute advertisements";

  leaf l-flag {
    type boolean;
  }
}
```

```
    description
      "Legacy Flag. When set, all of the applications
       specified in the bit mask MUST use the legacy
       advertisements.";
  }
  leaf sabm-length {
    type uint8;
    description
      "Standard Application Identifier Bit Mask Length in
       octets.";
  }
  leaf r-flag {
    type boolean;
    default false;
    description
      "Reserved.";
  }
  leaf udabm-length {
    type uint8;
    description
      "User Defined Application Identifier Bit Mask Length
       in octets.";
  }
  container sabm {
    leaf-list sabm-bits {
      type identityref {
        base sabm-bit;
      }
    }
    description
      "SABM bits list. This list will contain
       identities for the bits which are set in the
       SABA bits.";
  }
  description
    "Standard Application Identifier Bit Mask.";
}
container udabm {
  description
    "User Defined Application Identifier Bit Mask.
     This container is to be augmented by user defined
     applications.";
}
}

grouping application-specific-link-attributes-sub-tlv {
  description
    "Grouping for specification of the applications and
     application-specific attribute values.";
```

```
    container asla-sub-tlvs {
      list asla-sub-tlv {
        uses application-identifier-bit-mask;
        uses isis:unknown-tlvs;
        description
          "List of application specific link attributes sub-tlvs.";
      }
      description
        "Application specific link attributes sub-tlv.";
    }
  }

  grouping application-specific-srlg-tlv {
    description
      "Grouping of a TLV to advertise application-specific
      SRLGs for a given link.";
    container application-specific-srlg-tlv {
      list as-srlg-tlv {
        leaf neighbor-system-id {
          type isis:system-id;
          description
            "Neighbor System-ID.";
        }
        leaf pseudo-node-id {
          type uint8;
          description
            "Pseudo-node ID.";
        }
      }
      uses application-identifier-bit-mask;
      leaf length-of-sub-tlvs {
        type uint8;
        description
          "Length of sub-tlvs.";
      }
    }

    container link-id-sub-tlvs {
      description
        "Link Identifier sub-TLVs.";
      container link-local-remote-ids {
        description
          "Link local/remote identifier sub-tlv.";
        leaf link-local-id {
          type union {
            type inet:ipv4-address;
            type uint32;
          }
          description
            "Local identifier of the link."
        }
      }
    }
  }
}
```

```
        It could be an IPv4 address or a local identifier.";
    }
    leaf link-remote-id {
        type union {
            type inet:ipv4-address;
            type uint32;
        }
        description
            "Remote identifier of the link.
            It could be an IPv4 address or a remotely learned
            identifier.";
    }
}
container ipv4-interface-addr {
    leaf ipv4-int-addr {
        type inet:ipv4-address;
        description
            "IPv4 address for the interface.";
    }
    description
        "IPv4 interface address sub-tlv.";
}
container ipv4-neighbor-addr {
    leaf ipv4-neighbor-addr {
        type inet:ipv4-address;
        description
            "IPv4 address for a neighboring router
            on this link.";
    }
    description
        "IPv4 neighbor address sub-tlv.";
}
container ipv6-interface-addr {
    leaf ipv6-int-addr {
        type inet:ipv6-address;
        description
            "IPv6 address for the interface.";
    }
    description
        "IPv6 interface address sub-tlv.";
}
container ipv6-neighbor-addr {
    leaf ipv6-neighbor-addr {
        type inet:ipv6-address;
        description
            "IPv6 address for a neighboring router
            on this link.";
    }
}
```

```
        description
            "IPv6 neighbor address sub-tlv.";
    }
}

container srlgs {
    description "List of SRLGs.";
    leaf-list srlg {
        type uint32;
        description
            "SRLG value of the link.";
    }
}

description
    "List of application specific SRLG tlvs.";
}
description
    "Application specific SRLG tlv.";
}
}

/* Configuration */
augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis" {
    when "/rt:routing/rt:control-plane-protocols/" +
        "rt:control-plane-protocol/rt:type = 'isis:isis'" {
        description
            "This augment ISIS routing protocol when used";
    }
    description
        "This augments ISIS protocol configuration
        with application specific link attributes.";

    container isis-link-attr-op {
        choice link-attr-op-mode {
            mandatory "true";
            leaf legacy {
                type empty;
                description
                    "Only send legacy advertisements.";
            }
            leaf transition {
                type empty;
                description
                    "Send both application-specific and legacy
                    advertisements.";
            }
        }
    }
}
```

```
    }
    leaf app-specific{
      type empty;
      description
        "Only send application-specific advertisements.";
    }
    description
      "Link attributes mode";
  }

  description
    "Link attributes operation mode.";
}

augment "/rt:routing/" +
  "rt:control-plane-protocols/rt:control-plane-protocol"+
  "/isis:isis/isis:interfaces/isis:interface" {
  when "/rt:routing/rt:control-plane-protocols/"+
    "rt:control-plane-protocol/"+
    "rt:type = 'isis:isis'" {
    description
      "This augment ISIS routing protocol when used.";
  }
  description
    "This augments ISIS interface configuration
    with application specific link attributes.";

  container isis-asla {
    list interface-asla {
      key app-id;

      leaf app-id {
        type uint16 {
          range "0 .. 1023";
        }
        description
          "Application ID.
          0 - RSVP TE. 1 - Segment Routing Policy.
          2 - Loop-Free Alternate.";
      }

      leaf unidirectional-link-delay {
        type uint32 {
          range "0 .. 16777215";
        }
        description
          "This 24-bit field carries the average link delay in
```

```
        microseconds.";
    }

    leaf metric-type {
        type uint8;
        description
            "IGP metric type.";
    }

    leaf metric {
        type uint32 {
            range "1 .. 16777215";
        }
        description
            "metric value.";
    }

    description
        "ASLA interface configuration.";
}
description
    "Application specific link attributes configuration.";
}

/* TLV 22 */
augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:database/isis:levels/isis:lsp"+
    "/isis:extended-is-neighbor/isis:neighbor"+
    "/isis:instances/isis:instance" {
    when "/rt:routing/rt:control-plane-protocols/"+
        "rt:control-plane-protocol/rt:type = 'isis:isis'" {
        description
            "This augment ISIS routing protocol when used";
    }
    description
        "This augments ISIS protocol LSDB TLV22.";

    uses application-specific-link-attributes-sub-tlv;
}

/* TLV 223 */
augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:database/isis:levels/isis:lsp"+
    "/isis:mt-is-neighbor/isis:neighbor"+
    "/isis:instances/isis:instance" {
```

```

when "/rt:routing/rt:control-plane-protocols/" +
  "rt:control-plane-protocol/rt:type = 'isis:isis'" {
  description
    "This augment ISIS routing protocol when used";
}
description
  "This augments ISIS protocol LSDB TLV223.";

  uses application-specific-link-attributes-sub-tlv;
}

/* application-specific SRLG TLV 238 */
augment "/rt:routing/" +
  "rt:control-plane-protocols/rt:control-plane-protocol"+
  "/isis:isis/isis:database/isis:levels/isis:lsp" {
when "/rt:routing/rt:control-plane-protocols/" +
  "rt:control-plane-protocol/rt:type = 'isis:isis'" {
  description
    "This augment ISIS routing protocol when used";
}
description
  "This augments ISIS protocol LSDB.";

  uses application-specific-srlg-tlv;
}
}
<CODE ENDS>

```

3. YANG Module for IS-IS Flexible Algorithm

This section defines the YANG module for IS-IS Flexible Algorithm. The module uses the identities defined in the IANA-maintained YANG modules for IGP Algorithm Types [IANA-IGP-ALGO-Types] and IGP Metric Type [IANA-IGP-Metric-Types] in [I-D.ietf-lsr-ospf-flex-algo-yang].

```

module: ietf-isis-flex-algo
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis:
  +-rw isis-flex-algo
    +-rw flex-algo* [algo-number]
      +-rw algo-number          uint8
      +-rw advertise-definition? boolean
      +-rw admin-groups
      |   {te-types:extended-admin-groups,
      |     te-types:named-extended-admin-groups}?
      +-rw exclude-admin-groups* leafref
      +-rw include-any-admin-groups* leafref
      +-rw include-all-admin-groups* leafref

```

```

    +--rw exclude-srlgs*
    |   -> /te:te/globals/named-srlgs/named-srlg/name
    |   {te-types:named-srlg-groups}?
    +--rw metric-type?          identityref
    +--rw calc-type?            identityref
    +--rw prefix-metric!
    +--rw priority?             uint8
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:database
    /isis:levels/isis:lsp/isis:router-capabilities:
+--ro fad-tlvs
+--ro fad-tlv* []
+--ro flex-algo?          uint8
+--ro metric-type?        identityref
+--ro calc-type?          identityref
+--ro priority?           uint8
+--ro fa-ex-ag-sub-tlv
| +--ro extended-admin-groups*  uint64
+--ro fa-in-any-ag-sub-tlv
| +--ro extended-admin-groups*  uint64
+--ro fa-in-all-ag-sub-tlv
| +--ro extended-admin-groups*  uint64
+--ro fad-flags-sub-tlv
| +--ro fad-flags*  identityref
+--ro fa-ex-srlg-sub-tlv
| +--ro srlgs*  uint32
+--ro unknown-tlvs
+--ro unknown-tlv* []
+--ro type?      uint16
+--ro length?    uint16
+--ro value?     yang:hex-string
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:database
    /isis:levels/isis:lsp/isis:extended-ipv4-reachability
    /isis:prefixes:
+--ro fapm-sub-tlvs
+--ro fapm-sub-tlv* []
+--ro flex-algo?  uint8
+--ro metric?     uint32
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:database
    /isis:levels/isis:lsp/isis:mt-extended-ipv4-reachability
    /isis:prefixes:
+--ro fapm-sub-tlvs
+--ro fapm-sub-tlv* []
+--ro flex-algo?  uint8
+--ro metric?     uint32
augment /rt:routing/rt:control-plane-protocols

```

```

    /rt:control-plane-protocol/isis:isis/isis:database
    /isis:levels/isis:lsp/isis:ipv6-reachability
    /isis:prefixes:
+--ro fapm-sub-tlvs
  +--ro fapm-sub-tlv* []
    +--ro flex-algo?   uint8
    +--ro metric?     uint32
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/isis:isis/isis:database
  /isis:levels/isis:lsp/isis:mt-ipv6-reachability
  /isis:prefixes:
+--ro fapm-sub-tlvs
  +--ro fapm-sub-tlv* []
    +--ro flex-algo?   uint8
    +--ro metric?     uint32

notifications:
+---n flex-algo-not-supported
  +--ro routing-protocol-name?  leafref
  +--ro isis-level?            level
  +--ro flex-algo-number?       uint8

<CODE BEGINS> file "ietf-isis-flex-algo@2025-07-06.yang"
module ietf-isis-flex-algo {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-isis-flex-algo";
  prefix isis-flex-algo;

  import ietf-routing {
    prefix rt;
    reference
      "RFC 8349: A YANG Data Model for Routing
        Management (NMDA Version)";
  }

  import ietf-te-types {
    prefix te-types;
    reference
      "RFC8776: Common YANG Data Types for Traffic Engineering.";
  }

  import ietf-isis {
    prefix isis;
    reference
      "RFC 9130: YANG Data Model for the IS-IS Protocol";
  }

  import ietf-te {
```

```
    prefix te;
  }

  import iana-igp-algo-types {
    prefix iana-algo-types;
  }

  import iana-igp-metric-types {
    prefix iana-metric-type;
  }

  organization
    "IETF LSR - Link State Routing Working Group";
  contact
    "WG Web:    <https://datatracker.ietf.org/wg/lsr>
    WG List:    <mailto:spring@ietf.org>

    Author:     Yingzhen Qu
                <mailto:yingzhen.ietf@gmail.com>
    Author:     Acee Lindem
                <mailto:acee.ietf@gmail.com>
    Author:     Stephane Litkowski
                <mailto:slitkows.ietf@gmail.com>
    Author:     Madhavi Joshi
                <madhavi@arrcus.com>

    ";

  description
    "The YANG module defines the configuration and operational
    state for ISIS Flexible Algorithm as defined in RFC 9350.

    This YANG model conforms to the Network Management
    Datastore Architecture (NMDA) as described in RFC 8342.

    Copyright (c) 2025 IETF Trust and the persons identified as
    authors of the code.  All rights reserved.

    Redistribution and use in source and binary forms, with or
    without modification, is permitted pursuant to, and subject to
    the license terms contained in, the Revised BSD License set
    forth in Section 4.c of the IETF Trust's Legal Provisions
    Relating to IETF Documents
    (https://trustee.ietf.org/license-info).

    This version of this YANG module is part of RFC XXXX;
    see the RFC itself for full legal notices.
```

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document are to be interpreted as described in BCP 14 (RFC 2119) (RFC 8174) when, and only when, they appear in all capitals, as shown here.";

reference

"RFC XXXX: YANG Data Model for ISIS Flexible Algorithm.";

revision 2025-07-06 {

description

"Initial Version";

reference

"RFC XXXX: YANG Data Model for ISIS Flexible Algorithm.";

}

/* Identities */

identity fad-flags {

description

"Base identity for ISIS FAD flags.";

}

identity m-bit {

base fad-flags;

description

"M bit, when set, the flex-algo specific prefix and ASBR metric MUST be used for inter-area and external prefix calculation.";

}

/* Groupings */

grouping fa-ex-ag-sub-tlv {

container fa-ex-ag-sub-tlv {

leaf-list extended-admin-groups {

type uint64;

description

"Extended administrative group as defined in RFC 7308.";

}

description

"The flex-algo exclude admin group sub-tlv.";

}

description

"The flex-algo exclude admin group sub-tlv.";

}

grouping fa-in-any-ag-sub-tlv {

```
    container fa-in-any-ag-sub-tlv {
      leaf-list extended-admin-groups {
        type uint64;
        description
          "Extended administrative group as defined in RFC 7308.";
      }
      description
        "The flex-algo include-any admin group sub-tlv.";
    }
  description
    "The flex-algo include-any admin group sub-tlv.";
}

grouping fa-in-all-ag-sub-tlv {
  container fa-in-all-ag-sub-tlv {
    leaf-list extended-admin-groups {
      type uint64;
      description
        "Extended administrative group as defined in RFC 7308.";
    }
    description
      "The flex-algo include-all admin group sub-tlv.";
  }
  description
    "The flex-algo include-all admin group sub-tlv.";
}

grouping fad-flags-sub-tlv {
  container fad-flags-sub-tlv {
    leaf-list fad-flags {
      type identityref {
        base fad-flags;
      }
      description
        "Flex-algo definition flags list.";
    }
    description
      "ISIS flex-algo definition flags.";
  }
  description
    "The flex-algo definition flags sub-tlv.";
}

grouping fa-ex-srlg-sub-tlv {
  container fa-ex-srlg-sub-tlv {
    leaf-list srlgs {
      type uint32;
      description
```

```
        "SRLG value as defined in RFC 4203.";
    }
    description
        "The flex-algo exclude SRLG sub-tlv.";
}
description
    "The flex-algo exclude SRLG sub-tlv.";
}

grouping fad-tlvs {
    container fad-tlvs {
        list fad-tlv {
            leaf flex-algo {
                type uint8;
                description
                    "Flex-algo number, value between 128 and 255 inclusive.";
            }
            leaf metric-type {
                type identityref {
                    base iana-metric-type:metric-type;
                }
                description
                    "Type of metric to be used during the calculation.";
            }
            leaf calc-type {
                type identityref {
                    base iana-algo-types:algo-type;
                }
                description
                    "IGP algorithm types, value from 0 to 127 as
                    defined under 'Interior Gateway Protocol (IGP)
                    Parameter' by IANA.";
            }
            leaf priority {
                type uint8;
                description
                    "Priority of the advertisement.";
            }
        }

        uses fa-ex-ag-sub-tlv;
        uses fa-in-any-ag-sub-tlv;
        uses fa-in-all-ag-sub-tlv;
        uses fad-flags-sub-tlv;
        uses fa-ex-srlg-sub-tlv;
        uses isis:unknown-tlvs;

        description
            "List of flex-algo definition TLVs.";
```

```
    }
    description
      "ISIS Flexible Algorithm Definition TLV.";
  }
  description
    "ISIS Flexible Algorithm Definition (FAD) TLV.";
}

grouping fapm-sub-tlvs {
  container fapm-sub-tlvs {
    list fapm-sub-tlv {
      leaf flex-algo {
        type uint8;
        description
          "Flex-algo number, value between 128 and 255
            inclusive.";
      }
      leaf metric {
        type uint32;
        description
          "Prefix metric.";
      }
    }
    description
      "List of flex-algo prefix sub-tlvs.";
  }
  description
    "Flex-algo prefix metric sub-tlvs.";
}
description
  "Flexible Algorithm Prefix Metric (FAPM) sub TLVs.";
}

/* Configurations */

augment "/rt:routing/" +
  "rt:control-plane-protocols/rt:control-plane-protocol"+
  "/isis:isis" {
  when "/rt:routing/rt:control-plane-protocols/" +
    "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
      "This augment ISIS routing protocol when used";
  }
  description
    "This augments ISIS protocol configuration
      with flexible algorithm.";

  container isis-flex-algo {
```

```
list flex-algo {
  key "algo-number";

  leaf algo-number {
    type uint8 {
      range "128..255";
    }
    description
      "An identifier in the range 128-255 that's associated
       with the Flexible Algorithm Definition.";
  }

  leaf advertise-definition {
    type boolean;
    default true;
    description
      "Enable to advertise the flex-algo definition.";
  }

  container admin-groups {
    if-feature "te-types:extended-admin-groups";
    if-feature "te-types:named-extended-admin-groups";
    leaf-list exclude-admin-groups {
      type leafref {
        path "/te:te/te:globals/te:named-admin-groups/"
          + "te:named-admin-group/te:name";
      }
      description
        "Exclude rule used during the flex-algo
         path computation.";
    }
    leaf-list include-any-admin-groups {
      type leafref {
        path "/te:te/te:globals/te:named-admin-groups/"
          + "te:named-admin-group/te:name";
      }
      description
        "Include-any rule used during the flex-algo
         path computation.";
    }
    leaf-list include-all-admin-groups {
      type leafref {
        path "/te:te/te:globals/te:named-admin-groups/"
          + "te:named-admin-group/te:name";
      }
      description
        "Include-all rule used during the flex-algo
         path computation.";
    }
  }
}
```

```
    }
    description
      "Specify links for the flex-algo path computation.";
  }

  leaf-list exclude-srlgs {
    if-feature "te-types:named-srlg-groups";
    type leafref {
      path "/te:te/te:globals/te:named-srlgs/te:named-srlg/"
        + "te:name";
    }
    description
      "Shared Risk Link Groups (SRLGs) to be excluded during
      the flex-algo path computation.";
  }

  leaf metric-type {
    type identityref {
      base iana-metric-type:metric-type;
    }
    description
      "Type of metric to be used during the calculation.";
  }

  leaf calc-type {
    type identityref {
      base iana-algo-types:algo-type;
    }
    default iana-algo-types:algo-spf;
    description
      "Calculation-type. Value from 0-127 inclusive from the IANA
      'IGP Algorithm Types' registry defined under the 'Interior
      Gateway Protocol (IGP) Parameters' registry.";
  }

  container prefix-metric {
    presence
      "Use flex-algo specific prefix metric.";
    description
      "Use flex-algo prefix metric.";
  }

  leaf priority {
    type uint8;
    description
      "Priority of the advertisement.";
  }
}
```

```
        description
            "List of flex-algo configurations.";
    }
    description
        "Flexible Algorithm configuration.";
}

/* Database */

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:database/isis:levels/isis:lsp"+
    "/isis:router-capabilities" {
    when "/rt:routing/rt:control-plane-protocols/" +
        "rt:control-plane-protocol/" +
        "rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
    }
    description
        "This augments ISIS protocol LSDB router capability.";

    uses fad-tlvs;
}

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:database/isis:levels/isis:lsp"+
    "/isis:extended-ipv4-reachability/" +
    "isis:prefixes" {
    when "/rt:routing/rt:control-plane-protocols/" +
        "rt:control-plane-protocol/" +
        "rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
    }
    description
        "This augments ISIS protocol LSDB prefix.";
    uses fapm-sub-tlvs;
}

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:database/isis:levels/isis:lsp"+
    "/isis:mt-extended-ipv4-reachability/isis:prefixes" {
    when "/rt:routing/rt:control-plane-protocols/" +
        "rt:control-plane-protocol/" +
```

```
        "rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
}
    description
        "This augments ISIS protocol LSDB prefix.";
        uses fapm-sub-tlvs;
}

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:database/isis:levels/isis:lsp"+
    "/isis:ipv6-reachability/isis:prefixes" {
when "/rt:routing/rt:control-plane-protocols/" +
    "rt:control-plane-protocol/" +
    "rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
}
    description
        "This augments ISIS protocol LSDB prefix.";
        uses fapm-sub-tlvs;
}

augment "/rt:routing/" +
    "rt:control-plane-protocols/rt:control-plane-protocol"+
    "/isis:isis/isis:database/isis:levels/isis:lsp"+
    "/isis:mt-ipv6-reachability/isis:prefixes" {
when "/rt:routing/rt:control-plane-protocols/" +
    "rt:control-plane-protocol/" +
    "rt:type = 'isis:isis'" {
    description
        "This augment ISIS routing protocol when used";
}
    description
        "This augments ISIS protocol LSDB prefix.";
        uses fapm-sub-tlvs;
}

/* notification */

notification flex-algo-not-supported {
    uses isis:notification-instance-hdr;
    leaf flex-algo-number {
        type uint8 {
            range "128..255";
        }
    }
    description
```

```
        "Flex-algo identifier which is not supported by the IS-IS
          instance.";
      }
      description
        "This notification is sent when an IS-IS instance does not
         support this flex-algo.";
    }
  }
<CODE ENDS>
```

4. Security Considerations

The YANG modules specified in this document define a schema for data that is designed to be accessed via network management protocols such as NETCONF [RFC6241] or RESTCONF [RFC8040]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [RFC6242]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [RFC5246].

The NETCONF access control model [RFC6536] provides the means to restrict access for particular NETCONF or RESTCONF users to a pre-configured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in the modules that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations.

Some of the readable data nodes in the modules may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. The exposure of the Link State Database (LSDB) will expose the detailed topology of the network. This may be undesirable since both due to the fact that exposure may facilitate other attacks. Additionally, network operators may consider their topologies to be sensitive confidential data.

5. IANA Considerations

This document registers a URI in the IETF XML registry [RFC3688]. Following the format in [RFC3688], the following registrations are requested:

URI: urn:ietf:params:xml:ns:yang:ietf-isis-link-attr
Registrant Contact: The IESG.
XML: N/A, the requested URI is an XML namespace.

URI: urn:ietf:params:xml:ns:yang:ietf-isis-flex-algo
Registrant Contact: The IESG.
XML: N/A, the requested URI is an XML namespace.

This document registers the YANG module in the YANG Module Names registry [RFC6020].

name: ietf-isis-link-attr
Maintained by IANA? N
namespace: urn:ietf:params:xml:ns:yang:ietf-isis-link-attr
prefix: isis-link-attr
reference: RFC XXXX

name: ietf-isis-flex-algo
Maintained by IANA? N
namespace: urn:ietf:params:xml:ns:yang:ietf-isis-flex-algo
prefix: isis-flex-algo
reference: RFC XXXX

6. Acknowledgements

This document was produced using Marshall Rose's xml2rfc tool.

The YANG model was developed using the suite of YANG tools written and maintained by numerous authors.

7. Normative References

[I-D.ietf-lsr-ospf-flex-algo-yang]
Qu, Y. and A. Lindem, "YANG Data Model for OSPF Application-Specific Link Attributes and Flexible Algorithm", Work in Progress, Internet-Draft, draft-ietf-lsr-ospf-flex-algo-yang-00, 6 July 2025, <<https://datatracker.ietf.org/doc/html/draft-ietf-lsr-ospf-flex-algo-yang-00>>.

[IANA-IGP-ALGO-Types]
IANA, "IGP Algorithm Types", <<https://www.iana.org/assignments/igp-parameters>>.

[IANA-IGP-Metric-Types]
IANA, "IGP Metric-Type", <<https://www.iana.org/assignments/igp-parameters>>.

[IANA-YANG-Parameters]

IANA, "YANG Module Names",
<<https://www.iana.org/assignments/yang-parameters>>.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", RFC 5246, DOI 10.17487/RFC5246, August 2008, <<https://www.rfc-editor.org/info/rfc5246>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", RFC 6242, DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC6536] Bierman, A. and M. Bjorklund, "Network Configuration Protocol (NETCONF) Access Control Model", RFC 6536, DOI 10.17487/RFC6536, March 2012, <<https://www.rfc-editor.org/info/rfc6536>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.

- [RFC8349] Lhotka, L., Lindem, A., and Y. Qu, "A YANG Data Model for Routing Management (NMDA Version)", RFC 8349, DOI 10.17487/RFC8349, March 2018, <<https://www.rfc-editor.org/info/rfc8349>>.
- [RFC8792] Watsen, K., Auerswald, E., Farrel, A., and Q. Wu, "Handling Long Lines in Content of Internet-Drafts and RFCs", RFC 8792, DOI 10.17487/RFC8792, June 2020, <<https://www.rfc-editor.org/info/rfc8792>>.
- [RFC9130] Litkowski, S., Ed., Yeung, D., Lindem, A., Zhang, J., and L. Lhotka, "YANG Data Model for the IS-IS Protocol", RFC 9130, DOI 10.17487/RFC9130, October 2022, <<https://www.rfc-editor.org/info/rfc9130>>.
- [RFC9350] Psenak, P., Ed., Hegde, S., Filsfils, C., Talaulikar, K., and A. Gulko, "IGP Flexible Algorithm", RFC 9350, DOI 10.17487/RFC9350, February 2023, <<https://www.rfc-editor.org/info/rfc9350>>.
- [RFC9479] Ginsberg, L., Psenak, P., Previdi, S., Henderickx, W., and J. Drake, "IS-IS Application-Specific Link Attributes", RFC 9479, DOI 10.17487/RFC9479, October 2023, <<https://www.rfc-editor.org/info/rfc9479>>.

Appendix A. Example IS-IS Flex-Algo Configuration

The following is an example configuration for IS-IS Flexible Algorithm using the YANG model defined in this document.

Note: '\ ' line wrapping per [RFC8792].

```
<routing xmlns="urn:ietf:params:xml:ns:yang:ietf-routing">
  <control-plane-protocols>
    <control-plane-protocol>
      <type>isis:isis</type>
      <name>default</name>
      <isis xmlns="urn:ietf:params:xml:ns:yang:ietf-isis">
        <isis-flex-algo xmlns="urn:ietf:params:xml:ns:yang:\
ietf-isis-flex-algo">
          <flex-algo>
            <algo-number>128</algo-number>
            <advertise-definition>true</advertise-definition>
            <admin-groups>
              <exclude-admin-groups>red</exclude-admin-groups>
              <include-any-admin-groups>blue</include-any-admin-groups>
              <include-all-admin-groups>green</include-all-admin-groups>
            </admin-groups>
            <exclude-srlgs>SRLG1</exclude-srlgs>
            <metric-type>iana-metric-type:igp-metric</metric-type>
            <calc-type>iana-algo-types:algo-spf</calc-type>
            <prefix-metric/>
            <priority>10</priority>
          </flex-algo>
        </isis-flex-algo>
      </isis>
    </control-plane-protocol>
  </control-plane-protocols>
</routing>
```

Appendix B. Example IS-IS Flex-Algo Configuration (JSON)

The following is an example configuration for IS-IS Flexible Algorithm in JSON format using the YANG model defined in this document.

```
{
  "ietf-routing:routing": {
    "control-plane-protocols": {
      "control-plane-protocol": [
        {
          "type": "ietf-isis:isis",
          "name": "default",
          "ietf-isis:isis": {
            "ietf-isis-flex-algo:isis-flex-algo": {
              "flex-algo": [
                {
                  "algo-number": 128,
                  "advertise-definition": true,
                  "admin-groups": {
                    "exclude-admin-groups": ["red"],
                    "include-any-admin-groups": ["blue"],
                    "include-all-admin-groups": ["green"]
                  },
                  "exclude-srlgs": ["SRLG1"],
                  "metric-type": "iana-metric-type:igp-metric",
                  "calc-type": "iana-algo-types:algo-spf",
                  "prefix-metric": {},
                  "priority": 10
                }
              ]
            }
          }
        }
      ]
    }
  }
}
```

Authors' Addresses

Yingzhen Qu
Futurewei Technologies
United States of America
Email: yingzhen.ietf@gmail.com

Acee Lindem
Arrcus, Inc.
United States of America
Email: acee.ietf@gmail.com

Madhavi Joshi
Arrcus, Inc.
United States of America
Email: madhavi@arrcus.com