

Internet
Internet-Draft
Intended status: Standards Track
Expires: 1 November 2026

Y. Qu
Futurewei Technologies
A. Lindem
M. Joshi
Arrcus, Inc.
30 April 2026

YANG Data Model for IS-IS Application-Specific Link Attributes and
Flexible Algorithm
draft-ietf-lsr-isis-flex-algo-yang-08

Abstract

This document defines a YANG data model to support IS-IS Application-Specific Link Attributes and Flexible Algorithm.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 1 November 2026.

Copyright Notice

Copyright (c) 2026 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Overview	2
1.1. Requirements Language	2
2. YANG Module for IS-IS Application-Specific Link Attributes	2
3. YANG Module for IS-IS Flexible Algorithm	15
4. Security Considerations	27
5. IANA Considerations	27
6. Acknowledgements	28
7. References	28
7.1. Normative References	28
7.2. Informative References	30
Appendix A. Example IS-IS Flex-Algo Configuration	30
Appendix B. Example IS-IS Flex-Algo Configuration (JSON)	31
Authors' Addresses	32

1. Overview

This document defines two YANG [RFC7950] data modules. The first module is to provide support for configuration and operational state for IS-IS Application-Specific Link Attributes as defined in [RFC9479], and the second module is to support IS-IS Flexible Algorithm as defined in [RFC9350]. Both modules are augmenting the IETF IS-IS YANG model [RFC9130].

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

2. YANG Module for IS-IS Application-Specific Link Attributes

This document defines a YANG module for IS-IS Application-Specific Link Attributes as defined in [RFC9479]. This YANG module references [RFC6991], [RFC8349], [RFC9130], and [RFC9350].

```
module: ietf-isis-link-attr
```

```
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/isis:isis:
    +--rw isis-link-attr
      +--rw (link-attr-op-mode)?
        +--:(legacy)
          | +--rw legacy?          empty
        +--:(transition)
```

```

    |   +--rw transition?      empty
+--:(app-specific)
    +--rw app-specific?      empty
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:interfaces
    /isis:interface:
+--rw isis-asla
    +--rw interface-asla* [link-attr-app]
        +--rw link-attr-app      identityref
        +--rw te-metric?         uint32
        +--rw admin-group?      uint32
        +--rw srlgs
            +--rw srlg*         uint32
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:database
    /isis:levels/isis:lsp/isis:extended-is-neighbor
    /isis:neighbor/isis:instances/isis:instance:
+--ro asla-sub-tlvs
    +--ro asla-sub-tlv* []
        +--ro l-flag?           boolean
        +--ro sabm-length?      uint8
        +--ro udabm-length?     uint8
        +--ro sabm
            |   +--ro sabm-bits*  identityref
        +--ro udabm
        +--ro te-metric?        uint32
        +--ro admin-group?      uint32
        +--ro max-bandwidth?
            |   rt-types:bandwidth-ieee-float32
        +--ro max-reservable-bandwidth?
            |   rt-types:bandwidth-ieee-float32
        +--ro unreserved-bandwidths
            |   +--ro unreserved-bandwidth* []
            |       +--ro priority?          uint8
            |       +--ro unreserved-bandwidth?
            |           rt-types:bandwidth-ieee-float32
        +--ro unidirectional-link-delay
            |   +--ro flags
            |       |   +--ro unidirectional-link-delay-subtlv-flags*
            |       |       identityref
            |       +--ro value?      uint32
        +--ro min-max-unidirectional-link-delay
            |   +--ro flags
            |       |   +--ro min-max-unidirectional-link-delay-subtlv-flags*
            |       |       identityref
            |       +--ro min-value?  uint32
            |       +--ro max-value?  uint32
        +--ro unidirectional-link-delay-variation

```

```

    |   +--ro value?    uint32
+--ro unidirectional-link-loss
    |   +--ro flags
    |   |   +--ro unidirectional-link-loss-subtlv-flags*
    |   |   |   identityref
    |   +--ro value?    uint32
+--ro unidirectional-link-residual-bandwidth
    |   +--ro value?    rt-types:bandwidth-ieee-float32
+--ro unidirectional-link-available-bandwidth
    |   +--ro value?    rt-types:bandwidth-ieee-float32
+--ro unidirectional-link-utilized-bandwidth
    |   +--ro value?    rt-types:bandwidth-ieee-float32
+--ro unknown-tlvs
    +--ro unknown-tlv* []
        +--ro type?      uint16
        +--ro length?    uint16
        +--ro value?     yang:hex-string
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:database
    /isis:levels/isis:lsp/isis:mt-is-neighbor
    /isis:neighbor/isis:instances/isis:instance:
+--ro asla-sub-tlvs
    +--ro asla-sub-tlv* []
        +--ro l-flag?          boolean
        +--ro sabm-length?      uint8
        +--ro udabm-length?     uint8
        +--ro sabm
        |   +--ro sabm-bits*    identityref
        +--ro udabm
        +--ro te-metric?        uint32
        +--ro admin-group?      uint32
        +--ro max-bandwidth?
        |   rt-types:bandwidth-ieee-float32
        +--ro max-reservable-bandwidth?
        |   rt-types:bandwidth-ieee-float32
        +--ro unreserved-bandwidths
        |   +--ro unreserved-bandwidth* []
        |   |   +--ro priority?          uint8
        |   |   +--ro unreserved-bandwidth?
        |   |   |   rt-types:bandwidth-ieee-float32
        +--ro unidirectional-link-delay
        |   +--ro flags
        |   |   +--ro unidirectional-link-delay-subtlv-flags*
        |   |   |   identityref
        |   +--ro value?    uint32
        +--ro min-max-unidirectional-link-delay
        |   +--ro flags
        |   |   +--ro min-max-unidirectional-link-delay-subtlv-flags*

```

```

    | | identityref
    | +--ro min-value?   uint32
    | +--ro max-value?   uint32
+--ro unidirectional-link-delay-variation
    | +--ro value?       uint32
+--ro unidirectional-link-loss
    | +--ro flags
    | | +--ro unidirectional-link-loss-subtlv-flags*
    | | | identityref
    | | +--ro value?     uint32
+--ro unidirectional-link-residual-bandwidth
    | +--ro value?       rt-types:bandwidth-ieee-float32
+--ro unidirectional-link-available-bandwidth
    | +--ro value?       rt-types:bandwidth-ieee-float32
+--ro unidirectional-link-utilized-bandwidth
    | +--ro value?       rt-types:bandwidth-ieee-float32
+--ro unknown-tlvs
    +--ro unknown-tlv* []
        +--ro type?       uint16
        +--ro length?     uint16
        +--ro value?      yang:hex-string
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:database
    /isis:levels/isis:lsp:
+--ro application-specific-srlg-tlv
    +--ro as-srlg-tlv* []
        +--ro neighbor-system-id?   isis:system-id
        +--ro pseudo-node-id?       uint8
        +--ro l-flag?                boolean
        +--ro sabm-length?           uint8
        +--ro udabm-length?          uint8
        +--ro sabm
        | +--ro sabm-bits*   identityref
        +--ro udabm
        +--ro length-of-sub-tlvs?   uint8
        +--ro link-id-sub-tlvs
        | +--ro link-local-remote-ids
        | | +--ro link-local-id?   union
        | | +--ro link-remote-id?  union
        | +--ro ipv4-interface-addr
        | | +--ro ipv4-int-addr?   inet:ipv4-address
        | +--ro ipv4-neighbor-addr
        | | +--ro ipv4-neighbor-addr?   inet:ipv4-address
        | +--ro ipv6-interface-addr
        | | +--ro ipv6-int-addr?   inet:ipv6-address
        | +--ro ipv6-neighbor-addr
        | | +--ro ipv6-neighbor-addr?   inet:ipv6-address
        +--ro srlgs

```

+--ro srlg* uint32

```
<CODE BEGINS> file "ietf-isis-link-attr@2026-04-30.yang"
module iETF-isis-link-attr {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-isis-link-attr";
  prefix isis-link-attr;

  import iETF-inet-types {
    prefix inet;
    reference
      "RFC 6991: Common YANG Data Types";
  }
  import iETF-routing {
    prefix rt;
    reference
      "RFC 8349: A YANG Data Model for Routing
        Management (NMDA Version)";
  }
  import iETF-isis {
    prefix isis;
    reference
      "RFC 9130: YANG Data Model for the IS-IS Protocol";
  }
  import iETF-routing-types {
    prefix rt-types;
    reference
      "RFC 8294: Common YANG Data Types for the
        Routing Area";
  }
  import iana-igp-link-attr-apps {
    prefix iana-link-attr-apps;
    reference
      "RFC XXXX: YANG Data Model for OSPF Application-Specific
        Link Attributes and Flexible Algorithm";
  }

  organization
    "IETF LSR - Link State Routing Working Group";
  contact
    "WG Web:   <https://datatracker.ietf.org/wg/lsr>
    WG List:   <mailto:lsr@ietf.org>

    Author:    Yingzhen Qu
               <mailto:yingzhen.ietf@gmail.com>
    Author:    Acee Lindem
               <mailto:acee.ietf@gmail.com>
    Author:    Madhavi Joshi
```

```

        <madhavi@arrcus.com>
";
description
  "This YANG module defines the configuration and operational
  state for IS-IS application specific link attributes feature as
  defined in RFC 9479.

  This YANG model conforms to the Network Management
  Datastore Architecture (NMDA) as described in RFC 8342.

  Copyright (c) 2026 IETF Trust and the persons identified as
  authors of the code. All rights reserved.

  Redistribution and use in source and binary forms, with or
  without modification, is permitted pursuant to, and subject to
  the license terms contained in, the Revised BSD License set
  forth in Section 4.c of the IETF Trust's Legal Provisions
  Relating to IETF Documents
  (http://trustee.ietf.org/license-info).

  This version of this YANG module is part of RFC XXXX;
  see the RFC itself for full legal notices.

  The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL
  NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED',
  'MAY', and 'OPTIONAL' in this document are to be interpreted as
  described in BCP 14 (RFC 2119) (RFC 8174) when, and only when,
  they appear in all capitals, as shown here."
;

revision 2026-04-30 {
  description
    "Initial version";
  reference
    "RFC XXXX: YANG Data Model for IS-IS Application-Specific
    Link Attributes and Flexible Algorithm";
}

grouping isis-te-link-attrs {
  description
    "IS-IS Application-Specific Link Attributes (ASLA)
    inherited from the base IS-IS TE attributes";
  leaf te-metric {
    type uint32;
    description
      "TE default metric.";
    reference
      "RFC 5305: IS-IS Extensions for Traffic Engineering,
      Section 3.7";
  }
}
```

```
}
leaf admin-group {
  type uint32;
  description
    "Administrative Group / Resource Class/Color.";
  reference
    "RFC 5305: IS-IS Extensions for Traffic Engineering,
    Section 3.1";
}
leaf max-bandwidth {
  type rt-types:bandwidth-ieee-float32;
  description
    "Maximum bandwidth.";
  reference
    "RFC 5305: IS-IS Extensions for Traffic Engineering,
    Section 3.4";
}
leaf max-reservable-bandwidth {
  type rt-types:bandwidth-ieee-float32;
  description
    "Maximum reservable bandwidth.";
  reference
    "RFC 5305: IS-IS Extensions for Traffic Engineering,
    Section 3.5";
}
container unreserved-bandwidths {
  description
    "All unreserved bandwidths.";
  list unreserved-bandwidth {
    leaf priority {
      type uint8 {
        range "0 .. 7";
      }
      description
        "Priority from 0 to 7.";
    }
    leaf unreserved-bandwidth {
      type rt-types:bandwidth-ieee-float32;
      description
        "Unreserved bandwidth.";
    }
  }
  description
    "List of unreserved bandwidths for different
    priorities.";
}
reference
  "RFC 5305: IS-IS Extensions for Traffic Engineering,
  Section 3.6";
```



```
    }
    reference
      "RFC 5305: IS-IS Extensions for Traffic Engineering";
  }

  grouping application-identifier-bit-mask {
    description
      "Identification of the set of applications associated with
       link attribute advertisements";
    leaf l-flag {
      type boolean;
      description
        "Legacy Flag. When set, all of the applications
         specified in the bit mask MUST use the legacy
         advertisements.";
    }
    leaf sabm-length {
      type uint8;
      description
        "Standard Application Identifier Bit Mask Length in
         octets.";
    }
    leaf udabm-length {
      type uint8;
      description
        "User Defined Application Identifier Bit Mask Length
         in octets.";
    }
    container sabm {
      leaf-list sabm-bits {
        type identityref {
          base iana-link-attr-apps:igp-link-attr-app;
        }
        description
          "SABM bits list. This list will contain
           identities for the bits which are set in the
           SABM bits.";
      }
      description
        "Standard Application Identifier Bit Mask.";
    }
    container udabm {
      description
        "User Defined Application Identifier Bit Mask.
         This container is to be augmented by user defined
         applications.";
    }
  }
}
```

```
grouping application-specific-link-attributes-sub-tlv {
  description
    "Grouping for specification of the applications and
    application-specific attribute values.";
  container asla-sub-tlvs {
    list asla-sub-tlv {
      uses application-identifier-bit-mask;
      uses isis-te-link-attrs;
      uses isis:neighbor-extended-te-extensions;
      uses isis:unknown-tlvs;
      description
        "List of application specific link attributes sub-tlvs.";
    }
    description
      "Application specific link attributes sub-tlv.";
  }
}

grouping application-specific-srlg-tlv {
  description
    "Grouping of a TLV to advertise application-specific
    SRLGs for a given link.";
  container application-specific-srlg-tlv {
    list as-srlg-tlv {
      leaf neighbor-system-id {
        type isis:system-id;
        description
          "Neighbor System-ID.";
      }
      leaf pseudo-node-id {
        type uint8;
        description
          "Pseudo-node ID.";
      }
    }
    uses application-identifier-bit-mask;
    leaf length-of-sub-tlvs {
      type uint8;
      description
        "Length of sub-tlvs.";
    }
  }
  container link-id-sub-tlvs {
    description
      "Link Identifier sub-TLVs.";
    container link-local-remote-ids {
      description
        "Link local/remote identifier sub-tlv.";
      leaf link-local-id {
        type union {

```

```
        type inet:ipv4-address;
        type uint32;
    }
    description
        "Local identifier of the link.
        It could be an IPv4 address or a local identifier.";
    }
    leaf link-remote-id {
        type union {
            type inet:ipv4-address;
            type uint32;
        }
        description
            "Remote identifier of the link.
            It could be an IPv4 address or a remotely learned
            identifier.";
    }
}
container ipv4-interface-addr {
    leaf ipv4-int-addr {
        type inet:ipv4-address;
        description
            "IPv4 address for the interface.";
    }
    description
        "IPv4 interface address sub-tlv.";
}
container ipv4-neighbor-addr {
    leaf ipv4-neighbor-addr {
        type inet:ipv4-address;
        description
            "IPv4 address for a neighboring router
            on this link.";
    }
    description
        "IPv4 neighbor address sub-tlv.";
}
container ipv6-interface-addr {
    leaf ipv6-int-addr {
        type inet:ipv6-address;
        description
            "IPv6 address for the interface.";
    }
    description
        "IPv6 interface address sub-tlv.";
}
container ipv6-neighbor-addr {
    leaf ipv6-neighbor-addr {
```

```
        type inet:ipv6-address;
        description
            "IPv6 address for a neighboring router
             on this link.";
    }
    description
        "IPv6 neighbor address sub-tlv.";
    }
}
container srlgs {
    description
        "List of SRLGs.";
    leaf-list srlg {
        type uint32;
        description
            "SRLG value of the link.";
    }
}
description
    "List of application specific SRLG tlvs.";
}
description
    "Application specific SRLG tlv.";
}
}

/* Configuration */

augment "/rt:routing/"
+ "rt:control-plane-protocols/rt:control-plane-protocol"
+ "/isis:isis" {
    when "/rt:routing/rt:control-plane-protocols/"
    + "rt:control-plane-protocol/rt:type = 'isis:isis'" {
        description
            "This augment IS-IS routing protocol when used";
    }
    description
        "This augments IS-IS protocol configuration
         with application specific link attributes.";
    container isis-link-attr {
        choice link-attr-op-mode {
            default "legacy";
            leaf legacy {
                type empty;
                description
                    "Only send legacy advertisements.";
            }
        }
        leaf transition {
```

```
        type empty;
        description
            "Send both application-specific and legacy
             advertisements.";
    }
    leaf app-specific {
        type empty;
        description
            "Only send application-specific advertisements.";
    }
    description
        "Link attributes mode. Default to legacy mode for
         backward compatibility.";
}
description
    "Link attributes operation mode.";
}
}

augment "/rt:routing/"
    + "rt:control-plane-protocols/rt:control-plane-protocol"
    + "/isis:isis/isis:interfaces/isis:interface" {
when "/rt:routing/rt:control-plane-protocols/"
    + "rt:control-plane-protocol/"
    + "rt:type = 'isis:isis'" {
    description
        "This augment IS-IS routing protocol when used.";
}
description
    "This augments IS-IS interface configuration
     with application specific link attributes.";
container isis-asla {
    list interface-asla {
        key "link-attr-app";
        leaf link-attr-app {
            type identityref {
                base iana-link-attr-apps:igp-link-attr-app;
            }
            description
                "Application-specific attributes. Note that
                 when encoded, applications with identical
                 attributes may be included in the same sub-TLV.";
        }
        leaf te-metric {
            type uint32;
            description
                "TE metric.";
            reference

```

```

        "RFC 5305: IS-IS Extensions for Traffic Engineering";
    }
    leaf admin-group {
        type uint32;
        description
            "Administrative Group / Resource Class/Color.";
        reference
            "RFC 5305: IS-IS Extensions for Traffic Engineering";
    }
    container srlgs {
        description
            "List of SRLGs.";
        leaf-list srlg {
            type uint32;
            description
                "SRLG value of the link.";
        }
    }
    description
        "ASLA interface configuration.";
}
description
    "Application specific link attributes configuration.";
}
}

/* TLV 22 */

augment "/rt:routing/"
+ "rt:control-plane-protocols/rt:control-plane-protocol"
+ "/isis:isis/isis:database/isis:levels/isis:lsp"
+ "/isis:extended-is-neighbor/isis:neighbor"
+ "/isis:instances/isis:instance" {
    when "/rt:routing/rt:control-plane-protocols/"
    + "rt:control-plane-protocol/rt:type = 'isis:isis'" {
        description
            "This augment IS-IS routing protocol when used";
    }
    description
        "This augments IS-IS protocol LSDB TLV22.";
    uses application-specific-link-attributes-sub-tlv;
}

/* TLV 223 */

augment "/rt:routing/"
+ "rt:control-plane-protocols/rt:control-plane-protocol"
+ "/isis:isis/isis:database/isis:levels/isis:lsp"

```

```

    + "/isis:mt-isis-neighbor/isis:neighbor"
    + "/isis:instances/isis:instance" {
when "/rt:routing/rt:control-plane-protocols/"
    + "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
        "This augment IS-IS routing protocol when used";
    }
description
    "This augments IS-IS protocol LSDB TLV223.";
uses application-specific-link-attributes-sub-tlv;
}

/* Application-specific SRLG TLV 238 */

augment "/rt:routing/"
    + "rt:control-plane-protocols/rt:control-plane-protocol"
    + "/isis:isis/isis:database/isis:levels/isis:lsp" {
when "/rt:routing/rt:control-plane-protocols/"
    + "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
        "This augment IS-IS routing protocol when used";
    }
description
    "This augments IS-IS protocol LSDB.";
uses application-specific-srlg-tlv;
}
}
<CODE ENDS>

```

3. YANG Module for IS-IS Flexible Algorithm

This section defines the YANG module for IS-IS Flexible Algorithm. The module uses the identities defined in the IANA-maintained YANG modules for IGP Algorithm Types [IANA-IGP-ALGO-Types] and IGP Metric Type [IANA-IGP-Metric-Types] in [I-D.ietf-lsr-ospf-flex-algo-yang]. This YANG module references [RFC8349], [RFC8776], and [RFC9130].

```
module: ietf-isis-flex-algo
```

```

augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis:
--rw isis-flex-algo
    +--rw flex-algo* [algo-number]
        +--rw algo-number          uint8
        +--rw advertise-definition? boolean
        +--rw admin-groups
            | {te-types:extended-admin-groups,
            | te-types:named-extended-admin-groups}?

```

```

    |   +--rw exclude-admin-groups*      leafref
    |   +--rw include-any-admin-groups*   leafref
    |   +--rw include-all-admin-groups*   leafref
+--rw exclude-srlgs*
    |   -> /te:te/globals/named-srlgs/named-srlg/name
    |   {te-types:named-srlg-groups}?
+--rw metric-type?      identityref
+--rw calc-type?        identityref
+--rw prefix-metric!
+--rw priority?         uint8
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:database
    /isis:levels/isis:lsp/isis:router-capabilities:
+--ro fad-tlvs
+--ro fad-tlv* []
    +--ro algo-number?      uint8
    +--ro metric-type?      identityref
    +--ro calc-type?        identityref
    +--ro priority?         uint8
    +--ro fa-ex-ag-sub-tlv
    |   +--ro extended-admin-groups*   uint64
+--ro fa-in-any-ag-sub-tlv
    |   +--ro extended-admin-groups*   uint64
+--ro fa-in-all-ag-sub-tlv
    |   +--ro extended-admin-groups*   uint64
+--ro fad-flags-sub-tlv
    |   +--ro fad-flags*   identityref
+--ro fa-ex-srlg-sub-tlv
    |   +--ro srlgs*   uint32
+--ro unknown-tlvs
    +--ro unknown-tlv* []
        +--ro type?      uint16
        +--ro length?    uint16
        +--ro value?     yang:hex-string
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:database
    /isis:levels/isis:lsp/isis:extended-ipv4-reachability
    /isis:prefixes:
+--ro fapm-sub-tlvs
+--ro fapm-sub-tlv* []
    +--ro algo-number?   uint8
    +--ro metric?        uint32
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:database
    /isis:levels/isis:lsp
    /isis:mt-extended-ipv4-reachability/isis:prefixes:
+--ro fapm-sub-tlvs
+--ro fapm-sub-tlv* []

```



```

        +--ro algo-number?    uint8
        +--ro metric?         uint32
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:database
    /isis:levels/isis:lsp/isis:ipv6-reachability
    /isis:prefixes:
+--ro fapm-sub-tlvs
  +--ro fapm-sub-tlv* []
    +--ro algo-number?    uint8
    +--ro metric?         uint32
augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/isis:isis/isis:database
    /isis:levels/isis:lsp/isis:mt-ipv6-reachability
    /isis:prefixes:
+--ro fapm-sub-tlvs
  +--ro fapm-sub-tlv* []
    +--ro algo-number?    uint8
    +--ro metric?         uint32

notifications:
  +---n flex-algo-not-supported
    +--ro routing-protocol-name?  leafref
    +--ro isis-level?             level
    +--ro algo-number?            uint8

<CODE BEGINS> file "ietf-isis-flex-algo@2026-04-30.yang"
module ietf-isis-flex-algo {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-isis-flex-algo";
  prefix isis-flex-algo;

  import ietf-routing {
    prefix rt;
    reference
      "RFC 8349: A YANG Data Model for Routing
        Management (NMDA Version)";
  }
  import ietf-te-types {
    prefix te-types;
    reference
      "RFC8776: Common YANG Data Types for Traffic Engineering.";
  }
  import ietf-isis {
    prefix isis;
    reference
      "RFC 9130: YANG Data Model for the IS-IS Protocol";
  }
  import ietf-te {

```

```
prefix te;
reference
  "RFC XXXX: A YANG Data Model for Traffic Engineering
    Tunnels, Label Switched Paths, and Interfaces";
}
import iana-igp-algo-types {
  prefix iana-algo-types;
  reference
    "RFC XXXX: YANG Data Model for OSPF Application-Specific
      Link Attributes and Flexible Algorithm";
}
import iana-igp-metric-types {
  prefix iana-metric-type;
  reference
    "RFC XXXX: YANG Data Model for OSPF Application-Specific
      Link Attributes and Flexible Algorithm";
}

organization
  "IETF LSR - Link State Routing Working Group";
contact
  "WG Web:    <https://datatracker.ietf.org/wg/lsr>
   WG List:   <mailto:lsr@ietf.org>

   Author:    Yingzhen Qu
               <mailto:yingzhen.ietf@gmail.com>
   Author:    Acee Lindem
               <mailto:acee.ietf@gmail.com>
   Author:    Madhavi Joshi
               <madhavi@arrcus.com>

";
description
  "The YANG module defines the configuration and operational
   state for IS-IS Flexible Algorithm as defined in RFC 9350.

   This YANG model conforms to the Network Management
   Datastore Architecture (NMDA) as described in RFC 8342.

   Copyright (c) 2026 IETF Trust and the persons identified as
   authors of the code. All rights reserved.

   Redistribution and use in source and binary forms, with or
   without modification, is permitted pursuant to, and subject to
   the license terms contained in, the Revised BSD License set
   forth in Section 4.c of the IETF Trust's Legal Provisions
   Relating to IETF Documents
   (https://trustee.ietf.org/license-info).
```

This version of this YANG module is part of RFC XXXX;
see the RFC itself for full legal notices.

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document are to be interpreted as described in BCP 14 (RFC 2119) (RFC 8174) when, and only when, they appear in all capitals, as shown here.";

```
revision 2026-04-30 {
  description
    "Initial Version";
  reference
    "RFC XXXX: YANG Data Model for IS-IS Application-Specific
      Link Attributes and Flexible Algorithm";
}

/* Identities */

identity fad-flags {
  description
    "Base identity for IS-IS FAD flags.";
}

identity m-bit {
  base fad-flags;
  description
    "M bit, when set, the flex-algo specific prefix and ASBR
      metric MUST be used for inter-area and external prefix
      calculation.";
}

/* Groupings */

grouping fa-ex-ag-sub-tlv {
  container fa-ex-ag-sub-tlv {
    leaf-list extended-admin-groups {
      type uint64;
      description
        "Extended administrative group as defined in RFC 7308.";
    }
    description
      "The flex-algo exclude admin group sub-tlv.";
  }
  description
    "The flex-algo exclude admin group sub-tlv.";
}
```

```
grouping fa-in-any-ag-sub-tlv {
  container fa-in-any-ag-sub-tlv {
    leaf-list extended-admin-groups {
      type uint64;
      description
        "Extended administrative group as defined in RFC 7308.";
    }
    description
      "The flex-algo include-any admin group sub-tlv.";
  }
  description
    "The flex-algo include-any admin group sub-tlv.";
}

grouping fa-in-all-ag-sub-tlv {
  container fa-in-all-ag-sub-tlv {
    leaf-list extended-admin-groups {
      type uint64;
      description
        "Extended administrative group as defined in RFC 7308.";
    }
    description
      "The flex-algo include-all admin group sub-tlv.";
  }
  description
    "The flex-algo include-all admin group sub-tlv.";
}

grouping fad-flags-sub-tlv {
  container fad-flags-sub-tlv {
    leaf-list fad-flags {
      type identityref {
        base fad-flags;
      }
      description
        "Flex-algo definition flags list.";
    }
    description
      "IS-IS flex-algo definition flags.";
  }
  description
    "The flex-algo definition flags sub-tlv.";
}

grouping fa-ex-srlg-sub-tlv {
  container fa-ex-srlg-sub-tlv {
    leaf-list srlgs {
      type uint32;
```

```
        description
            "SRLG value as defined in RFC 4203.";
    }
    description
        "The flex-algo exclude SRLG sub-tlv.";
    }
    description
        "The flex-algo exclude SRLG sub-tlv.";
    }

    grouping fad-tlvs {
        container fad-tlvs {
            list fad-tlv {
                leaf algo-number {
                    type uint8;
                    description
                        "Flex-algo number - A value not in the inclusive range
                        of 128-255 is an invalid FAD TLV specification.";
                }
                leaf metric-type {
                    type identityref {
                        base iana-metric-type:metric-type;
                    }
                    description
                        "Type of metric to be used during the calculation.";
                }
                leaf calc-type {
                    type identityref {
                        base iana-algo-types:algo-type;
                    }
                    description
                        "IGP algorithm types, value from 0 to 127 as
                        defined under 'Interior Gateway Protocol (IGP)
                        Parameter' by IANA.";
                }
                leaf priority {
                    type uint8;
                    description
                        "Priority of the advertisement.";
                }
            }
            uses fa-ex-ag-sub-tlv;
            uses fa-in-any-ag-sub-tlv;
            uses fa-in-all-ag-sub-tlv;
            uses fad-flags-sub-tlv;
            uses fa-ex-srlg-sub-tlv;
            uses isis:unknown-tlvs;
            description
                "List of flex-algo definition TLVs.";
```

```
    }
    description
      "IS-IS Flexible Algorithm Definition TLV.";
  }
  description
    "IS-IS Flexible Algorithm Definition (FAD) TLV.";
}

grouping fapm-sub-tlvs {
  container fapm-sub-tlvs {
    list fapm-sub-tlv {
      leaf algo-number {
        type uint8;
        description
          "Flex-algo number - A value not in the inclusive range
            of 128-255 is an invalid FAPM sub-TLV specification.";
      }
      leaf metric {
        type uint32;
        description
          "Prefix metric.";
      }
    }
    description
      "List of flex-algo prefix sub-tlvs.";
  }
  description
    "Flex-algo prefix metric sub-tlvs.";
}
description
  "Flexible Algorithm Prefix Metric (FAPM) sub TLVs.";
}

/* Configurations */

augment "/rt:routing/"
  + "rt:control-plane-protocols/rt:control-plane-protocol"
  + "/isis:isis" {
  when "/rt:routing/rt:control-plane-protocols/"
    + "rt:control-plane-protocol/rt:type = 'isis:isis'" {
    description
      "This augment IS-IS routing protocol when used";
  }
  description
    "This augments IS-IS protocol configuration
      with flexible algorithm.";
  container isis-flex-algo {
    list flex-algo {
      key "algo-number";
    }
  }
}
```

```
leaf algo-number {
  type uint8 {
    range "128..255";
  }
  description
    "Flex-algo number - must in in the inclusive range
    of 128-255.";
}
leaf advertise-definition {
  type boolean;
  default "true";
  description
    "Enable to advertise the flex-algo definition.";
}
container admin-groups {
  if-feature "te-types:extended-admin-groups";
  if-feature "te-types:named-extended-admin-groups";
  leaf-list exclude-admin-groups {
    type leafref {
      path "/te:te/te:globals/te:named-admin-groups/"
        + "te:named-admin-group/te:name";
    }
    description
      "Exclude rule used during the flex-algo
      path computation.";
  }
  leaf-list include-any-admin-groups {
    type leafref {
      path "/te:te/te:globals/te:named-admin-groups/"
        + "te:named-admin-group/te:name";
    }
    description
      "Include-any rule used during the flex-algo
      path computation.";
  }
  leaf-list include-all-admin-groups {
    type leafref {
      path "/te:te/te:globals/te:named-admin-groups/"
        + "te:named-admin-group/te:name";
    }
    description
      "Include-all rule used during the flex-algo
      path computation.";
  }
  description
    "Specify links for the flex-algo path computation.";
}
leaf-list exclude-srlgs {
```

```
    if-feature "te-types:named-srlg-groups";
    type leafref {
      path "/te:te/te:globals/te:named-srlgs/te:named-srlg/"
        + "te:name";
    }
    description
      "Shared Risk Link Groups (SRLGs) to be excluded during
       the flex-algo path computation.";
  }
  leaf metric-type {
    type identityref {
      base iana-metric-type:metric-type;
    }
    description
      "Type of metric to be used during the calculation.";
  }
  leaf calc-type {
    type identityref {
      base iana-algo-types:algo-type;
    }
    default "iana-algo-types:algo-spf";
    description
      "Calculation-type. Value from 0-127 inclusive from the
       IANA 'IGP Algorithm Types' registry defined under the
       'Interior Gateway Protocol (IGP) Parameters' registry.";
  }
  container prefix-metric {
    presence "Use flex-algo specific prefix metric.";
    description
      "Use flex-algo prefix metric.";
  }
  leaf priority {
    type uint8;
    description
      "Priority of the advertisement.";
  }
  description
    "List of flex-algo configurations.";
}
description
  "Flexible Algorithm configuration.";
}
}

/* Database */

augment "/rt:routing/"
  + "rt:control-plane-protocols/rt:control-plane-protocol"
```



```
    + "/isis:isis/isis:database/isis:levels/isis:lsp"
    + "/isis:router-capabilities" {
when "/rt:routing/rt:control-plane-protocols/"
    + "rt:control-plane-protocol/"
    + "rt:type = 'isis:isis'" {
    description
        "This augment IS-IS routing protocol when used";
    }
description
    "This augments IS-IS protocol LSDB router capability.";
uses fad-tlvs;
}

augment "/rt:routing/"
    + "rt:control-plane-protocols/rt:control-plane-protocol"
    + "/isis:isis/isis:database/isis:levels/isis:lsp"
    + "/isis:extended-ipv4-reachability/"
    + "isis:prefixes" {
when "/rt:routing/rt:control-plane-protocols/"
    + "rt:control-plane-protocol/"
    + "rt:type = 'isis:isis'" {
    description
        "This augment IS-IS routing protocol when used";
    }
description
    "This augments IS-IS protocol LSDB prefix.";
uses fapm-sub-tlvs;
}

augment "/rt:routing/"
    + "rt:control-plane-protocols/rt:control-plane-protocol"
    + "/isis:isis/isis:database/isis:levels/isis:lsp"
    + "/isis:mt-extended-ipv4-reachability/isis:prefixes" {
when "/rt:routing/rt:control-plane-protocols/"
    + "rt:control-plane-protocol/"
    + "rt:type = 'isis:isis'" {
    description
        "This augment IS-IS routing protocol when used";
    }
description
    "This augments IS-IS protocol LSDB prefix.";
uses fapm-sub-tlvs;
}

augment "/rt:routing/"
    + "rt:control-plane-protocols/rt:control-plane-protocol"
    + "/isis:isis/isis:database/isis:levels/isis:lsp"
    + "/isis:ipv6-reachability/isis:prefixes" {
```

```
when "/rt:routing/rt:control-plane-protocols/"
  + "rt:control-plane-protocol/"
  + "rt:type = 'isis:isis'" {
  description
    "This augment IS-IS routing protocol when used";
}
description
  "This augments IS-IS protocol LSDB prefix.";
uses fapm-sub-tlvs;
}

augment "/rt:routing/"
  + "rt:control-plane-protocols/rt:control-plane-protocol"
  + "/isis:isis/isis:database/isis:levels/isis:lsp"
  + "/isis:mt-ipv6-reachability/isis:prefixes" {
when "/rt:routing/rt:control-plane-protocols/"
  + "rt:control-plane-protocol/"
  + "rt:type = 'isis:isis'" {
  description
    "This augment IS-IS routing protocol when used";
}
description
  "This augments IS-IS protocol LSDB prefix.";
uses fapm-sub-tlvs;
}

/* Notification */

notification flex-algo-not-supported {
  uses isis:notification-instance-hdr;
  leaf algo-number {
    type uint8;
    description
      "Flex-algo identifier which is not supported by the IS-IS
      instance. A value not in the inclusive range of 128-255
      is indicative of an invalid FAD algorithm specification.";
  }
  description
    "This notification is sent when an IS-IS instance does not
    support this flex-algo.";
}
}
<CODE ENDS>
```

4. Security Considerations

The YANG modules defined in this document are designed to be accessed via YANG-based management protocols, such as NETCONF [RFC6241] and RESTCONF [RFC8040]. These protocols have to use a secure transport layer (e.g., SSH [RFC4252], TLS [RFC8446], and QUIC [RFC9000]) and have to use mutual authentication.

The Network Configuration Access Control Model (NACM) [RFC8341] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., "config true", which is the default). All writable data nodes are likely to be reasonably sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) and delete operations to these data nodes without proper protection or authentication can have a negative effect on network operations. The following subtrees and data nodes have particular sensitivities/vulnerabilities:

/isis:isis/isis-link-attr/link-attr-op-mode - Modification to the protocol operation mode may result in traffic disruption.

/isis:isis/flex-algo - Modification to flex-algo configuration could be used to mount a DoS attack. For example, changing of calc-type may result in routing loops.

Some of the readable data nodes in the modules may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. The exposure of the Link State Database (LSDB) will expose the detailed topology of the network. This may be undesirable since both due to the fact that exposure may facilitate other attacks. Additionally, network operators may consider their topologies to be sensitive confidential data.

5. IANA Considerations

This document registers a URI in the IETF XML registry [RFC3688]. Following the format in [RFC3688], the following registrations are requested:

URI: urn:ietf:params:xml:ns:yang:ietf-isis-link-attr
Registrant Contact: The IESG.
XML: N/A, the requested URI is an XML namespace.

URI: urn:ietf:params:xml:ns:yang:ietf-isis-flex-algo
Registrant Contact: The IESG.
XML: N/A, the requested URI is an XML namespace.

This document registers the YANG module in the YANG Module Names registry [RFC7950].

name: ietf-isis-link-attr
Maintained by IANA? N
namespace: urn:ietf:params:xml:ns:yang:ietf-isis-link-attr
prefix: isis-link-attr
reference: RFC XXXX

name: ietf-isis-flex-algo
Maintained by IANA? N
namespace: urn:ietf:params:xml:ns:yang:ietf-isis-flex-algo
prefix: isis-flex-algo
reference: RFC XXXX

6. Acknowledgements

Thanks to Michal Vasko for his YANG doctors review.

Thanks to Adrian Farrel for his OPS directorate review.

Thanks to Renato Westphal for review and comments.

7. References

7.1. Normative References

[I-D.ietf-lsr-ospf-flex-algo-yang]
Qu, Y. and A. Lindem, "YANG Data Model for OSPF Application-Specific Link Attributes and Flexible Algorithm", Work in Progress, Internet-Draft, draft-ietf-lsr-ospf-flex-algo-yang-07, 30 March 2026, <<https://datatracker.ietf.org/doc/html/draft-ietf-lsr-ospf-flex-algo-yang-07>>.

[IANA-IGP-ALGO-Types]
IANA, "IGP Algorithm Types", <<https://www.iana.org/assignments/igp-parameters>>.

[IANA-IGP-Metric-Types]
IANA, "IGP Metric-Type", <<https://www.iana.org/assignments/igp-parameters>>.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC4252] Ylonen, T. and C. Lonvick, Ed., "The Secure Shell (SSH) Authentication Protocol", RFC 4252, DOI 10.17487/RFC4252, January 2006, <<https://www.rfc-editor.org/info/rfc4252>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", RFC 6991, DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, RFC 8341, DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8349] Lhotka, L., Lindem, A., and Y. Qu, "A YANG Data Model for Routing Management (NMDA Version)", RFC 8349, DOI 10.17487/RFC8349, March 2018, <<https://www.rfc-editor.org/info/rfc8349>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

- [RFC8776] Saad, T., Gandhi, R., Liu, X., Beeram, V., and I. Bryskin, "Common YANG Data Types for Traffic Engineering", RFC 8776, DOI 10.17487/RFC8776, June 2020, <<https://www.rfc-editor.org/info/rfc8776>>.
- [RFC9000] Iyengar, J., Ed. and M. Thomson, Ed., "QUIC: A UDP-Based Multiplexed and Secure Transport", RFC 9000, DOI 10.17487/RFC9000, May 2021, <<https://www.rfc-editor.org/info/rfc9000>>.
- [RFC9130] Litkowski, S., Ed., Yeung, D., Lindem, A., Zhang, J., and L. Lhotka, "YANG Data Model for the IS-IS Protocol", RFC 9130, DOI 10.17487/RFC9130, October 2022, <<https://www.rfc-editor.org/info/rfc9130>>.
- [RFC9350] Psenak, P., Ed., Hegde, S., Filsfils, C., Talaulikar, K., and A. Gulko, "IGP Flexible Algorithm", RFC 9350, DOI 10.17487/RFC9350, February 2023, <<https://www.rfc-editor.org/info/rfc9350>>.
- [RFC9479] Ginsberg, L., Psenak, P., Previdi, S., Henderickx, W., and J. Drake, "IS-IS Application-Specific Link Attributes", RFC 9479, DOI 10.17487/RFC9479, October 2023, <<https://www.rfc-editor.org/info/rfc9479>>.

7.2. Informative References

- [RFC8792] Watsen, K., Auerswald, E., Farrel, A., and Q. Wu, "Handling Long Lines in Content of Internet-Drafts and RFCs", RFC 8792, DOI 10.17487/RFC8792, June 2020, <<https://www.rfc-editor.org/info/rfc8792>>.

Appendix A. Example IS-IS Flex-Algo Configuration

The following is an example configuration for IS-IS Flexible Algorithm using the YANG model defined in this document.

Note: '\ ' line wrapping per [RFC8792].

```
<?xml version='1.0' encoding='UTF-8'?>
  <te xmlns="urn:ietf:params:xml:ns:yang:ietf-te">
    <enable>true</enable>
    <globals>
      <named-admin-groups>
        <named-admin-group>
          <name>blue</name>
        </named-admin-group>
      </named-admin-groups>
    </globals>
  </te>
  <routing xmlns="urn:ietf:params:xml:ns:yang:ietf-routing">
    <router-id>1.1.1.1</router-id>
    <control-plane-protocols>
      <control-plane-protocol>
        <type xmlns:isis="urn:ietf:params:xml:ns:yang:ietf-isis">\
          isis:isis</type>
        <name>isis</name>
        <isis xmlns="urn:ietf:params:xml:ns:yang:ietf-isis">
          <system-id>1111.2222.3333</system-id>
          <area-address>49.0001.0000.0000.0001</area-address>
          <isis-flex-algo xmlns="urn:ietf:params:xml:ns:yang:\
            ietf-isis-flex-algo">
            <flex-algo>
              <algo-number>200</algo-number>
              <admin-groups>
                <exclude-admin-groups>blue</exclude-admin-groups>
              </admin-groups>
              <metric-type xmlns:iana-metric-types=\
                "urn:ietf:params:xml:ns:yang:iana-igp-metric-types">\
                iana-metric-types:igp-metric</metric-type>
              <calc-type xmlns:iana-algo-types=\
                "urn:ietf:params:xml:ns:yang:iana-igp-algo-types">\
                iana-algo-types:algo-spf</calc-type>
              <prefix-metric/>
              <priority>100</priority>
            </flex-algo>
          </isis-flex-algo>
        </isis>
      </control-plane-protocol>
    </control-plane-protocols>
  </routing>
```

Appendix B. Example IS-IS Flex-Algo Configuration (JSON)

The following is an example configuration for IS-IS Flexible Algorithm in JSON format using the YANG model defined in this document.

```
{
  "te": {
    "enable": true,
    "globals": {
      "named-admin-groups": {
        "named-admin-group": {
          "name": "blue"
        }
      }
    }
  },
  "routing": {
    "router-id": "1.1.1.1",
    "control-plane-protocols": {
      "control-plane-protocol": {
        "type": "isis:isis",
        "name": "isis",
        "isis": {
          "system-id": "1111.2222.3333",
          "area-address": "49.0001.0000.0000.0001",
          "isis-flex-algo": {
            "flex-algo": {
              "algo-number": 200,
              "admin-groups": {
                "exclude-admin-groups": "blue"
              },
              "metric-type": "iana-metric-types:igp-metric",
              "calc-type": "iana-algo-types:algo-spf",
              "prefix-metric": "",
              "priority": 100
            }
          }
        }
      }
    }
  }
}
```

Authors' Addresses

Yingzhen Qu
Futurewei Technologies
United States of America
Email: yingzhen.ietf@gmail.com

Acee Lindem
Arrcus, Inc.
United States of America
Email: acee.ietf@gmail.com

Madhavi Joshi
Arrcus, Inc.
United States of America
Email: madhavi@arrcus.com