

NETCONF Working Group
Internet-Draft
Updates: 6241 (if approved)
Intended status: Standards Track
Expires: 16 August 2026

K. Watsen
Watsen Networks
Q. Wu
Huawei
P. Andersson
Ionio Systems
O. Hagsand
SUNET
H. Li
HPE
12 February 2026

NETCONF Extensions to Support List Pagination
draft-ietf-netconf-list-pagination-nc-10

Abstract

This document defines a mapping of the list pagination mechanism defined in [I-D.ietf-netconf-list-pagination] to NETCONF [RFC6241].

This document updates [RFC6241], to augment the <get> and <get-config> "rpc" statements, and [RFC8526], to augment the <get-data> "rpc" statement, to define input parameters necessary for list pagination.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 16 August 2026.

Copyright Notice

Copyright (c) 2026 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

| | |
|---|----|
| 1. Introduction | 2 |
| 1.1. Terminology | 3 |
| 1.2. Conventions | 3 |
| 2. Updates to NETCONF operations | 3 |
| 2.1. Updates to RFC 6241 | 3 |
| 2.2. Updates to RFC 8526 | 3 |
| 3. List Pagination for NETCONF | 3 |
| 4. Error Reporting | 5 |
| 5. YANG Module for List Pagination in NETCONF | 5 |
| 6. IANA Considerations | 7 |
| 6.1. The "IETF XML" Registry | 7 |
| 6.2. The "YANG Module Names" Registry | 8 |
| 7. Security Considerations | 8 |
| 7.1. The "ietf-netconf-list-pagination" YANG Module | 8 |
| 8. References | 8 |
| 8.1. Normative References | 8 |
| 8.2. Informative References | 10 |
| Appendix A. Example YANG Module | 10 |
| Appendix B. Example Data Set | 11 |
| Appendix C. Example Queries | 11 |
| C.1. List pagination with all query parameters | 11 |
| Acknowledgements | 13 |
| Authors' Addresses | 13 |

1. Introduction

This document defines a mapping of the list pagination mechanism defined in [I-D.ietf-netconf-list-pagination] to NETCONF [RFC6241].

This document updates [RFC6241] and [RFC8526], as described in Section 2.

While the pagination mechanism defined in this document is designed for the NETCONF protocol [RFC6241], the augmented RPCs MAY be used by the RESTCONF protocol [RFC8040] if the RESTCONF server implements the "ietf-list-pagination-nc" module.

The YANG data model in this document conforms to the Network Management Datastore Architecture defined in [RFC8342]

1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

1.2. Conventions

Various examples in this document use "BASE64VALUE=" as a placeholder value for binary data that has been base64 encoded (per Section 9.8 of [RFC7950]). This placeholder value is used because real base64 encoded structures are often many lines long and hence distracting to the example being presented.

2. Updates to NETCONF operations

2.1. Updates to RFC 6241

The <get> and <get-config> rpc statements are augmented to accept additional input parameters, as described in Section 3.

2.2. Updates to RFC 8526

The <get-data> rpc statement is augmented to accept additional input parameters, as described in in Section 3.

3. List Pagination for NETCONF

In order for NETCONF to support [I-D.ietf-netconf-list-pagination], this document extends the operations <get>, <get-config> and <get-data> to include additional input parameters and output annotations.

The updated operations accept a content filter parameter, similar to the "filter" parameter of <get-config>, but includes nodes for "list" and "leaf-list" filtering.

The content filter parameter is used to specify the YANG list or leaf-list that is to be retrieved. This must be a path expression used to represent a list or leaf-list data node.

The following tree diagram [RFC8340] illustrates the "ietf-netconf-list-pagination" module:

```
module: ietf-list-pagination-nc

augment /nc:get/nc:input:
  +---w list-pagination
    +---w where?          union
    +---w locale?         string {sort}?
    +---w sort-by?        union {sort}?
    +---w direction?      enumeration
    +---w cursor?          string
    +---w offset?          uint32
    +---w limit?           union
    +---w sublist-limit?  union
augment /nc:get-config/nc:input:
  +---w list-pagination
    +---w where?          union
    +---w locale?         string {sort}?
    +---w sort-by?        union {sort}?
    +---w direction?      enumeration
    +---w cursor?          string
    +---w offset?          uint32
    +---w limit?           union
    +---w sublist-limit?  union
augment /ncds:get-data/ncds:input:
  +---w list-pagination
    +---w where?          union
    +---w locale?         string {sort}?
    +---w sort-by?        union {sort}?
    +---w direction?      enumeration
    +---w cursor?          string
    +---w offset?          uint32
    +---w limit?           union
    +---w sublist-limit?  union
```

Comments:

- * This module augments three NETCONF "rpc" statements: get, get-config, and get-data.
- * The "get" and "get-config" augments are against the YANG module defined in [RFC6241]. The "get-data" augment is against the YANG module defined in [RFC8526].

4. Error Reporting

When an input query parameter is supplied with an erroneous value, an `<rpc-error>` MUST be returned containing the error-type value "application", the error-tag value "invalid-value", and MAY include the error-severity value "error". Additionally the error-app-tag SHOULD be set containing query parameter specific error value.

4.1. The "offset" Query Parameter

If the "offset" query parameter value supplied is larger than the number of instances in the working result-set, the `<rpc-error>` MUST contain error-app-tag with value "offset-out-of-range".

5. YANG Module for List Pagination in NETCONF

The "ietf-netconf-list-pagination-nc" module defines conceptual definitions within groupings, which are not meant to be implemented as datastore contents by a server.

This module has normative references to [RFC6241], [RFC6243], [RFC6991], and [RFC8342].

```
<CODE BEGINS> file "ietf-list-pagination-nc@2026-02-13.yang"
```

```
module ietf-list-pagination-nc {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-list-pagination-nc";
  prefix lpgnc;

  import ietf-netconf {
    prefix nc;
    reference
      "RFC 6241: Network Configuration Protocol (NETCONF)";
  }

  import ietf-netconf-nmda {
    prefix ncds;
    reference
      "RFC 8526: NETCONF Extensions to Support the
       Network Management Datastore Architecture";
  }

  import ietf-list-pagination {
    prefix lpg;
    reference
      "RFC XXXX: List Pagination for YANG-driven Protocols";
  }
}
```

organization

"IETF NETCONF (Network Configuration) Working Group";

contact

"WG Web: <<https://datatracker.ietf.org/wg/netconf/>>
WG List: <<mailto:netconf@ietf.org>>

Author: Kent Watsen
<kent+ietf@watsen.net>

Author: Qin Wu
<bill.wu@huawei.com>

Author: Per Andersson
<per.ietf@ionio.se>

Author: Olof Hagsand
<olof@hagsand.se>

Author: Hongwei Li
<flycoolman@gmail.com>";

description

"This module augments the <get>, <get-config>, and <get-data> 'rpc' statements to support list pagination.

Copyright (c) 2026 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Revised BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX (<https://www.rfc-editor.org/info/rfcXXXX>); see the RFC itself for full legal notices.

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document are to be interpreted as described in BCP 14 (RFC 2119) (RFC 8174) when, and only when, they appear in all capitals, as shown here.";

revision 2026-02-13 {

```
    description
      "Initial revision.";
    reference
      "RFC XXXX: NETCONF Extensions to Support List Pagination";
  }

  augment "/nc:get/nc:input" {
    description
      "Allow the 'get' operation to use content filter
       parameter for specifying the YANG list or leaf-list
       that is to be retrieved";
    uses lpg:pagination-parameters;
  }

  augment "/nc:get-config/nc:input" {
    description
      "Allow the 'get-config' operation to use content filter
       parameter for specifying the YANG list or leaf-list
       that is to be retrieved";
    uses lpg:pagination-parameters;
  }

  augment "/ncds:get-data/ncds:input" {
    description
      "Allow the 'get-data' operation to use content filter
       parameter for specifying the YANG list or leaf-list
       that is to be retrieved";
    uses lpg:pagination-parameters;
  }
}
```

<CODE ENDS>

6. IANA Considerations

6.1. The "IETF XML" Registry

This document registers one URI in the "ns" subregistry of the IETF XML Registry [RFC3688] maintained at <https://www.iana.org/assignments/xml-registry/xml-registry.xhtml#ns>. Following the format in [RFC3688], the following registration is requested:

URI: urn:ietf:params:xml:ns:yang:ietf-list-pagination-nc
Registrant Contact: The IESG.
XML: N/A, the requested URI is an XML namespace.

6.2. The "YANG Module Names" Registry

This document registers one YANG module in the YANG Module Names registry [RFC6020] maintained at <https://www.iana.org/assignments/yang-parameters/yang-parameters.xhtml>. Following the format defined in [RFC6020], the below registration is requested:

```
name: ietf-list-pagination-nc
namespace: urn:ietf:params:xml:ns:yang:ietf-list-pagination-nc
prefix: pgnc
RFC: XXXX
```

7. Security Considerations

7.1. The "ietf-netconf-list-pagination" YANG Module

This section follows the template defined in Section 3.7.1 of [RFC8407].

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF [RFC6241] or RESTCONF [RFC8040]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [RFC6242]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [RFC8446].

The Network Configuration Access Control Model (NACM) [RFC8341] provides the means to restrict access for particular NETCONF users to a preconfigured subset of all available NETCONF protocol operations and content.

The security considerations for the base NETCONF protocol operations (see Section 9 of [RFC6241] and Section 6 of [RFC8526]) apply to the extension of operations <get>, <get-config>, and <get-data> defined in this document.

8. References

8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

- [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", RFC 6242, DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC6243] Bierman, A. and B. Lengyel, "With-defaults Capability for NETCONF", RFC 6243, DOI 10.17487/RFC6243, June 2011, <<https://www.rfc-editor.org/info/rfc6243>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", RFC 6991, DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, RFC 8341, DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", RFC 8342, DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

[RFC8526] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "NETCONF Extensions to Support the Network Management Datastore Architecture", RFC 8526, DOI 10.17487/RFC8526, March 2019, <<https://www.rfc-editor.org/info/rfc8526>>.

[I-D.ietf-netconf-list-pagination]
Watsen, K., Wu, Q., Andersson, P., Hagsand, O., and H. Li, "List Pagination for YANG-driven Protocols", Work in Progress, Internet-Draft, draft-ietf-netconf-list-pagination-09, 12 February 2026, <<https://datatracker.ietf.org/doc/html/draft-ietf-netconf-list-pagination-09>>.

8.2. Informative References

[RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.

[RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.

[RFC8407] Bierman, A., "Guidelines for Authors and Reviewers of Documents Containing YANG Data Models", BCP 216, RFC 8407, DOI 10.17487/RFC8407, October 2018, <<https://www.rfc-editor.org/info/rfc8407>>.

[I-D.ietf-netconf-restconf-collection]
Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Collection Resource", Work in Progress, Internet-Draft, draft-ietf-netconf-restconf-collection-00, 30 January 2015, <<https://datatracker.ietf.org/doc/html/draft-ietf-netconf-restconf-collection-00>>.

[I-D.zheng-netconf-fragmentation]
Zheng, G. and Z. Wang, "A NETCONF Extension for Data Fragmentation", Work in Progress, Internet-Draft, draft-zheng-netconf-fragmentation-02, 26 June 2018, <<https://datatracker.ietf.org/doc/html/draft-zheng-netconf-fragmentation-02>>.

Appendix A. Example YANG Module

The examples within this document use the "example-social" YANG module defined in Appendix A.1 of [I-D.ietf-netconf-list-pagination].

Appendix B. Example Data Set

The Example Data Set used by the examples is defined in Appendix A.2 of [I-D.ietf-netconf-list-pagination].

Appendix C. Example Queries

C.1. List pagination with all query parameters

This example mimics that Appendix A.3.9 of [I-D.ietf-netconf-list-pagination]. In this XML example, The xmlns:es attribute binds the "es" prefix to the example-social module name. The urn:ietf:params:xml:ns:yang:ietf-list-pagination-nc namespace is used for the list-pagination query parameters.

```
<rpc xmlns="urn:ietf:params:xml:ns:netconf:base:1.0" message-id="42">
  <get>
    <source>
      <running/>
    </source>
    <filter type="xpath" select="/es:members/es:member"
      xmlns:es="https://example.com/ns/example-social"/>
    <list-pagination
      xmlns="urn:ietf:params:xml:ns:yang:ietf-list-pagination-nc">
      <where>stats[starts-with(joined,'2020')]</where>
      <sort-by>joined</sort-by>
      <direction>backwards</direction>
      <offset>2</offset>
      <limit>2</limit>
      <sublist-limit>1</sublist-limit>
      <locale>sv_US</locale>
    </list-pagination>
  </get>
</rpc>
```

Response from the NETCONF server:

===== NOTE: '\ ' line wrapping per RFC 8792 =====

```
<rpc-reply message-id="101"
  xmlns="urn:ietf:params:xml:ns:netconf:base:1.0">
  <data>
    <members
      xmlns="https://example.com/ns/example-social"
      xmlns:lp="urn:ietf:params:xml:ns:yang:ietf-list-pagination">
      <member lp:remaining="1" lp:locale="en_US">
        <member-id>eric</member-id>
        <email-address>eric@example.com</email-address>
```

```

    <password>$0$1543</password>
    <avatar>BASE64VALUE=</avatar>
    <tagline>Go to bed with dreams; wake up with purpose.</tagline>
ne>
    <following>alice</following>
    <posts>
      <post>
        <timestamp>2020-09-17T18:02:04Z</timestamp>
        <title>Son, brother, husband, father</title>
        <body>What's your story?</body>
      </post>
    </posts>
    <favorites>
      <bits lp:remaining="2" lp:locale="en_US">two</bits>
    </favorites>
    <stats>
      <joined>2020-09-17T19:38:32Z</joined>
      <membership-level>pro</membership-level>
      <last-activity>2020-09-17T18:02:04Z</last-activity>
    </stats>
  </member>
  <member lp:remaining="1" lp:locale="en_US">
    <member-id>bob</member-id>
    <email-address>bob@example.com</email-address>
    <password>$0$1543</password>
    <avatar>BASE64VALUE=</avatar>
    <tagline>Here and now, like never before.</tagline>
    <posts>
      <post lp:remaining="2" lp:locale="en_US">
        <timestamp>2020-08-14T03:32:25Z</timestamp>
        <body>Just got in.</body>
      </post>
    </posts>
    <favorites>
      <decimal64-numbers lp:remaining="1" lp:locale="en_US">3.14\
159</decimal64-numbers>
    </favorites>
    <stats>
      <joined>2020-08-14T03:30:00Z</joined>
      <membership-level>standard</membership-level>
      <last-activity>2020-08-14T03:34:30Z</last-activity>
    </stats>
  </member>
</members>
</data>
</rpc-reply>

```

Acknowledgements

This work has benefited from the discussions of RESTCONF resource collection over the years, in particular, [I-D.ietf-netconf-restconf-collection] which provides enhanced filtering features for the retrieval of data nodes with the GET method and [I-D.zheng-netconf-fragmentation] which document large size data handling challenge. The authors would like to thank the following for lively discussions on list (ordered by first name): Andy Bierman, Martin Björklund, Robert Varga, and Robert Wilton.

Authors' Addresses

Kent Watsen
Watsen Networks
Email: kent+ietf@watsen.net

Qin Wu
Huawei
Email: bill.wu@huawei.com

Per Andersson
Ionio Systems
Email: per.ietf@ionio.se

Olof Hagsand
SUNET
Email: olof@hagsand.se

Hongwei Li
HPE
Email: flycoolman@gmail.com