

Network Working Group
Internet-Draft
Obsoletes: 6991 (if approved)
Intended status: Standards Track
Expires: 25 December 2025

J. Schinw辰lder, Ed.
Constructor University
23 June 2025

Common YANG Data Types
draft-ietf-netmod-rfc6991-bis-18

Abstract

This document defines a collection of common data types to be used with the YANG data modeling language. This version of the document adds several new type definitions and obsoletes RFC 6991.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 25 December 2025.

Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Table of Contents

1. Introduction	2
2. Overview	3
3. Core YANG Types	8
4. Internet Protocol Suite Types	24
5. IANA Considerations	38
6. Security Considerations	39
7. Acknowledgments	39
8. Normative References	39
9. Informative References	40
Author's Address	44

1. Introduction

YANG [RFC7950] is a data modeling language used to model configuration and state data manipulated by the Network Configuration Protocol (NETCONF) [RFC6241]. The YANG language supports a small set of built-in data types and provides mechanisms to derive other types from the built-in types.

This document defines a collection of common data types. The definitions are organized into two YANG modules:

- * The "ietf-yang-types" module defines generally useful data types such as types for counters, gauges, date and time related types, or types for common string values such as uuids, dotted-quads, or language tags.
- * The "ietf-inet-types" module defines data types relevant for the Internet protocol suite such as IP address related types, domain-name and host-name types, uri and email types, as well as types for values in common protocol fields such as port numbers.

The initial version of these YANG modules were published as [RFC6021]. The first revision of [RFC6021], published as [RFC6991], added several new type definitions to the YANG modules. This second revision adds further new type definitions and addresses errata 4076 [ERR4076] and 5105 [ERR5105] of [RFC6991]. Furthermore, the yang-identifier definition has been aligned with YANG 1.1 [RFC7950] and some pattern statements have been improved. For further details, see the revision statements of the YANG modules in Section 3 and Section 4. A brief overview of all types and when they were introduced can be found in Section 2. Additional type definitions may be added in the future by submitting proposals to the NETMOD working group.

This document uses the YANG terminology defined in Section 3 of [RFC7950].

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

2. Overview

Table 1 and Table 2 list the types defined in the YANG modules "ietf-yang-types" and "ietf-inet-types". For each type, the name of the type, the base type it was derived from, and the RFC introducing the type is listed.

Type	Base Type	Introduced
counter32	uint32	RFC 6021
zero-based-counter32	uint32	RFC 6021
counter64	uint64	RFC 6021
zero-based-counter64	uint64	RFC 6021
gauge32	uint32	RFC 6021
gauge64	uint64	RFC 6021
object-identifier	string	RFC 6021
object-identifier-128	object-identifier	RFC 6021

date-and-time	string	RFC 6021	
+-----+-----+-----+			
date	string	RFC XXXX	
+-----+-----+-----+			
date-no-zone	string	RFC XXXX	
+-----+-----+-----+			
time	string	RFC XXXX	
+-----+-----+-----+			
time-no-zone	string	RFC XXXX	
+-----+-----+-----+			
hours32	int32	RFC XXXX	
+-----+-----+-----+			
minutes32	int32	RFC XXXX	
+-----+-----+-----+			
seconds32	int32	RFC XXXX	
+-----+-----+-----+			
centiseconds32	int32	RFC XXXX	
+-----+-----+-----+			
milliseconds32	int32	RFC XXXX	
+-----+-----+-----+			
microseconds32	int32	RFC XXXX	
+-----+-----+-----+			
microseconds64	int64	RFC XXXX	
+-----+-----+-----+			
nanoseconds32	int32	RFC XXXX	
+-----+-----+-----+			
nanoseconds64	int64	RFC XXXX	
+-----+-----+-----+			
timeticks	int32	RFC 6021	
+-----+-----+-----+			
timestamp	timeticks	RFC 6021	
+-----+-----+-----+			
phys-address	string	RFC 6021	
+-----+-----+-----+			
mac-address	string	RFC 6021	
+-----+-----+-----+			
xpath1.0	string	RFC 6021	
+-----+-----+-----+			
hex-string	string	RFC 6991	
+-----+-----+-----+			
uuid	string	RFC 6991	
+-----+-----+-----+			
dotted-quad	string	RFC 6991	
+-----+-----+-----+			
language-tag	string	RFC XXXX	
+-----+-----+-----+			
yang-identifier	string	RFC 6991	
+-----+-----+-----+			

Table 1: Types defined in ietf-yang-types

Type	Base Type	Introduced
ip-version	enum	RFC 6021
dscp	uint8	RFC 6021
ipv6-flow-label	uint32	RFC 6021
port-number	uint16	RFC 6021
protocol-number	uint8	RFC XXXX
upper-layer-protocol-number	protocol-number	RFC XXXX
as-number	uint32	RFC 6021
ip-address	union	RFC 6021
ipv4-address	string	RFC 6021
ipv6-address	string	RFC 6021
ip-address-no-zone	union	RFC 6991
ipv4-address-no-zone	ipv4-address	RFC 6991
ipv6-address-no-zone	ipv6-address	RFC 6991
ip-address-link-local	union	RFC XXXX
ipv4-address-link-local	ipv4-address	RFC XXXX
ipv6-address-link-local	ipv6-address	RFC XXXX
ip-prefix	union	RFC 6021
ipv4-prefix	string	RFC 6021
ipv6-prefix	string	RFC 6021
ip-address-and-prefix	union	RFC XXXX
ipv4-address-and-prefix	string	RFC XXXX
ipv6-address-and-prefix	string	RFC XXXX

domain-name	string	RFC 6021	
host-name	domain-name	RFC XXXX	
host	union	RFC 6021	
uri	string	RFC 6021	
email-address	string	RFC XXXX	

Table 2: Types defined in ietf-inet-types

Some types have an equivalent Structure of Management Information Version 2 (SMIV2) [RFC2578] [RFC2579] data type. A YANG data type is equivalent to an SMIV2 data type if the data types have the same set of values and the semantics of the values are equivalent.

Table 3 lists the types defined in the "ietf-yang-types" YANG module with their corresponding SMIV2 types and Table 4 lists the types defined in the "ietf-inet-types" module with their corresponding SMIV2 types.

YANG type	Equivalent SMIV2 type (module)
counter32	Counter32 (SNMPv2-SMI)
zero-based-counter32	ZeroBasedCounter32 (RMON2-MIB)
counter64	Counter64 (SNMPv2-SMI)
zero-based-counter64	ZeroBasedCounter64 (HCNUM-TC)
gauge32	Gauge32 (SNMPv2-SMI)
gauge64	CounterBasedGauge64 (HCNUM-TC)
object-identifier-128	OBJECT IDENTIFIER
centiseconds32	TimeInterval (SNMPv2-TC)
timeticks	TimeTicks (SNMPv2-SMI)
timestamp	TimeStamp (SNMPv2-TC)
phys-address	PhysAddress (SNMPv2-TC)
mac-address	MacAddress (SNMPv2-TC)
language-tag	LangTag (LANGTAG-TC-MIB)

Table 3: Equivalent SMIV2 types for ietf-yang-types

YANG type	Equivalent SMIV2 type (module)
ip-version	InetVersion (INET-ADDRESS-MIB)
dscp	Dscp (DIFFSERV-DSCP-TC)
ipv6-flow-label	IPv6FlowLabel (IPV6-FLOW-LABEL-MIB)
port-number	InetPortNumber (INET-ADDRESS-MIB)
as-number	InetAutonomousSystemNumber (INET-ADDRESS-MIB)
uri	Uri (URI-TC-MIB)

Table 4: Equivalent SMIV2 types for ietf-inet-types

3. Core YANG Types

The ietf-yang-types YANG module references [IEEE-802-2001], [ISO-9834-1], [RFC2578], [RFC2579], [RFC2856], [RFC3339], [RFC4122], [RFC4502], [RFC5131], [RFC5646], [RFC7950], [RFC8294], [RFC9557], [W3C.xpath], and [W3C.xmlschema11-2].

```
<CODE BEGINS> file "ietf-yang-types@2025-06-23.yang"
module ietf-yang-types {

    namespace "urn:ietf:params:xml:ns:yang:ietf-yang-types";
    prefix "yang";

    organization
        "IETF Network Modeling (NETMOD) Working Group";

    contact
        "WG Web:    <https://datatracker.ietf.org/wg/netmod/>
        WG List:    <mailto:netmod@ietf.org>

        Editor:     Juergen Schoenwaelder
                    <mailto:jschoenwaelder@constructor.university>";

    description
        "This module contains a collection of generally useful derived
        YANG data types.

        The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL
        NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED',
        'MAY', and 'OPTIONAL' in this document are to be interpreted as
```


described in BCP 14 (RFC 2119) (RFC 8174) when, and only when, they appear in all capitals, as shown here.

Copyright (c) 2025 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Revised BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
revision 2025-06-23 {
  description
    "This revision adds the following new data types:
    - yang:date
    - yang:date-no-zone
    - yang:time
    - yang:time-no-zone
    - yang:hours32
    - yang:minutes32
    - yang:seconds32
    - yang:centiseconds32
    - yang:milliseconds32
    - yang:microseconds32
    - yang:microseconds64
    - yang:nanoseconds32
    - yang:nanoseconds64
    - yang:language-tag
    The yang-identifier definition has been aligned with YANG
    1.1 and types representing time support the representation
    of leap seconds. The representation of time zone offsets
    has been aligned with RFC 9557. Several description and
    pattern statements have been improved.";
  reference
    "RFC XXXX: Common YANG Data Types";
}
```

```
revision 2013-07-15 {
  description
    "This revision adds the following new data types:
    - yang:yang-identifier
    - yang:hex-string
    - yang:uuid
```

```

    - yang:dotted-quad";
  reference
    "RFC 6991: Common YANG Data Types";
}

revision 2010-09-24 {
  description
    "Initial revision.";
  reference
    "RFC 6021: Common YANG Data Types";
}

/*** collection of counter and gauge types ***/

typedef counter32 {
  type uint32;
  description
    "The counter32 type represents a non-negative integer
    that monotonically increases until it reaches a
    maximum value of 2^32-1 (4294967295 decimal), when it
    wraps around and starts increasing again from zero.

    Counters have no defined 'initial' value, and thus, a
    single value of a counter has (in general) no information
    content. Discontinuities in the monotonically increasing
    value normally occur at re-initialization of the
    management system, and at other times as specified in the
    description of a schema node using this type. If such
    other times can occur, for example, the instantiation of
    a schema node of type counter32 at times other than
    re-initialization, then a corresponding schema node
    should be defined, with an appropriate type, to indicate
    the last discontinuity.

    The counter32 type should not be used for configuration
    schema nodes. A default statement SHOULD NOT be used in
    combination with the type counter32.

    In the value set and its semantics, this type is equivalent
    to the Counter32 type of the SMIV2.";
  reference
    "RFC 2578: Structure of Management Information Version 2
    (SMIV2)";
}

typedef zero-based-counter32 {
  type counter32;
  default "0";

```

description

"The zero-based-counter32 type represents a counter32 that has the defined 'initial' value zero.

A data tree node using this type will be set to zero (0) on creation and will thereafter increase monotonically until it reaches a maximum value of $2^{32}-1$ (4294967295 decimal), when it wraps around and starts increasing again from zero.

Provided that an application discovers a new data tree node using this type within the minimum time to wrap, it can use the 'initial' value as a delta. It is important for a management station to be aware of this minimum time and the actual time between polls, and to discard data if the actual time is too long or there is no defined minimum time.

In the value set and its semantics, this type is equivalent to the ZeroBasedCounter32 textual convention of the SMIV2.";

reference

"RFC 4502: Remote Network Monitoring Management Information Base Version 2";

}

typedef counter64 {

type uint64;

description

"The counter64 type represents a non-negative integer that monotonically increases until it reaches a maximum value of $2^{64}-1$ (18446744073709551615 decimal), when it wraps around and starts increasing again from zero.

Counters have no defined 'initial' value, and thus, a single value of a counter has (in general) no information content. Discontinuities in the monotonically increasing value normally occur at re-initialization of the management system, and at other times as specified in the description of a schema node using this type. If such other times can occur, for example, the instantiation of a schema node of type counter64 at times other than re-initialization, then a corresponding schema node should be defined, with an appropriate type, to indicate the last discontinuity.

The counter64 type should not be used for configuration schema nodes. A default statement SHOULD NOT be used in combination with the type counter64.

In the value set and its semantics, this type is equivalent

```
    to the Counter64 type of the SMIV2.";
reference
    "RFC 2578: Structure of Management Information Version 2
      (SMIV2)";
}

typedef zero-based-counter64 {
    type counter64;
    default "0";
    description
        "The zero-based-counter64 type represents a counter64 that
        has the defined 'initial' value zero.

        A data tree node using this type will be set to zero (0)
        on creation and will thereafter increase monotonically until
        it reaches a maximum value of 2^64-1 (18446744073709551615
        decimal), when it wraps around and starts increasing again
        from zero.

        Provided that an application discovers a new data tree node
        using this type within the minimum time to wrap, it can use
        the 'initial' value as a delta. It is important for a
        management station to be aware of this minimum time and the
        actual time between polls, and to discard data if the actual
        time is too long or there is no defined minimum time.

        In the value set and its semantics, this type is equivalent
        to the ZeroBasedCounter64 textual convention of the SMIV2.";
reference
    "RFC 2856: Textual Conventions for Additional High Capacity
      Data Types";
}

typedef gauge32 {
    type uint32;
    description
        "The gauge32 type represents a non-negative integer, which
        may increase or decrease, but shall never exceed a maximum
        value, nor fall below a minimum value. The maximum value
        cannot be greater than 2^32-1 (4294967295 decimal), and
        the minimum value cannot be smaller than 0. The value of
        a gauge32 has its maximum value whenever the information
        being modeled is greater than or equal to its maximum
        value, and has its minimum value whenever the information
        being modeled is smaller than or equal to its minimum value.
        If the information being modeled subsequently decreases
        below (increases above) the maximum (minimum) value, the
        gauge32 also decreases (increases)."
```

```

    In the value set and its semantics, this type is equivalent
    to the Gauge32 type of the SMIV2.";
reference
    "RFC 2578: Structure of Management Information Version 2
      (SMIV2)";
}

typedef gauge64 {
    type uint64;
    description
        "The gauge64 type represents a non-negative integer, which
        may increase or decrease, but shall never exceed a maximum
        value, nor fall below a minimum value. The maximum value
        cannot be greater than 2^64-1 (18446744073709551615), and
        the minimum value cannot be smaller than 0. The value of
        a gauge64 has its maximum value whenever the information
        being modeled is greater than or equal to its maximum
        value, and has its minimum value whenever the information
        being modeled is smaller than or equal to its minimum value.
        If the information being modeled subsequently decreases
        below (increases above) the maximum (minimum) value, the
        gauge64 also decreases (increases).

        In the value set and its semantics, this type is equivalent
        to the CounterBasedGauge64 SMIV2 textual convention defined
        in RFC 2856";
reference
    "RFC 2856: Textual Conventions for Additional High Capacity
      Data Types";
}

/*** collection of identifier-related types ***/

typedef object-identifier {
    type string {
        pattern '([0-1](\.[1-3]?[0-9]))|(2\.(0|([1-9][0-9]*)))'
            + '(\.(0|([1-9][0-9]*)))';
    }
    description
        "The object-identifier type represents administratively
        assigned names in a registration-hierarchical-name tree.

        Values of this type are denoted as a sequence of numerical
        non-negative sub-identifier values. Each sub-identifier
        value MUST NOT exceed 2^32-1 (4294967295). Sub-identifiers
        are separated by single dots and without any intermediate
        whitespace."

```

The ASN.1 standard restricts the value space of the first sub-identifier to 0, 1, or 2. Furthermore, the value space of the second sub-identifier is restricted to the range 0 to 39 if the first sub-identifier is 0 or 1. Finally, the ASN.1 standard requires that an object identifier has always at least two sub-identifiers. The pattern captures these restrictions.

Although the number of sub-identifiers is not limited, module designers should realize that there may be implementations that stick with the SMIV2 limit of 128 sub-identifiers.

This type is a superset of the SMIV2 OBJECT IDENTIFIER type since it is not restricted to 128 sub-identifiers. Hence, this type SHOULD NOT be used to represent the SMIV2 OBJECT IDENTIFIER type; the object-identifier-128 type SHOULD be used instead.";

reference

"ISO9834-1: Information technology -- Open Systems Interconnection -- Procedures for the operation of OSI Registration Authorities: General procedures and top arcs of the ASN.1 Object Identifier tree";

}

```
typedef object-identifier-128 {
  type object-identifier {
    pattern '[0-9]*(\.[0-9]*){1,127}';
  }
}
```

description

"This type represents object-identifiers restricted to 128 sub-identifiers.

In the value set and its semantics, this type is equivalent to the OBJECT IDENTIFIER type of the SMIV2.";

reference

"RFC 2578: Structure of Management Information Version 2 (SMIV2)";

}

/** collection of types related to date and time */

```
typedef date-and-time {
  type string {
    pattern
      '[0-9]{4}-(1[0-2]|0[1-9])-(0[1-9]|1[1-2][0-9]|3[0-1])'
      + 'T(0[0-9]|1[0-9]|2[0-3]):[0-5][0-9]:([0-5][0-9]|60)(\.[0-9]+)?'
      + '(Z|[\+\-]((1[0-3]|0[0-9]):([0-5][0-9])|14:00))?'
  }
}
```

```

    }
    description
      "The date-and-time type is a profile of the ISO 8601
      standard for representation of dates and times using the
      Gregorian calendar. The profile is defined by the
      date-time production in Section 5.6 of RFC 3339 and the
      update defined in Section 2 of RFC 9557 . The value of
      60 for seconds is allowed only in the case of leap seconds.

      The date-and-time type is compatible with the dateTime XML
      schema dateTime type with the following notable exceptions:

      (a) The date-and-time type does not allow negative years.

      (b) The time-offset Z indicates that the date-and-time
          value is reported in UTC and that the local time zone
          reference point is unknown. The time-offsets +00:00
          indicates that the date-and-time value is reported in
          UTC and that the local time reference point is UTC
          (see RFC 9557 section 2).

      This type is not equivalent to the DateAndTime textual
      convention of the SMIV2 since RFC 3339 uses a different
      separator between full-date and full-time and provides
      higher resolution of time-secfrac.

      The canonical format for date-and-time values with a known time
      zone uses a numeric time zone offset that is calculated using
      the device's configured known offset to UTC time. A change of
      the device's offset to UTC time will cause date-and-time values
      to change accordingly. Such changes might happen periodically
      in case a server follows automatically daylight saving time
      (DST) time zone offset changes. The canonical format for
      date-and-time values reported in UTC with an unknown local
      time zone offset SHOULD use the time-offset Z and MAY use
      -00:00 for backwards compatibility.";
    reference
      "RFC 3339: Date and Time on the Internet: Timestamps
      RFC 9557: Date and Time on the Internet: Timestamps
        with Additional Information
      RFC 2579: Textual Conventions for SMIV2
      XSD-TYPES: XML Schema Definition Language (XSD) 1.1
        Part 2: Datatypes";
  }

  typedef date {
    type string {
      pattern

```

```

        '[0-9]{4}-(1[0-2]|0[1-9])-(0[1-9]|[1-2][0-9]|3[0-1])'
    + '(Z|[\+\-]((1[0-3]|0[0-9]):([0-5][0-9])|14:00))?';
    }
    description
        "The date type represents a time-interval of the length
        of a day, i.e., 24 hours. It includes an optional time
        zone offset.

        The date type is compatible with the XML schema date
        type with the following notable exceptions:

        (a) The date type does not allow negative years.

        (b) The time-offset Z indicates that the date value is
            reported in UTC and that the local time zone reference
            point is unknown. The time-offset +00:00 indicates that
            the date value is reported in UTC and that the local
            time reference point is UTC (see RFC 9557 section 2).

        The canonical format for date values with a known time
        zone uses a numeric time zone offset that is calculated using
        the device's configured known offset to UTC time. A change of
        the device's offset to UTC time will cause date values
        to change accordingly. Such changes might happen periodically
        in case a server follows automatically daylight saving time
        (DST) time zone offset changes. The canonical format for
        date values reported in UTC with an unknown local time zone
        offset uses the time-offset Z.";
    reference
        "RFC 3339: Date and Time on the Internet: Timestamps
        RFC 9557: Date and Time on the Internet: Timestamps
            with Additional Information
        XSD-TYPES: XML Schema Definition Language (XSD) 1.1
            Part 2: Datatypes";
    }

    typedef date-no-zone {
        type date {
            pattern '[0-9]{4}-(1[0-2]|0[1-9])-(0[1-9]|[1-2][0-9]|3[0-1])';
        }
        description
            "The date-no-zone type represents a date without the optional
            time zone offset information.";
    }

    typedef time {
        type string {
            pattern

```



```

        '(0[0-9]|1[0-9]|2[0-3]):[0-5][0-9]:([0-5][0-9]|60)(\[0-9]+\)?'
    + '(Z|[\+\-]((1[0-3]|0[0-9]):([0-5][0-9])|14:00))?'
    }
description
    "The time type represents an instance of time of zero-duration
    that recurs every day. It includes an optional time zone
    offset. The value of 60 for seconds is allowed only in the
    case of leap seconds.

    The time type is compatible with the XML schema time
    type with the following notable exception:

    (a) The time-offset Z indicates that the time value is
    reported in UTC and that the local time zone reference
    point is unknown. The time-offset +00:00 indicates that
    the time value is reported in UTC and that the local
    time reference point is UTC (see RFC 9557 section 2).

    The canonical format for time values with a known time
    zone uses a numeric time zone offset that is calculated using
    the device's configured known offset to UTC time. A change of
    the device's offset to UTC time will cause time values
    to change accordingly. Such changes might happen periodically
    in case a server follows automatically daylight saving time
    (DST) time zone offset changes. The canonical format for
    time values reported in UTC with an unknown local time zone
    offset uses the time-offset Z."
reference
    "RFC 3339: Date and Time on the Internet: Timestamps
    RFC 9557: Date and Time on the Internet: Timestamps
        with Additional Information
    XSD-TYPES: XML Schema Definition Language (XSD) 1.1
        Part 2: Datatypes";
}

typedef time-no-zone {
    type time {
        pattern
            '(0[0-9]|1[0-9]|2[0-3]):[0-5][0-9]:([0-5][0-9]|60)(\[0-9]+\)?';
    }
description
    "The time-no-zone type represents a time without the optional
    time zone offset information."
}

typedef hours32 {
    type int32;
    units "hours";
}

```

```
description
  "A period of time, measured in units of hours.

  The maximum time period that can be expressed is in the
  range [-89478485 days 08:00:00 to 89478485 days 07:00:00].

  This type should be range restricted in situations
  where only non-negative time periods are desirable,
  (i.e., range '0..max').";
}

typedef minutes32 {
  type int32;
  units "minutes";
  description
    "A period of time, measured in units of minutes.

    The maximum time period that can be expressed is in the
    range [-1491308 days 2:08:00 to 1491308 days 2:07:00].

    This type should be range restricted in situations
    where only non-negative time periods are desirable,
    (i.e., range '0..max').";
}

typedef seconds32 {
  type int32;
  units "seconds";
  description
    "A period of time, measured in units of seconds.

    The maximum time period that can be expressed is in the
    range [-24855 days 03:14:08 to 24855 days 03:14:07].

    This type should be range restricted in situations
    where only non-negative time periods are desirable,
    (i.e., range '0..max').";
}

typedef centiseconds32 {
  type int32;
  units "centiseconds";
  description
    "A period of time, measured in units of 10-2 seconds.

    The maximum time period that can be expressed is in the
    range [-248 days 13:13:56 to 248 days 13:13:56].
```

```
    This type should be range restricted in situations
    where only non-negative time periods are desirable,
    (i.e., range '0..max').";
}

typedef milliseconds32 {
    type int32;
    units "milliseconds";
    description
        "A period of time, measured in units of 10-3 seconds.

        The maximum time period that can be expressed is in the
        range [-24 days 20:31:23 to 24 days 20:31:23].

        This type should be range restricted in situations
        where only non-negative time periods are desirable,
        (i.e., range '0..max').";
}

typedef microseconds32 {
    type int32;
    units "microseconds";
    description
        "A period of time, measured in units of 10-6 seconds.

        The maximum time period that can be expressed is in the
        range [-00:35:47 to 00:35:47].

        This type should be range restricted in situations
        where only non-negative time periods are desirable,
        (i.e., range '0..max').";
}

typedef microseconds64 {
    type int64;
    units "microseconds";
    description
        "A period of time, measured in units of 10-6 seconds.

        The maximum time period that can be expressed is in the
        range [-106751991 days 04:00:54 to 106751991 days 04:00:54].

        This type should be range restricted in situations
        where only non-negative time periods are desirable,
        (i.e., range '0..max').";
}

typedef nanoseconds32 {
```

```
type int32;
units "nanoseconds";
description
  "A period of time, measured in units of 10^-9 seconds.

  The maximum time period that can be expressed is in the
  range [-00:00:02 to 00:00:02].

  This type should be range restricted in situations
  where only non-negative time periods are desirable,
  (i.e., range '0..max').";
}

typedef nanoseconds64 {
  type int64;
  units "nanoseconds";
  description
    "A period of time, measured in units of 10^-9 seconds.

    The maximum time period that can be expressed is in the
    range [-106753 days 23:12:44 to 106752 days 0:47:16].

    This type should be range restricted in situations
    where only non-negative time periods are desirable,
    (i.e., range '0..max').";
}

typedef timeticks {
  type uint32;
  description
    "The timeticks type represents a non-negative integer that
    represents the time, modulo 2^32 (4294967296 decimal), in
    hundredths of a second between two epochs.  When a schema
    node is defined that uses this type, the description of
    the schema node identifies both of the reference epochs.

    In the value set and its semantics, this type is equivalent
    to the TimeTicks type of the SMIV2.";
  reference
    "RFC 2578: Structure of Management Information Version 2
    (SMIV2)";
}

typedef timestamp {
  type timeticks;
  description
    "The timestamp type represents the value of an associated
    timeticks schema node instance at which a specific occurrence
```

happened. The specific occurrence must be defined in the description of any schema node defined using this type. When the specific occurrence occurred prior to the last time the associated timeticks schema node instance was zero, then the timestamp value is zero.

Note that this requires all timestamp values to be reset to zero when the value of the associated timeticks schema node instance reaches 497+ days and wraps around to zero.

The associated timeticks schema node must be specified in the description of any schema node using this type.

In the value set and its semantics, this type is equivalent to the TimeStamp textual convention of the SMIV2.";

reference

"RFC 2579: Textual Conventions for SMIV2";

}

/** collection of generic address types */

typedef phys-address {

type string {

pattern '([0-9a-fA-F]{2}(:[0-9a-fA-F]{2})*)?';

}

description

"Represents media- or physical-level addresses represented as a sequence octets, each octet represented by two hexadecimal numbers. Octets are separated by colons. The canonical representation uses lowercase characters.

In the value set and its semantics, this type is equivalent to the PhysAddress textual convention of the SMIV2.";

reference

"RFC 2579: Textual Conventions for SMIV2";

}

typedef mac-address {

type string {

pattern '[0-9a-fA-F]{2}(:[0-9a-fA-F]{2}){5}';

}

description

"The mac-address type represents a 48-bit IEEE 802 MAC address. The canonical representation uses lowercase characters. Note that there are IEEE 802 MAC addresses with a different length that this type cannot represent. The phys-address type may be used to represent physical addresses of varying length.

```

    In the value set and its semantics, this type is equivalent
    to the MacAddress textual convention of the SMIV2.";
reference
  "IEEE 802: IEEE Standard for Local and Metropolitan Area
    Networks: Overview and Architecture
    RFC 2579: Textual Conventions for SMIV2";
}

/*** collection of XML-specific types ***/

typedef xpath1.0 {
  type string;
  description
    "This type represents an XPATH 1.0 expression.

    When a schema node is defined that uses this type, the
    description of the schema node MUST specify the XPath
    context in which the XPath expression is evaluated.";
  reference
    "XPath: XML Path Language (XPath) Version 1.0";
}

/*** collection of string types ***/

typedef hex-string {
  type string {
    pattern '([0-9a-fA-F]{2}(:[0-9a-fA-F]{2}))*?';
  }
  description
    "A hexadecimal string with octets represented as hex digits
    separated by colons. The canonical representation uses
    lowercase characters.";
}

typedef uuid {
  type string {
    pattern '[0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-'
      + '[0-9a-fA-F]{4}-[0-9a-fA-F]{12}';
  }
  description
    "A Universally Unique IDentifier in the string representation
    defined in RFC 4122. The canonical representation uses
    lowercase characters.

    The following is an example of a UUID in string representation:
    f81d4fae-7dec-11d0-a765-00a0c91e6bf6
    ";
  reference

```

```
    "RFC 4122: A Universally Unique IDentifier (UUID) URN
      Namespace";
}

typedef dotted-quad {
  type string {
    pattern
      '([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\.){3}'
      + '([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])';
  }
  description
    "An unsigned 32-bit number expressed in the dotted-quad
    notation, i.e., four octets written as decimal numbers
    and separated with the '.' (full stop) character.";
}

typedef language-tag {
  type string;
  description
    "A language tag according to RFC 5646 (BCP 47). The
    canonical representation uses lowercase characters.

    Values of this type must be well-formed language tags,
    in conformance with the definition of well-formed tags
    in BCP 47. Implementations MAY further limit the values
    they accept to those permitted by a 'validating'
    processor, as defined in BCP 47.

    The canonical representation of values of this type is
    aligned with the SMIV2 LangTag textual convention for
    language tags fitting the length constraints imposed
    by the LangTag textual convention.";
  reference
    "RFC 5646: Tags for Identifying Languages
    RFC 5131: A MIB Textual Convention for Language Tags";
}

/*** collection of YANG specific types ***/

typedef yang-identifier {
  type string {
    length "1..max";
    pattern '[a-zA-Z_][a-zA-Z0-9\-\_\.]*';
  }
  description
    "A YANG identifier string as defined by the 'identifier'
    rule in Section 14 of RFC 7950. An identifier must
    start with an alphabetic character or an underscore
```

followed by an arbitrary sequence of alphabetic or numeric characters, underscores, hyphens, or dots.

This definition conforms to YANG 1.1 defined in RFC 7950. An earlier version of this definition excluded all identifiers starting with any possible combination of the lowercase or uppercase character sequence 'xml', as required by YANG 1 defined in RFC 6020. If this type is used in a YANG 1 context, then this restriction still applies.";

reference

"RFC 7950: The YANG 1.1 Data Modeling Language

RFC 6020: YANG - A Data Modeling Language for the
Network Configuration Protocol (NETCONF)";

}

}

<CODE ENDS>

4. Internet Protocol Suite Types

The ietf-inet-types YANG module references [RFC0768], [RFC0791], [RFC0952], [RFC1034], [RFC1123], [RFC1930], [RFC2317], [RFC2474], [RFC2780], [RFC2782], [RFC3289], [RFC3305], [RFC3595], [RFC3927], [RFC3986], [RFC4001], [RFC4007], [RFC4271], [RFC4291], [RFC4340], [RFC4592], [RFC5017], [RFC5322], [RFC5890], [RFC5952], [RFC6793], [RFC8200], [RFC9260], [RFC9293], and [RFC9499].

<CODE BEGINS> file "ietf-inet-types@2025-06-23.yang"

module ietf-inet-types {

namespace "urn:ietf:params:xml:ns:yang:ietf-inet-types";
prefix "inet";

organization

"IETF Network Modeling (NETMOD) Working Group";

contact

"WG Web: <<https://datatracker.ietf.org/wg/netmod/>>

WG List: <<mailto:netmod@ietf.org>>

Editor: Juergen Schoenwaelder

<<mailto:jschoenwaelder@constructor.university>>;

description

"This module contains a collection of generally useful derived
YANG data types for Internet addresses and related things.

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document are to be interpreted as described in BCP 14 (RFC 2119) (RFC 8174) when, and only when, they appear in all capitals, as shown here.

Copyright (c) 2025 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Revised BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
revision 2025-06-23 {
  description
    "This revision adds the following new data types:
    - inet:ip-address-and-prefix
    - inet:ipv4-address-and-prefix
    - inet:ipv6-address-and-prefix
    - inet:protocol-number
    - inet:upper-layer-protocol-number
    - inet:host-name
    - inet:email-address
    - inet:ip-address-link-local
    - inet:ipv4-address-link-local
    - inet:ipv6-address-link-local
    The inet:host union was changed to use inet:host-name instead
    of inet:domain-name. Several pattern statements have been
    improved.";
  reference
    "RFC XXXX: Common YANG Data Types";
}

revision 2013-07-15 {
  description
    "This revision adds the following new data types:
    - inet:ip-address-no-zone
    - inet:ipv4-address-no-zone
    - inet:ipv6-address-no-zone";
  reference
    "RFC 6991: Common YANG Data Types";
}
```

```
revision 2010-09-24 {
  description
    "Initial revision.";
  reference
    "RFC 6021: Common YANG Data Types";
}

/** collection of types related to protocol fields */

typedef ip-version {
  type enumeration {
    enum unknown {
      value "0";
      description
        "An unknown or unspecified version of the Internet
        protocol.";
    }
    enum ipv4 {
      value "1";
      description
        "The IPv4 protocol as defined in RFC 791.";
    }
    enum ipv6 {
      value "2";
      description
        "The IPv6 protocol as defined in RFC 8200.";
    }
  }
  description
    "This value represents the version of the IP protocol.

    In the value set and its semantics, this type is equivalent
    to the InetVersion textual convention of the SMIV2.";
  reference
    "RFC 791: Internet Protocol
    RFC 8200: Internet Protocol, Version 6 (IPv6) Specification
    RFC 4001: Textual Conventions for Internet Network Addresses";
}

typedef dscp {
  type uint8 {
    range "0..63";
  }
  description
    "The dscp type represents a Differentiated Services Code Point
    that may be used for marking packets in a traffic stream.

    In the value set and its semantics, this type is equivalent
```

```
    to the Dscp textual convention of the SMIV2.";
reference
  "RFC 3289: Management Information Base for the Differentiated
    Services Architecture
  RFC 2474: Definition of the Differentiated Services Field
    (DS Field) in the IPv4 and IPv6 Headers
  RFC 2780: IANA Allocation Guidelines For Values In
    the Internet Protocol and Related Headers";
}

typedef ipv6-flow-label {
  type uint32 {
    range "0..1048575";
  }
  description
    "The ipv6-flow-label type represents the flow identifier or
    Flow Label in an IPv6 packet header that may be used to
    discriminate traffic flows.

    In the value set and its semantics, this type is equivalent
    to the IPv6FlowLabel textual convention of the SMIV2.";
reference
  "RFC 3595: Textual Conventions for IPv6 Flow Label
  RFC 8200: Internet Protocol, Version 6 (IPv6) Specification";
}

typedef port-number {
  type uint16 {
    range "0..65535";
  }
  description
    "The port-number type represents a 16-bit port number of an
    Internet transport-layer protocol such as UDP, TCP, DCCP, or
    SCTP.

    Port numbers are assigned by IANA. The current list of
    all assignments is available from <https://www.iana.org/>.

    Note that the port number value zero is reserved by IANA. In
    situations where the value zero does not make sense, it can
    be excluded by subtyping the port-number type.

    In the value set and its semantics, this type is equivalent
    to the InetPortNumber textual convention of the SMIV2.";
reference
  "RFC 768: User Datagram Protocol
  RFC 9293: Transmission Control Protocol (TCP)
  RFC 9260: Stream Control Transmission Protocol
```

```
    RFC 4340: Datagram Congestion Control Protocol (DCCP)
    RFC 4001: Textual Conventions for Internet Network Addresses";
}

typedef protocol-number {
    type uint8;
    description
        "The protocol-number type represents an 8-bit Internet
        protocol number, carried in the 'protocol' field of the
        IPv4 header or in the 'next header' field of the IPv6
        header.

        Protocol numbers are assigned by IANA. The current list of
        all assignments is available from <https://www.iana.org/>.";
    reference
        "RFC 791: Internet Protocol
        RFC 8200: Internet Protocol, Version 6 (IPv6) Specification";
}

typedef upper-layer-protocol-number {
    type protocol-number;
    description
        "The upper-layer-protocol-number represents the upper-layer
        protocol number carried in an IP packet. For IPv6 packets
        with extension headers, this is the protocol number carried
        in the last 'next header' field of the chain of IPv6 extension
        headers.";
    reference
        "RFC 791: Internet Protocol
        RFC 8200: Internet Protocol, Version 6 (IPv6) Specification";
}

/** collection of types related to autonomous systems */

typedef as-number {
    type uint32;
    description
        "The as-number type represents autonomous system numbers
        which identify an Autonomous System (AS). An AS is a set
        of routers under a single technical administration, using
        an interior gateway protocol and common metrics to route
        packets within the AS, and using an exterior gateway
        protocol to route packets to other ASes. IANA maintains
        the AS number space and has delegated large parts to the
        regional registries.

        Autonomous system numbers were originally limited to 16
        bits. BGP extensions have enlarged the autonomous system
```

number space to 32 bits. This type therefore uses an uint32 base type without a range restriction in order to support a larger autonomous system number space.

In the value set and its semantics, this type is equivalent to the InetAutonomousSystemNumber textual convention of the SMIV2."

reference

"RFC 1930: Guidelines for creation, selection, and registration of an Autonomous System (AS)
RFC 4271: A Border Gateway Protocol 4 (BGP-4)
RFC 4001: Textual Conventions for Internet Network Addresses
RFC 6793: BGP Support for Four-Octet Autonomous System (AS) Number Space";

}

/** collection of types related to IP addresses and hostnames */

typedef ip-address {

type union {

type ipv4-address;

type ipv6-address;

}

description

"The ip-address type represents an IP address and is IP version neutral. The format of the textual representation implies the IP version. This type supports scoped addresses by allowing zone identifiers in the address format.";

reference

"RFC 4007: IPv6 Scoped Address Architecture";

}

typedef ipv4-address {

type string {

pattern

'([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\.){3}'

+ '([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])'

+ '(%.)?';

}

description

"The ipv4-address type represents an IPv4 address in dotted-quad notation. The IPv4 address may include a zone index, separated by a % sign. If a system uses zone names that are not represented in UTF-8, then an implementation needs to use some mechanism to transform the local name into UTF-8. The definition of such a mechanism is outside the scope of this document.

The zone index is used to disambiguate identical address values. For link-local addresses, the zone index will typically be the interface index number or the name of an interface. If the zone index is not present, the default zone of the device will be used.

The canonical format for the zone index is the numerical format";

}

```
typedef ipv6-address {
  type string {
    pattern '((:[0-9a-fA-F]{0,4})|([0-9a-fA-F]{0,4}:){0,5}'
      + '([0-9a-fA-F]{0,4}:)?(:|[0-9a-fA-F]{0,4}))|'
      + '(((25[0-5]|2[0-4][0-9]|[01]?[0-9]?[0-9])\.){3}'
      + '(25[0-5]|2[0-4][0-9]|[01]?[0-9]?[0-9]))|'
      + '(%[A-Za-z0-9][A-Za-z0-9\-\.\_~/*]?);'
    pattern '([[:^:]]+){6}([[:^:]]+:[[:^:]]+)|(.*\..*)|'
      + '([[:^:]]+)*[[:^:]]+?:([[:^:]]+)*[[:^:]]+)?'
      + '(%.+)?';
  }
}
```

description

"The ipv6-address type represents an IPv6 address in full, mixed, shortened, and shortened-mixed notation. The IPv6 address may include a zone index, separated by a % sign. If a system uses zone names that are not represented in UTF-8, then an implementation needs to use some mechanism to transform the local name into UTF-8. The definition of such a mechanism is outside the scope of this document.

The zone index is used to disambiguate identical address values. For link-local addresses, the zone index will typically be the interface index number or the name of an interface. If the zone index is not present, the default zone of the device will be used.

The canonical format of IPv6 addresses uses the textual representation defined in Section 4 of RFC 5952. The canonical format for the zone index is the numerical format as described in Section 11.2 of RFC 4007.";

reference

"RFC 4291: IP Version 6 Addressing Architecture
 RFC 4007: IPv6 Scoped Address Architecture
 RFC 5952: A Recommendation for IPv6 Address Text Representation";

}

```
typedef ip-address-no-zone {
```

```
    type union {
      type ipv4-address-no-zone;
      type ipv6-address-no-zone;
    }
    description
      "The ip-address-no-zone type represents an IP address and is
      IP version neutral. The format of the textual representation
      implies the IP version. This type does not support scoped
      addresses since it does not allow zone identifiers in the
      address format.";
    reference
      "RFC 4007: IPv6 Scoped Address Architecture";
  }

  typedef ipv4-address-no-zone {
    type ipv4-address {
      pattern '[0-9\\.]*';
    }
    description
      "An IPv4 address without a zone index. This type, derived
      from the type ipv4-address, may be used in situations where
      the zone is known from the context and no zone index is
      needed.";
  }

  typedef ipv6-address-no-zone {
    type ipv6-address {
      pattern '[0-9a-fA-F:\\.]*';
    }
    description
      "An IPv6 address without a zone index. This type, derived
      from the type ipv6-address, may be used in situations where
      the zone is known from the context and no zone index is
      needed.";
    reference
      "RFC 4291: IP Version 6 Addressing Architecture
      RFC 4007: IPv6 Scoped Address Architecture
      RFC 5952: A Recommendation for IPv6 Address Text
      Representation";
  }

  typedef ip-address-link-local {
    type union {
      type ipv4-address-link-local;
      type ipv6-address-link-local;
    }
    description
      "The ip-address-link-local type represents a link-local IP
```

```
    address and is IP version neutral. The format of the textual
    representation implies the IP version.";
}

typedef ipv4-address-link-local {
  type ipv4-address {
    pattern '169\.254\..*';
  }
  description
    "A link-local IPv4 address in the prefix 169.254.0.0/16 as
    defined in section 2.1. of RFC 3927.";
  reference
    "RFC 3927: Dynamic Configuration of IPv4 Link-Local Addresses";
}

typedef ipv6-address-link-local {
  type ipv6-address {
    pattern '[fF][eE]80:.*';
  }
  description
    "A link-local IPv6 address in the prefix fe80::/10 as defined
    in section 2.5.6. of RFC 4291.";
  reference
    "RFC 4291: IP Version 6 Addressing Architecture";
}

typedef ip-prefix {
  type union {
    type ipv4-prefix;
    type ipv6-prefix;
  }
  description
    "The ip-prefix type represents an IP prefix and is IP
    version neutral. The format of the textual representations
    implies the IP version.";
}

typedef ipv4-prefix {
  type string {
    pattern
      '([([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\.]{3})'
      + '([([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])'
      + '/([([0-9])|([1-2][0-9])|(3[0-2])))'
  }
  description
    "The ipv4-prefix type represents an IPv4 prefix.
    The prefix length is given by the number following the
    slash character and must be less than or equal to 32.
```


A prefix length value of *n* corresponds to an IP address mask that has *n* contiguous 1-bits from the most significant bit (MSB) and all other bits set to 0.

The canonical format of an IPv4 prefix has all bits of the IPv4 address set to zero that are not part of the IPv4 prefix.

The definition of `ipv4-prefix` does not require that bits, which are not part of the prefix, are set to zero. However, implementations have to return values in canonical format, which requires non-prefix bits to be set to zero. This means that 192.0.2.1/24 must be accepted as a valid value but it will be converted into the canonical format 192.0.2.0/24."

}

```
typedef ipv6-prefix {
  type string {
    pattern '((:[0-9a-fA-F]{0,4})|([0-9a-fA-F]{0,4}:){0,5}'
      + '([0-9a-fA-F]{0,4}:)?(:[0-9a-fA-F]{0,4})|'
      + '(((25[0-5]|2[0-4][0-9]|[01]?[0-9]?[0-9])\.){3}'
      + '(25[0-5]|2[0-4][0-9]|[01]?[0-9]?[0-9]))'
      + '(/(((0-9)|([0-9]{2})|(1[0-1][0-9])|(12[0-8]))))';
    pattern '([[:^:]]+){6}([[:^:]]+:[[:^:]]+|(.*\..*))|'
      + '([[:^:]]+)*[[:^:]]+?:([[:^:]]+)*[[:^:]]+?'
      + '(/.+)';
  }
}
```

description

"The `ipv6-prefix` type represents an IPv6 prefix.

The prefix length is given by the number following the slash character and must be less than or equal to 128.

A prefix length value of *n* corresponds to an IP address mask that has *n* contiguous 1-bits from the most significant bit (MSB) and all other bits set to 0.

The canonical format of an IPv6 prefix has all bits of the IPv6 address set to zero that are not part of the IPv6 prefix. Furthermore, the IPv6 address is represented as defined in Section 4 of RFC 5952.

The definition of `ipv6-prefix` does not require that bits, which are not part of the prefix, are set to zero. However, implementations have to return values in canonical format, which requires non-prefix bits to be set to zero. This means that 2001:db8::1/64 must be accepted as a valid value but it will be converted into the canonical format 2001:db8::/64."

reference

```

"RFC 5952: A Recommendation for IPv6 Address Text
Representation";
}

typedef ip-address-and-prefix {
    type union {
        type ipv4-address-and-prefix;
        type ipv6-address-and-prefix;
    }
    description
        "The ip-address-and-prefix type represents an IP address and
        prefix and is IP version neutral.  The format of the textual
        representations implies the IP version.";
}

typedef ipv4-address-and-prefix {
    type string {
        pattern
            '([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\.([0-9]|'
            + '([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5]))'
            + '/(((0-9)|([1-2][0-9])|([30-2]))';
    }
    description
        "The ipv4-address-and-prefix type represents an IPv4
        address and an associated IPv4 prefix.
        The prefix length is given by the number following the
        slash character and must be less than or equal to 32.

        A prefix length value of n corresponds to an IP address
        mask that has n contiguous 1-bits from the most
        significant bit (MSB) and all other bits set to 0.";
}

typedef ipv6-address-and-prefix {
    type string {
        pattern '(:|[0-9a-fA-F]{0,4}):([0-9a-fA-F]{0,4}:){0,5}'
            + '(((0-9a-fA-F){0,4}:)?(:|[0-9a-fA-F]{0,4}))|'
            + '(((25[0-5]|2[0-4][0-9]|01?[0-9]?[0-9])\.){3}'
            + '(25[0-5]|2[0-4][0-9]|01?[0-9]?[0-9]))'
            + '/(((0-9)|([0-9]{2})|([10-1][0-9])|([120-8]))));';
        pattern '([[:^:]]+){6}([[:^:]]+:[[:^:]]+)|(.*\.\.)*|'
            + '((([:^:]]+)*[[:^:]]+)?::([[:^:]]+)*[[:^:]]+)?'
            + '(/.+)';
    }
    description
        "The ipv6-address-and-prefix type represents an IPv6
        address and an associated IPv6 prefix.
        The prefix length is given by the number following the

```

slash character and must be less than or equal to 128.

A prefix length value of *n* corresponds to an IP address mask that has *n* contiguous 1-bits from the most significant bit (MSB) and all other bits set to 0.

The canonical format requires that the IPv6 address is represented as defined in Section 4 of RFC 5952.";

```
reference
  "RFC 5952: A Recommendation for IPv6 Address Text
    Representation";
}
```

/** collection of domain name and URI types */

```
typedef domain-name {
  type string {
    length "1..253";
    pattern
      '((([a-zA-Z0-9_]([a-zA-Z0-9\_-]){0,61})?[a-zA-Z0-9]\.)*'
      + '([a-zA-Z0-9_]([a-zA-Z0-9\_-]){0,61})?[a-zA-Z0-9]\.?)'
      + '\.';
  }
}
```

description

"The domain-name type represents a DNS domain name. The name SHOULD be fully qualified whenever possible. This type does not support wildcards (see RFC 4592) or classless in-addr.arpa delegations (see RFC 2317).

Internet domain names are only loosely specified. Section 3.5 of RFC 1034 recommends a syntax (modified in Section 2.1 of RFC 1123). The pattern above is intended to allow for current practice in domain name use, and some possible future expansion. Note that Internet host names have a stricter syntax (described in RFC 952) than the DNS recommendations in RFCs 1034 and 1123. Schema nodes representing host names should use the host-name type instead of the domain-type.

The encoding of DNS names in the DNS protocol is limited to 255 characters. Since the encoding consists of labels prefixed by a length bytes and there is a trailing NULL byte, only 253 characters can appear in the textual dotted notation.

The description clause of schema nodes using the domain-name type MUST describe when and how these names are resolved to IP addresses. Note that the resolution of a domain-name value

may require to query multiple DNS records (e.g., A for IPv4 and AAAA for IPv6). The order of the resolution process and which DNS record takes precedence can either be defined explicitly or may depend on the configuration of the resolver.

Domain-name values use the US-ASCII encoding. Their canonical format uses lowercase US-ASCII characters. Internationalized domain names MUST be A-labels as per RFC 5890.";

reference

"RFC 952: DoD Internet Host Table Specification
 RFC 1034: Domain Names - Concepts and Facilities
 RFC 1123: Requirements for Internet Hosts -- Application and Support
 RFC 2317: Classless IN-ADDR.ARPA delegation
 RFC 2782: A DNS RR for specifying the location of services (DNS SRV)
 RFC 4592: The Role of Wildcards in the Domain Name System
 RFC 5890: Internationalized Domain Names in Applications (IDNA): Definitions and Document Framework
 RFC 9499: DNS Terminology";

}

```
typedef host-name {
  type domain-name {
    length "2..max";
    pattern '[a-zA-Z0-9\-\.\.]+';
  }
}
```

description

"The host-name type represents (fully qualified) host names. Host names must be at least two characters long (see RFC 952) and they are restricted to labels consisting of letters, digits and hyphens separated by dots (see RFC1123 and RFC 952).";

reference

"RFC 952: DoD Internet Host Table Specification
 RFC 1123: Requirements for Internet Hosts -- Application and Support";

}

```
typedef host {
  type union {
    type ip-address;
    type host-name;
  }
}
```

description

"The host type represents either an IP address or a (fully qualified) host name.";

}

```
typedef uri {
  type string {
    pattern '[a-z][a-z0-9+.-]*:.~*';
  }
  description
    "The uri type represents a Uniform Resource Identifier
    (URI) as defined by the rule 'URI' in RFC 3986.

    Objects using the uri type MUST be in US-ASCII encoding,
    and MUST be normalized as described by RFC 3986 Sections
    6.2.1, 6.2.2.1, and 6.2.2.2. Characters that can be
    represented without using percent-encoding are represented
    as characters (without percent-encoding), and all
    case-insensitive characters are set to lowercase except
    for hexadecimal digits within a percent-encoded triplet,
    which are normalized to uppercase as described in
    Section 6.2.2.1 of RFC 3986.

    The purpose of this normalization is to help provide
    unique URIs. Note that this normalization is not
    sufficient to provide uniqueness. Two URIs that are
    textually distinct after this normalization may still be
    equivalent.

    Objects using the uri type may restrict the schemes that
    they permit. For example, 'data:' and 'urn:' schemes
    might not be appropriate.

    A zero-length URI is not a valid URI. This can be used to
    express 'URI absent' where required.

    In the value set and its semantics, this type is equivalent
    to the Uri SMIV2 textual convention defined in RFC 5017."
  reference
    "RFC 3986: Uniform Resource Identifier (URI): Generic Syntax
    RFC 3305: Report from the Joint W3C/IETF URI Planning Interest
    Group: Uniform Resource Identifiers (URIs), URLs,
    and Uniform Resource Names (URNs): Clarifications
    and Recommendations
    RFC 5017: MIB Textual Conventions for Uniform Resource
    Identifiers (URIs)"
}

typedef email-address {
  type string {
    pattern '.+@.+';
  }
  description
```

"The email-address type represents an internationalized email address.

The email address format is defined by the addr-spec ABNF rule in RFC 5322 section 3.4.1. This format has been extended by RFC 6532 to support internationalized email addresses. Implementations MUST support the internationalization extensions of RFC 6532. Support of the obsolete obs-local-part, obs-domain, and obs-qtext parts of RFC 5322 is not required.

The domain part may use both A-labels and U-labels (see RFC 5890). The canonical format of the domain part uses lowercase characters and U-labels (RFC 5890) where applicable.";

reference

"RFC 5322: Internet Message Format
RFC 5890: Internationalized Domain Names in Applications (IDNA): Definitions and Document Framework
RFC 6531: SMTP Extension for Internationalized Email";

}

}

<CODE ENDS>

5. IANA Considerations

This document reuses the URIs for "ietf-yang-types" and "ietf-inet-types" in the "IETF XML Registry" [RFC3688].

This document updates the module registration in the "YANG Module Names" registry to reference this RFC instead of [RFC6991] for "ietf-yang-types" and "ietf-inet-types". Following the format in [RFC6020], the following has been registered.

```
name:      ietf-yang-types
namespace: urn:ietf:params:xml:ns:yang:ietf-yang-types
prefix:    yang
reference:  RFC XXXX
```

```
name:      ietf-inet-types
namespace: urn:ietf:params:xml:ns:yang:ietf-inet-types
prefix:    inet
reference:  RFC XXXX
```

6. Security Considerations

This document defines common data types using the YANG data modeling language. The definitions themselves have no security impact on the Internet, but the usage of these definitions in concrete YANG modules might have. The security considerations spelled out in the YANG specification [RFC7950] apply for this document as well.

7. Acknowledgments

The following people contributed significantly to the original version of this document published as [RFC6020]: Andy Bierman, Martin Bjorklund, Balazs Lengyel, David Partain and Phil Shafer.

Helpful comments on various versions of this document were provided by the following individuals: Andy Bierman, Martin Bjorklund, Benoit Claise, Joel M. Halpern, Ladislav Lhotka, Lars-Johan Liman, and Dan Romascanu.

8. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3339] Klyne, G. and C. Newman, "Date and Time on the Internet: Timestamps", RFC 3339, DOI 10.17487/RFC3339, July 2002, <<https://www.rfc-editor.org/info/rfc3339>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, RFC 3986, DOI 10.17487/RFC3986, January 2005, <<https://www.rfc-editor.org/info/rfc3986>>.
- [RFC4007] Deering, S., Haberman, B., Jinmei, T., Nordmark, E., and B. Zill, "IPv6 Scoped Address Architecture", RFC 4007, DOI 10.17487/RFC4007, March 2005, <<https://www.rfc-editor.org/info/rfc4007>>.
- [RFC4122] Leach, P., Mealling, M., and R. Salz, "A Universally Unique IDentifier (UUID) URN Namespace", RFC 4122, DOI 10.17487/RFC4122, July 2005, <<https://www.rfc-editor.org/info/rfc4122>>.

- [RFC4291] Hinden, R. and S. Deering, "IP Version 6 Addressing Architecture", RFC 4291, DOI 10.17487/RFC4291, February 2006, <<https://www.rfc-editor.org/info/rfc4291>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8294] Liu, X., Qu, Y., Lindem, A., Hopps, C., and L. Berger, "Common YANG Data Types for the Routing Area", RFC 8294, DOI 10.17487/RFC8294, December 2017, <<https://www.rfc-editor.org/info/rfc8294>>.
- [RFC9499] Hoffman, P. and K. Fujiwara, "DNS Terminology", BCP 219, RFC 9499, DOI 10.17487/RFC9499, March 2024, <<https://www.rfc-editor.org/info/rfc9499>>.
- [RFC9557] Sharma, U. and C. Bormann, "Date and Time on the Internet: Timestamps with Additional Information", RFC 9557, DOI 10.17487/RFC9557, April 2024, <<https://www.rfc-editor.org/info/rfc9557>>.
- [W3C.xpath] Clark, J. and S. DeRose, "XML Path Language (XPath) Version 1.0", W3C REC xpath, W3C Recommendation xpath, W3C xpath, 16 November 1999, <<http://www.w3.org/TR/xpath>>.
- [W3C.xmlschema11-2] "W3C XML Schema Definition Language (XSD) 1.1 Part 2: Datatypes", W3C REC xmlschema11-2, W3C xmlschema11-2, <<https://www.w3.org/TR/xmlschema11-2/>>.

9. Informative References

- [RFC0768] Postel, J., "User Datagram Protocol", STD 6, RFC 768, DOI 10.17487/RFC0768, August 1980, <<https://www.rfc-editor.org/info/rfc768>>.

- [RFC0791] Postel, J., "Internet Protocol", STD 5, RFC 791, DOI 10.17487/RFC0791, September 1981, <<https://www.rfc-editor.org/info/rfc791>>.
- [RFC0952] Harrenstien, K., Stahl, M., and E. Feinler, "DoD Internet host table specification", RFC 952, DOI 10.17487/RFC0952, October 1985, <<https://www.rfc-editor.org/info/rfc952>>.
- [RFC1034] Mockapetris, P., "Domain names - concepts and facilities", STD 13, RFC 1034, DOI 10.17487/RFC1034, November 1987, <<https://www.rfc-editor.org/info/rfc1034>>.
- [RFC1123] Braden, R., Ed., "Requirements for Internet Hosts - Application and Support", STD 3, RFC 1123, DOI 10.17487/RFC1123, October 1989, <<https://www.rfc-editor.org/info/rfc1123>>.
- [RFC1930] Hawkinson, J. and T. Bates, "Guidelines for creation, selection, and registration of an Autonomous System (AS)", BCP 6, RFC 1930, DOI 10.17487/RFC1930, March 1996, <<https://www.rfc-editor.org/info/rfc1930>>.
- [RFC2317] Eidnes, H., de Groot, G., and P. Vixie, "Classless IN-ADDR.ARPA delegation", BCP 20, RFC 2317, DOI 10.17487/RFC2317, March 1998, <<https://www.rfc-editor.org/info/rfc2317>>.
- [RFC2474] Nichols, K., Blake, S., Baker, F., and D. Black, "Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers", RFC 2474, DOI 10.17487/RFC2474, December 1998, <<https://www.rfc-editor.org/info/rfc2474>>.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, DOI 10.17487/RFC2578, April 1999, <<https://www.rfc-editor.org/info/rfc2578>>.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, RFC 2579, DOI 10.17487/RFC2579, April 1999, <<https://www.rfc-editor.org/info/rfc2579>>.
- [RFC2780] Bradner, S. and V. Paxson, "IANA Allocation Guidelines For Values In the Internet Protocol and Related Headers", BCP 37, RFC 2780, DOI 10.17487/RFC2780, March 2000, <<https://www.rfc-editor.org/info/rfc2780>>.

- [RFC2782] Gulbrandsen, A., Vixie, P., and L. Esibov, "A DNS RR for specifying the location of services (DNS SRV)", RFC 2782, DOI 10.17487/RFC2782, February 2000, <<https://www.rfc-editor.org/info/rfc2782>>.
- [RFC2856] Bierman, A., McCloghrie, K., and R. Presuhn, "Textual Conventions for Additional High Capacity Data Types", RFC 2856, DOI 10.17487/RFC2856, June 2000, <<https://www.rfc-editor.org/info/rfc2856>>.
- [RFC3289] Baker, F., Chan, K., and A. Smith, "Management Information Base for the Differentiated Services Architecture", RFC 3289, DOI 10.17487/RFC3289, May 2002, <<https://www.rfc-editor.org/info/rfc3289>>.
- [RFC3305] Mealling, M., Ed. and R. Denenberg, Ed., "Report from the Joint W3C/IETF URI Planning Interest Group: Uniform Resource Identifiers (URIs), URLs, and Uniform Resource Names (URNs): Clarifications and Recommendations", RFC 3305, DOI 10.17487/RFC3305, August 2002, <<https://www.rfc-editor.org/info/rfc3305>>.
- [RFC3595] Wijnen, B., "Textual Conventions for IPv6 Flow Label", RFC 3595, DOI 10.17487/RFC3595, September 2003, <<https://www.rfc-editor.org/info/rfc3595>>.
- [RFC3927] Cheshire, S., Aboba, B., and E. Guttman, "Dynamic Configuration of IPv4 Link-Local Addresses", RFC 3927, DOI 10.17487/RFC3927, May 2005, <<https://www.rfc-editor.org/info/rfc3927>>.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", RFC 4001, DOI 10.17487/RFC4001, February 2005, <<https://www.rfc-editor.org/info/rfc4001>>.
- [RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", RFC 4271, DOI 10.17487/RFC4271, January 2006, <<https://www.rfc-editor.org/info/rfc4271>>.
- [RFC4340] Kohler, E., Handley, M., and S. Floyd, "Datagram Congestion Control Protocol (DCCP)", RFC 4340, DOI 10.17487/RFC4340, March 2006, <<https://www.rfc-editor.org/info/rfc4340>>.

- [RFC4502] Waldbusser, S., "Remote Network Monitoring Management Information Base Version 2", RFC 4502, DOI 10.17487/RFC4502, May 2006, <<https://www.rfc-editor.org/info/rfc4502>>.
- [RFC4592] Lewis, E., "The Role of Wildcards in the Domain Name System", RFC 4592, DOI 10.17487/RFC4592, July 2006, <<https://www.rfc-editor.org/info/rfc4592>>.
- [RFC5017] McWalter, D., Ed., "MIB Textual Conventions for Uniform Resource Identifiers (URIs)", RFC 5017, DOI 10.17487/RFC5017, September 2007, <<https://www.rfc-editor.org/info/rfc5017>>.
- [RFC5131] McWalter, D., Ed., "A MIB Textual Convention for Language Tags", RFC 5131, DOI 10.17487/RFC5131, December 2007, <<https://www.rfc-editor.org/info/rfc5131>>.
- [RFC5322] Resnick, P., Ed., "Internet Message Format", RFC 5322, DOI 10.17487/RFC5322, October 2008, <<https://www.rfc-editor.org/info/rfc5322>>.
- [RFC5646] Phillips, A., Ed. and M. Davis, Ed., "Tags for Identifying Languages", BCP 47, RFC 5646, DOI 10.17487/RFC5646, September 2009, <<https://www.rfc-editor.org/info/rfc5646>>.
- [RFC5890] Klensin, J., "Internationalized Domain Names for Applications (IDNA): Definitions and Document Framework", RFC 5890, DOI 10.17487/RFC5890, August 2010, <<https://www.rfc-editor.org/info/rfc5890>>.
- [RFC5952] Kawamura, S. and M. Kawashima, "A Recommendation for IPv6 Address Text Representation", RFC 5952, DOI 10.17487/RFC5952, August 2010, <<https://www.rfc-editor.org/info/rfc5952>>.
- [RFC6021] Schoenwaelder, J., Ed., "Common YANG Data Types", RFC 6021, DOI 10.17487/RFC6021, October 2010, <<https://www.rfc-editor.org/info/rfc6021>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.

- [RFC6793] Vohra, Q. and E. Chen, "BGP Support for Four-Octet Autonomous System (AS) Number Space", RFC 6793, DOI 10.17487/RFC6793, December 2012, <<https://www.rfc-editor.org/info/rfc6793>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", RFC 6991, DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/info/rfc6991>>.
- [RFC8200] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", STD 86, RFC 8200, DOI 10.17487/RFC8200, July 2017, <<https://www.rfc-editor.org/info/rfc8200>>.
- [RFC9260] Stewart, R., 端 xen, M., and K. Nielsen, "Stream Control Transmission Protocol", RFC 9260, DOI 10.17487/RFC9260, June 2022, <<https://www.rfc-editor.org/info/rfc9260>>.
- [RFC9293] Eddy, W., Ed., "Transmission Control Protocol (TCP)", STD 7, RFC 9293, DOI 10.17487/RFC9293, August 2022, <<https://www.rfc-editor.org/info/rfc9293>>.
- [ISO-9834-1]
ISO/IEC 9834-1:2008, "Information technology -- Open Systems Interconnection -- Procedures for the operation of OSI Registration Authorities: General procedures and top arcs of the ASN.1 Object Identifier tree", 2008.
- [IEEE-802-2001]
IEEE Std 802-2001, "IEEE Standard for Local and Metropolitan Area Networks: Overview and Architecture", June 2001.
- [ERR4076] "RFC Errata, Erratum 4076, RFC 6991", <<https://www.rfc-editor.org/errata/eid4076>>.
- [ERR5105] "RFC Errata, Erratum 5105, RFC 6991", <<https://www.rfc-editor.org/errata/eid5105>>.

Author's Address

端 rgen Sch旦 nw辰 lder (editor)
Constructor University
Email: jschoenwaelder@constructor.university