

sipcore
Internet-Draft
Obsoletes: 7976 (if approved)
Updates: 7315 (if approved)
Intended status: Informational
Expires: 14 February 2026

C. Holmberg
N. Biondic
Ericsson
G. Salgueiro
Cisco Systems, Inc.
R. Jesske
Deutsche Telekom
13 August 2025

Updates to Private Header (P-Header) Extension Usage in Session
Initiation Protocol (SIP) Requests and Responses
draft-ietf-sipcore-rfc7976bis-04.txt

Abstract

The Third Generation Partnership Project (3GPP) has identified cases where different SIP private header extensions referred to as "P-" header fields, and defined in RFC 7315, need to be included in SIP requests and responses currently not allowed according to RFC 7315. This document updates RFC 7315, in order to allow inclusion of the affected "P-" header fields in such requests and responses. This Document obsoletes RFC 7976. The changes related to RFC7976 involve the inclusion of the P-Visited-Network-ID header field in SIP responses.

This document also makes updates for RFC 7315 in order to fix misalignments that occurred when RFC 3455 was updated and subsequently obsoleted by the publication of RFC 7315.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 13 February 2026.

Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	2
2. Misalignments and 3GPP Use Cases	3
2.1. General	3
2.2. Misalignments	3
2.3. 3GPP Use Cases	4
2.3.1. General	4
2.3.2. P-Access-Network-Info	4
2.3.3. P-Charging-Vector	5
3. Updates to RFC 7315	6
4. IANA Considerations	7
5. Security Considerations	7
6. Operational considerations	7
7. Changes since RFC7976	7
8. Acknowledgments	8
9. References	8
9.1. Normative References	8
9.2. Informative References	8
Authors' Addresses	8

1. Introduction

The Third Generation Partnership Project (3GPP) has identified cases where different Session Initiation Protocol (SIP) [RFC3261] private header extensions referred to as "P-" header fields, and defined in [RFC7315], need to be included in SIP requests and responses currently not allowed according to [RFC7315]. This document updates [RFC7315], in order to allow inclusion of the affected "P-" header fields in such requests and responses.

This document also makes updates for [RFC7315] in order to fix misalignments that occurred when [RFC3455] was updated and subsequently obsoleted by the publication of [RFC7315].

2. Misalignments and 3GPP Use Cases

2.1. General

[RFC7315] contains contradicting statements regarding the usage of SIP "P-" header fields in SIP requests and responses, which leave the presence of the SIP "P-" header fields in the SIP requests and responses open to interpretation and different implementations. Statements in Section 5.7 of that RFC are not aligned with the definitions and usage of the SIP "P-" header fields specified in Section 4. This section describes the misalignments that occurred when [RFC3455] was updated and subsequently obsoleted by the publication of [RFC7315], and how they are fixed.

NOTE: In the case of the P-Called-Party-ID header field, allowing it in PUBLISH requests was done deliberately in [RFC7315]. Therefore, it is not considered a misalignment.

Since [RFC7315] was published, 3GPP defined new use cases that require the RFC to be updated. This section describes the 3GPP use cases behind the updates, and the updates needed to [RFC7315] in order to support the use cases.

Section 3 updates [RFC7315], based on the misalignments and 3GPP use cases.

2.2. Misalignments

The following updates are needed in order to fix the misalignments that occurred when [RFC3455] was updated and obsoleted by [RFC7315]:

- o P-Associated-URI: Remove the statement that the header field can appear in the SIP REGISTER method.
- o P-Called-Party-ID: Delete the statement that the P-Called-Party-ID header field can appear in SIP responses. Add a statement that the P-Called-Party-ID header field can appear in the SIP REFER method.
- o P-Access-Network-Info: Add a statement that the P-Access-Network-Info header field can appear in SIP responses.
- o P-Charging-Vector: Add a statement that the P-Charging-Vector header field can appear in SIP responses. Add a statement that the P-Charging-Vector header field cannot appear in the SIP ACK method.
- o P-Charging-Function-Addresses: Add a statement that the P-Charging-Function-Addresses header field can appear in SIP responses.

The following update is needed in order to clarify the usage of the header compared to [RFC7315]:

- o P-Visited-Network-ID: Add a statement that the P-Visited-Network-ID header field cannot appear in the SIP NOTIFY, PRACK, INFO, and UPDATE methods. Add statement that the P-Visited-Network-ID header field can appear in all non-100 (Trying) responses.

2.3. 3GPP Use Cases

2.3.1. General

The following updates are needed in order to implement the 3GPP use cases:

- o P-Access-Network-Info: Add statement that the P-Access-Network-Info header field can appear in the SIP ACK method when triggered by a SIP 2xx response.

- o P-Charging-Vector: Add statement that the P-Charging-Vector header field can appear in the SIP ACK method when triggered by a SIP 2xx response.

The following sections describe, for individual "P-" header fields, the 3GPP use cases that are the basis for the updates. The use cases are based on the procedures defined in [TS24.229].

2.3.2. P-Access-Network-Info

The P-Access-Network-Info header field may contain the Network Provided Location Information (NPLI). The NPLI is described in [TS23.228].

A proxy in possession of appropriate information about the access technology might insert a P-Access-Network-Info header field with its own values. Such values are identified by the string "network-provided" defined in [RFC7315]. Based on operator policy, roaming agreement or both, the local time of the visited network may be included.

The Call Data Records (CDRs) generated within the IP Multimedia Subsystem (IMS) have to contain the NPLI in order to guarantee correct billing. When an IMS session is modified, the NPLI also needs to be stored as the location of the user at the time when the session is modified may generate a charging event. In case of a session modification event at IMS, the NPLI needs to be provided:

- o when the bearer establishment is triggered, or

- o at session release when the bearer deactivation is triggered, or
- o when the bearer modification is triggered, e.g., a QoS modification for the use of a newly negotiated codec.

In some scenarios, the bearer modification may be triggered by the proxy upon reception of a Session Description Protocol (SDP) answer within SIP 2xx response to the SIP INVITE request. In such case, the NPLI needs to be provided within the SIP ACK request. However, [RFC7315] does not allow the usage of the P-Access-Network-Info header field in SIP ACK request.

Upon reception of the SDP answer within SIP 2xx response on the SIP INVITE request, a proxy may initiate procedures to obtain the NPLI and may include the P-Access-Network-Info header field with the NPLI in the SIP ACK request.

The P-Access-Network-Info header field shall not be included in SIP ACK requests triggered by non-2xx responses.

2.3.3. P-Charging-Vector

[RFC7315] defines an Inter Operator Identifier (IOI) to enable different operators involved in a SIP dialog or a transaction outside a dialog to identify each other by exchanging operator identification information within the P-Charging-Vector header field.

In the interconnection scenarios in multi-operator environments, where one or more transit operators are between the originating and terminating operator, the identities of the involved transit operators are represented by a transit-ioi parameter of the P-Charging-Vector header field.

Transit operators can be selected independently for each SIP method and direction of request. A transit network will only have knowledge of an individual SIP request, and transit network selection will be an independent decision for each request and could be made based on load, cost, percentage, time of day, and other factors. For this reason, it is necessary that the P-Charging-Vector header field, which carries the transit IOI information, is included in each SIP request and response. However, [RFC7315] does not allow the usage of the P-Charging-Vector header field in the SIP ACK request.

A SIP proxy that supports this extension and receives the SIP ACK request may include a P-Charging-Vector header field in the SIP ACK request.

The P-Charging-Vector header field shall not be included in SIP ACK requests triggered by SIP non-2xx responses.

3. Updates to RFC 7315

This section implements the update to Section 5.7 of [RFC7315], in order to implement the misalignment fixes and the 3GPP requirements described in Section 2.

Old text:

The P-Associated-URI header field can appear in SIP REGISTER method and 2xx responses.

The P-Called-Party-ID header field can appear in SIP INVITE, OPTIONS, PUBLISH, SUBSCRIBE, and MESSAGE methods and all responses.

The P-Visited-Network-ID header field can appear in all SIP methods except ACK, BYE, and CANCEL and all responses.

The P-Access-Network-Info header field can appear in all SIP methods except ACK and CANCEL.

The P-Charging-Vector header field can appear in all SIP methods except CANCEL.

The P-Charging-Function-Addresses header field can appear in all SIP methods except ACK and CANCEL.

New text:

The P-Associated-URI header field can appear in SIP REGISTER 2xx responses.

The P-Called-Party-ID header field can appear in the SIP INVITE, OPTIONS, PUBLISH, REFER, SUBSCRIBE, and MESSAGE requests.

The P-Visited-Network-ID header field can appear in all SIP requests and the associated non-100 response message except in ACK, BYE, CANCEL, NOTIFY, PRACK, INFO, UPDATE.

The P-Access-Network-Info header field can appear in all SIP requests and the associated non-100 responses, except in CANCEL requests, CANCEL responses, and ACK methods triggered by non-2xx responses.

The P-Charging-Vector header field can appear in all SIP requests and the associated non-100 responses, except in CANCEL requests, CANCEL responses, and ACK requests triggered by non-2xx responses.

The P-Charging-Function-Addresses header field can appear in all SIP methods and the associated non-100 responses, except in CANCEL requests, CANCEL responses, and ACK requests.

4. IANA Considerations

No IANA Considerations.

5. Security Considerations

The security considerations for these "P-" header fields are defined in [RFC7315]. This specification allows some header fields to be present in messages where they were previously not allowed, and the security considerations and assumptions described in [RFC7315] (e.g., regarding only sending information to trusted entities) also apply to those messages. In addition, this specification also disallows some header fields to be present in messages where they were previously allowed. That does not cause any security issues, but implementors need to be aware that implementations may not have been updated according to this document, and take proper actions if a header field occurs, or does not occur, in a message where it should occur (or occurs in a message where it should not occur). This document adds the ability to include P-Access-Network-Info in ACK requests. As documented in [RFC7315], P-Access-Network-Info may include privacy sensitive information, including the user's location. The security and privacy considerations for P-Access-Network-Info in ACK requests are similar to those for the other SIP requests discussed in Section 6.4 of [RFC7315]. The security and privacy considerations for the P-Visited-Network-ID header field are similar to those for the other SIP responses discussed in Section 6.3 of [RFC7315].

6. Operational considerations

As the "P-" header fields are mainly used in (and in most cases, only defined for) networks defined by the 3GPP, where the updates defined in this document are already defined [TS24.229], the updates are not seen to cause backward-compatibility concerns.

7. Changes since RFC7976

The changes related to RFC7976 involve the inclusion of the P-Visited-Network-ID header field in SIP responses. Specifically, any SIP response message, with the exception of a 100 (Trying) response, may include a P-Visited-Network-ID header field.

8. Acknowledgments

The author would like to acknowledge the constructive feedback provided by Michael Kreipl, Charles Eckel and Paul Kyzivat. Thanks to Paul Kyzivat, Jean Mahoney, Ben Campbell, and Adam Roach for providing comments on the former version of the document.

9. References

9.1. Normative References

- [RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", RFC 3261, DOI 10.17487/RFC3261, June 2002, <<https://www.rfc-editor.org/info/rfc3261>>.
- [RFC7315] Jesske, R., Drage, K., and C. Holmberg, "Private Header (P-Header) Extensions to the Session Initiation Protocol (SIP) for the 3GPP", RFC 7315, DOI 10.17487/RFC7315, July 2014, <<https://www.rfc-editor.org/info/rfc7315>>.
- [TS23.228] 3GPP, "3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; "IP multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP);", TS 23.228, V 13.6.0, June 2016.
- [TS24.229] 3GPP, "3rd Generation Partnership Project; Technical Specification Group Core Network and Terminals; IP multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3", TS 24.229, V 13.6.0, June 2016.

9.2. Informative References

- [RFC3455] Garcia-Martin, M., Henrikson, E., and D. Mills, "Private Header (P-Header) Extensions to the Session Initiation Protocol (SIP) for the 3rd-Generation Partnership Project (3GPP)", RFC 3455, DOI 10.17487/RFC3455, January 2003, <<https://www.rfc-editor.org/info/rfc3455>>.

Authors' Addresses

Christer Holmberg
Ericsson
Hirsalantie 11
FI-02420 Jorvas
Finland
Email: christer.holmberg@ericsson.com

Nevenka Biondic
Ericsson
Krapinska 45
HR-10002 Zagreb
Croatia
Email: nevenka.biondic.ext@ericsson.com

Gonzalo Salgueiro
Cisco Systems, Inc.
7200-12 Kit Creek Road
Research Triangle Park, NC 27709
United States of America
Email: gsalguei@cisco.com

Roland Jesske
Deutsche Telekom
Telekom Allee 9
64295 Darmstadt
Germany
Email: r.jesske@telekom.de
URI: www.telekom.com