

TEAS Working Group
Internet-Draft
Obsoletes: 8776 (if approved)
Intended status: Standards Track
Expires: 22 June 2026

I. Busi
Huawei
A. Guo
Futurewei Technologies
X. Liu
Alef Edge
T. Saad
Cisco Systems Inc.
I. Bryskin
Individual
19 December 2025

Common YANG Data Types for Traffic Engineering
draft-ietf-teas-rfc8776-update-20

Abstract

This document defines a collection of common data types, identities, and groupings in YANG data modeling language. These derived common data types, identities and groupings are intended to be imported by other modules, e.g., those which model the Traffic Engineering (TE) configuration and state capabilities.

This document obsoletes RFC 8776.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 22 June 2026.

Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	2
1.1. Terminology	3
1.2. Prefixes in Data Node Names	3
1.3. Tree Diagrams	4
2. Acronyms and Abbreviations	4
3. Overview	5
3.1. TE Types Module Contents	5
3.1.1. Identities	5
3.1.2. Data Types	8
3.1.3. Groupings	9
3.2. Packet TE Types Module Contents	10
3.2.1. Identities	10
3.2.2. Data Types	10
3.2.3. Groupings	11
4. TE Types YANG Module	11
5. Packet TE Types YANG Module	106
6. IANA Considerations	124
7. Security Considerations	125
8. References	125
8.1. Normative References	125
8.2. Informative References	133
Appendix A. The Complete Schema Trees	136
A.1. TE Types Schema Tree	136
A.2. Packet TE Types Schema Tree	151
Appendix B. Changes from RFC 8776	154
Acknowledgements	159
Contributors	159
Authors' Addresses	160

1. Introduction

YANG [RFC6020] [RFC7950] is a data modeling language used to model configuration data, state data, Remote Procedure Calls, and notifications for network management protocols such as the Network Configuration Protocol (NETCONF) [RFC6241] or RESTCONF [RFC8040]. The YANG language supports a small set of built-in data types and provides mechanisms to derive other types from the built-in types.

This document introduces a collection of common data types derived from the built-in YANG data types. The derived data types, identities, and groupings are mainly designed to be the common definitions applicable for modeling Traffic Engineering (TE) features in models defined outside of this document. Nevertheless, these common definitions can be used by any other module per the guidance in Sections 4.12 and 4.13 of [I-D.ietf-netmod-rfc8407bis].

Note: Some groupings defined in this document do not follow the guidelines of Section 4.13 of [I-D.ietf-netmod-rfc8407bis] not to include "default" statements. This is due to the fact that they were already defined in [RFC8776] and removing "default" statements is not a backward compatible change, as defined in Section 11 of [RFC7950].

This document adds new common data types, identities, and groupings to both the "ietf-te-types" and the "ietf-te-packet-types" YANG modules and obsoletes [RFC8776]. For further details, refer to Appendix B.

1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

The terminology for describing YANG data models is found in [RFC7950].

1.2. Prefixes in Data Node Names

Names of data nodes and other data model objects are prefixed using the standard prefix associated with the corresponding YANG imported modules, as shown in Table 1.

Prefix	YANG module	Reference
yang	ietf-yang-types	Section 3 of [RFC6991]
inet	ietf-inet-types	Section 4 of [RFC6991]
rt-types	ietf-routing-types	[RFC8294]
te-types	ietf-te-types	RFCXXXX
te-packet-types	ietf-te-packet-types	RFCXXXX

Table 1: Prefixes and corresponding YANG modules

RFC Editor: Please replace XXXX above with the RFC number assigned to this document. Please remove this note.

1.3. Tree Diagrams

Tree diagrams used in this document follow the notation defined in [RFC8340].

2. Acronyms and Abbreviations

APS: Automatic Protection Switching

DS-TE: Differentiated Services Traffic Engineering

GMPLS: Generalized Multiprotocol Label Switching

LER: Label Edge Router

LSP: Label Switched Path

LSR: Label Switching Router

MPLS: Multiprotocol Label Switching

NBMA: Non-Broadcast Multi-Access

PM: Performance Metrics

RSVP: Resource Reservation Protocol

SD: Signal Degrade

SF: Signal Fail

SRLG: Shared Risk Link Group

TE: Traffic Engineering

WTR: Wait-to-Restore

3. Overview

This document defines two YANG modules for common TE types: "ietf-te-types" (Section 4) for TE generic types and "ietf-te-packet-types" (Section 5) for packet-specific types. Other technology-specific TE types are outside the scope of this document.

3.1. TE Types Module Contents

The "ietf-te-types" module (Section 4) contains common TE types that are independent and agnostic of any specific technology or control-plane instance.

3.1.1. Identities

The "ietf-te-types" module contains the following YANG reusable identities:

path-attribute-flags: A base identity for supported LSP path flags as defined in [RFC3209], [RFC4090], [RFC4736], [RFC5712], [RFC4920], [RFC5420], [RFC7570], [RFC4875], [RFC5151], [RFC5150], [RFC6001], [RFC6790], [RFC7260], [RFC8001], [RFC8149], and [RFC8169].

link-protection-type: A base identity for supported link protection types as defined in [RFC4872].

restoration-scheme-type: A base identity for supported LSP restoration schemes as defined in [RFC4872].

protection-external-commands: A base identity for supported protection-related external commands used for troubleshooting purposes, as defined in [RFC4872], [RFC6368], [RFC7271], and [RFC4427].

association-type: A base identity for supported LSP association types as defined in [RFC6780], [RFC4872], [RFC4873], and [RFC8800].

objective-function-type: A base identity for supported path

objective functions as defined in [RFC5541].

te-tunnel-type: A base identity for supported TE tunnel types as defined in [RFC3209] and [RFC4875].

lsp-encoding-types: A base identity for supported LSP encoding types as defined in [RFC3471], [RFC4328], and [RFC6004]. These defined identities includes also technology-specific LSP encoding types for backward compatibility with [RFC8776].

Additional technology-specific LSP encoding types can be defined in specific technology-specific modules.

lsp-protection-type: A base identity for supported LSP protection types as defined in [RFC4872] and [RFC4873].

switching-capabilities: A base identity for supported interface switching capabilities as defined in [RFC3471], [RFC6002], [RFC6004], [RFC7074], and [RFC7138]. These defined identities includes also technology-specific interface switching capabilities for backward compatibility with [RFC8776].

Additional technology-specific interface switching capabilities can be defined in specific technology-specific modules.

resource-affinities-type: A base identity for supported attribute filters associated with a tunnel that must be satisfied for a link to be acceptable as defined in [RFC3209] and [RFC2702].

path-metric-type: A base identity for supported path metric types as defined in [RFC3630], [RFC3785], [RFC5440], [RFC7471], [RFC8233], [RFC8570], and [I-D.ietf-pce-sid-algo].

The unit of the path metric value is interpreted in the context of the path metric type. The derived identities SHOULD describe the unit and maximum value of the path metric types they define.

For example, the measurement unit is not applicable for the number of hops metric ('path-metric-hop'). Conversely, the bound of the 'path-metric-loss', defined in 'ietf-te-packet-types', is defined in multiples of the basic unit 0.000003% as described in [RFC7471] and [RFC8570].

lsp-provisioning-error-reason: A base identity for indicating LSP provisioning error reasons. No standard LSP provisioning error reasons are defined in this document.

path-computation-error-reason: A base identity for indicating path

computation error reasons as defined in Section 3.1.1.1.

protocol-origin-type: A base identity for the type of protocol origin as defined in Section 3.1.1.2.

svec-objective-function-type: A base identity for supported SVEC objective functions as defined in [RFC5541] and [RFC8685].

svec-metric-type: A base identity for supported SVEC metric types as defined in [RFC5541].

3.1.1.1. Path Computation Errors

The "ietf-te-types" module contains the YANG reusable identities for indicating path computation error reasons as defined in [RFC5440], [RFC5441], [RFC5520], [RFC5557], [RFC8306], and [RFC8685].

It also defines the following additional YANG reusable identities for indicating the following path computation error reasons:

path-computation-error-no-topology: A base identity for indicating path computation error when there is no topology with the provided topology identifier.

path-computation-error-no-dependent-server: A base identity for indicating path computation error when one or more dependent path computation servers are unavailable.

The dependent path computation server could be a Backward-Recursive Path Computation (BRPC) downstream PCE, as defined in [RFC5441], or a child PCE, as defined in [RFC8685].

The derived identities are defined in the "ietf-te-types" module, instead of an IANA-maintained module, because there are error reasons which are:

1. applicable only to the TE YANG modules and not to PCEP environments (e.g., path-computation-error-no-topology);
2. technology-specific (e.g., No RWA constraints met) which are better defined in technology-specific YANG modules;
3. match more than one PCEP number in order to hide the details of the underlay PCE architecture (e.g., path-computation-error-no-dependent-server).

3.1.1.2. Protocol Origin

The protocol origin identifies the protocol or mechanism a controller uses to instantiate a TE tunnel. To model this, the "ietf-te-types" module provides a set of reusable YANG identities. In addition to identities for protocols like PCEP [RFC5440] and BGP [RFC9012], the module defines the following identity for tunnels created via an Application Programmable Interface (API):

protocol-origin-api: A YANG identity used when the TE tunnel is instantiated through an API.

3.1.2. Data Types

The "ietf-te-types" module contains the following YANG reusable data types:

te-ds-class: A type representing the Differentiated Services (DS) Class-Type of traffic as defined in [RFC4124].

te-label-direction: An enumerated type for specifying the forward or reverse direction of a label.

te-hop-type: An enumerated type for specifying that a hop is loose or strict.

te-global-id: A type representing the identifier that uniquely identifies an operator, which can be either a provider or a client. The definition of this type is taken from Section 3 of [RFC6370] and Section 3 of [RFC5003]. This attribute type is used solely to provide a globally unique context for TE topologies.

te-node-id: A type representing the identifier for a node in a TE topology. The identifier is represented either as 4-octet in dotted-quad notation or as 16-octet in full, mixed, shortened, or shortened-mixed IPv6 address notation.

This attribute MAY be mapped to the Router Address TLV described in Section 2.4.1 of [RFC3630], the TE Router ID described in Section 6.2 of [RFC6827], the Traffic Engineering Router ID TLV described in Section 4.3 of [RFC5305], or the TE Router ID TLV described in Section 3.2.1 of [RFC6119].

The reachability of such a TE node MAY be achieved by a mechanism such as that described in Section 6.2 of [RFC6827].

te-topology-id: A type representing the identifier for a topology.

It is optional to have one or more prefixes at the beginning, separated by colons. The prefixes can be "network-types" as defined in the "ietf-network" module in [RFC8345], to help the user better understand the topology before further inquiry is made.

te-tp-id: A type representing the identifier of a TE interface Link Termination Point (LTP) on a specific TE node where the TE link connects. This attribute is mapped to a local or remote link identifier [RFC3630] [RFC5305].

te-path-disjointness: A type representing the different resource disjointness options for a TE tunnel path as defined in [RFC4872].

admin-groups: A union type for a TE link's classic administrative groups, as defined in [RFC3630] and [RFC5305], or extended administrative groups, as defined in [RFC7308].

srlg: A type representing the Shared Risk Link Group (SRLG) as defined in [RFC4203] and [RFC5307].

te-metric: A type representing the TE metric as defined in [RFC3785].

te-recovery-status: An enumerated type for the different status of a recovery action as defined in [RFC6378] and [RFC4427].

te-link-access-type: An enumerated type for the different TE link access types as defined in [RFC3630].

3.1.3. Groupings

The "ietf-te-types" module contains the following YANG reusable groupings:

te-bandwidth: A grouping that defines the generic TE bandwidth. The modeling structure allows augmentation for each technology. For unspecified technologies, the string-encoded "te-bandwidth" type is used.

te-label: A grouping that defines the generic TE label. The modeling structure allows augmentation for each technology. For unspecified technologies, "rt-types:generalized-label" is used.

performance-metrics-attributes: A grouping that defines one-way and two-way measured Performance Metrics (PM) and indications of anomalies on links or the path as defined in [RFC7471], [RFC8570], and [RFC7823].

performance-metrics-throttle-container: A grouping that defines thresholds for advertisement suppression and measurement intervals.

explicit-route-hop: A grouping that defines supported explicit routes as defined in [RFC3209] and [RFC3477].

explicit-route-hop-with-srlg: A grouping that augments the 'explicit-route-hop' to specify also SRLG hops.

encoding-and-switching-type: A grouping that defines the LSP encoding and switching types.

3.2. Packet TE Types Module Contents

The "ietf-te-packet-types" module (Section 5) covers the common types and groupings that are specific to packet technology.

3.2.1. Identities

The "ietf-te-packet-types" module contains the following YANG reusable identities:

backup-protection-type: A base identity for supported protection types that a backup or bypass tunnel can provide as defined in [RFC4090].

bc-model-type: A base identity for supported Diffserv-TE Bandwidth Constraints Models as defined in [RFC4125], [RFC4126], and [RFC4127].

bandwidth-profile-type: A base identity for various bandwidth profiles, also known as traffic profiles in Section 2.3.2 of [RFC2475], as specified in [MEF_10.3], [RFC2697] and [RFC2698], that may be used to specify the temporal properties of a packet stream (e.g., MPLS-TE LSPs).

3.2.2. Data Types

The "ietf-te-packet-types" module contains the following YANG reusable data type:

te-bandwidth-requested-type: An enumerated type for the different options to request bandwidth for a specific tunnel.

3.2.3. Groupings

The "ietf-te-packet-types" module contains the following YANG reusable groupings:

performance-metrics-attributes-packet: A grouping that contains the generic performance metrics and additional packet-specific metrics.

bandwidth-profile-parameters: A grouping that defines common parameters for bandwidth profiles in packet networks.

te-packet-path-bandwidth: A grouping that defines the path bandwidth information and could be used in any Packet TE model (e.g., MPLS-TE topology model) for the path bandwidth representation (e.g., the bandwidth of an MPLS-TE LSP).

All the path and LSP bandwidth related sections in the "ietf-te-types" generic module, Section 4, need to be augmented with this grouping for the usage of Packet TE technologies.

te-packet-link-bandwidth: A grouping that defines the link bandwidth information and could be used in any Packet TE model (e.g., MPLS-TE topology) for link bandwidth representation.

All the link bandwidth related sections in the "ietf-te-types" generic module, Section 4, need to be augmented with this grouping for the usage of Packet TE technologies.

4. TE Types YANG Module

The "ietf-te-types" module imports the following modules:

- * "ietf-yang-types" and "ietf-inet-types" as defined in [RFC6991]
- * "ietf-routing-types" as defined in [RFC8294]

In addition to [RFC6991] and [RFC8294], this module references the following documents in defining the types and YANG groupings:

[RFC9522], [RFC4090], [RFC4202], [RFC4328], [RFC4561], [RFC4657], [RFC4736], [RFC6004], [RFC6378], [RFC6511], [RFC7139], [RFC7271], [RFC7308], [RFC7551], [RFC7571], [RFC7579], and [ITU-T_G.709].

```
<CODE BEGINS> file "ietf-te-types@2025-12-19.yang"
module ietf-te-types {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-te-types";
  prefix te-types;

  import ietf-inet-types {
    prefix inet;
    reference
      "RFC 6991: Common YANG Data Types, Section 4";
  }
  import ietf-yang-types {
    prefix yang;
    reference
      "RFC 6991: Common YANG Data Types, Section 3";
  }
  import ietf-routing-types {
    prefix rt-types;
    reference
      "RFC 8294: Common YANG Data Types for the Routing Area";
  }
  import ietf-network {
    prefix nw;
    reference
      "RFC 8345: A YANG Data Model for Network Topologies";
  }
  import ietf-network-topology {
    prefix nt;
    reference
      "RFC 8345: A YANG Data Model for Network Topologies";
  }

  organization
    "IETF Traffic Engineering Architecture and Signaling (TEAS)
     Working Group";
  contact
    "WG Web:    <https://datatracker.ietf.org/wg/teas/>
     WG List:   <mailto:teas@ietf.org>

     Editor:    Tarek Saad
                <mailto:tsaad.net@gmail.com>

     Editor:    Rakesh Gandhi
                <mailto:rgandhi@cisco.com>

     Editor:    Vishnu Pavan Beeram
                <mailto:vbeeram@juniper.net>
```

Editor: Xufeng Liu
<mailto:xufeng.liu.ietf@gmail.com>

Editor: Igor Bryskin
<mailto:i_bryskin@yahoo.com>";

description

"This YANG module contains a collection of generally useful
YANG data type definitions specific to TE.

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL
NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED',
'MAY', and 'OPTIONAL' in this document are to be interpreted as
described in BCP 14 (RFC 2119) (RFC 8174) when, and only when,
they appear in all capitals, as shown here.

Copyright (c) 2025 IETF Trust and the persons identified as
authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or
without modification, is permitted pursuant to, and subject to
the license terms contained in, the Revised BSD License set
forth in Section 4.c of the IETF Trust's Legal Provisions
Relating to IETF Documents
(<https://trustee.ietf.org/license-info>).

All revisions of IETF and IANA published modules can be found
at the YANG Parameters registry group
(<https://www.iana.org/assignments/yang-parameters>).

This version of this YANG module is part of RFC XXXX; see
the RFC itself for full legal notices.";

// RFC Editor: Please replace XXXX above with the RFC number
// assigned to this document.
// Please remove this note.

revision 2025-12-19 {

description

"This revision adds the following new identities:

- lsp-provisioning-error-reason;
- association-type-diversity;
- tunnel-admin-state-auto;
- lsp-restoration-restore-none;
- restoration-scheme-rerouting;
- path-metric-optimization-type;
- link-path-metric-type;
- link-metric-type and its derived identities;
- path-computation-error-reason and its derived identities;

- protocol-origin-type and its derived identities;
- svec-objective-function-type and its derived identities;
- svec-metric-type and its derived identities.

This revision adds the following new data types:

- path-type.

This revision adds the following new groupings:

- explicit-route-hop-with-srlg;
- encoding-and-switching-type;
- te-generic-node-id.

This revision updates the following identities:

- objective-function-type;
- action-exercise;
- path-metric-type;
- path-metric-te;
- path-metric-igp;
- path-metric-hop;
- path-metric-delay-average;
- path-metric-delay-minimum;
- path-metric-residual-bandwidth;
- path-metric-optimize-includes;
- path-metric-optimize-excludes;
- te-optimization-criterion.

This revision updates the following data types:

- te-node-id.

This revision updates the following groupings:

- explicit-route-hop:
 - adds the following leaves:
 - node-id-uri;
 - link-tp-id-uri;
 - updates the following leaves:
 - node-id;
 - link-tp-id;
- record-route-state:
 - adds the following leaves:
 - node-id-uri;
 - link-tp-id-uri;
 - updates the following leaves:
 - node-id;
 - link-tp-id;
- optimization-metric-entry:
 - updates the following leaves:
 - metric-type;
- tunnel-constraints;

- adds the following leaves:
 - network-id;
- path-constraints-route-objects:
 - updates the following containers:
 - explicit-route-objects-always;
- generic-path-metric-bounds:
 - updates the following leaves:
 - metric-type;
- generic-path-optimization
 - adds the following leaves:
 - tiebreaker;
- deprecate the following containers:
 - tiebreakers.

This revision obsoletes the following identities:

- of-minimize-agg-bandwidth-consumption;
- of-minimize-load-most-loaded-link;
- of-minimize-cost-path-set;
- lsp-protection-reroute-extra;
- lsp-protection-reroute.

This revision provides also few editorial changes.";

reference

"RFC XXXX: Common YANG Data Types for Traffic Engineering";

}

// RFC Editor: Please replace the revision date above with the
// module publication date in the format is (year-month-day).
// Please replace XXXX above with the RFC number assigned to
// this document.
// Please remove this note.

revision 2020-06-10 {

description

"Initial Version of TE types.";

reference

"RFC 8776: Common YANG Data Types for Traffic Engineering";

}

/*

* Features

*/

feature p2mp-te {

description

"Indicates support for Point-to-Multipoint TE (P2MP-TE).";

reference

"RFC 4875: Extensions to Resource Reservation Protocol -

```
        Traffic Engineering (RSVP-TE) for
        Point-to-Multipoint TE Label Switched Paths (LSPs)";
    }

    feature frr-te {
        description
            "Indicates support for TE Fast Reroute (FRR).";
        reference
            "RFC 4090: Fast Reroute Extensions to RSVP-TE for LSP Tunnels";
    }

    feature extended-admin-groups {
        description
            "Indicates support for TE link extended administrative
            groups.";
        reference
            "RFC 7308: Extended Administrative Groups in MPLS Traffic
            Engineering (MPLS-TE)";
    }

    feature named-path-affinities {
        description
            "Indicates support for named path affinities.";
    }

    feature named-extended-admin-groups {
        description
            "Indicates support for named extended administrative groups.";
    }

    feature named-srlg-groups {
        description
            "Indicates support for named Shared Risk Link Group (SRLG).";
    }

    feature named-path-constraints {
        description
            "Indicates support for named path constraints.";
    }

    feature path-optimization-metric {
        description
            "Indicates support for path optimization metrics.";
    }

    feature path-optimization-objective-function {
        description
            "Indicates support for path optimization objective functions.";
```



```
}

/*
 * Identities
 */

identity lsp-provisioning-error-reason {
  description
    "Base identity for LSP provisioning errors.";
}

identity session-attributes-flags {
  description
    "Base identity for the RSVP-TE session attributes flags.";
}

identity local-protection-desired {
  base session-attributes-flags;
  description
    "Local protection is desired.";
  reference
    "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels,
      Section 4.7.1";
}

identity se-style-desired {
  base session-attributes-flags;
  description
    "Shared explicit style, to allow the LSP to be established
    and share resources with the old LSP.";
  reference
    "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels";
}

identity local-recording-desired {
  base session-attributes-flags;
  description
    "Label recording is desired.";
  reference
    "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels,
      Section 4.7.1";
}

identity bandwidth-protection-desired {
  base session-attributes-flags;
  description
    "Requests FRR bandwidth protection on LSRs, if present.";
  reference
```

```
    "RFC 4090: Fast Reroute Extensions to RSVP-TE for LSP
      Tunnels";
  }

  identity node-protection-desired {
    base session-attributes-flags;
    description
      "Requests FRR node protection on LSRs, if present.";
    reference
      "RFC 4090: Fast Reroute Extensions to RSVP-TE for LSP
        Tunnels";
  }

  identity path-reevaluation-request {
    base session-attributes-flags;
    description
      "Indicates that a path re-evaluation (of the
        current path in use) is requested.

        Note that this does not trigger any LSP reroutes but
        instead just signals a request to evaluate whether a
        preferable path exists.";
    reference
      "RFC 4736: Reoptimization of Multiprotocol Label Switching
        (MPLS) Traffic Engineering (TE) Loosely Routed
        Label Switched Path (LSP)";
  }

  identity soft-preemption-desired {
    base session-attributes-flags;
    description
      "Soft preemption of LSP resources is desired.";
    reference
      "RFC 5712: MPLS Traffic Engineering Soft Preemption";
  }

  identity lsp-attributes-flags {
    description
      "Base identity for LSP attributes flags.";
  }

  identity end-to-end-rerouting-desired {
    base lsp-attributes-flags;
    description
      "Indicates end-to-end rerouting behavior for an LSP
        undergoing establishment.

        This MAY also be used to specify the behavior of end-to-end
```

```
    LSP recovery for established LSPs.";
  reference
    "RFC 4920: Crankback Signaling Extensions for MPLS and GMPLS
      RSVP-TE
    RFC 5420: Encoding of Attributes for MPLS LSP Establishment
      Using Resource Reservation Protocol Traffic
      Engineering (RSVP-TE)
    RFC 7570: Label Switched Path (LSP) Attribute in the
      Explicit Route Object (ERO)";
}

identity boundary-rerouting-desired {
  base lsp-attributes-flags;
  description
    "Indicates boundary rerouting behavior for an LSP undergoing
    establishment.

    This MAY also be used to specify segment-based LSP recovery
    through nested crankback for established LSPs.

    The boundary Area Border Router (ABR) / Autonomous System
    Border Router (ASBR) can decide to forward the PathErr
    message upstream to either an upstream boundary ABR/ASBR or
    the ingress LSR.

    Alternatively, it can try to select another egress boundary
    LSR.";
  reference
    "RFC 4920: Crankback Signaling Extensions for MPLS and GMPLS
      RSVP-TE
    RFC 5420: Encoding of Attributes for MPLS LSP Establishment
      Using Resource Reservation Protocol Traffic
      Engineering (RSVP-TE)
    RFC 7570: Label Switched Path (LSP) Attribute in the
      Explicit Route Object (ERO)";
}

identity segment-based-rerouting-desired {
  base lsp-attributes-flags;
  description
    "Indicates segment-based rerouting behavior for an LSP
    undergoing establishment.

    This MAY also be used to specify segment-based LSP recovery
    for established LSPs.";
  reference
    "RFC 4920: Crankback Signaling Extensions for MPLS and GMPLS
      RSVP-TE
```

```

    RFC 5420: Encoding of Attributes for MPLS LSP Establishment
              Using Resource Reservation Protocol
              Traffic Engineering (RSVP-TE)
    RFC 7570: Label Switched Path (LSP) Attribute in the
              Explicit Route Object (ERO)";
}

identity lsp-integrity-required {
  base lsp-attributes-flags;
  description
    "Indicates that LSP integrity is required.";
  reference
    "RFC 4875: Extensions to Resource Reservation Protocol -
      Traffic Engineering (RSVP-TE) for
      Point-to-Multipoint TE Label Switched Paths (LSPs)
    RFC 7570: Label Switched Path (LSP) Attribute in the
      Explicit Route Object (ERO)";
}

identity contiguous-lsp-desired {
  base lsp-attributes-flags;
  description
    "Indicates that a contiguous LSP is desired.";
  reference
    "RFC 5151: Inter-Domain MPLS and GMPLS Traffic Engineering --
      Resource Reservation Protocol-Traffic Engineering
      (RSVP-TE) Extensions
    RFC 7570: Label Switched Path (LSP) Attribute in the
      Explicit Route Object (ERO)";
}

identity lsp-stitching-desired {
  base lsp-attributes-flags;
  description
    "Indicates that LSP stitching is desired.";
  reference
    "RFC 5150: Label Switched Path Stitching with Generalized
      Multiprotocol Label Switching Traffic Engineering
      (GMPLS TE)
    RFC 7570: Label Switched Path (LSP) Attribute in the
      Explicit Route Object (ERO)";
}

identity pre-planned-lsp-flag {
  base lsp-attributes-flags;
  description
    "Indicates that the LSP MUST be provisioned in the
      control plane only.";
```

```
reference
  "RFC 6001: Generalized MPLS (GMPLS) Protocol Extensions for
    Multi-Layer and Multi-Region Networks (MLN/MRN)
    RFC 7570: Label Switched Path (LSP) Attribute in the
      Explicit Route Object (ERO)";
}

identity non-php-behavior-flag {
  base lsp-attributes-flags;
  description
    "Indicates that non-PHP (non-Penultimate Hop Popping)
      behavior for the LSP is desired.";
  reference
    "RFC 6511: Non-Penultimate Hop Popping Behavior and
      Out-of-Band Mapping for RSVP-TE Label Switched
      Paths
      RFC 7570: Label Switched Path (LSP) Attribute in the
        Explicit Route Object (ERO)";
}

identity oob-mapping-flag {
  base lsp-attributes-flags;
  description
    "Indicates that signaling of the egress binding information
      is out of band (e.g., via the Border Gateway Protocol
      (BGP)).";
  reference
    "RFC 6511: Non-Penultimate Hop Popping Behavior and
      Out-of-Band Mapping for RSVP-TE Label Switched
      Paths
      RFC 7570: Label Switched Path (LSP) Attribute in the
        Explicit Route Object (ERO)";
}

identity entropy-label-capability {
  base lsp-attributes-flags;
  description
    "Indicates entropy label capability.";
  reference
    "RFC 6790: The Use of Entropy Labels in MPLS Forwarding
      RFC 7570: Label Switched Path (LSP) Attribute in the
        Explicit Route Object (ERO)";
}

identity oam-mep-entity-desired {
  base lsp-attributes-flags;
  description
    "OAM Maintenance Entity Group End Point (MEP) entities
```

```
        desired.";
    reference
        "RFC 7260: GMPLS RSVP-TE Extensions for Operations,
        Administration, and Maintenance (OAM)
        Configuration";
}

identity oam-mip-entity-desired {
    base lsp-attributes-flags;
    description
        "OAM Maintenance Entity Group Intermediate Points (MIP)
        entities desired.";
    reference
        "RFC 7260: GMPLS RSVP-TE Extensions for Operations,
        Administration, and Maintenance (OAM)
        Configuration";
}

identity srlg-collection-desired {
    base lsp-attributes-flags;
    description
        "Shared Risk Link Group (SRLG) collection desired.";
    reference
        "RFC 7570: Label Switched Path (LSP) Attribute in the
        Explicit Route Object (ERO)
        RFC 8001: RSVP-TE Extensions for Collecting Shared Risk
        Link Group (SRLG) Information";
}

identity loopback-desired {
    base lsp-attributes-flags;
    description
        "Indicates that a particular node on the LSP is
        required to enter loopback mode.

        This can also be used to specify the loopback state of the
        node.";
    reference
        "RFC 7571: GMPLS RSVP-TE Extensions for Lock Instruct and
        Loopback";
}

identity p2mp-te-tree-eval-request {
    base lsp-attributes-flags;
    description
        "P2MP-TE tree re-evaluation request.";
    reference
        "RFC 8149: RSVP Extensions for Reoptimization of Loosely
```

```
        Routed Point-to-Multipoint Traffic Engineering
        Label Switched Paths (LSPs)";
    }

    identity rtm-set-desired {
        base lsp-attributes-flags;
        description
            "Residence Time Measurement (RTM) attribute flag requested.";
        reference
            "RFC 8169: Residence Time Measurement in MPLS Networks";
    }

    identity link-protection-type {
        description
            "Base identity for the link protection type.";
        reference
            "RFC 4202: Routing Extensions in Support of Generalized
            Multi-Protocol Label Switching (GMPLS),
            section 2.2
            RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
            Signaling Functional Description, section 7";
    }

    identity link-protection-unprotected {
        base link-protection-type;
        description
            "'Unprotected' link protection type.";
        reference
            "RFC 4202: Routing Extensions in Support of Generalized
            Multi-Protocol Label Switching (GMPLS),
            section 2.2
            RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
            Signaling Functional Description, section 7";
    }

    identity link-protection-extra-traffic {
        base link-protection-type;
        description
            "'Extra-Traffic' link protection type.";
        reference
            "RFC 4202: Routing Extensions in Support of Generalized
            Multi-Protocol Label Switching (GMPLS),
            section 2.2
            RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
            Signaling Functional Description, section 7";
    }

    identity link-protection-shared {
```

```
base link-protection-type;
description
  "'Shared' link protection type.";
reference
  "RFC 4202: Routing Extensions in Support of Generalized
    Multi-Protocol Label Switching (GMPLS),
    section 2.2
  RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
    Signaling Functional Description, section 7";
}

identity link-protection-1-for-1 {
  base link-protection-type;
  description
    "'Dedicated 1:1' link protection type.";
  reference
    "RFC 4202: Routing Extensions in Support of Generalized
      Multi-Protocol Label Switching (GMPLS),
      section 2.2
    RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
      Signaling Functional Description, section 7";
}

identity link-protection-1-plus-1 {
  base link-protection-type;
  description
    "'Dedicated 1+1' link protection type.";
  reference
    "RFC 4202: Routing Extensions in Support of Generalized
      Multi-Protocol Label Switching (GMPLS),
      section 2.2
    RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
      Signaling Functional Description, section 7";
}

identity link-protection-enhanced {
  base link-protection-type;
  description
    "'Enhanced' link protection type.";
  reference
    "RFC 4202: Routing Extensions in Support of Generalized
      Multi-Protocol Label Switching (GMPLS),
      section 2.2
    RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
      Signaling Functional Description, section 7";
}

identity association-type {
```



```
    description
      "Base identity for the tunnel association.";
  }

  identity association-type-recovery {
    base association-type;
    description
      "Association type for recovery, used to associate LSPs of the
       same tunnel for recovery.";
    reference
      "RFC 4872: RSVP-TE Extensions in Support of End-to-End
       Generalized Multi-Protocol Label Switching (GMPLS)
       Recovery
       RFC 6780: RSVP ASSOCIATION Object Extensions";
  }

  identity association-type-resource-sharing {
    base association-type;
    description
      "Association type for resource sharing, used to enable
       resource sharing during make-before-break.";
    reference
      "RFC 4873: GMPLS Segment Recovery
       RFC 6780: RSVP ASSOCIATION Object Extensions";
  }

  identity association-type-double-sided-bidir {
    base association-type;
    description
      "Association type for double-sided bidirectional LSPs,
       used to associate two LSPs of two tunnels that are
       independently configured on either endpoint.";
    reference
      "RFC 7551: RSVP-TE Extensions for Associated Bidirectional
       Label Switched Paths (LSPs)";
  }

  identity association-type-single-sided-bidir {
    base association-type;
    description
      "Association type for single-sided bidirectional LSPs,
       used to associate two LSPs of two tunnels, where one
       tunnel is configured on one side/endpoint and the other
       tunnel is dynamically created on the other endpoint.";
    reference
      "RFC 6780: RSVP ASSOCIATION Object Extensions
       RFC 7551: RSVP-TE Extensions for Associated Bidirectional
       Label Switched Paths (LSPs)";
  }
```

```
}

identity association-type-diversity {
  base association-type;
  description
    "Association Type diversity used to associate LSPs whose
    paths are to be diverse from each other.";
  reference
    "RFC 8800: Path Computation Element Communication Protocol
    (PCEP) Extension for Label Switched Path (LSP)
    Diversity Constraint Signaling";
}

identity objective-function-type {
  description
    "Base identity for path objective function types.";
}

identity of-minimize-cost-path {
  base objective-function-type;
  description
    "Objective function for minimizing path cost.";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
    Computation Element Communication Protocol
    (PCEP)";
}

identity of-minimize-load-path {
  base objective-function-type;
  description
    "Objective function for minimizing the load on one or more
    paths.";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
    Computation Element Communication Protocol
    (PCEP)";
}

identity of-maximize-residual-bandwidth {
  base objective-function-type;
  description
    "Objective function for maximizing residual bandwidth.";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
    Computation Element Communication Protocol
    (PCEP)";
}
```

```
identity of-minimize-agg-bandwidth-consumption {
  base objective-function-type;
  status obsolete;
  description
    "Objective function for minimizing aggregate bandwidth
    consumption.

    This identity has been obsoleted: the
    'svec-of-minimize-agg-bandwidth-consumption' identity SHOULD
    be used instead.";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
    Computation Element Communication Protocol
    (PCEP)";
}

identity of-minimize-load-most-loaded-link {
  base objective-function-type;
  status obsolete;
  description
    "Objective function for minimizing the load on the link that
    is carrying the highest load.

    This identity has been obsoleted: the
    'svec-of-minimize-load-most-loaded-link' identity SHOULD
    be used instead.";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
    Computation Element Communication Protocol
    (PCEP)";
}

identity of-minimize-cost-path-set {
  base objective-function-type;
  status obsolete;
  description
    "Objective function for minimizing the cost on a path set.

    This identity has been obsoleted: the
    'svec-of-minimize-cost-path-set' identity SHOULD
    be used instead.";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
    Computation Element Communication Protocol
    (PCEP)";
}

identity path-computation-method {
```

```
    description
      "Base identity for supported path computation mechanisms.";
  }

  identity path-locally-computed {
    base path-computation-method;
    description
      "Indicates a constrained-path LSP in which the
       path is computed by the local LER.";
    reference
      "RFC 9522: Overview and Principles of Internet Traffic
       Engineering, Section 4.4";
  }

  identity path-externally-queried {
    base path-computation-method;
    description
      "Constrained-path LSP in which the path is obtained by
       querying an external source, such as a PCE server.
       In the case that an LSP is defined to be externally queried,
       it may also have associated explicit definitions (provided
       to the external source to aid computation).

       The path that is returned by the external source may
       require further local computation on the device.";
    reference
      "RFC 9522: Overview and Principles of Internet Traffic
       Engineering
       RFC 4657: Path Computation Element (PCE) Communication
       Protocol Generic Requirements";
  }

  identity path-explicitly-defined {
    base path-computation-method;
    description
      "Constrained-path LSP in which the path is
       explicitly specified as a collection of strict and/or loose
       hops.";
    reference
      "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels
       RFC 9522: Overview and Principles of Internet Traffic
       Engineering";
  }

  identity lsp-metric-type {
    description
      "Base identity for the LSP metric specification types.";
  }
```

```
identity lsp-metric-relative {
  base lsp-metric-type;
  description
    "The metric specified for the LSPs to which this identity
     refers is specified as a value relative to the IGP metric
     cost to the LSP's tail end.";
  reference
    "RFC 4657: Path Computation Element (PCE) Communication
     Protocol Generic Requirements";
}

identity lsp-metric-absolute {
  base lsp-metric-type;
  description
    "The metric specified for the LSPs to which this identity
     refers is specified as an absolute value.";
  reference
    "RFC 4657: Path Computation Element (PCE) Communication
     Protocol Generic Requirements";
}

identity lsp-metric-inherited {
  base lsp-metric-type;
  description
    "The metric for the LSPs to which this identity refers is
     not specified explicitly; rather, it is directly inherited
     from the IGP cost.";
  reference
    "RFC 4657: Path Computation Element (PCE) Communication
     Protocol Generic Requirements";
}

identity te-tunnel-type {
  description
    "Base identity from which specific tunnel types are derived.";
}

identity te-tunnel-p2p {
  base te-tunnel-type;
  description
    "TE Point-to-Point (P2P) tunnel type.";
  reference
    "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels";
}

identity te-tunnel-p2mp {
  base te-tunnel-type;
  description
```

```
    "TE P2MP tunnel type.";
  reference
    "RFC 4875: Extensions to Resource Reservation Protocol -
      Traffic Engineering (RSVP-TE) for
      Point-to-Multipoint TE Label Switched Paths
      (LSPs)";
}

identity tunnel-action-type {
  description
    "Base identity from which specific tunnel action types
      are derived.";
}

identity tunnel-action-resetup {
  base tunnel-action-type;
  description
    "TE tunnel action that tears down the tunnel's current LSP
      (if any) and attempts to re-establish a new LSP.";
}

identity tunnel-action-reoptimize {
  base tunnel-action-type;
  description
    "TE tunnel action that reoptimizes the placement of the
      tunnel LSP(s).";
}

identity tunnel-action-switchpath {
  base tunnel-action-type;
  description
    "TE tunnel action that switches the tunnel's LSP to use the
      specified path.";
}

identity te-action-result {
  description
    "Base identity from which specific TE action results
      are derived.";
}

identity te-action-success {
  base te-action-result;
  description
    "TE action was successful.";
}

identity te-action-fail {
```

```
    base te-action-result;
    description
        "TE action failed.";
}

identity tunnel-action-inprogress {
    base te-action-result;
    description
        "TE action is in progress.";
}

identity tunnel-admin-state-type {
    description
        "Base identity for TE tunnel administrative states.";
}

identity tunnel-admin-state-up {
    base tunnel-admin-state-type;
    description
        "Tunnel's administrative state is up.";
}

identity tunnel-admin-state-down {
    base tunnel-admin-state-type;
    description
        "Tunnel's administrative state is down.";
}

identity tunnel-admin-state-auto {
    base tunnel-admin-state-type;
    description
        "Tunnel administrative auto state. The administrative status
        in state datastore transitions to 'tunnel-admin-up' when the
        tunnel used by the client layer, and to 'tunnel-admin-down'
        when it is not used by the client layer.";
}

identity tunnel-state-type {
    description
        "Base identity for TE tunnel states.";
}

identity tunnel-state-up {
    base tunnel-state-type;
    description
        "Tunnel's state is up.";
}
```

```
identity tunnel-state-down {
  base tunnel-state-type;
  description
    "Tunnel's state is down.";
}

identity lsp-state-type {
  description
    "Base identity for TE LSP states.";
}

identity lsp-path-computing {
  base lsp-state-type;
  description
    "State path computation is in progress.";
}

identity lsp-path-computation-ok {
  base lsp-state-type;
  description
    "State path computation was successful.";
}

identity lsp-path-computation-failed {
  base lsp-state-type;
  description
    "State path computation failed.";
}

identity lsp-state-setting-up {
  base lsp-state-type;
  description
    "State is being set up.";
}

identity lsp-state-setup-ok {
  base lsp-state-type;
  description
    "State setup was successful.";
}

identity lsp-state-setup-failed {
  base lsp-state-type;
  description
    "State setup failed.";
}

identity lsp-state-up {
```



```
    base lsp-state-type;
    description
        "State is up.";
}

identity lsp-state-tearing-down {
    base lsp-state-type;
    description
        "State is being torn down.";
}

identity lsp-state-down {
    base lsp-state-type;
    description
        "State is down.";
}

identity path-invalidation-action-type {
    description
        "Base identity for TE path invalidation action types.";
}

identity path-invalidation-action-drop {
    base path-invalidation-action-type;
    description
        "Upon invalidation of the TE tunnel path, the tunnel remains
        valid, but any packet mapped over the tunnel is dropped.";
    reference
        "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels,
        Section 2.5";
}

identity path-invalidation-action-teardown {
    base path-invalidation-action-type;
    description
        "TE path invalidation action teardown.";
    reference
        "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels,
        Section 2.5";
}

identity lsp-restoration-type {
    description
        "Base identity from which LSP restoration types are derived.";
}

identity lsp-restoration-restore-none {
    base lsp-restoration-type;
```

```
    description
      "No LSP affected by a failure is restored.";
  }

  identity lsp-restoration-restore-any {
    base lsp-restoration-type;
    description
      "Any LSP affected by a failure is restored.";
  }

  identity lsp-restoration-restore-all {
    base lsp-restoration-type;
    description
      "Affected LSPs are restored after all LSPs of the tunnel are
      broken.";
  }

  identity restoration-scheme-type {
    description
      "Base identity for LSP restoration schemes.";
  }

  identity restoration-scheme-rerouting {
    base restoration-scheme-type;
    description
      "Restoration LSP is computed, signalled and configured after
      the failure detection.

      This restoration scheme is also known as
      'Full LSP Re-routing', with the alternate route being
      computed after the failure occurs.";
    reference
      "RFC 4872: RSVP-TE Extensions in Support of End-to-End
      Generalized Multi-Protocol Label Switching (GMPLS)
      Recovery, section 11";
  }

  identity restoration-scheme-preconfigured {
    base restoration-scheme-type;
    description
      "Restoration LSP is precomputed, presignalled and
      preconfigured prior to the failure.";
  }

  identity restoration-scheme-precomputed {
    base restoration-scheme-type;
    description
      "Restoration LSP is precomputed, but not presignalled nor
```

```
    preconfigured, prior to the failure.

    This restoration scheme is also known as
    'Full LSP Re-routing', with the alternate route being
    pre-computed and stored for use when the failure occurs.";
  reference
    "RFC 4872: RSVP-TE Extensions in Support of End-to-End
     Generalized Multi-Protocol Label Switching (GMPLS)
     Recovery, section 11";
}

identity restoration-scheme-presignaled {
  base restoration-scheme-type;
  description
    "Restoration LSP is presignaled, but not preconfigured,
     prior to the failure.

     This restoration scheme is also known as
     'Pre-planned LSP Re-routing'.";
  reference
    "RFC 4872: RSVP-TE Extensions in Support of End-to-End
     Generalized Multi-Protocol Label Switching (GMPLS)
     Recovery, section 8";
}

identity lsp-protection-type {
  description
    "Base identity from which LSP protection types are derived.";
  reference
    "RFC 4872: RSVP-TE Extensions in Support of End-to-End
     Generalized Multi-Protocol Label Switching (GMPLS)
     Recovery";
}

identity lsp-protection-unprotected {
  base lsp-protection-type;
  description
    "'Unprotected' LSP protection type.";
  reference
    "RFC 4872: RSVP-TE Extensions in Support of End-to-End
     Generalized Multi-Protocol Label Switching (GMPLS)
     Recovery";
}

identity lsp-protection-reroute-extra {
  base lsp-protection-type;
  status obsolete;
  description
```

```
    "'(Full) Rerouting' LSP protection type.

    This identity has been obsoleted: the
    'restoration-scheme-rerouting' or
    'restoration-scheme-precomputed' identity SHOULD be used
    instead.";
  reference
    "RFC 4872: RSVP-TE Extensions in Support of End-to-End
      Generalized Multi-Protocol Label Switching (GMPLS)
      Recovery, section 11";
}

identity lsp-protection-reroute {
  base lsp-protection-type;
  status obsolete;
  description
    "'Rerouting without Extra-Traffic' LSP protection type.

    This identity has been obsoleted: the
    'restoration-scheme-presignaled' identity SHOULD be used
    instead.";
  reference
    "RFC 4872: RSVP-TE Extensions in Support of End-to-End
      Generalized Multi-Protocol Label Switching (GMPLS)
      Recovery, section 8";
}

identity lsp-protection-1-for-n {
  base lsp-protection-type;
  description
    "'1:N Protection with Extra-Traffic' LSP protection type.";
  reference
    "RFC 4872: RSVP-TE Extensions in Support of End-to-End
      Generalized Multi-Protocol Label Switching (GMPLS)
      Recovery, section 7.3";
}

identity lsp-protection-1-for-1 {
  base lsp-protection-type;
  description
    "LSP protection '1:1 Protection Type'.";
  reference
    "RFC 4872: RSVP-TE Extensions in Support of End-to-End
      Generalized Multi-Protocol Label Switching (GMPLS)
      Recovery, section 7";
}

identity lsp-protection-unidir-1-plus-1 {
```

```
base lsp-protection-type;
description
  "'1+1 Unidirectional Protection' LSP protection type.";
reference
  "RFC 4872: RSVP-TE Extensions in Support of End-to-End
    Generalized Multi-Protocol Label Switching (GMPLS)
    Recovery, section 5";
}

identity lsp-protection-bidir-1-plus-1 {
  base lsp-protection-type;
  description
    "'1+1 Bidirectional Protection' LSP protection type.";
  reference
    "RFC 4872: RSVP-TE Extensions in Support of End-to-End
      Generalized Multi-Protocol Label Switching (GMPLS)
      Recovery, section 6";
}

identity lsp-protection-extra-traffic {
  base lsp-protection-type;
  description
    "Extra-Traffic LSP protection type.";
  reference
    "RFC 4872: RSVP-TE Extensions in Support of End-to-End
      Generalized Multi-Protocol Label Switching (GMPLS)
      Recovery, section 7";
}

identity lsp-protection-state {
  description
    "Base identity of protection states for reporting purposes.";
}

identity normal {
  base lsp-protection-state;
  description
    "Normal state.";
  reference
    "RFC 6378: MPLS Transport Profile (MPLS-TP) Linear Protection
      RFC 4427: Recovery (Protection and Restoration) Terminology
      for Generalized Multi-Protocol Label Switching
      (GMPLS)";
}

identity signal-fail-of-protection {
  base lsp-protection-state;
  description
```

```
    "The protection transport entity has a signal fail condition
    that is of higher priority than the forced switchover
    command.";
  reference
    "RFC 6378: MPLS Transport Profile (MPLS-TP) Linear Protection
    RFC 4427: Recovery (Protection and Restoration) Terminology
    for Generalized Multi-Protocol Label Switching
    (GMPLS)";
}

identity lockout-of-protection {
  base lsp-protection-state;
  description
    "A Loss of Protection (LoP) command is active.";
  reference
    "RFC 6378: MPLS Transport Profile (MPLS-TP) Linear Protection
    RFC 4427: Recovery (Protection and Restoration) Terminology
    for Generalized Multi-Protocol Label Switching
    (GMPLS)";
}

identity forced-switch {
  base lsp-protection-state;
  description
    "A forced switchover command is active.";
  reference
    "RFC 6378: MPLS Transport Profile (MPLS-TP) Linear Protection
    RFC 4427: Recovery (Protection and Restoration) Terminology
    for Generalized Multi-Protocol Label Switching
    (GMPLS)";
}

identity signal-fail {
  base lsp-protection-state;
  description
    "There is a signal fail condition on either the working path
    or the protection path.";
  reference
    "RFC 6378: MPLS Transport Profile (MPLS-TP) Linear Protection
    RFC 4427: Recovery (Protection and Restoration) Terminology
    for Generalized Multi-Protocol Label Switching
    (GMPLS)";
}

identity signal-degrade {
  base lsp-protection-state;
  description
    "There is a signal degrade condition on either the working
```

```
    path or the protection path.";
  reference
    "RFC 6378: MPLS Transport Profile (MPLS-TP) Linear Protection
     RFC 4427: Recovery (Protection and Restoration) Terminology
     for Generalized Multi-Protocol Label Switching
     (GMPLS)";
}

identity manual-switch {
  base lsp-protection-state;
  description
    "A manual switchover command is active.";
  reference
    "RFC 6378: MPLS Transport Profile (MPLS-TP) Linear Protection
     RFC 4427: Recovery (Protection and Restoration) Terminology
     for Generalized Multi-Protocol Label Switching
     (GMPLS)";
}

identity wait-to-restore {
  base lsp-protection-state;
  description
    "A Wait-to-Restore (WTR) timer is running.";
  reference
    "RFC 6378: MPLS Transport Profile (MPLS-TP) Linear Protection
     RFC 4427: Recovery (Protection and Restoration) Terminology
     for Generalized Multi-Protocol Label Switching
     (GMPLS)";
}

identity do-not-revert {
  base lsp-protection-state;
  description
    "A Do Not Revert (DNR) condition is active because of
     non-revertive behavior.";
  reference
    "RFC 6378: MPLS Transport Profile (MPLS-TP) Linear Protection
     RFC 4427: Recovery (Protection and Restoration) Terminology
     for Generalized Multi-Protocol Label Switching
     (GMPLS)";
}

identity failure-of-protocol {
  base lsp-protection-state;
  description
    "LSP protection is not working because of a protocol failure
     condition.";
  reference
```

```
"RFC 7271: MPLS Transport Profile (MPLS-TP) Linear Protection
to Match the Operational Expectations of
Synchronous Digital Hierarchy, Optical Transport
Network, and Ethernet Transport Network Operators
RFC 4427: Recovery (Protection and Restoration) Terminology
for Generalized Multi-Protocol Label Switching
(GMPLS)";
}

identity protection-external-commands {
  description
    "Base identity from which protection-related external commands
    used for troubleshooting purposes are derived.";
}

identity action-freeze {
  base protection-external-commands;
  description
    "A temporary configuration action initiated by an operator
    command that prevents any switchover action from being taken
    and, as such, freezes the current state.";
  reference
    "RFC 7271: MPLS Transport Profile (MPLS-TP) Linear Protection
    to Match the Operational Expectations of
    Synchronous Digital Hierarchy, Optical Transport
    Network, and Ethernet Transport Network Operators
    RFC 4427: Recovery (Protection and Restoration) Terminology
    for Generalized Multi-Protocol Label Switching
    (GMPLS)";
}

identity clear-freeze {
  base protection-external-commands;
  description
    "An action that clears the active freeze state.";
  reference
    "RFC 7271: MPLS Transport Profile (MPLS-TP) Linear Protection
    to Match the Operational Expectations of
    Synchronous Digital Hierarchy, Optical Transport
    Network, and Ethernet Transport Network Operators
    RFC 4427: Recovery (Protection and Restoration) Terminology
    for Generalized Multi-Protocol Label Switching
    (GMPLS)";
}

identity action-lockout-of-normal {
  base protection-external-commands;
  description
```



```
"A temporary configuration action initiated by an operator
command to ensure that the normal traffic is not allowed
to use the protection transport entity.";
reference
  "RFC 4872: RSVP-TE Extensions in Support of End-to-End
    Generalized Multi-Protocol Label Switching (GMPLS)
    Recovery
  RFC 4427: Recovery (Protection and Restoration) Terminology
    for Generalized Multi-Protocol Label Switching
    (GMPLS)";
}

identity clear-lockout-of-normal {
  base protection-external-commands;
  description
    "An action that clears the active lockout of the
    normal state.";
  reference
    "RFC 4872: RSVP-TE Extensions in Support of End-to-End
      Generalized Multi-Protocol Label Switching (GMPLS)
      Recovery
    RFC 4427: Recovery (Protection and Restoration) Terminology
      for Generalized Multi-Protocol Label Switching
      (GMPLS)";
}

identity action-lockout-of-protection {
  base protection-external-commands;
  description
    "A temporary configuration action initiated by an operator
    command to ensure that the protection transport entity is
    temporarily not available to transport a traffic signal
    (either normal or Extra-Traffic).";
  reference
    "RFC 4872: RSVP-TE Extensions in Support of End-to-End
      Generalized Multi-Protocol Label Switching (GMPLS)
      Recovery
    RFC 4427: Recovery (Protection and Restoration) Terminology
      for Generalized Multi-Protocol Label Switching
      (GMPLS)";
}

identity action-forced-switch {
  base protection-external-commands;
  description
    "A switchover action initiated by an operator command to
    switch the Extra-Traffic signal, the normal traffic signal,
    or the null signal to the protection transport entity,
```

```
        unless a switchover command of equal or higher priority is
        in effect.";
    reference
        "RFC 4872: RSVP-TE Extensions in Support of End-to-End
        Generalized Multi-Protocol Label Switching (GMPLS)
        Recovery
        RFC 4427: Recovery (Protection and Restoration) Terminology
        for Generalized Multi-Protocol Label Switching
        (GMPLS)";
}

identity action-manual-switch {
    base protection-external-commands;
    description
        "A switchover action initiated by an operator command to
        switch the Extra-Traffic signal, the normal traffic signal,
        or the null signal to the protection transport entity,
        unless a fault condition exists on other transport entities
        or a switchover command of equal or higher priority is in
        effect.";
    reference
        "RFC 4872: RSVP-TE Extensions in Support of End-to-End
        Generalized Multi-Protocol Label Switching (GMPLS)
        Recovery
        RFC 4427: Recovery (Protection and Restoration) Terminology
        for Generalized Multi-Protocol Label Switching
        (GMPLS)";
}

identity action-exercise {
    base protection-external-commands;
    description
        "An action that starts testing whether or not Automatic
        Protection Switching (APS) communication is operating
        correctly.

        It is of lower priority than any other state or command.";
    reference
        "RFC 7271: MPLS Transport Profile (MPLS-TP) Linear Protection
        to Match the Operational Expectations of
        Synchronous Digital Hierarchy, Optical Transport
        Network, and Ethernet Transport Network Operators
        RFC 4427: Recovery (Protection and Restoration) Terminology
        for Generalized Multi-Protocol Label Switching
        (GMPLS)";
}

identity clear {
```

```
base protection-external-commands;
description
  "An action that clears the active near-end lockout of a
  protection, forced switchover, manual switchover,
  Wait-to-Restore (WTR) state, or exercise command.";
reference
  "RFC 6378: MPLS Transport Profile (MPLS-TP) Linear Protection
  RFC 4427: Recovery (Protection and Restoration) Terminology
  for Generalized Multi-Protocol Label Switching
  (GMPLS)";
}

identity switching-capabilities {
  description
    "Base identity for interface switching capabilities.";
  reference
    "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
    Signaling Functional Description";
}

identity switching-psc1 {
  base switching-capabilities;
  description
    "Packet-Switch Capable-1 (PSC-1).";
  reference
    "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
    Signaling Functional Description";
}

identity switching-evpl {
  base switching-capabilities;
  description
    "Ethernet Virtual Private Line (EVPL).";
  reference
    "RFC 6004: Generalized MPLS (GMPLS) Support for Metro
    Ethernet Forum and G.8011 Ethernet Service
    Switching";
}

identity switching-l2sc {
  base switching-capabilities;
  description
    "Layer-2 Switch Capable (L2SC).";
  reference
    "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
    Signaling Functional Description";
}
```

```
identity switching-tdm {
  base switching-capabilities;
  description
    "Time-Division-Multiplex Capable (TDM).";
  reference
    "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
      Signaling Functional Description";
}

identity switching-otn {
  base switching-capabilities;
  description
    "OTN-TDM capable.";
  reference
    "RFC 7138: Traffic Engineering Extensions to OSPF for GMPLS
      Control of Evolving G.709 Optical Transport
      Networks";
}

identity switching-dcsc {
  base switching-capabilities;
  description
    "Data Channel Switching Capable (DCSC).";
  reference
    "RFC 6002: Generalized MPLS (GMPLS) Data Channel
      Switching Capable (DCSC) and Channel Set Label
      Extensions";
}

identity switching-lsc {
  base switching-capabilities;
  description
    "Lambda-Switch Capable (LSC).";
  reference
    "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
      Signaling Functional Description";
}

identity switching-fsc {
  base switching-capabilities;
  description
    "Fiber-Switch Capable (FSC).";
  reference
    "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
      Signaling Functional Description";
}

identity lsp-encoding-types {
```

```
    description
      "Base identity for encoding types.";
    reference
      "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
        Signaling Functional Description";
  }

  identity lsp-encoding-packet {
    base lsp-encoding-types;
    description
      "Packet LSP encoding.";
    reference
      "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
        Signaling Functional Description";
  }

  identity lsp-encoding-ethernet {
    base lsp-encoding-types;
    description
      "Ethernet LSP encoding.";
    reference
      "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
        Signaling Functional Description";
  }

  identity lsp-encoding-pdh {
    base lsp-encoding-types;
    description
      "ANSI/ETSI PDH LSP encoding.";
    reference
      "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
        Signaling Functional Description";
  }

  identity lsp-encoding-sdh {
    base lsp-encoding-types;
    description
      "SDH ITU-T G.707 / SONET ANSI T1.105 LSP encoding.";
    reference
      "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
        Signaling Functional Description";
  }

  identity lsp-encoding-digital-wrapper {
    base lsp-encoding-types;
    description
      "Digital Wrapper LSP encoding.";
    reference
```

```
        "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
          Signaling Functional Description";
    }

    identity lsp-encoding-lambda {
        base lsp-encoding-types;
        description
            "Lambda (photonic) LSP encoding.";
        reference
            "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
              Signaling Functional Description";
    }

    identity lsp-encoding-fiber {
        base lsp-encoding-types;
        description
            "Fiber LSP encoding.";
        reference
            "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
              Signaling Functional Description";
    }

    identity lsp-encoding-fiber-channel {
        base lsp-encoding-types;
        description
            "FiberChannel LSP encoding.";
        reference
            "RFC 3471: Generalized Multi-Protocol Label Switching (GMPLS)
              Signaling Functional Description";
    }

    identity lsp-encoding-oduk {
        base lsp-encoding-types;
        description
            "G.709 ODUk (Digital Path) LSP encoding.";
        reference
            "RFC 4328: Generalized Multi-Protocol Label Switching (GMPLS)
              Signaling Extensions for G.709 Optical Transport
              Networks Control";
    }

    identity lsp-encoding-optical-channel {
        base lsp-encoding-types;
        description
            "G.709 Optical Channel LSP encoding.";
        reference
            "RFC 4328: Generalized Multi-Protocol Label Switching (GMPLS)
              Signaling Extensions for G.709 Optical Transport
```

```
        Networks Control";
    }

    identity lsp-encoding-line {
        base lsp-encoding-types;
        description
            "Line (e.g., 8B/10B) LSP encoding.";
        reference
            "RFC 6004: Generalized MPLS (GMPLS) Support for Metro
             Ethernet Forum and G.8011 Ethernet Service
             Switching";
    }

    identity path-signaling-type {
        description
            "Base identity from which specific LSP path setup types
             are derived.";
    }

    identity path-setup-static {
        base path-signaling-type;
        description
            "Static LSP provisioning path setup.";
    }

    identity path-setup-rsvp {
        base path-signaling-type;
        description
            "RSVP-TE signaling path setup.";
        reference
            "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels";
    }

    identity path-setup-sr {
        base path-signaling-type;
        description
            "Segment-routing path setup.";
    }

    identity path-scope-type {
        description
            "Base identity from which specific path scope types are
             derived.";
    }

    identity path-scope-segment {
        base path-scope-type;
        description
```

```
    "Path scope segment.";
  reference
    "RFC 4873: GMPLS Segment Recovery";
}

identity path-scope-end-to-end {
  base path-scope-type;
  description
    "Path scope end to end.";
  reference
    "RFC 4873: GMPLS Segment Recovery";
}

identity route-usage-type {
  description
    "Base identity for route usage.";
}

identity route-include-object {
  base route-usage-type;
  description
    "'Include route' object.";
  reference
    "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels,
      Section 4.3.2
    RFC 5440: Path Computation Element (PCE) Communication
      Protocol (PCEP), Section 7.12
    RFC 7896: Update to the Include Route Object (IRO)
      Specification in the Path Computation Element
      Communication Protocol (PCEP)";
}

identity route-exclude-object {
  base route-usage-type;
  description
    "'Exclude route' object.";
  reference
    "RFC 4874: Exclude Routes - Extension to Resource ReserVation
      Protocol-Traffic Engineering (RSVP-TE)";
}

identity route-exclude-srlg {
  base route-usage-type;
  description
    "Excludes Shared Risk Link Groups (SRLGs).";
  reference
    "RFC 4874: Exclude Routes - Extension to Resource ReserVation
      Protocol-Traffic Engineering (RSVP-TE)";
}
```



```
}

identity path-metric-optimization-type {
  description
    "Base identity used to define the path metric optimization
    types.";
}

identity link-path-metric-type {
  description
    "Base identity used to define the link and the path metric
    types.

    The unit of the path metric value is interpreted in the
    context of the path metric type and the derived identities
    SHOULD describe the unit of the path metric types they
    define.";
}

identity link-metric-type {
  base link-path-metric-type;
  description
    "Base identity for the link metric types.";
}

identity link-metric-te {
  base link-metric-type;
  description
    "Traffic Engineering (TE) Link Metric.";
  reference
    "RFC 3630: Traffic Engineering (TE) Extensions to OSPF
    Version 2, Section 2.5.5
    RFC 5305: IS-IS Extensions for Traffic Engineering,
    Section 3.7";
}

identity link-metric-igp {
  base link-metric-type;
  description
    "Interior Gateway Protocol (IGP) Link Metric.";
  reference
    "RFC 3785: Use of Interior Gateway Protocol (IGP) Metric
    as a second MPLS Traffic Engineering (TE)
    Metric";
}

identity link-metric-delay-average {
  base link-metric-type;
```

```
description
  "Unidirectional Link Delay, measured in units of
  microseconds.";
reference
  "RFC 7471: OSPF Traffic Engineering (TE) Metric
  Extensions, Section 4.1
  RFC 8570: IS-IS Traffic Engineering (TE) Metric
  Extensions, Section 4.1";
}

identity link-metric-delay-minimum {
  base link-metric-type;
  description
    "Minimum unidirectional Link Delay, measured in units of
    microseconds.";
  reference
    "RFC 7471: OSPF Traffic Engineering (TE) Metric
    Extensions, Section 4.2
    RFC 8570: IS-IS Traffic Engineering (TE) Metric
    Extensions, Section 4.2";
}

identity link-metric-delay-maximum {
  base link-metric-type;
  description
    "Maximum unidirectional Link Delay, measured in units of
    microseconds.";
  reference
    "RFC 7471: OSPF Traffic Engineering (TE) Metric
    Extensions, Section 4.2
    RFC 8570: IS-IS Traffic Engineering (TE) Metric
    Extensions, Section 4.2";
}

identity link-metric-residual-bandwidth {
  base link-metric-type;
  description
    "Unidirectional Residual Bandwidth, measured in units of
    bytes per second.

    It is defined to be Maximum Bandwidth minus the bandwidth
    currently allocated to LSPs.";
  reference
    "RFC 7471: OSPF Traffic Engineering (TE) Metric
    Extensions, Section 4.5
    RFC 8570: IS-IS Traffic Engineering (TE) Metric
    Extensions, Section 4.5";
}
```

```
identity path-metric-type {
  base link-path-metric-type;
  base path-metric-optimization-type;
  description
    "Base identity for the path metric types.";
}

identity path-metric-te {
  base path-metric-type;
  description
    "Traffic Engineering (TE) Path Metric.";
  reference
    "RFC 5440: Path Computation Element (PCE) Communication
      Protocol (PCEP), Section 7.8";
}

identity path-metric-igp {
  base path-metric-type;
  description
    "Interior Gateway Protocol (IGP) Path Metric.";
  reference
    "RFC 5440: Path Computation Element (PCE) Communication
      Protocol (PCEP), section 7.8";
}

identity path-metric-hop {
  base path-metric-type;
  description
    "Hop Count Path Metric.";
  reference
    "RFC 5440: Path Computation Element (PCE) Communication
      Protocol (PCEP), Section 7.8";
}

identity path-metric-delay-average {
  base path-metric-type;
  description
    "The Path Delay Metric, measured in units of
      microseconds.";
  reference
    "RFC 8233: Extensions to the Path Computation Element
      Communication Protocol (PCEP) to Compute
      Service-Aware Label Switched Paths (LSPs),
      Section 3.1.1";
}

identity path-metric-delay-minimum {
  base path-metric-type;
```

```
description
  "The Path Min Delay Metric, measured in units of
  microseconds.";
reference
  "I-D.ietf-pce-sid-algo: Carrying SR-Algorithm information
  in PCE-based Networks,
  draft-ietf-pce-sid-algo-29,
  Sections 4.5.1 and 4.5.2";
}

// RFC Editor: Please replace the section and draft version in the
// reference to draft-ietf-pce-sid-algo-29 above with the latest
// version at the time the RFC is published.
// Please remove this note.

identity path-metric-residual-bandwidth {
  base path-metric-type;
  description
    "The Path Residual Bandwidth, defined as the minimum Link
    Residual Bandwidth all the links along the path.

    The Path Residual Bandwidth can be seen as the path
    metric associated with the Maximum residual Bandwidth Path
    (MBP) objective function.";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
    Computation Element Communication Protocol
    (PCEP)";
}

identity path-metric-optimize-includes {
  base path-metric-optimization-type;
  description
    "A metric that optimizes the number of included resources
    specified in a set.";
}

identity path-metric-optimize-excludes {
  base path-metric-optimization-type;
  description
    "A metric that optimizes to a maximum the number of excluded
    resources specified in a set.";
}

identity path-tiebreaker-type {
  description
    "Base identity for the path tiebreaker type.";
}
```

```
identity path-tiebreaker-minfill {
  base path-tiebreaker-type;
  description
    "Min-Fill LSP path placement: selects the path with the most
    available bandwidth (load balance LSPs over more links).";
}

identity path-tiebreaker-maxfill {
  base path-tiebreaker-type;
  description
    "Max-Fill LSP path placement: selects the path with the least
    available bandwidth (packing more LSPs over few links).";
}

identity path-tiebreaker-random {
  base path-tiebreaker-type;
  description
    "Random LSP path placement.";
}

identity resource-affinities-type {
  description
    "Base identity for resource class affinities.";
  reference
    "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels
    RFC 2702: Requirements for Traffic Engineering Over MPLS";
}

identity resource-aff-include-all {
  base resource-affinities-type;
  description
    "The set of attribute filters associated with a
    tunnel, all of which must be present for a link
    to be acceptable.";
  reference
    "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels
    RFC 2702: Requirements for Traffic Engineering Over MPLS";
}

identity resource-aff-include-any {
  base resource-affinities-type;
  description
    "The set of attribute filters associated with a
    tunnel, any of which must be present for a link
    to be acceptable.";
  reference
    "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels
    RFC 2702: Requirements for Traffic Engineering Over MPLS";
}
```

```
}

identity resource-aff-exclude-any {
  base resource-affinities-type;
  description
    "The set of attribute filters associated with a
    tunnel, any of which renders a link unacceptable.";
  reference
    "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels
    RFC 2702: Requirements for Traffic Engineering Over MPLS";
}

identity te-optimization-criterion {
  description
    "Base identity for the TE optimization criteria.";
  reference
    "RFC 9522: Overview and Principles of Internet Traffic
    Engineering";
}

identity not-optimized {
  base te-optimization-criterion;
  description
    "Optimization is not applied.";
}

identity cost {
  base te-optimization-criterion;
  description
    "Optimized on cost.";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
    Computation Element Communication Protocol
    (PCEP)";
}

identity delay {
  base te-optimization-criterion;
  description
    "Optimized on delay.";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
    Computation Element Communication Protocol
    (PCEP)";
}

identity path-computation-srlg-type {
  description
```

```
    "Base identity for Shared Risk Link Group (SRLG) path
    computation.";
}

identity srlg-ignore {
    base path-computation-srlg-type;
    description
        "Ignores Shared Risk Link Groups (SRLGs) in the path
        computation.";
}

identity srlg-strict {
    base path-computation-srlg-type;
    description
        "Includes a strict Shared Risk Link Group (SRLG) check in
        the path computation.";
}

identity srlg-preferred {
    base path-computation-srlg-type;
    description
        "Includes a preferred Shared Risk Link Group (SRLG) check in
        the path computation.";
}

identity srlg-weighted {
    base path-computation-srlg-type;
    description
        "Includes a weighted Shared Risk Link Group (SRLG) check in
        the path computation.";
}

identity path-computation-error-reason {
    description
        "Base identity for path computation error reasons.";
}

identity path-computation-error-path-not-found {
    base path-computation-error-reason;
    description
        "Path computation has failed because of an unspecified
        reason.";
    reference
        "RFC 5440: Path Computation Element (PCE) Communication
        Protocol (PCEP), Section 7.5";
}

identity path-computation-error-no-topology {
```

```
    base path-computation-error-reason;
    description
      "Path computation has failed because there is no topology
       with the provided topology-identifier.";
  }

  identity path-computation-error-no-dependent-server {
    base path-computation-error-reason;
    description
      "Path computation has failed because one or more dependent
       path computation servers are unavailable.

       The dependent path computation server could be
       a Backward-Recursive Path Computation (BRPC) downstream
       PCE or a child PCE.";
    reference
      "RFC 5441: A Backward-Recursive PCE-Based Computation (BRPC)
       Procedure to Compute Shortest Constrained
       Inter-Domain Traffic Engineering Label Switched
       Paths
       RFC 8685: Path Computation Element Communication Protocol
       (PCEP) Extensions for the Hierarchical Path
       Computation Element (H-PCE) Architecture";
  }

  identity path-computation-error-pce-unavailable {
    base path-computation-error-reason;
    description
      "Path computation has failed because PCE is not available.

       It corresponds to bit 31 of the Flags field of the
       NO-PATH-VECTOR TLV.";
    reference
      "RFC 5440: Path Computation Element (PCE) Communication
       Protocol (PCEP)

       https://www.iana.org/assignments/pcep
       /pcep.xhtml#no-path-vector-tlv";
  }

  identity path-computation-error-no-inclusion-hop {
    base path-computation-error-reason;
    description
      "Path computation has failed because there is no
       node or link provided by one or more inclusion hops.";
  }

  identity path-computation-error-destination-unknown-in-domain {
```



```
base path-computation-error-reason;
description
  "Path computation has failed because the destination node is
   unknown in indicated destination domain.

   It corresponds to bit 19 of the Flags field of the
   NO-PATH-VECTOR TLV.";
reference
  "RFC 8685: Path Computation Element Communication Protocol
   (PCEP) Extensions for the Hierarchical Path
   Computation Element (H-PCE) Architecture

   https://www.iana.org/assignments/pcep
   /pcep.xhtml#no-path-vector-tlv";
}

identity path-computation-error-no-resource {
  base path-computation-error-reason;
  description
    "Path computation has failed because there is no
     available resource in one or more domains.

     It corresponds to bit 20 of the Flags field of the
     NO-PATH-VECTOR TLV.";
  reference
    "RFC 8685: Path Computation Element Communication Protocol
     (PCEP) Extensions for the Hierarchical Path
     Computation Element (H-PCE) Architecture

     https://www.iana.org/assignments/pcep
     /pcep.xhtml#no-path-vector-tlv";
}

identity path-computation-error-child-pce-unresponsive {
  base path-computation-error-no-dependent-server;
  description
    "Path computation has failed because child PCE is not
     responsive.

     It corresponds to bit 21 of the Flags field of the
     NO-PATH-VECTOR TLV.";
  reference
    "RFC 8685: Path Computation Element Communication Protocol
     (PCEP) Extensions for the Hierarchical Path
     Computation Element (H-PCE) Architecture

     https://www.iana.org/assignments/pcep
     /pcep.xhtml#no-path-vector-tlv";
}
```

```
}

identity path-computation-error-destination-domain-unknown {
  base path-computation-error-reason;
  description
    "Path computation has failed because the destination domain
    was unknown.

    It corresponds to bit 22 of the Flags field of the
    NO-PATH-VECTOR TLV.";
  reference
    "RFC 8685: Path Computation Element Communication Protocol
    (PCEP) Extensions for the Hierarchical Path
    Computation Element (H-PCE) Architecture

    https://www.iana.org/assignments/pcep
    /pcep.xhtml#no-path-vector-tlv";
}

identity path-computation-error-p2mp {
  base path-computation-error-reason;
  description
    "Path computation has failed because of P2MP reachability
    problem.

    It corresponds to bit 24 of the Flags field of the
    NO-PATH-VECTOR TLV.";
  reference
    "RFC 8306: Extensions to the Path Computation Element
    Communication Protocol (PCEP) for
    Point-to-Multipoint Traffic Engineering Label
    Switched Paths

    https://www.iana.org/assignments/pcep
    /pcep.xhtml#no-path-vector-tlv";
}

identity path-computation-error-no-gco-migration {
  base path-computation-error-reason;
  description
    "Path computation has failed because of no Global Concurrent
    Optimization (GCO) migration path found.

    It corresponds to bit 26 of the Flags field of the
    NO-PATH-VECTOR TLV.";
  reference
    "RFC 5557: Path Computation Element Communication Protocol
    (PCEP) Requirements and Protocol Extensions in
```

Support of Global Concurrent Optimization

```
    https://www.iana.org/assignments/pcep
    /pcep.xhtml#no-path-vector-tlv";
}

identity path-computation-error-no-gco-solution {
  base path-computation-error-reason;
  description
    "Path computation has failed because of no GCO solution
    found.

    It corresponds to bit 25 of the Flags field of the
    NO-PATH-VECTOR TLV.";
  reference
    "RFC 5557: Path Computation Element Communication Protocol
    (PCEP) Requirements and Protocol Extensions in
    Support of Global Concurrent Optimization

    https://www.iana.org/assignments/pcep
    /pcep.xhtml#no-path-vector-tlv";
}

identity path-computation-error-pks-expansion {
  base path-computation-error-reason;
  description
    "Path computation has failed because of Path-Key Subobject
    (PKS) expansion failure.

    It corresponds to bit 27 of the Flags field of the
    NO-PATH-VECTOR TLV.";
  reference
    "RFC 5520: Preserving Topology Confidentiality in
    Inter-Domain Path Computation Using a
    Path-Key-Based Mechanism

    https://www.iana.org/assignments/pcep
    /pcep.xhtml#no-path-vector-tlv";
}

identity path-computation-error-brpc-chain-unavailable {
  base path-computation-error-no-dependent-server;
  description
    "Path computation has failed because PCE BRPC chain
    unavailable.

    It corresponds to bit 28 of the Flags field of the
    NO-PATH-VECTOR TLV.";
```

```
reference
  "RFC 5441: A Backward-Recursive PCE-Based Computation (BRPC)
    Procedure to Compute Shortest Constrained
    Inter-Domain Traffic Engineering Label Switched
    Paths

    https://www.iana.org/assignments/pcep
    /pcep.xhtml#no-path-vector-tlv";
}

identity path-computation-error-source-unknown {
  base path-computation-error-reason;
  description
    "Path computation has failed because source node is
    unknown.

    It corresponds to bit 29 of the Flags field of the
    NO-PATH-VECTOR TLV.";
  reference
    "RFC 5440: Path Computation Element (PCE) Communication
    Protocol (PCEP);

    https://www.iana.org/assignments/pcep
    /pcep.xhtml#no-path-vector-tlv";
}

identity path-computation-error-destination-unknown {
  base path-computation-error-reason;
  description
    "Path computation has failed because destination node is
    unknown.

    It corresponds to bit 30 of the Flags field of the
    NO-PATH-VECTOR TLV.";
  reference
    "RFC 5440: Path Computation Element (PCE) Communication
    Protocol (PCEP);

    https://www.iana.org/assignments/pcep
    /pcep.xhtml#no-path-vector-tlv";
}

identity protocol-origin-type {
  description
    "Base identity for protocol origin type.";
}

identity protocol-origin-api {
```

```
    base protocol-origin-type;
    description
        "Protocol origin is via Application Programming Interface
        (API).";
}

identity protocol-origin-pcep {
    base protocol-origin-type;
    description
        "Protocol origin is Path Computation Engine Protocol
        (PCEP).";
    reference
        "RFC 5440: Path Computation Element (PCE) Communication
        Protocol (PCEP)";
}

identity protocol-origin-bgp {
    base protocol-origin-type;
    description
        "Protocol origin is Border Gateway Protocol (BGP).";
    reference
        "RFC 9012: The BGP Tunnel Encapsulation Attribute";
}

identity svec-objective-function-type {
    description
        "Base identity for SVEC objective function type.";
    reference
        "RFC 5541: Encoding of Objective Functions in the Path
        Computation Element Communication Protocol (PCEP)";
}

identity svec-of-minimize-agg-bandwidth-consumption {
    base svec-objective-function-type;
    description
        "Objective function for minimizing aggregate bandwidth
        consumption (MBC).";
    reference
        "RFC 5541: Encoding of Objective Functions in the Path
        Computation Element Communication Protocol
        (PCEP)";
}

identity svec-of-minimize-load-most-loaded-link {
    base svec-objective-function-type;
    description
        "Objective function for minimizing the load on the link that
        is carrying the highest load (MLL).";
```

```
reference
  "RFC 5541: Encoding of Objective Functions in the Path
    Computation Element Communication Protocol
    (PCEP)";
}

identity svec-of-minimize-cost-path-set {
  base svec-objective-function-type;
  description
    "Objective function for minimizing the cost on a path set
    (MCC).";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
      Computation Element Communication Protocol
      (PCEP)";
}

identity svec-of-minimize-common-transit-domain {
  base svec-objective-function-type;
  description
    "Objective function for minimizing the number of common
    transit domains (MCTD).";
  reference
    "RFC 8685: Path Computation Element Communication Protocol
      (PCEP) Extensions for the Hierarchical Path
      Computation Element (H-PCE) Architecture.";
}

identity svec-of-minimize-shared-link {
  base svec-objective-function-type;
  description
    "Objective function for minimizing the number of shared
    links (MSL).";
  reference
    "RFC 8685: Path Computation Element Communication Protocol
      (PCEP) Extensions for the Hierarchical Path
      Computation Element (H-PCE) Architecture.";
}

identity svec-of-minimize-shared-srlg {
  base svec-objective-function-type;
  description
    "Objective function for minimizing the number of shared
    Shared Risk Link Groups (SRLG) (MSS).";
  reference
    "RFC 8685: Path Computation Element Communication Protocol
      (PCEP) Extensions for the Hierarchical Path
      Computation Element (H-PCE) Architecture.";
```

```
}

identity svec-of-minimize-shared-nodes {
  base svec-objective-function-type;
  description
    "Objective function for minimizing the number of shared
     nodes (MSN).";
  reference
    "RFC 8685: Path Computation Element Communication Protocol
     (PCEP) Extensions for the Hierarchical Path
     Computation Element (H-PCE) Architecture.";
}

identity svec-metric-type {
  description
    "Base identity for SVEC metric type.";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
     Computation Element Communication Protocol (PCEP)";
}

identity svec-metric-cumulative-te {
  base svec-metric-type;
  description
    "Cumulative TE cost.";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
     Computation Element Communication Protocol
     (PCEP)";
}

identity svec-metric-cumulative-igp {
  base svec-metric-type;
  description
    "Cumulative IGP cost.";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
     Computation Element Communication Protocol
     (PCEP)";
}

identity svec-metric-cumulative-hop {
  base svec-metric-type;
  description
    "Cumulative Hop path metric.";
  reference
    "RFC 5541: Encoding of Objective Functions in the Path
     Computation Element Communication Protocol";
}
```

```
        (PCEP)";
    }

    identity svec-metric-aggregate-bandwidth-consumption {
        base svec-metric-type;
        description
            "Aggregate bandwidth consumption.";
        reference
            "RFC 5541: Encoding of Objective Functions in the Path
             Computation Element Communication Protocol
             (PCEP)";
    }

    identity svec-metric-load-of-the-most-loaded-link {
        base svec-metric-type;
        description
            "Load of the most loaded link.";
        reference
            "RFC 5541: Encoding of Objective Functions in the Path
             Computation Element Communication Protocol
             (PCEP)";
    }

    /*
     * Typedefs
     */

    typedef admin-group {
        type yang:hex-string {
            /* 01:02:03:04 */
            length "1..11";
        }
        description
            "Administrative group / resource class / color representation
             in 'hex-string' type.

             The most significant byte in the hex-string is the farthest
             to the left in the byte sequence.

             Leading zero bytes in the configured value may be omitted
             for brevity.";
        reference
            "RFC 3630: Traffic Engineering (TE) Extensions to OSPF
             Version 2
             RFC 5305: IS-IS Extensions for Traffic Engineering
             RFC 7308: Extended Administrative Groups in MPLS Traffic
             Engineering (MPLS-TE)";
    }
}
```



```
typedef admin-groups {
  type union {
    type admin-group;
    type extended-admin-group;
  }
  description
    "Derived types for TE administrative groups.";
}

typedef extended-admin-group {
  type yang:hex-string;
  description
    "Extended administrative group / resource class / color
    representation in 'hex-string' type.

    The most significant byte in the hex-string is the farthest
    to the left in the byte sequence.

    Leading zero bytes in the configured value may be omitted
    for brevity.";
  reference
    "RFC 7308: Extended Administrative Groups in MPLS Traffic
    Engineering (MPLS-TE)";
}

typedef path-attribute-flags {
  type union {
    type identityref {
      base session-attributes-flags;
    }
    type identityref {
      base lsp-attributes-flags;
    }
  }
  description
    "Path attributes flags type.";
}

typedef performance-metrics-normality {
  type enumeration {
    enum unknown {
      value 0;
      description
        "Unknown.";
    }
    enum normal {
      value 1;
      description
```

```
        "Normal.

        Indicates that the anomalous bit is not set.";
    }
    enum abnormal {
        value 2;
        description
            "Abnormal.

            Indicates that the anomalous bit is set.";
    }
}
description
    "Indicates whether a performance metric is normal (anomalous
    bit not set), abnormal (anomalous bit set), or unknown.";
reference
    "RFC 7471: OSPF Traffic Engineering (TE) Metric Extensions
    RFC 7823: Performance-Based Path Selection for Explicitly
        Routed Label Switched Paths (LSPs) Using TE Metric
        Extensions
    RFC 8570: IS-IS Traffic Engineering (TE) Metric Extensions";
}

typedef srlg {
    type uint32;
    description
        "Shared Risk Link Group (SRLG) type.";
    reference
        "RFC 4203: OSPF Extensions in Support of Generalized
            Multi-Protocol Label Switching (GMPLS)
        RFC 5307: IS-IS Extensions in Support of Generalized
            Multi-Protocol Label Switching (GMPLS)";
}

typedef te-common-status {
    type enumeration {
        enum up {
            description
                "Enabled.";
        }
        enum down {
            description
                "Disabled.";
        }
        enum testing {
            description
                "In some test mode.";
        }
    }
}
```

```

enum preparing-maintenance {
  description
    "The resource is disabled in the control plane to prepare
    for a graceful shutdown for maintenance purposes.";
  reference
    "RFC 5817: Graceful Shutdown in MPLS and Generalized MPLS
    Traffic Engineering Networks";
}
enum maintenance {
  description
    "The resource is disabled in the data plane for maintenance
    purposes.";
}
enum unknown {
  description
    "Status is unknown.";
}
}
description
  "Defines a type representing the common states of a TE
  resource.";
}

typedef te-bandwidth {
  type string {
    pattern '0[xX](0((\.\.0?)?[pP](\+)?0?|(\.\.0?))|'
      + '1(\.([\da-fA-F]{0,5}[02468aAcCeE]?))?)?'
      + '[pP](\+)?(12[0-7]|'
      + '1[01]\d|0?\d?\d)?|0[xX][\da-fA-F]{1,8}|\d+'
      + '(, (0[xX](0((\.\.0?)?[pP](\+)?0?|(\.\.0?))|'
      + '1(\.([\da-fA-F]{0,5}[02468aAcCeE]?))?)?'
      + '[pP](\+)?(12[0-7]|'
      + '1[01]\d|0?\d?\d)?|0[xX][\da-fA-F]{1,8}|\d+))*';
  }
  description
    "This is the generic bandwidth type.

    It is a string containing a list of numbers separated by
    commas, where each of these numbers can be non-negative
    decimal, hex integer, or hex float:

    (dec | hex | float)[*(','(dec | hex | float))]

    For the packet-switching type, the string encoding may follow
    the type 'bandwidth-ieee-float32' as defined in RFC 8294
    (e.g., 0x1p10), where the units are in bytes per second.

    Canonically, the string is represented as all lowercase and in

```

```
    hex, where the prefix '0x' precedes the hex number.";
  reference
    "RFC 8294: Common YANG Data Types for the Routing Area
    ITU-T G.709: Interfaces for the optical transport network -
      Edition 6.0 (06/2020)";
}

typedef te-ds-class {
  type uint8 {
    range "0..7";
  }
  description
    "The Differentiated Services Class-Type of traffic.";
  reference
    "RFC 4124: Protocol Extensions for Support of Diffserv-aware
      MPLS Traffic Engineering, Section 4.3.1";
}

typedef te-global-id {
  type uint32;
  description
    "An identifier to uniquely identify an operator, which can be
    either a provider or a client.

    The definition of this type is taken from RFCs 6370 and 5003.

    This attribute type is used solely to provide a globally
    unique context for TE topologies.";
  reference
    "RFC 5003: Attachment Individual Identifier (AII) Types for
      Aggregation
    RFC 6370: MPLS Transport Profile (MPLS-TP) Identifiers";
}

typedef te-hop-type {
  type enumeration {
    enum loose {
      description
        "A loose hop in an explicit path.";
    }
    enum strict {
      description
        "A strict hop in an explicit path.";
    }
  }
  description
    "Enumerated type for specifying loose or strict paths.";
  reference
```

```
        "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels,  
          Section 4.3.3";  
    }  
  
    typedef te-link-access-type {  
        type enumeration {  
            enum point-to-point {  
                description  
                    "The link is point-to-point.";  
            }  
            enum multi-access {  
                description  
                    "The link is multi-access, including broadcast and NBMA.";  
            }  
        }  
        description  
            "Defines a type representing the access type of a TE link.";  
        reference  
            "RFC 3630: Traffic Engineering (TE) Extensions to OSPF  
              Version 2";  
    }  
  
    typedef te-label-direction {  
        type enumeration {  
            enum forward {  
                description  
                    "Label allocated for the forward LSP direction.";  
            }  
            enum reverse {  
                description  
                    "Label allocated for the reverse LSP direction.";  
            }  
        }  
        description  
            "Enumerated type for specifying the forward or reverse  
              label.";  
    }  
  
    typedef te-link-direction {  
        type enumeration {  
            enum incoming {  
                description  
                    "The explicit route represents an incoming link on  
                      a node.";  
            }  
            enum outgoing {  
                description  
                    "The explicit route represents an outgoing link on
```

```
        a node.";
    }
}
description
    "Enumerated type for specifying the direction of a link on
    a node.";
}

typedef te-metric {
    type uint32;
    description
        "Traffic Engineering (TE) metric.";
    reference
        "RFC 3630: Traffic Engineering (TE) Extensions to OSPF
        Version 2, Section 2.5.5
        RFC 5305: IS-IS Extensions for Traffic Engineering,
        Section 3.7";
}

typedef te-node-id {
    type union {
        type yang:dotted-quad;
        type inet:ipv6-address-no-zone;
    }
    description
        "A type representing the identifier for a node in a TE
        topology.

        The identifier is represented either as 4 octets in
        dotted-quad notation, or as 16 octets in full, mixed,
        shortened, or shortened-mixed IPv6 address notation.

        This attribute MAY be mapped to the Router Address TLV
        described in Section 2.4.1 of RFC 3630, the TE Router ID
        described in Section 3 of RFC 6827, the Traffic Engineering
        Router ID TLV described in Section 4.3 of RFC 5305, the TE
        Router ID TLV described in Section 3.2.1 of RFC 6119, or the
        IPv6 TE Router ID TLV described in Section 4.1 of RFC 6119.

        The reachability of such a TE node MAY be achieved by a
        mechanism such as that described in Section 6.2 of RFC 6827.";
    reference
        "RFC 3630: Traffic Engineering (TE) Extensions to OSPF
        Version 2, Section 2.4.1
        RFC 5305: IS-IS Extensions for Traffic Engineering,
        Section 4.3
        RFC 6119: IPv6 Traffic Engineering in IS-IS, Section 3.2.1
        RFC 6827: Automatically Switched Optical Network (ASON)
```

```

        Routing for OSPFv2 Protocols, Section 3";
    }

    typedef te-oper-status {
        type te-common-status;
        description
            "Defines a type representing the operational status of
             a TE resource.";
    }

    typedef te-admin-status {
        type te-common-status;
        description
            "Defines a type representing the administrative status of
             a TE resource.";
    }

    typedef te-path-disjointness {
        type bits {
            bit node {
                position 0;
                description
                    "Node disjoint.";
            }
            bit link {
                position 1;
                description
                    "Link disjoint.";
            }
            bit srlg {
                position 2;
                description
                    "Shared Risk Link Group (SRLG) disjoint.";
            }
        }
        description
            "Type of the resource disjointness for a TE tunnel path.";
        reference
            "RFC 4872: RSVP-TE Extensions in Support of End-to-End
             Generalized Multi-Protocol Label Switching (GMPLS)
             Recovery";
    }

    typedef te-recovery-status {
        type enumeration {
            enum normal {
                description
                    "Both the recovery span and the working span are fully

```

```
        allocated and active, data traffic is being
        transported over (or selected from) the working
        span, and no trigger events are reported.";
    }
    enum recovery-started {
        description
            "The recovery action has been started but not completed.";
    }
    enum recovery-succeeded {
        description
            "The recovery action has succeeded.

            The working span has reported a failure/degrade condition,
            and the user traffic is being transported (or selected)
            on the recovery span.";
    }
    enum recovery-failed {
        description
            "The recovery action has failed.";
    }
    enum reversion-started {
        description
            "The reversion has started.";
    }
    enum reversion-succeeded {
        description
            "The reversion action has succeeded.";
    }
    enum reversion-failed {
        description
            "The reversion has failed.";
    }
    enum recovery-unavailable {
        description
            "The recovery is unavailable, as a result of either an
            operator's lockout command or a failure condition
            detected on the recovery span.";
    }
    enum recovery-admin {
        description
            "The operator has issued a command to switch the user
            traffic to the recovery span.";
    }
    enum wait-to-restore {
        description
            "The recovery domain is recovering from a failure/degrade
            condition on the working span that is being controlled by
            the Wait-to-Restore (WTR) timer.";
```



```
    }
  }
  description
    "Defines the status of a recovery action.";
  reference
    "RFC 6378: MPLS Transport Profile (MPLS-TP) Linear Protection
    RFC 4427: Recovery (Protection and Restoration) Terminology
    for Generalized Multi-Protocol Label Switching
    (GMPLS)";
}

typedef te-template-name {
  type string {
    pattern '/?([a-zA-Z0-9\-\_\.]+)(/[a-zA-Z0-9\-\_\.]+)*';
  }
  description
    "A type for the name of a TE node template or TE link
    template.";
}

typedef te-topology-event-type {
  type enumeration {
    enum add {
      value 0;
      description
        "A TE node or TE link has been added.";
    }
    enum remove {
      value 1;
      description
        "A TE node or TE link has been removed.";
    }
    enum update {
      value 2;
      description
        "A TE node or TE link has been updated.";
    }
  }
  description
    "TE event type for notifications.";
}

typedef te-topology-id {
  type union {
    type string {
      length "0";
      // empty string
    }
  }
}
```

```
    type string {
      pattern '([a-zA-Z0-9\-\_\.]+:)*'
        + '/?([a-zA-Z0-9\-\_\.]+)(/[a-zA-Z0-9\-\_\.]+)*';
    }
  }
  description
    "An identifier for a topology.

    It is optional to have one or more prefixes at the beginning,
    separated by colons.

    The prefixes can be 'network-types' as defined in the
    'ietf-network' module in RFC 8345, to help the user better
    understand the topology before further inquiry is made.";
  reference
    "RFC 8345: A YANG Data Model for Network Topologies";
}

typedef te-tp-id {
  type union {
    type uint32;
    // Unnumbered
    type inet:ip-address;
    // IPv4 or IPv6 address
  }
  description
    "An identifier for a TE link endpoint on a node.

    This attribute is mapped to a local or remote link identifier
    as defined in RFCs 3630 and 5305.";
  reference
    "RFC 3630: Traffic Engineering (TE) Extensions to OSPF
      Version 2
    RFC 5305: IS-IS Extensions for Traffic Engineering";
}

typedef path-type {
  type enumeration {
    enum primary-path {
      description
        "Indicates that the TE path is a primary path.";
    }
    enum secondary-path {
      description
        "Indicates that the TE path is a secondary path.";
    }
    enum primary-reverse-path {
      description
```

```
        "Indicates that the TE path is a primary reverse path.";
    }
    enum secondary-reverse-path {
        description
            "Indicates that the TE path is a secondary reverse path.";
    }
}
description
    "The type of TE path, indicating whether a path is a primary,
    or a reverse primary, or a secondary, or a reverse secondary
    path.";
}

/*
 * TE bandwidth groupings
 */

grouping te-bandwidth {
    description
        "This grouping defines the generic TE bandwidth.

        For some known data-plane technologies, specific modeling
        structures are specified.

        The string-encoded 'te-bandwidth' type is used for
        unspecified technologies.

        The modeling structure can be augmented later for other
        technologies.";
    container te-bandwidth {
        description
            "Container that specifies TE bandwidth.

            The choices can be augmented for specific data-plane
            technologies.";
        choice technology {
            default "generic";
            description
                "Data-plane technology type.";
            case generic {
                leaf generic {
                    type te-bandwidth;
                    description
                        "Bandwidth specified in a generic format.";
                }
            }
        }
    }
}
```

```
}

/*
 * TE label groupings
 */

grouping te-label {
  description
    "This grouping defines the generic TE label.

    The modeling structure can be augmented for each technology.

    For unspecified technologies, 'rt-types:generalized-label'
    is used.";
  container te-label {
    description
      "Container that specifies the TE label.

      The choices can be augmented for specific data-plane
      technologies.";
    choice technology {
      default "generic";
      description
        "Data-plane technology type.";
      case generic {
        leaf generic {
          type rt-types:generalized-label;
          description
            "TE label specified in a generic format.";
        }
      }
    }
    leaf direction {
      type te-label-direction;
      default "forward";
      description
        "Label direction.";
    }
  }
}

grouping te-topology-identifier {
  description
    "Augmentation for a TE topology.";
  container te-topology-identifier {
    description
      "TE topology identifier container.";
    leaf provider-id {
```

```
    type te-global-id;
    default "0";
    description
      "An identifier to uniquely identify a provider.
      If omitted, it assumes that the topology provider ID
      value = 0 (the default).";
  }
  leaf client-id {
    type te-global-id;
    default "0";
    description
      "An identifier to uniquely identify a client.
      If omitted, it assumes that the topology client ID
      value = 0 (the default).";
  }
  leaf topology-id {
    type te-topology-id;
    default "";
    description
      "When the datastore contains several topologies,
      'topology-id' distinguishes between them.

      If omitted, the default (empty) string for this leaf is
      assumed.";
  }
}

/*
 * TE performance metrics groupings
 */

grouping performance-metrics-one-way-delay-loss {
  description
    "Performance Metrics (PM) information in real time that can
    be applicable to links or connections.

    PM defined in this grouping are applicable to generic TE PM
    as well as packet TE PM.";
  reference
    "RFC 7471: OSPF Traffic Engineering (TE) Metric Extensions
    RFC 8570: IS-IS Traffic Engineering (TE) Metric Extensions
    RFC 7823: Performance-Based Path Selection for Explicitly
    Routed Label Switched Paths (LSPs) Using TE Metric
    Extensions";
  leaf one-way-delay {
    type uint32 {
      range "0..16777215";
    }
  }
}
```

```
    }
    units "microseconds";
    description
        "One-way delay or latency.";
    }
    leaf one-way-delay-normality {
        type te-types:performance-metrics-normality;
        description
            "One-way delay normality.";
    }
}

grouping performance-metrics-two-way-delay-loss {
    description
        "Performance Metrics (PM) information in real time that can be
        applicable to links or connections.

        PM defined in this grouping are applicable to generic TE PM
        as well as packet TE PM.";
    reference
        "RFC 7471: OSPF Traffic Engineering (TE) Metric Extensions
        RFC 8570: IS-IS Traffic Engineering (TE) Metric Extensions
        RFC 7823: Performance-Based Path Selection for Explicitly
        Routed Label Switched Paths (LSPs) Using TE Metric
        Extensions";
    leaf two-way-delay {
        type uint32 {
            range "0..16777215";
        }
        units "microseconds";
        description
            "Two-way delay or latency.";
    }
    leaf two-way-delay-normality {
        type te-types:performance-metrics-normality;
        description
            "Two-way delay normality.";
    }
}

grouping performance-metrics-one-way-bandwidth {
    description
        "Performance Metrics (PM) information in real time that can be
        applicable to links.

        PM defined in this grouping are applicable to generic TE PM
        as well as packet TE PM.";
    reference
```

```
"RFC 7471: OSPF Traffic Engineering (TE) Metric Extensions
RFC 8570: IS-IS Traffic Engineering (TE) Metric Extensions
RFC 7823: Performance-Based Path Selection for Explicitly
        Routed Label Switched Paths (LSPs) Using TE Metric
        Extensions";
leaf one-way-residual-bandwidth {
    type rt-types:bandwidth-ieee-float32;
    units "bytes per second";
    default "0x0p0";
    description
        "Residual bandwidth that subtracts tunnel reservations from
        Maximum Bandwidth (or link capacity) (RFC 3630) and
        provides an aggregated remainder across QoS classes.";
    reference
        "RFC 3630: Traffic Engineering (TE) Extensions to OSPF
        Version 2";
}
leaf one-way-residual-bandwidth-normality {
    type te-types:performance-metrics-normality;
    default "normal";
    description
        "Residual bandwidth normality.";
}
leaf one-way-available-bandwidth {
    type rt-types:bandwidth-ieee-float32;
    units "bytes per second";
    default "0x0p0";
    description
        "Available bandwidth that is defined to be residual
        bandwidth minus the measured bandwidth used for the
        actual forwarding of non-RSVP-TE LSP packets.

        For a bundled link, available bandwidth is defined to be
        the sum of the component link available bandwidths.";
}
leaf one-way-available-bandwidth-normality {
    type te-types:performance-metrics-normality;
    default "normal";
    description
        "Available bandwidth normality.";
}
leaf one-way-utilized-bandwidth {
    type rt-types:bandwidth-ieee-float32;
    units "bytes per second";
    default "0x0p0";
    description
        "Bandwidth utilization that represents the actual
        utilization of the link (i.e., as measured in the router).
```

```
        For a bundled link, bandwidth utilization is defined to
        be the sum of the component link bandwidth utilizations.";
    }
    leaf one-way-utilized-bandwidth-normality {
        type te-types:performance-metrics-normality;
        default "normal";
        description
            "Bandwidth utilization normality.";
    }
}

grouping one-way-performance-metrics {
    description
        "One-way Performance Metrics (PM) throttle grouping.";
    leaf one-way-delay {
        type uint32 {
            range "0..16777215";
        }
        units "microseconds";
        default "0";
        description
            "One-way delay or latency.";
    }
    leaf one-way-residual-bandwidth {
        type rt-types:bandwidth-ieee-float32;
        units "bytes per second";
        default "0x0p0";
        description
            "Residual bandwidth that subtracts tunnel reservations from
            Maximum Bandwidth (or link capacity) (RFC 3630) and
            provides an aggregated remainder across QoS classes.";
        reference
            "RFC 3630: Traffic Engineering (TE) Extensions to OSPF
            Version 2";
    }
    leaf one-way-available-bandwidth {
        type rt-types:bandwidth-ieee-float32;
        units "bytes per second";
        default "0x0p0";
        description
            "Available bandwidth that is defined to be residual
            bandwidth minus the measured bandwidth used for the
            actual forwarding of non-RSVP-TE LSP packets.

            For a bundled link, available bandwidth is defined to be
            the sum of the component link available bandwidths.";
    }
    leaf one-way-utilized-bandwidth {
```



```
    type rt-types:bandwidth-ieee-float32;
    units "bytes per second";
    default "0x0p0";
    description
      "Bandwidth utilization that represents the actual
       utilization of the link (i.e., as measured in the router).
       For a bundled link, bandwidth utilization is defined to
       be the sum of the component link bandwidth utilizations.";
  }
}

grouping two-way-performance-metrics {
  description
    "Two-way Performance Metrics (PM) throttle grouping.";
  leaf two-way-delay {
    type uint32 {
      range "0..16777215";
    }
    units "microseconds";
    default "0";
    description
      "Two-way delay or latency.";
  }
}

grouping performance-metrics-thresholds {
  description
    "Grouping for configurable thresholds for measured
     attributes.";
  uses one-way-performance-metrics;
  uses two-way-performance-metrics;
}

grouping performance-metrics-attributes {
  description
    "Contains Performance Metrics (PM) attributes.";
  container performance-metrics-one-way {
    description
      "One-way link performance information in real time.";
    reference
      "RFC 7471: OSPF Traffic Engineering (TE) Metric Extensions
       RFC 8570: IS-IS Traffic Engineering (TE) Metric Extensions
       RFC 7823: Performance-Based Path Selection for Explicitly
        Routed Label Switched Paths (LSPs) Using TE Metric
        Extensions";
    uses performance-metrics-one-way-delay-loss;
    uses performance-metrics-one-way-bandwidth;
  }
}
```

```
    container performance-metrics-two-way {
      description
        "Two-way link performance information in real time.";
      reference
        "RFC 6374: Packet Loss and Delay Measurement for MPLS
          Networks";
      uses performance-metrics-two-way-delay-loss;
    }
  }

  grouping performance-metrics-throttle-container {
    description
      "Controls Performance Metrics (PM) throttling.";
    container throttle {
      must 'suppression-interval >= measure-interval' {
        error-message "'suppression-interval' cannot be less than "
          + "'measure-interval'.";
        description
          "Constraint on 'suppression-interval' and
            'measure-interval'.";
      }
    }
    description
      "Link performance information in real time.";
    reference
      "RFC 7471: OSPF Traffic Engineering (TE) Metric Extensions
        RFC 8570: IS-IS Traffic Engineering (TE) Metric Extensions
        RFC 7823: Performance-Based Path Selection for Explicitly
          Routed Label Switched Paths (LSPs) Using TE Metric
          Extensions";
    leaf one-way-delay-offset {
      type uint32 {
        range "0..16777215";
      }
      units "microseconds";
      default "0";
      description
        "Offset value to be added to the measured delay value.";
    }
    leaf measure-interval {
      type uint32;
      units "seconds";
      default "30";
      description
        "Interval to measure the extended metric values.";
    }
    leaf advertisement-interval {
      type uint32;
      units "seconds";
    }
  }
}
```

```

        default "0";
        description
            "Interval to advertise the extended metric values.";
    }
    leaf suppression-interval {
        type uint32 {
            range "1..max";
        }
        units "seconds";
        default "120";
        description
            "Interval to suppress advertisement of the extended metric
            values.";
        reference
            "RFC 8570: IS-IS Traffic Engineering (TE) Metric
            Extensions, Section 6";
    }
    container threshold-out {
        description
            "If the measured parameter falls outside an upper bound
            for all but the minimum-delay metric (or a lower bound
            for the minimum-delay metric only) and the advertised
            value is not already outside that bound, an 'anomalous'
            announcement (anomalous bit set) will be triggered.";
        uses performance-metrics-thresholds;
    }
    container threshold-in {
        description
            "If the measured parameter falls inside an upper bound
            for all but the minimum-delay metric (or a lower bound
            for the minimum-delay metric only) and the advertised
            value is not already inside that bound, a 'normal'
            announcement (anomalous bit cleared) will be triggered.";
        uses performance-metrics-thresholds;
    }
    container threshold-accelerated-advertisement {
        description
            "When the difference between the last advertised value and
            the current measured value exceeds this threshold, an
            'anomalous' announcement (anomalous bit set) will be
            triggered.";
        uses performance-metrics-thresholds;
    }
}
}
/*
 * TE tunnel generic groupings

```

```
*/

grouping explicit-route-hop {
  description
    "The explicit route entry grouping.";
  choice type {
    description
      "The explicit route entry type.";
    case numbered-node-hop {
      container numbered-node-hop {
        must 'node-id-uri or node-id' {
          description
            "At least one node identifier needs to be present.";
        }
        description
          "Numbered node route hop.";
        reference
          "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels,
            Section 4.3, EXPLICIT_ROUTE in RSVP-TE
            RFC 3477: Signalling Unnumbered Links in Resource
            ReSerVation Protocol - Traffic Engineering
            (RSVP-TE)";
        leaf node-id-uri {
          type nw:node-id;
          description
            "The identifier of a node in the topology.";
        }
        leaf node-id {
          type te-node-id;
          description
            "The identifier of a node in the TE topology.";
        }
        leaf hop-type {
          type te-hop-type;
          default "strict";
          description
            "Strict or loose hop.";
        }
      }
    }
  }
  case numbered-link-hop {
    container numbered-link-hop {
      description
        "Numbered link explicit route hop.";
      reference
        "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels,
          Section 4.3, EXPLICIT_ROUTE in RSVP-TE
          RFC 3477: Signalling Unnumbered Links in Resource
```

```

        ReSerVation Protocol - Traffic Engineering
        (RSVP-TE)";
    leaf link-tp-id {
        type te-tp-id;
        mandatory true;
        description
            "TE Link Termination Point (LTP) identifier.";
    }
    leaf hop-type {
        type te-hop-type;
        default "strict";
        description
            "Strict or loose hop.";
    }
    leaf direction {
        type te-link-direction;
        default "outgoing";
        description
            "Link route object direction.";
    }
}
}
case unnumbered-link-hop {
    container unnumbered-link-hop {
        must '(link-tp-id-uri or link-tp-id) and '
            + '(node-id-uri or node-id)' {
            description
                "At least one node identifier and at least one Link
                Termination Point (LTP) identifier need to be
                present.";
        }
        description
            "Unnumbered link explicit route hop.";
        reference
            "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels,
            Section 4.3, EXPLICIT_ROUTE in RSVP-TE
            RFC 3477: Signalling Unnumbered Links in Resource
            ReSerVation Protocol - Traffic Engineering
            (RSVP-TE)";
    }
    leaf link-tp-id-uri {
        type nt:tp-id;
        description
            "Link Termination Point (LTP) identifier.";
    }
    leaf link-tp-id {
        type te-tp-id;
        description
            "TE LTP identifier.

```

```
        The combination of the TE link ID and the TE node ID
        is used to identify an unnumbered TE link.";
    }
    leaf node-id-uri {
        type nw:node-id;
        description
            "The identifier of a node in the topology.";
    }
    leaf node-id {
        type te-node-id;
        description
            "The identifier of a node in the TE topology.";
    }
    leaf hop-type {
        type te-hop-type;
        default "strict";
        description
            "Strict or loose hop.";
    }
    leaf direction {
        type te-link-direction;
        default "outgoing";
        description
            "Link route object direction.";
    }
}
}
case as-number {
    container as-number-hop {
        description
            "Autonomous System (AS) explicit route hop.";
        leaf as-number {
            type inet:as-number;
            mandatory true;
            description
                "The Autonomous System (AS) number.";
        }
        leaf hop-type {
            type te-hop-type;
            default "strict";
            description
                "Strict or loose hop.";
        }
    }
}
case label {
    description
        "The label explicit route hop type.";
```

```

        container label-hop {
            description
                "Label hop type.";
            uses te-label;
        }
    }
}

grouping explicit-route-hop-with-srlg {
    description
        "Augments the explicit route entry grouping with Shared Risk
        Link Group (SRLG) hop type.";
    uses explicit-route-hop {
        augment "type" {
            description
                "Augmentation for a generic explicit route for Shared
                Risk Link Group (SRLG) inclusion or exclusion.";
            case srlg {
                description
                    "An Shared Risk Link Group (SRLG) value to be
                    included or excluded.";
                container srlg {
                    description
                        "Shared Risk Link Group (SRLG) container.";
                    leaf srlg {
                        type uint32;
                        description
                            "Shared Risk Link Group (SRLG) value.";
                    }
                }
            }
        }
    }
}

grouping record-route-state {
    description
        "The Record Route grouping.";
    leaf index {
        type uint32;
        description
            "Record Route hop index.

            The index is used to identify an entry in the list.

            The order of entries is defined by the user without relying
            on key values.";
    }
}

```

```
}
choice type {
  description
    "The Record Route entry type.";
  case numbered-node-hop {
    description
      "Numbered node route hop.";
    container numbered-node-hop {
      must 'node-id-uri or node-id' {
        description
          "At least one node identifier need to be present.";
      }
      description
        "Numbered node route hop container.";
      leaf node-id-uri {
        type nw:node-id;
        description
          "The identifier of a node in the topology.";
      }
      leaf node-id {
        type te-node-id;
        description
          "The identifier of a node in the TE topology.";
      }
      leaf-list flags {
        type path-attribute-flags;
        description
          "Path attributes flags.";
        reference
          "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels
           RFC 4090: Fast Reroute Extensions to RSVP-TE for LSP
            Tunnels
           RFC 4561: Definition of a Record Route Object (RRO)
            Node-Id Sub-Object";
      }
    }
  }
}
case numbered-link-hop {
  description
    "Numbered link route hop.";
  container numbered-link-hop {
    description
      "Numbered link route hop container.";
    leaf link-tp-id {
      type te-tp-id;
      mandatory true;
      description
        "Numbered TE LTP identifier.";
    }
  }
}
```



```
    }
    leaf-list flags {
      type path-attribute-flags;
      description
        "Path attributes flags.";
      reference
        "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels
        RFC 4090: Fast Reroute Extensions to RSVP-TE for LSP
        Tunnels
        RFC 4561: Definition of a Record Route Object (RRO)
        Node-Id Sub-Object";
    }
  }
}
case unnumbered-link-hop {
  description
    "Unnumbered link route hop.";
  container unnumbered-link-hop {
    must '(link-tp-id-uri or link-tp-id) and '
      + '(node-id-uri or node-id)' {
      description
        "At least one node identifier and at least one Link
        Termination Point (LTP) identifier need to be
        present.";
    }
  }
  description
    "Unnumbered link Record Route hop.";
  reference
    "RFC 3477: Signalling Unnumbered Links in Resource
    ReSerVation Protocol - Traffic Engineering
    (RSVP-TE)";
  leaf link-tp-id-uri {
    type nt:tp-id;
    description
      "Link Termination Point (LTP) identifier.";
  }
  leaf link-tp-id {
    type te-tp-id;
    description
      "TE LTP identifier.

      The combination of the TE link ID and the TE node ID
      is used to identify an unnumbered TE link.";
  }
  leaf node-id-uri {
    type nw:node-id;
    description
      "The identifier of a node in the topology.";
```

```

    }
    leaf node-id {
      type te-node-id;
      description
        "The identifier of a node in the TE topology.";
    }
    leaf-list flags {
      type path-attribute-flags;
      description
        "Path attributes flags.";
      reference
        "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels
         RFC 4090: Fast Reroute Extensions to RSVP-TE for LSP
         Tunnels
         RFC 4561: Definition of a Record Route Object (RRO)
         Node-Id Sub-Object";
    }
  }
}
case label {
  description
    "The label Record Route entry types.";
  container label-hop {
    description
      "Label route hop type.";
    uses te-label;
    leaf-list flags {
      type path-attribute-flags;
      description
        "Path attributes flags.";
      reference
        "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels
         RFC 4090: Fast Reroute Extensions to RSVP-TE for LSP
         Tunnels
         RFC 4561: Definition of a Record Route Object (RRO)
         Node-Id Sub-Object";
    }
  }
}
}
}
}

grouping label-restriction-info {
  description
    "Label set item information.";
  leaf restriction {
    type enumeration {
      enum inclusive {

```

```
        description
            "The label or label range is inclusive.";
    }
    enum exclusive {
        description
            "The label or label range is exclusive.";
    }
}
default "inclusive";
description
    "Indicates whether the list item is inclusive or exclusive.";
}
leaf index {
    type uint32;
    description
        "The index of the label restriction list entry.";
}
container label-start {
    must "(not(..../label-end/te-label/direction) and"
        + " not(te-label/direction))"
        + " or "
        + "(../label-end/te-label/direction = te-label/direction)"
        + " or "
        + "(not(te-label/direction) and"
        + " (../label-end/te-label/direction = 'forward'))"
        + " or "
        + "(not(..../label-end/te-label/direction) and"
        + " (te-label/direction = 'forward'))" {
        error-message "'label-start' and 'label-end' must have the "
            + "same direction.";
    }
    description
        "This is the starting label if a label range is specified.
        This is the label value if a single label is specified,
        in which case the 'label-end' attribute is not set.";
    uses te-label;
}
container label-end {
    must "(not(..../label-start/te-label/direction) and"
        + " not(te-label/direction))"
        + " or "
        + "(../label-start/te-label/direction = "
        + "te-label/direction)"
        + " or "
        + "(not(te-label/direction) and"
        + " (../label-start/te-label/direction = 'forward'))"
        + " or "
        + "(not(..../label-start/te-label/direction) and"
```

```

    + " (te-label/direction = 'forward'))" {
      error-message "'label-start' and 'label-end' must have the "
        + "same direction.";
    }
  }
  description
    "This is the ending label if a label range is specified.
    This attribute is not set if a single label is specified.";
  uses te-label;
}
container label-step {
  description
    "The step increment between labels in the label range.

    The label start/end values MUST be consistent with the sign
    of label step.

    For example:
      'label-start' < 'label-end' enforces 'label-step' > 0
      'label-start' > 'label-end' enforces 'label-step' < 0.";
  choice technology {
    default "generic";
    description
      "Data-plane technology type.";
    case generic {
      leaf generic {
        type int32;
        default "1";
        description
          "Label range step.";
      }
    }
  }
}
leaf range-bitmap {
  type yang:hex-string;
  description
    "When there are gaps between 'label-start' and 'label-end',
    this attribute is used to specify the positions
    of the used labels.

    This is represented in big endian as 'hex-string'.

    In case the restriction is 'inclusive', the bit-position is
    set if the corresponding mapped label is available.
    In this case, if the range-bitmap is not present, all the
    labels in the range are available.

    In case the restriction is 'exclusive', the bit-position is

```

set if the corresponding mapped label is not available.
In this case, if the range-bitmap is not present, all the labels in the range are not available.

The most significant byte in the hex-string is the farthest to the left in the byte sequence.

Leading zero bytes in the configured value may be omitted for brevity.

Each bit position in the 'range-bitmap' 'hex-string' maps to a label in the range derived from 'label-start'.

For example, assuming that 'label-start' = 16000 and 'range-bitmap' = 0x01000001, then:

- bit position (0) is set, and the corresponding mapped label from the range is $16000 + (0 * 'label-step')$ or 16000 for default 'label-step' = 1.
- bit position (24) is set, and the corresponding mapped label from the range is $16000 + (24 * 'label-step')$ or 16024 for default 'label-step' = 1.";

```

    }
  }
  grouping label-set-info {
    description
      "Grouping for the list of label restrictions specifying what
       labels may or may not be used.";
    container label-restrictions {
      description
        "The label restrictions container.";
      list label-restriction {
        key "index";
        description
          "The absence of the label restrictions container implies
           that all labels are acceptable; otherwise, only restricted
           labels are available.";
        reference
          "RFC 7579: General Network Element Constraint Encoding
           for GMPLS-Controlled Networks";
        uses label-restriction-info;
      }
    }
  }
}

```

```

grouping optimization-metric-entry {
  description
    "Optimization metrics configuration grouping.";
}

```

```
leaf metric-type {
  type identityref {
    base path-metric-optimization-type;
  }
  description
    "Identifies the 'metric-type' that the path computation
    process uses for optimization.";
}
leaf weight {
  type uint8;
  default "1";
  description
    "TE path metric normalization weight.";
}
container explicit-route-exclude-objects {
  when "../metric-type = "
    + "'te-types:path-metric-optimize-excludes'";
  description
    "Container for the 'exclude route' object list.";
  uses path-route-exclude-objects;
}
container explicit-route-include-objects {
  when "../metric-type = "
    + "'te-types:path-metric-optimize-includes'";
  description
    "Container for the 'include route' object list.";
  uses path-route-include-objects;
}
}

grouping common-constraints {
  description
    "Common constraints grouping that can be set on
    a constraint set or directly on the tunnel.";
  uses te-bandwidth {
    description
      "A requested bandwidth to use for path computation.";
  }
  leaf link-protection {
    type identityref {
      base link-protection-type;
    }
    default "te-types:link-protection-unprotected";
    description
      "Link protection type required for the links included
      in the computed path.";
    reference
      "RFC 4202: Routing Extensions in Support of
```

```

        Generalized Multi-Protocol Label Switching
        (GMPLS)";
    }
    leaf setup-priority {
        type uint8 {
            range "0..7";
        }
        default "7";
        description
            "TE LSP requested setup priority.";
        reference
            "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels";
    }
    leaf hold-priority {
        type uint8 {
            range "0..7";
        }
        default "7";
        description
            "TE LSP requested hold priority.";
        reference
            "RFC 3209: RSVP-TE: Extensions to RSVP for LSP Tunnels";
    }
    leaf signaling-type {
        type identityref {
            base path-signaling-type;
        }
        default "te-types:path-setup-rsvp";
        description
            "TE tunnel path signaling type.";
    }
}

grouping tunnel-constraints {
    description
        "Tunnel constraints grouping that can be set on
        a constraint set or directly on the tunnel.";
    leaf network-id {
        type nw:network-id;
        description
            "The network topology identifier.";
    }
    uses te-topology-identifier;
    uses common-constraints;
}

grouping path-constraints-route-objects {
    description
```

```

    "List of route entries to be included or excluded when
    performing the path computation.";
  container explicit-route-objects {
    description
      "Container for the explicit route object lists.";
    list route-object-exclude-always {
      key "index";
      ordered-by user;
      description
        "List of route objects to always exclude from the path
        computation.";
      leaf index {
        type uint32;
        description
          "Explicit Route Object index.

          The index is used to identify an entry in the list.

          The order of entries is defined by the user without
          relying on key values.";
      }
      uses explicit-route-hop {
        refine "type/numbered-node-hop/numbered-node-hop"
          + "/hop-type" {
          must '. = "strict"' {
            description
              "Loose hops can only be used for 'include' route
              objects.";
            reference
              "RFC 4874: Exclude Routes - Extension to Resource
              ReserVation Protocol-Traffic Engineering
              (RSVP-TE), Section 3.1";
          }
        }
      }
    }
  }
  list route-object-include-exclude {
    key "index";
    ordered-by user;
    description
      "List of route objects to include or exclude in the path
      computation.";
    leaf explicit-route-usage {
      type identityref {
        base route-usage-type;
      }
      default "te-types:route-include-object";
      description

```



```

    "Indicates whether to include or exclude the
    route object.

    The default is to include it.";
  }
  leaf index {
    type uint32;
    description
      "Route object include-exclude index.

      The index is used to identify an entry in the list.

      The order of entries is defined by the user without
      relying on key values.";
  }
  uses explicit-route-hop-with-srlg {
    refine "type/numbered-node-hop/numbered-node-hop"
      + "/hop-type" {
      must '(. = "strict") or '
        + 'derived-from-or-self ../../explicit-route-usage,'
        + '"te-types:route-include-object")' {
      description
        "Loose hops can only be used for 'include' route
        objects.";
      reference
        "RFC 4874: Exclude Routes - Extension to Resource
        ReserVation Protocol-Traffic Engineering
        (RSVP-TE), Section 3.1";
      }
    }
  }
}

grouping path-route-include-objects {
  description
    "List of route objects to be included when performing
    the path computation.";
  list route-object-include-object {
    key "index";
    ordered-by user;
    description
      "List of Explicit Route Objects to be included in the
      path computation.";
    leaf index {
      type uint32;
      description

```

```
    "Route object entry index.

    The index is used to identify an entry in the list.

    The order of entries is defined by the user without
    relying on key values.";
  }
  uses explicit-route-hop;
}

grouping path-route-exclude-objects {
  description
    "List of route objects to be excluded when performing
    the path computation.";
  list route-object-exclude-object {
    key "index";
    ordered-by user;
    description
      "List of Explicit Route Objects to be excluded in the
      path computation.";
    leaf index {
      type uint32;
      description
        "Route object entry index.

        The index is used to identify an entry in the list.

        The order of entries is defined by the user without
        relying on key values.";
    }
    uses explicit-route-hop-with-srlg;
  }
}

grouping generic-path-metric-bounds {
  description
    "TE path metric bounds grouping.";
  container path-metric-bounds {
    description
      "Top-level container for the list of path metric bounds.";
    list path-metric-bound {
      key "metric-type";
      description
        "List of path metric bounds, which can apply to link and
        path metrics.

        TE paths which have at least one path metric which
```

exceeds the specified bounds MUST NOT be selected.

TE paths that traverse TE links which have at least one link metric which exceeds the specified bounds MUST NOT be selected.";

```

leaf metric-type {
  type identityref {
    base link-path-metric-type;
  }
  description
    "Identifies an entry in the list of 'metric-type' items
    bound for the TE path.";
}
leaf upper-bound {
  type uint64;
  default "0";
  description
    "Upper bound on the specified 'metric-type'."

    A zero indicates an unbounded upper limit for the
    specified 'metric-type'.

    The unit of is interpreted in the context of the
    'metric-type' identity.";
}
}
}
}

```

```

grouping generic-path-optimization {
  description
    "TE generic path optimization grouping.";
  container optimizations {
    description
      "The objective function container that includes
      attributes to impose when computing a TE path.";
    choice algorithm {
      description
        "Optimizations algorithm.";
      case metric {
        if-feature "path-optimization-metric";
        /* Optimize by metric */
        list optimization-metric {
          key "metric-type";
          description
            "TE path metric type.";
          uses optimization-metric-entry;
        }
      }
    }
  }
}

```

```

/* Tiebreakers */
container tiebreakers {
  status deprecated;
  description
    "Container for the list of tiebreakers.

    This container has been deprecated by the tiebreaker
    leaf.";
  list tiebreaker {
    key "tiebreaker-type";
    status deprecated;
    description
      "The list of tiebreaker criteria to apply on an
      equally favored set of paths, in order to pick
      the best.";
    leaf tiebreaker-type {
      type identityref {
        base path-metric-type;
      }
      status deprecated;
      description
        "Identifies an entry in the list of tiebreakers.";
    }
  }
}

case objective-function {
  if-feature "path-optimization-objective-function";
  /* Objective functions */
  container objective-function {
    description
      "The objective function container that includes
      attributes to impose when computing a TE path.";
    leaf objective-function-type {
      type identityref {
        base objective-function-type;
      }
      default "te-types:of-minimize-cost-path";
      description
        "Objective function entry.";
    }
  }
}

leaf tiebreaker {
  type identityref {
    base path-tiebreaker-type;
  }
}

```

```
    }
    default "te-types:path-tiebreaker-random";
    description
      "The tiebreaker criteria to apply on an equally favored set
       of paths, in order to pick the best.";
  }
}

grouping generic-path-affinities {
  description
    "Path affinities grouping.";
  container path-affinities-values {
    description
      "Path affinities represented as values.";
    list path-affinities-value {
      key "usage";
      description
        "List of named affinity constraints.";
      leaf usage {
        type identityref {
          base resource-affinities-type;
        }
        description
          "Identifies an entry in the list of value affinity
           constraints.";
      }
      leaf value {
        type admin-groups;
        default "";
        description
          "The affinity value.

           The default is empty.";
      }
    }
  }
}

container path-affinity-names {
  description
    "Path affinities represented as names.";
  list path-affinity-name {
    key "usage";
    description
      "List of named affinity constraints.";
    leaf usage {
      type identityref {
        base resource-affinities-type;
      }
    }
    description

```

```
        "Identifies an entry in the list of named affinity
        constraints.";
    }
    list affinity-name {
        key "name";
        description
            "List of named affinities.";
        leaf name {
            type string;
            description
                "Identifies a named affinity entry.";
        }
    }
}

grouping generic-path-srlgs {
    description
        "Path Shared Risk Link Group (SRLG) grouping.";
    container path-srlgs-lists {
        description
            "Path Shared Risk Link Group (SRLG) properties container.";
        list path-srlgs-list {
            key "usage";
            description
                "List of Shared Risk Link Group (SRLG) values to be
                included or excluded.";
            leaf usage {
                type identityref {
                    base route-usage-type;
                }
                description
                    "Identifies an entry in a list of Shared Risk Link Groups
                    (SRLGs) to either include or exclude.";
            }
            leaf-list values {
                type srlg;
                description
                    "List of Shared Risk Link Group (SRLG) values.";
            }
        }
    }
}
container path-srlgs-names {
    description
        "Container for the list of named Shared Risk Link Groups
        (SRLGs).";
    list path-srlgs-name {
```

```
    key "usage";
    description
      "List of named Shared Risk Link Groups (SRLGs) to be
       included or excluded.";
    leaf usage {
      type identityref {
        base route-usage-type;
      }
      description
        "Identifies an entry in a list of named Shared Risk Link
         Groups (SRLGs) to either include or exclude.";
    }
    leaf-list names {
      type string;
      description
        "List of named Shared Risk Link Groups (SRLGs).";
    }
  }
}

grouping generic-path-disjointness {
  description
    "Path disjointness grouping.";
  leaf disjointness {
    type te-path-disjointness;
    description
      "The type of resource disjointness.
       When configured for a primary path, the disjointness level
       applies to all secondary LSPs.

       When configured for a secondary path, the disjointness
       level overrides the level configured for the primary path.";
  }
}

grouping common-path-constraints-attributes {
  description
    "Common path constraints configuration grouping.";
  uses common-constraints;
  uses generic-path-metric-bounds;
  uses generic-path-affinities;
  uses generic-path-srlgs;
}

grouping generic-path-constraints {
  description
    "Global named path constraints configuration grouping.";
```

```
    container path-constraints {
      description
        "TE named path constraints container.";
      uses common-path-constraints-attributes;
      uses generic-path-disjointness;
    }
  }

  grouping generic-path-properties {
    description
      "TE generic path properties grouping.";
    container path-properties {
      config false;
      description
        "The TE path properties.";
      list path-metric {
        key "metric-type";
        description
          "TE path metric type.";
        leaf metric-type {
          type identityref {
            base path-metric-type;
          }
          description
            "TE path metric type.";
        }
        leaf accumulative-value {
          type uint64;
          description
            "TE path metric accumulative value.";
        }
      }
    }
    uses generic-path-affinities;
    uses generic-path-srlgs;
    container path-route-objects {
      description
        "Container for the list of route objects either returned by
        the computation engine or actually used by an LSP.";
      list path-route-object {
        key "index";
        ordered-by user;
        description
          "List of route objects either returned by the computation
          engine or actually used by an LSP.";
        leaf index {
          type uint32;
          description
            "Route object entry index."
        }
      }
    }
  }
}
```


The index is used to identify an entry in the list.

The order of entries is defined by the user without relying on key values.";

```
    }
    uses explicit-route-hop;
  }
}
}

grouping encoding-and-switching-type {
  description
    "Common grouping to define the LSP encoding and
    switching types";
  leaf encoding {
    type identityref {
      base te-types:lsp-encoding-types;
    }
    description
      "LSP encoding type.";
    reference
      "RFC 3945: Generalized Multi-Protocol Label Switching (GMPLS)
      Architecture";
  }
  leaf switching-type {
    type identityref {
      base te-types:switching-capabilities;
    }
    description
      "LSP switching type.";
    reference
      "RFC 3945: Generalized Multi-Protocol Label Switching (GMPLS)
      Architecture";
  }
}

grouping te-generic-node-id {
  description
    "A reusable grouping for a TE generic node identifier.";
  leaf id {
    type union {
      type te-node-id;
      type inet:ip-address;
      type nw:node-id;
    }
    description
      "The identifier of the node.
```

It can be represented as IP address or dotted quad address or as an URI.

The type data node disambiguates the union type.";

```

}
leaf type {
  type enumeration {
    enum ip {
      description
        "IP address representation of the node identifier.";
    }
    enum te-id {
      description
        "TE identifier of the node";
    }
    enum node-id {
      description
        "URI representation of the node identifier.";
    }
  }
  description
    "Type of node identifier representation.";
}
}
}
<CODE ENDS>

```

Figure 1: TE Types YANG module

5. Packet TE Types YANG Module

The "ietf-te-packet-types" module imports from the "ietf-te-types" module defined in Section 4 of this document.

```

<CODE BEGINS> file "ietf-te-packet-types@2025-12-19.yang"
module ietf-te-packet-types {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-te-packet-types";
  prefix te-packet-types;

  import ietf-yang-types {
    prefix yang;
    reference
      "RFC 6991: Common YANG Data Types";
  }
  import ietf-te-types {
    prefix te-types;
    reference

```

```
"RFC XXXX: Common YANG Data Types for Traffic Engineering";
}

// RFC Editor: Please replace XXXX above with the RFC number
// assigned to this document.
// Please remove this note.

organization
  "IETF Traffic Engineering Architecture and Signaling (TEAS)
  Working Group";
contact
  "WG Web:    <https://datatracker.ietf.org/wg/teas/>
  WG List:    <mailto:teas@ietf.org>

  Editor:     Tarek Saad
               <mailto:tsaad.net@gmail.com>

  Editor:     Rakesh Gandhi
               <mailto:rgandhi@cisco.com>

  Editor:     Vishnu Pavan Beeram
               <mailto:vbeeram@juniper.net>

  Editor:     Xufeng Liu
               <mailto:xufeng.liu.ietf@gmail.com>

  Editor:     Igor Bryskin
               <mailto:i_bryskin@yahoo.com>";
description
  "This YANG module contains a collection of generally useful YANG
  data type definitions specific to Packet Traffic Engineering
  (TE).

  The model conforms to the Network Management Datastore
  Architecture (NMDA).

  The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL
  NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED',
  'MAY', and 'OPTIONAL' in this document are to be interpreted as
  described in BCP 14 (RFC 2119) (RFC 8174) when, and only when,
  they appear in all capitals, as shown here.

  Copyright (c) 2025 IETF Trust and the persons identified as
  authors of the code. All rights reserved.

  Redistribution and use in source and binary forms, with or
  without modification, is permitted pursuant to, and subject to
  the license terms contained in, the Revised BSD License set
```

forth in Section 4.c of the IETF Trust's Legal Provisions
Relating to IETF Documents
(<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX
(<https://www.rfc-editor.org/info/rfcXXXX>); see the RFC itself
for full legal notices.";

// RFC Editor: Please replace XXXX above with the RFC number
// assigned to this document.
// Please remove this note.

```
revision 2025-12-19 {  
  description  
    "This revision adds the following new identities:  
    - bandwidth-profile-type;  
    - link-metric-delay-variation;  
    - link-metric-loss;  
    - path-metric-delay-variation;  
    - path-metric-loss.  
  
    This revision adds the following new groupings:  
    - bandwidth-profile-parameters;  
    - te-packet-path-bandwidth;  
    - te-packet-link-bandwidth.  
  
    This revision provides also few editorial changes.";  
  reference  
    "RFC XXXX: Common YANG Data Types for Traffic Engineering";  
}
```

// RFC Editor: Please replace the revision date above with the
// module publication date in the format is (year-month-day).
// Please replace XXXX above with the RFC number assigned to
// this document.
// Please remove this note.

```
revision 2020-06-10 {  
  description  
    "Latest revision of TE MPLS types.";  
  reference  
    "RFC 8776: Common YANG Data Types for Traffic Engineering";  
}  
  
/*  
 * Identities  
 */
```

```
identity bandwidth-profile-type {
  description
    "Bandwidth Profile Types";
}

identity mef-10 {
  base bandwidth-profile-type;
  description
    "MEF 10 Bandwidth Profile";
  reference
    "MEF 10.3: Ethernet Services Attributes Phase 3";
}

identity rfc-2697 {
  base bandwidth-profile-type;
  description
    "RFC 2697 Bandwidth Profile";
  reference
    "RFC 2697: A Single Rate Three Color Marker";
}

identity rfc-2698 {
  base bandwidth-profile-type;
  description
    "RFC 2698 Bandwidth Profile";
  reference
    "RFC 2698: A Two Rate Three Color Marker";
}

// Derived identities from te-types:link-metric-type

identity link-metric-delay-variation {
  base te-types:link-metric-type;
  description
    "The Unidirectional Delay Variation Metric,
     measured in units of microseconds.";
  reference
    "RFC 7471: OSPF Traffic Engineering (TE) Metric Extensions,
     Section 4.3
     RFC 8570: IS-IS Traffic Engineering (TE) Metric Extensions,
     Section 4.3";
}

identity link-metric-loss {
  base te-types:link-metric-type;
  description
    "The Unidirectional Link Loss Metric,
     measured in units of 0.000003%.";
```

```
    reference
      "RFC 7471: OSPF Traffic Engineering (TE) Metric Extensions,
       Section 4.4
       RFC 8570: IS-IS Traffic Engineering (TE) Metric Extensions,
       Section 4.4";
  }

// Derived identities from te-types:path-metric-type

identity path-metric-delay-variation {
  base te-types:path-metric-type;
  description
    "The Path Delay Variation Metric,
     measured in units of microseconds.";
  reference
    "RFC 8233: Extensions to the Path Computation Element
     Communication Protocol (PCEP) to Compute
     Service-Aware Label Switched Paths (LSPs),
     Section 3.1.2";
}

identity path-metric-loss {
  base te-types:path-metric-type;
  description
    "The Path Loss Metric, measured in units of 0.000003%.";
  reference
    "RFC 8233: Extensions to the Path Computation Element
     Communication Protocol (PCEP) to Compute
     Service-Aware Label Switched Paths (LSPs),
     Section 3.1.3";
}

identity backup-protection-type {
  description
    "Base identity for the backup protection type.";
}

identity backup-protection-link {
  base backup-protection-type;
  description
    "Backup provides link protection only.";
}

identity backup-protection-node-link {
  base backup-protection-type;
  description
    "Backup offers node (preferred) or link protection.";
}
```

```
identity bc-model-type {
  description
    "Base identity for the Diffserv-TE Bandwidth Constraints
    Model type.";
  reference
    "RFC 4124: Protocol Extensions for Support of Diffserv-aware
    MPLS Traffic Engineering";
}

identity bc-model-rdm {
  base bc-model-type;
  description
    "Russian Dolls Bandwidth Constraints Model type.";
  reference
    "RFC 4127: Russian Dolls Bandwidth Constraints Model for
    Diffserv-aware MPLS Traffic Engineering";
}

identity bc-model-mam {
  base bc-model-type;
  description
    "Maximum Allocation Bandwidth Constraints Model type.";
  reference
    "RFC 4125: Maximum Allocation Bandwidth Constraints Model for
    Diffserv-aware MPLS Traffic Engineering";
}

identity bc-model-mar {
  base bc-model-type;
  description
    "Maximum Allocation with Reservation Bandwidth Constraints
    Model type.";
  reference
    "RFC 4126: Max Allocation with Reservation Bandwidth
    Constraints Model for Diffserv-aware MPLS Traffic
    Engineering & Performance Comparisons";
}

/*
 * Typedefs
 */

typedef te-bandwidth-requested-type {
  type enumeration {
    enum specified-value {
      description
        "Bandwidth value is explicitly specified.";
    }
  }
}
```

```
    enum specified-profile {
        description
            "Bandwidth profile is explicitly specified.";
    }
    enum auto {
        description
            "Bandwidth is automatically computed.";
    }
}
description
    "Enumerated type for specifying whether bandwidth is
    explicitly specified or automatically computed.";
}

typedef te-class-type {
    type uint8;
    description
        "Diffserv-TE Class-Type.
        Defines a set of Traffic Trunks crossing a link that is
        governed by a specific set of bandwidth constraints.

        Class-Type is used for the purposes of link bandwidth
        allocation, constraint-based routing, and admission control.";
    reference
        "RFC 4124: Protocol Extensions for Support of Diffserv-aware
        MPLS Traffic Engineering";
}

typedef bc-type {
    type uint8 {
        range "0..7";
    }
    description
        "Diffserv-TE bandwidth constraints as defined in RFC 4124.";
    reference
        "RFC 4124: Protocol Extensions for Support of Diffserv-aware
        MPLS Traffic Engineering";
}

typedef bandwidth-kbps {
    type uint64;
    units "kilobits per second";
    description
        "Bandwidth values, expressed in kilobits per second.";
}

typedef bandwidth-mbps {
    type uint64;
```



```
    units "megabits per second";
    description
        "Bandwidth values, expressed in megabits per second.";
}

typedef bandwidth-gbps {
    type uint64;
    units "gigabits per second";
    description
        "Bandwidth values, expressed in gigabits per second.";
}

/*
 * Groupings
 */

grouping performance-metrics-attributes-packet {
    description
        "Contains Performance Metrics (PM) information.";
    reference
        "RFC 7471: OSPF Traffic Engineering (TE) Metric Extensions
        RFC 8570: IS-IS Traffic Engineering (TE) Metric Extensions
        RFC 7823: Performance-Based Path Selection for Explicitly
        Routed Label Switched Paths (LSPs) Using TE Metric
        Extensions";
    uses te-types:performance-metrics-attributes {
        augment "performance-metrics-one-way" {
            description
                "Performance Metrics (PM) one-way packet-specific
                augmentation for a generic PM grouping.";
            leaf one-way-min-delay {
                type uint32 {
                    range "0..16777215";
                }
                units "microseconds";
                description
                    "One-way minimum delay or latency.";
            }
            leaf one-way-min-delay-normality {
                type te-types:performance-metrics-normality;
                default "normal";
                description
                    "One-way minimum delay or latency normality.";
            }
            leaf one-way-max-delay {
                type uint32 {
                    range "0..16777215";
                }
            }
        }
    }
}
```

```
    units "microseconds";
    description
        "One-way maximum delay or latency.";
}
leaf one-way-max-delay-normality {
    type te-types:performance-metrics-normality;
    default "normal";
    description
        "One-way maximum delay or latency normality.";
}
leaf one-way-delay-variation {
    type uint32 {
        range "0..16777215";
    }
    units "microseconds";
    description
        "One-way delay variation.";
    reference
        "RFC 5481: Packet Delay Variation Applicability
        Statement, Section 4.2";
}
leaf one-way-delay-variation-normality {
    type te-types:performance-metrics-normality;
    default "normal";
    description
        "One-way delay variation normality.";
    reference
        "RFC 7471: OSPF Traffic Engineering (TE) Metric
        Extensions
        RFC 8570: IS-IS Traffic Engineering (TE) Metric
        Extensions
        RFC 7823: Performance-Based Path Selection for
        Explicitly Routed Label Switched Paths (LSPs)
        Using TE Metric Extensions";
}
leaf one-way-packet-loss {
    type decimal64 {
        fraction-digits 6;
        range "0..50.331642";
    }
    units "percent";
    description
        "One-way packet loss as a percentage of the total traffic
        sent over a configurable interval.

        The finest precision is 0.000003%.";
    reference
        "RFC 8570: IS-IS Traffic Engineering (TE) Metric
```

```
        Extensions, Section 4.4";
    }
    leaf one-way-packet-loss-normality {
        type te-types:performance-metrics-normality;
        default "normal";
        description
            "Packet loss normality.";
        reference
            "RFC 7471: OSPF Traffic Engineering (TE) Metric
              Extensions
             RFC 8570: IS-IS Traffic Engineering (TE) Metric
              Extensions
             RFC 7823: Performance-Based Path Selection for
              Explicitly Routed Label Switched Paths (LSPs)
              Using TE Metric Extensions";
    }
}
augment "performance-metrics-two-way" {
    description
        "Performance Metrics (PM) two-way packet-specific
         augmentation for a generic PM grouping.";
    reference
        "RFC 7471: OSPF Traffic Engineering (TE) Metric Extensions
         RFC 8570: IS-IS Traffic Engineering (TE) Metric Extensions
         RFC 7823: Performance-Based Path Selection for Explicitly
           Routed Label Switched Paths (LSPs) Using TE
           Metric Extensions";
    leaf two-way-min-delay {
        type uint32 {
            range "0..16777215";
        }
        units "microseconds";
        default "0";
        description
            "Two-way minimum delay or latency.";
    }
    leaf two-way-min-delay-normality {
        type te-types:performance-metrics-normality;
        default "normal";
        description
            "Two-way minimum delay or latency normality.";
        reference
            "RFC 7471: OSPF Traffic Engineering (TE) Metric
              Extensions
             RFC 8570: IS-IS Traffic Engineering (TE) Metric
              Extensions
             RFC 7823: Performance-Based Path Selection for
              Explicitly Routed Label Switched Paths (LSPs)";
    }
}
```

```
        Using TE Metric Extensions";
    }
    leaf two-way-max-delay {
        type uint32 {
            range "0..16777215";
        }
        units "microseconds";
        default "0";
        description
            "Two-way maximum delay or latency.";
    }
    leaf two-way-max-delay-normality {
        type te-types:performance-metrics-normality;
        default "normal";
        description
            "Two-way maximum delay or latency normality.";
        reference
            "RFC 7471: OSPF Traffic Engineering (TE) Metric
              Extensions
             RFC 8570: IS-IS Traffic Engineering (TE) Metric
              Extensions
             RFC 7823: Performance-Based Path Selection for
              Explicitly Routed Label Switched Paths (LSPs)
              Using TE Metric Extensions";
    }
    leaf two-way-delay-variation {
        type uint32 {
            range "0..16777215";
        }
        units "microseconds";
        default "0";
        description
            "Two-way delay variation.";
        reference
            "RFC 5481: Packet Delay Variation Applicability
              Statement, Section 4.2";
    }
    leaf two-way-delay-variation-normality {
        type te-types:performance-metrics-normality;
        default "normal";
        description
            "Two-way delay variation normality.";
        reference
            "RFC 7471: OSPF Traffic Engineering (TE) Metric
              Extensions
             RFC 8570: IS-IS Traffic Engineering (TE) Metric
              Extensions
             RFC 7823: Performance-Based Path Selection for
```

```
        Explicitly Routed Label Switched Paths (LSPs)
        Using TE Metric Extensions";
    }
    leaf two-way-packet-loss {
        type decimal64 {
            fraction-digits 6;
            range "0..50.331642";
        }
        units "percent";
        default "0";
        description
            "Two-way packet loss as a percentage of the total traffic
            sent over a configurable interval.

            The finest precision is 0.000003%.";
    }
    leaf two-way-packet-loss-normality {
        type te-types:performance-metrics-normality;
        default "normal";
        description
            "Two-way packet loss normality.";
    }
}
}
}

grouping one-way-performance-metrics-packet {
    description
        "One-way packet Performance Metrics (PM) throttle grouping.";
    leaf one-way-min-delay {
        type uint32 {
            range "0..16777215";
        }
        units "microseconds";
        default "0";
        description
            "One-way minimum delay or latency.";
    }
    leaf one-way-max-delay {
        type uint32 {
            range "0..16777215";
        }
        units "microseconds";
        default "0";
        description
            "One-way maximum delay or latency.";
    }
    leaf one-way-delay-variation {
```

```
    type uint32 {
      range "0..16777215";
    }
    units "microseconds";
    default "0";
    description
      "One-way delay variation.";
  }
  leaf one-way-packet-loss {
    type decimal64 {
      fraction-digits 6;
      range "0..50.331642";
    }
    units "percent";
    default "0";
    description
      "One-way packet loss as a percentage of the total traffic
      sent over a configurable interval.

      The finest precision is 0.000003%.";
  }
}

grouping one-way-performance-metrics-gauge-packet {
  description
    "One-way packet Performance Metrics (PM) throttle grouping.

    This grouping is used to report the same metrics defined in
    the one-way-performance-metrics-packet grouping, using gauges
    instead of uint32 data types and referencing IPPM RFCs
    instead of IGP-TE RFCs.";
  leaf one-way-min-delay {
    type yang:gauge64;
    units "microseconds";
    description
      "One-way minimum delay or latency.";
  }
  leaf one-way-max-delay {
    type yang:gauge64;
    units "microseconds";
    description
      "One-way maximum delay or latency.";
    reference
      "RFC 7679: A One-Way Delay Metric for IP Performance
      Metrics (IPPM)";
  }
  leaf one-way-delay-variation {
    type yang:gauge64;
```

```
    units "microseconds";
    description
      "One-way delay variation.";
    reference
      "RFC 3393: IP Packet Delay Variation Metric for IP
        Performance Metrics (IPPM)";
  }
  leaf one-way-packet-loss {
    type decimal64 {
      fraction-digits 5;
      range "0..100";
    }
    description
      "The ratio of packets dropped to packets transmitted between
        two endpoints.";
    reference
      "RFC 7680: A One-Way Loss Metric for IP Performance
        Metrics (IPPM)";
  }
}

grouping two-way-performance-metrics-packet {
  description
    "Two-way packet Performance Metrics (PM) throttle grouping.";
  leaf two-way-min-delay {
    type uint32 {
      range "0..16777215";
    }
    units "microseconds";
    default "0";
    description
      "Two-way minimum delay or latency.";
  }
  leaf two-way-max-delay {
    type uint32 {
      range "0..16777215";
    }
    units "microseconds";
    default "0";
    description
      "Two-way maximum delay or latency.";
  }
  leaf two-way-delay-variation {
    type uint32 {
      range "0..16777215";
    }
    units "microseconds";
    default "0";
  }
}
```

```
    description
      "Two-way delay variation.";
  }
  leaf two-way-packet-loss {
    type decimal64 {
      fraction-digits 6;
      range "0..50.331642";
    }
    units "percent";
    default "0";
    description
      "Two-way packet loss as a percentage of the total traffic
      sent over a configurable interval.

      The finest precision is 0.000003%.";
  }
}

grouping two-way-performance-metrics-gauge-packet {
  description
    "Two-way packet Performance Metrics (PM) throttle grouping.

    This grouping is used to report the same metrics defined in
    the two-way-performance-metrics-packet grouping, using gauges
    instead of uint32 data types and referencing IPPM RFCs
    instead of IGP-TE RFCs.";
  leaf two-way-min-delay {
    type yang:gauge64;
    units "microseconds";
    description
      "Two-way minimum delay or latency.";
    reference
      "RFC 2681: A Round-trip Delay Metric for IPPM";
  }
  leaf two-way-max-delay {
    type yang:gauge64;
    units "microseconds";
    description
      "Two-way maximum delay or latency.";
    reference
      "RFC 2681: A Round-trip Delay Metric for IPPM";
  }
  leaf two-way-delay-variation {
    type yang:gauge64;
    units "microseconds";
    description
      "Two-way delay variation.";
    reference
```



```
    "RFC 5481: Packet Delay Variation Applicability Statement";
  }
  leaf two-way-packet-loss {
    type decimal64 {
      fraction-digits 5;
      range "0..100";
    }
    description
      "The ratio of packets dropped to packets transmitted between
       two endpoints.";
  }
}

grouping performance-metrics-throttle-container-packet {
  description
    "Packet Performance Metrics (PM) threshold grouping.";
  uses te-types:performance-metrics-throttle-container {
    augment "throttle/threshold-out" {
      description
        "Performance Metrics (PM) threshold-out packet
         augmentation for a generic grouping.";
      uses one-way-performance-metrics-packet;
      uses two-way-performance-metrics-packet;
    }
    augment "throttle/threshold-in" {
      description
        "Performance Metrics (PM) threshold-in packet augmentation
         for a generic grouping.";
      uses one-way-performance-metrics-packet;
      uses two-way-performance-metrics-packet;
    }
    augment "throttle/threshold-accelerated-advertisement" {
      description
        "Performance Metrics (PM) accelerated advertisement packet
         augmentation for a generic grouping.";
      uses one-way-performance-metrics-packet;
      uses two-way-performance-metrics-packet;
    }
  }
}

grouping bandwidth-profile-parameters {
  description
    "Common parameters to define bandwidth profiles in packet
     networks.";
  leaf cir {
    type uint64;
    units "bits per second";
  }
}
```

```
    description
      "Committed Information Rate (CIR).";
  }
  leaf cbs {
    type uint64;
    units "bytes";
    description
      "Committed Burst Size (CBS).";
  }
  leaf eir {
    type uint64;
    units "bits per second";
    description
      "Excess Information Rate (EIR).";
  }
  leaf ebs {
    type uint64;
    units "bytes";
    description
      "Excess Burst Size (EBS).";
  }
  leaf pir {
    type uint64;
    units "bits per second";
    description
      "Peak Information Rate (PIR).";
  }
  leaf pbs {
    type uint64;
    units "bytes";
    description
      "Peak Burst Size (PBS).";
  }
}

grouping te-packet-path-bandwidth {
  description
    "Bandwidth attributes for TE Packet paths.";
  container packet-bandwidth {
    description
      "Bandwidth attributes for TE Packet paths.";
    leaf specification-type {
      type te-bandwidth-requested-type;
      description
        "The bandwidth specification type, either explicitly
        specified or automatically computed.";
    }
    leaf set-bandwidth {
```

```
    when "../specification-type = 'specified-value'" {
      description
        "When the bandwidth value is explicitly specified.";
    }
    type bandwidth-kbps;
    description
      "Set the bandwidth value explicitly, e.g., using offline
      calculation.";
  }
  container bandwidth-profile {
    when "../specification-type = 'specified-profile'" {
      description
        "When the bandwidth profile is explicitly specified.";
    }
    description
      "Set the bandwidth profile attributes explicitly.";
    leaf bandwidth-profile-name {
      type string;
      description
        "Name of Bandwidth Profile.";
    }
    leaf bandwidth-profile-type {
      type identityref {
        base bandwidth-profile-type;
      }
      description
        "Type of Bandwidth Profile.";
    }
    uses bandwidth-profile-parameters;
  }
  leaf class-type {
    type te-types:te-ds-class;
    description
      "The Class-Type of traffic transported by the LSP.";
    reference
      "RFC 4124: Protocol Extensions for Support of
      Diffserv-aware MPLS Traffic Engineering,
      Section 4.3.1";
  }
  leaf signaled-bandwidth {
    type te-packet-types:bandwidth-kbps;
    config false;
    description
      "The currently signaled bandwidth of the LSP.

      In the case where the bandwidth is specified
      explicitly, then this will match the value of the
      set-bandwidth leaf.
```

```
        In the cases where the bandwidth is dynamically
        computed by the system, the current value of the
        bandwidth should be reflected.";
    }
}

grouping te-packet-link-bandwidth {
  description
    "Bandwidth attributes for Packet TE links.";
  leaf packet-bandwidth {
    type uint64;
    units "bits per second";
    description
      "Bandwidth value for Packet TE links.";
  }
}
}
<CODE ENDS>
```

Figure 2: Packet TE Types YANG module

6. IANA Considerations

This document requests IANA to update the following URIs in the "IETF XML Registry" [RFC3688] to refer to this document:

URI: urn:ietf:params:xml:ns:yang:ietf-te-types
Registrant Contact: The IESG.
XML: N/A, the requested URI is an XML namespace.

URI: urn:ietf:params:xml:ns:yang:ietf-te-packet-types
Registrant Contact: The IESG.
XML: N/A, the requested URI is an XML namespace.

This document requests IANA to register the following YANG modules in the "YANG Module Names" registry [RFC6020][RFC9890] within the "YANG Parameters" registry group.

```
name:      ietf-te-types
Maintained by IANA? N
namespace: urn:ietf:params:xml:ns:yang:ietf-te-types
prefix:    te-types
reference:  RFC XXXX

name:      ietf-te-packet-types
Maintained by IANA? N
namespace: urn:ietf:params:xml:ns:yang:ietf-te-packet-types
prefix:    te-packet-types
reference:  RFC XXXX
```

RFC Editor: Please replace XXXX above with the RFC number assigned to this document. Please remove this note.

7. Security Considerations

This section is modeled after the template described in Section 3.7 of [I-D.ietf-netmod-rfc8407bis].

The "ietf-te-types" and the "ietf-te-packet-types" YANG modules define data models that are designed to be accessed via YANG-based management protocols, such as NETCONF [RFC6241] and RESTCONF [RFC8040]. These YANG-based management protocols (1) have to use a secure transport layer (e.g., SSH [RFC4252], TLS [RFC8446], and QUIC [RFC9000]) and (2) have to use mutual authentication.

The Network Configuration Access Control Model (NACM) [RFC8341] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

The YANG modules define a set of identities, types, and groupings. These nodes are intended to be reused by other YANG modules. The modules by themselves do not expose any data nodes that are writable, data nodes that contain read-only state, or RPCs. As such, there are no additional security issues related to the YANG module that need to be considered.

Modules that use the groupings that are defined in this document should identify the corresponding security considerations. For example using 'explicit-route-hop', 'record-route-state' or 'te-topology-identifier' (which includes the 'client-id') groupings may expose sensitive topology information.

8. References

8.1. Normative References

[ITU-T_G.709]

International Telecommunication Union, "Interfaces for the optical transport network", ITU-T G.709 , June 2020, <<https://www.itu.int/rec/T-REC-G.709>>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/rfc/rfc2119>>.

[RFC3209] Awduche, D., Berger, L., Gan, D., Li, T., Srinivasan, V., and G. Swallow, "RSVP-TE: Extensions to RSVP for LSP Tunnels", RFC 3209, DOI 10.17487/RFC3209, December 2001, <<https://www.rfc-editor.org/rfc/rfc3209>>.

[RFC3471] Berger, L., Ed., "Generalized Multi-Protocol Label Switching (GMPLS) Signaling Functional Description", RFC 3471, DOI 10.17487/RFC3471, January 2003, <<https://www.rfc-editor.org/rfc/rfc3471>>.

[RFC3477] Kompella, K. and Y. Rekhter, "Signalling Unnumbered Links in Resource ReSerVation Protocol - Traffic Engineering (RSVP-TE)", RFC 3477, DOI 10.17487/RFC3477, January 2003, <<https://www.rfc-editor.org/rfc/rfc3477>>.

[RFC3630] Katz, D., Kompella, K., and D. Yeung, "Traffic Engineering (TE) Extensions to OSPF Version 2", RFC 3630, DOI 10.17487/RFC3630, September 2003, <<https://www.rfc-editor.org/rfc/rfc3630>>.

[RFC3785] Le Faucheur, F., Uppili, R., Vedrenne, A., Merckx, P., and T. Telkamp, "Use of Interior Gateway Protocol (IGP) Metric as a second MPLS Traffic Engineering (TE) Metric", BCP 87, RFC 3785, DOI 10.17487/RFC3785, May 2004, <<https://www.rfc-editor.org/rfc/rfc3785>>.

[RFC4090] Pan, P., Ed., Swallow, G., Ed., and A. Atlas, Ed., "Fast Reroute Extensions to RSVP-TE for LSP Tunnels", RFC 4090, DOI 10.17487/RFC4090, May 2005, <<https://www.rfc-editor.org/rfc/rfc4090>>.

[RFC4124] Le Faucheur, F., Ed., "Protocol Extensions for Support of Diffserv-aware MPLS Traffic Engineering", RFC 4124, DOI 10.17487/RFC4124, June 2005, <<https://www.rfc-editor.org/rfc/rfc4124>>.

- [RFC4202] Kompella, K., Ed. and Y. Rekhter, Ed., "Routing Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS)", RFC 4202, DOI 10.17487/RFC4202, October 2005, <<https://www.rfc-editor.org/rfc/rfc4202>>.
- [RFC4203] Kompella, K., Ed. and Y. Rekhter, Ed., "OSPF Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS)", RFC 4203, DOI 10.17487/RFC4203, October 2005, <<https://www.rfc-editor.org/rfc/rfc4203>>.
- [RFC4328] Papadimitriou, D., Ed., "Generalized Multi-Protocol Label Switching (GMPLS) Signaling Extensions for G.709 Optical Transport Networks Control", RFC 4328, DOI 10.17487/RFC4328, January 2006, <<https://www.rfc-editor.org/rfc/rfc4328>>.
- [RFC4561] Vasseur, J.-P., Ed., Ali, Z., and S. Sivabalan, "Definition of a Record Route Object (RRO) Node-Id Sub-Object", RFC 4561, DOI 10.17487/RFC4561, June 2006, <<https://www.rfc-editor.org/rfc/rfc4561>>.
- [RFC4872] Lang, J.P., Ed., Rekhter, Y., Ed., and D. Papadimitriou, Ed., "RSVP-TE Extensions in Support of End-to-End Generalized Multi-Protocol Label Switching (GMPLS) Recovery", RFC 4872, DOI 10.17487/RFC4872, May 2007, <<https://www.rfc-editor.org/rfc/rfc4872>>.
- [RFC4873] Berger, L., Bryskin, I., Papadimitriou, D., and A. Farrel, "GMPLS Segment Recovery", RFC 4873, DOI 10.17487/RFC4873, May 2007, <<https://www.rfc-editor.org/rfc/rfc4873>>.
- [RFC4875] Aggarwal, R., Ed., Papadimitriou, D., Ed., and S. Yasukawa, Ed., "Extensions to Resource Reservation Protocol - Traffic Engineering (RSVP-TE) for Point-to-Multipoint TE Label Switched Paths (LSPs)", RFC 4875, DOI 10.17487/RFC4875, May 2007, <<https://www.rfc-editor.org/rfc/rfc4875>>.
- [RFC4920] Farrel, A., Ed., Satyanarayana, A., Iwata, A., Fujita, N., and G. Ash, "Crankback Signaling Extensions for MPLS and GMPLS RSVP-TE", RFC 4920, DOI 10.17487/RFC4920, July 2007, <<https://www.rfc-editor.org/rfc/rfc4920>>.
- [RFC5003] Metz, C., Martini, L., Balus, F., and J. Sugimoto, "Attachment Individual Identifier (AII) Types for Aggregation", RFC 5003, DOI 10.17487/RFC5003, September 2007, <<https://www.rfc-editor.org/rfc/rfc5003>>.

- [RFC5150] Ayyangar, A., Kompella, K., Vasseur, JP., and A. Farrel, "Label Switched Path Stitching with Generalized Multiprotocol Label Switching Traffic Engineering (GMPLS TE)", RFC 5150, DOI 10.17487/RFC5150, February 2008, <<https://www.rfc-editor.org/rfc/rfc5150>>.
- [RFC5151] Farrel, A., Ed., Ayyangar, A., and JP. Vasseur, "Inter-Domain MPLS and GMPLS Traffic Engineering -- Resource Reservation Protocol-Traffic Engineering (RSVP-TE) Extensions", RFC 5151, DOI 10.17487/RFC5151, February 2008, <<https://www.rfc-editor.org/rfc/rfc5151>>.
- [RFC5305] Li, T. and H. Smit, "IS-IS Extensions for Traffic Engineering", RFC 5305, DOI 10.17487/RFC5305, October 2008, <<https://www.rfc-editor.org/rfc/rfc5305>>.
- [RFC5307] Kompella, K., Ed. and Y. Rekhter, Ed., "IS-IS Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS)", RFC 5307, DOI 10.17487/RFC5307, October 2008, <<https://www.rfc-editor.org/rfc/rfc5307>>.
- [RFC5420] Farrel, A., Ed., Papadimitriou, D., Vasseur, JP., and A. Ayyangar, "Encoding of Attributes for MPLS LSP Establishment Using Resource Reservation Protocol Traffic Engineering (RSVP-TE)", RFC 5420, DOI 10.17487/RFC5420, February 2009, <<https://www.rfc-editor.org/rfc/rfc5420>>.
- [RFC5440] Vasseur, JP., Ed. and JL. Le Roux, Ed., "Path Computation Element (PCE) Communication Protocol (PCEP)", RFC 5440, DOI 10.17487/RFC5440, March 2009, <<https://www.rfc-editor.org/rfc/rfc5440>>.
- [RFC5441] Vasseur, JP., Ed., Zhang, R., Bitar, N., and JL. Le Roux, "A Backward-Recursive PCE-Based Computation (BRPC) Procedure to Compute Shortest Constrained Inter-Domain Traffic Engineering Label Switched Paths", RFC 5441, DOI 10.17487/RFC5441, April 2009, <<https://www.rfc-editor.org/rfc/rfc5441>>.
- [RFC5520] Bradford, R., Ed., Vasseur, JP., and A. Farrel, "Preserving Topology Confidentiality in Inter-Domain Path Computation Using a Path-Key-Based Mechanism", RFC 5520, DOI 10.17487/RFC5520, April 2009, <<https://www.rfc-editor.org/rfc/rfc5520>>.

- [RFC5541] Le Roux, JL., Vasseur, JP., and Y. Lee, "Encoding of Objective Functions in the Path Computation Element Communication Protocol (PCEP)", RFC 5541, DOI 10.17487/RFC5541, June 2009, <<https://www.rfc-editor.org/rfc/rfc5541>>.
- [RFC5557] Lee, Y., Le Roux, JL., King, D., and E. Oki, "Path Computation Element Communication Protocol (PCEP) Requirements and Protocol Extensions in Support of Global Concurrent Optimization", RFC 5557, DOI 10.17487/RFC5557, July 2009, <<https://www.rfc-editor.org/rfc/rfc5557>>.
- [RFC5712] Meyer, M., Ed. and JP. Vasseur, Ed., "MPLS Traffic Engineering Soft Preemption", RFC 5712, DOI 10.17487/RFC5712, January 2010, <<https://www.rfc-editor.org/rfc/rfc5712>>.
- [RFC6001] Papadimitriou, D., Vigoureux, M., Shiimoto, K., Brungard, D., and JL. Le Roux, "Generalized MPLS (GMPLS) Protocol Extensions for Multi-Layer and Multi-Region Networks (MLN/MRN)", RFC 6001, DOI 10.17487/RFC6001, October 2010, <<https://www.rfc-editor.org/rfc/rfc6001>>.
- [RFC6002] Berger, L. and D. Fedyk, "Generalized MPLS (GMPLS) Data Channel Switching Capable (DCSC) and Channel Set Label Extensions", RFC 6002, DOI 10.17487/RFC6002, October 2010, <<https://www.rfc-editor.org/rfc/rfc6002>>.
- [RFC6004] Berger, L. and D. Fedyk, "Generalized MPLS (GMPLS) Support for Metro Ethernet Forum and G.8011 Ethernet Service Switching", RFC 6004, DOI 10.17487/RFC6004, October 2010, <<https://www.rfc-editor.org/rfc/rfc6004>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/rfc/rfc6020>>.
- [RFC6119] Harrison, J., Berger, J., and M. Bartlett, "IPv6 Traffic Engineering in IS-IS", RFC 6119, DOI 10.17487/RFC6119, February 2011, <<https://www.rfc-editor.org/rfc/rfc6119>>.
- [RFC6368] Marques, P., Raszuk, R., Patel, K., Kumaki, K., and T. Yamagata, "Internal BGP as the Provider/Customer Edge Protocol for BGP/MPLS IP Virtual Private Networks (VPNs)", RFC 6368, DOI 10.17487/RFC6368, September 2011, <<https://www.rfc-editor.org/rfc/rfc6368>>.

- [RFC6370] Bocci, M., Swallow, G., and E. Gray, "MPLS Transport Profile (MPLS-TP) Identifiers", RFC 6370, DOI 10.17487/RFC6370, September 2011, <<https://www.rfc-editor.org/rfc/rfc6370>>.
- [RFC6378] Weingarten, Y., Ed., Bryant, S., Osborne, E., Sprecher, N., and A. Fulignoli, Ed., "MPLS Transport Profile (MPLS-TP) Linear Protection", RFC 6378, DOI 10.17487/RFC6378, October 2011, <<https://www.rfc-editor.org/rfc/rfc6378>>.
- [RFC6511] Ali, Z., Swallow, G., and R. Aggarwal, "Non-Penultimate Hop Popping Behavior and Out-of-Band Mapping for RSVP-TE Label Switched Paths", RFC 6511, DOI 10.17487/RFC6511, February 2012, <<https://www.rfc-editor.org/rfc/rfc6511>>.
- [RFC6780] Berger, L., Le Faucheur, F., and A. Narayanan, "RSVP ASSOCIATION Object Extensions", RFC 6780, DOI 10.17487/RFC6780, October 2012, <<https://www.rfc-editor.org/rfc/rfc6780>>.
- [RFC6790] Kompella, K., Drake, J., Amante, S., Henderickx, W., and L. Yong, "The Use of Entropy Labels in MPLS Forwarding", RFC 6790, DOI 10.17487/RFC6790, November 2012, <<https://www.rfc-editor.org/rfc/rfc6790>>.
- [RFC6827] Malis, A., Ed., Lindem, A., Ed., and D. Papadimitriou, Ed., "Automatically Switched Optical Network (ASON) Routing for OSPFv2 Protocols", RFC 6827, DOI 10.17487/RFC6827, January 2013, <<https://www.rfc-editor.org/rfc/rfc6827>>.
- [RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types", RFC 6991, DOI 10.17487/RFC6991, July 2013, <<https://www.rfc-editor.org/rfc/rfc6991>>.
- [RFC7074] Berger, L. and J. Meuric, "Revised Definition of the GMPLS Switching Capability and Type Fields", RFC 7074, DOI 10.17487/RFC7074, November 2013, <<https://www.rfc-editor.org/rfc/rfc7074>>.
- [RFC7138] Ceccarelli, D., Ed., Zhang, F., Belotti, S., Rao, R., and J. Drake, "Traffic Engineering Extensions to OSPF for GMPLS Control of Evolving G.709 Optical Transport Networks", RFC 7138, DOI 10.17487/RFC7138, March 2014, <<https://www.rfc-editor.org/rfc/rfc7138>>.

- [RFC7139] Zhang, F., Ed., Zhang, G., Belotti, S., Ceccarelli, D., and K. Pithewan, "GMPLS Signaling Extensions for Control of Evolving G.709 Optical Transport Networks", RFC 7139, DOI 10.17487/RFC7139, March 2014, <<https://www.rfc-editor.org/rfc/rfc7139>>.
- [RFC7260] Takacs, A., Fedyk, D., and J. He, "GMPLS RSVP-TE Extensions for Operations, Administration, and Maintenance (OAM) Configuration", RFC 7260, DOI 10.17487/RFC7260, June 2014, <<https://www.rfc-editor.org/rfc/rfc7260>>.
- [RFC7271] Ryoo, J., Ed., Gray, E., Ed., van Helvoort, H., D'Alessandro, A., Cheung, T., and E. Osborne, "MPLS Transport Profile (MPLS-TP) Linear Protection to Match the Operational Expectations of Synchronous Digital Hierarchy, Optical Transport Network, and Ethernet Transport Network Operators", RFC 7271, DOI 10.17487/RFC7271, June 2014, <<https://www.rfc-editor.org/rfc/rfc7271>>.
- [RFC7308] Osborne, E., "Extended Administrative Groups in MPLS Traffic Engineering (MPLS-TE)", RFC 7308, DOI 10.17487/RFC7308, July 2014, <<https://www.rfc-editor.org/rfc/rfc7308>>.
- [RFC7471] Giacalone, S., Ward, D., Drake, J., Atlas, A., and S. Previdi, "OSPF Traffic Engineering (TE) Metric Extensions", RFC 7471, DOI 10.17487/RFC7471, March 2015, <<https://www.rfc-editor.org/rfc/rfc7471>>.
- [RFC7551] Zhang, F., Ed., Jing, R., and R. Gandhi, Ed., "RSVP-TE Extensions for Associated Bidirectional Label Switched Paths (LSPs)", RFC 7551, DOI 10.17487/RFC7551, May 2015, <<https://www.rfc-editor.org/rfc/rfc7551>>.
- [RFC7570] Margaria, C., Ed., Martinelli, G., Balls, S., and B. Wright, "Label Switched Path (LSP) Attribute in the Explicit Route Object (ERO)", RFC 7570, DOI 10.17487/RFC7570, July 2015, <<https://www.rfc-editor.org/rfc/rfc7570>>.
- [RFC7571] Dong, J., Chen, M., Li, Z., and D. Ceccarelli, "GMPLS RSVP-TE Extensions for Lock Instruct and Loopback", RFC 7571, DOI 10.17487/RFC7571, July 2015, <<https://www.rfc-editor.org/rfc/rfc7571>>.

- [RFC7579] Bernstein, G., Ed., Lee, Y., Ed., Li, D., Imajuku, W., and J. Han, "General Network Element Constraint Encoding for GMPLS-Controlled Networks", RFC 7579, DOI 10.17487/RFC7579, June 2015, <<https://www.rfc-editor.org/rfc/rfc7579>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/rfc/rfc7950>>.
- [RFC8001] Zhang, F., Ed., Gonzalez de Dios, O., Ed., Margaria, C., Hartley, M., and Z. Ali, "RSVP-TE Extensions for Collecting Shared Risk Link Group (SRLG) Information", RFC 8001, DOI 10.17487/RFC8001, January 2017, <<https://www.rfc-editor.org/rfc/rfc8001>>.
- [RFC8149] Saad, T., Ed., Gandhi, R., Ed., Ali, Z., Venator, R., and Y. Kamite, "RSVP Extensions for Reoptimization of Loosely Routed Point-to-Multipoint Traffic Engineering Label Switched Paths (LSPs)", RFC 8149, DOI 10.17487/RFC8149, April 2017, <<https://www.rfc-editor.org/rfc/rfc8149>>.
- [RFC8169] Mirsky, G., Ruffini, S., Gray, E., Drake, J., Bryant, S., and A. Vainshtein, "Residence Time Measurement in MPLS Networks", RFC 8169, DOI 10.17487/RFC8169, May 2017, <<https://www.rfc-editor.org/rfc/rfc8169>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/rfc/rfc8174>>.
- [RFC8233] Dhody, D., Wu, Q., Manral, V., Ali, Z., and K. Kumaki, "Extensions to the Path Computation Element Communication Protocol (PCEP) to Compute Service-Aware Label Switched Paths (LSPs)", RFC 8233, DOI 10.17487/RFC8233, September 2017, <<https://www.rfc-editor.org/rfc/rfc8233>>.
- [RFC8294] Liu, X., Qu, Y., Lindem, A., Hopps, C., and L. Berger, "Common YANG Data Types for the Routing Area", RFC 8294, DOI 10.17487/RFC8294, December 2017, <<https://www.rfc-editor.org/rfc/rfc8294>>.
- [RFC8306] Zhao, Q., Dhody, D., Ed., Palleti, R., and D. King, "Extensions to the Path Computation Element Communication Protocol (PCEP) for Point-to-Multipoint Traffic Engineering Label Switched Paths", RFC 8306, DOI 10.17487/RFC8306, November 2017, <<https://www.rfc-editor.org/rfc/rfc8306>>.

- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, RFC 8341, DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/rfc/rfc8341>>.
- [RFC8345] Clemm, A., Medved, J., Varga, R., Bahadur, N., Ananthakrishnan, H., and X. Liu, "A YANG Data Model for Network Topologies", RFC 8345, DOI 10.17487/RFC8345, March 2018, <<https://www.rfc-editor.org/rfc/rfc8345>>.
- [RFC8570] Ginsberg, L., Ed., Previdi, S., Ed., Giacalone, S., Ward, D., Drake, J., and Q. Wu, "IS-IS Traffic Engineering (TE) Metric Extensions", RFC 8570, DOI 10.17487/RFC8570, March 2019, <<https://www.rfc-editor.org/rfc/rfc8570>>.
- [RFC8685] Zhang, F., Zhao, Q., Gonzalez de Dios, O., Casellas, R., and D. King, "Path Computation Element Communication Protocol (PCEP) Extensions for the Hierarchical Path Computation Element (H-PCE) Architecture", RFC 8685, DOI 10.17487/RFC8685, December 2019, <<https://www.rfc-editor.org/rfc/rfc8685>>.
- [RFC8776] Saad, T., Gandhi, R., Liu, X., Beeram, V., and I. Bryskin, "Common YANG Data Types for Traffic Engineering", RFC 8776, DOI 10.17487/RFC8776, June 2020, <<https://www.rfc-editor.org/rfc/rfc8776>>.
- [RFC8800] Litkowski, S., Sivabalan, S., Barth, C., and M. Negi, "Path Computation Element Communication Protocol (PCEP) Extension for Label Switched Path (LSP) Diversity Constraint Signaling", RFC 8800, DOI 10.17487/RFC8800, July 2020, <<https://www.rfc-editor.org/rfc/rfc8800>>.
- [RFC9012] Patel, K., Van de Velde, G., Sangli, S., and J. Scudder, "The BGP Tunnel Encapsulation Attribute", RFC 9012, DOI 10.17487/RFC9012, April 2021, <<https://www.rfc-editor.org/rfc/rfc9012>>.
- [RFC9890] Bierman, A., Boucadair, M., Ed., and Q. Wu, "An Update to YANG Module Names Registration", RFC 9890, DOI 10.17487/RFC9890, October 2025, <<https://www.rfc-editor.org/rfc/rfc9890>>.

8.2. Informative References

- [I-D.ietf-netmod-rfc8407bis]
Bierman, A., Boucadair, M., and Q. Wu, "Guidelines for Authors and Reviewers of Documents Containing YANG Data

Models", Work in Progress, Internet-Draft, draft-ietf-netmod-rfc8407bis-28, 5 June 2025, <<https://datatracker.ietf.org/doc/html/draft-ietf-netmod-rfc8407bis-28>>.

[I-D.ietf-pce-sid-algo]

Sidor, S., Rose, Z., Peng, S., Peng, S., and A. Stone, "Carrying SR-Algorithm in Path Computation Element Communication Protocol (PCEP)", Work in Progress, Internet-Draft, draft-ietf-pce-sid-algo-29, 15 October 2025, <<https://datatracker.ietf.org/doc/html/draft-ietf-pce-sid-algo-29>>.

[MEF_10.3] MEF, "Ethernet Services Attributes Phase 3", MEF 10.3 , October 2013, <https://www.mef.net/Assets/Technical_Specifications/PDF/MEF_10.pdf>.

[RFC2475] Blake, S., Black, D., Carlson, M., Davies, E., Wang, Z., and W. Weiss, "An Architecture for Differentiated Services", RFC 2475, DOI 10.17487/RFC2475, December 1998, <<https://www.rfc-editor.org/rfc/rfc2475>>.

[RFC2697] Heinanen, J. and R. Guerin, "A Single Rate Three Color Marker", RFC 2697, DOI 10.17487/RFC2697, September 1999, <<https://www.rfc-editor.org/rfc/rfc2697>>.

[RFC2698] Heinanen, J. and R. Guerin, "A Two Rate Three Color Marker", RFC 2698, DOI 10.17487/RFC2698, September 1999, <<https://www.rfc-editor.org/rfc/rfc2698>>.

[RFC2702] Awduche, D., Malcolm, J., Agogbua, J., O'Dell, M., and J. McManus, "Requirements for Traffic Engineering Over MPLS", RFC 2702, DOI 10.17487/RFC2702, September 1999, <<https://www.rfc-editor.org/rfc/rfc2702>>.

[RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/rfc/rfc3688>>.

[RFC4125] Le Faucheur, F. and W. Lai, "Maximum Allocation Bandwidth Constraints Model for Diffserv-aware MPLS Traffic Engineering", RFC 4125, DOI 10.17487/RFC4125, June 2005, <<https://www.rfc-editor.org/rfc/rfc4125>>.

- [RFC4126] Ash, J., "Max Allocation with Reservation Bandwidth Constraints Model for Diffserv-aware MPLS Traffic Engineering & Performance Comparisons", RFC 4126, DOI 10.17487/RFC4126, June 2005, <<https://www.rfc-editor.org/rfc/rfc4126>>.
- [RFC4127] Le Faucheur, F., Ed., "Russian Dolls Bandwidth Constraints Model for Diffserv-aware MPLS Traffic Engineering", RFC 4127, DOI 10.17487/RFC4127, June 2005, <<https://www.rfc-editor.org/rfc/rfc4127>>.
- [RFC4252] Ylonen, T. and C. Lonvick, Ed., "The Secure Shell (SSH) Authentication Protocol", RFC 4252, DOI 10.17487/RFC4252, January 2006, <<https://www.rfc-editor.org/rfc/rfc4252>>.
- [RFC4427] Mannie, E., Ed. and D. Papadimitriou, Ed., "Recovery (Protection and Restoration) Terminology for Generalized Multi-Protocol Label Switching (GMPLS)", RFC 4427, DOI 10.17487/RFC4427, March 2006, <<https://www.rfc-editor.org/rfc/rfc4427>>.
- [RFC4657] Ash, J., Ed. and J.L. Le Roux, Ed., "Path Computation Element (PCE) Communication Protocol Generic Requirements", RFC 4657, DOI 10.17487/RFC4657, September 2006, <<https://www.rfc-editor.org/rfc/rfc4657>>.
- [RFC4736] Vasseur, JP., Ed., Ikejiri, Y., and R. Zhang, "Reoptimization of Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Loosely Routed Label Switched Path (LSP)", RFC 4736, DOI 10.17487/RFC4736, November 2006, <<https://www.rfc-editor.org/rfc/rfc4736>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/rfc/rfc6241>>.
- [RFC7823] Atlas, A., Drake, J., Giacalone, S., and S. Previdi, "Performance-Based Path Selection for Explicitly Routed Label Switched Paths (LSPs) Using TE Metric Extensions", RFC 7823, DOI 10.17487/RFC7823, May 2016, <<https://www.rfc-editor.org/rfc/rfc7823>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/rfc/rfc8040>>.

- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/rfc/rfc8340>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/rfc/rfc8446>>.
- [RFC9000] Iyengar, J., Ed. and M. Thomson, Ed., "QUIC: A UDP-Based Multiplexed and Secure Transport", RFC 9000, DOI 10.17487/RFC9000, May 2021, <<https://www.rfc-editor.org/rfc/rfc9000>>.
- [RFC9522] Farrel, A., Ed., "Overview and Principles of Internet Traffic Engineering", RFC 9522, DOI 10.17487/RFC9522, January 2024, <<https://www.rfc-editor.org/rfc/rfc9522>>.

Appendix A. The Complete Schema Trees

This appendix presents the complete tree of the TE and Packet TE types data model. See [RFC8340] for an explanation of the symbols used. The data type of every leaf node is shown near the right end of the corresponding line.

Editors' Note: The YANG trees have been generated by pyang and have some bugs to be fixed before publication. Please manually fix the YANG tree before sending the document to the RFC EDITOR.

A.1. TE Types Schema Tree

===== NOTE: '\ ' line wrapping per RFC 8792 =====

```
module: ietf-te-types

  grouping te-bandwidth:
    +-- te-bandwidth
      +-- (technology)?
        +--:(generic)
          +-- generic?      te-bandwidth
  grouping te-label:
    +-- te-label
      +-- (technology)?
        | +--:(generic)
        |   +-- generic?      rt-types:generalized-label
      +-- direction?      te-label-direction
  grouping te-topology-identifier:
    +-- te-topology-identifier
      +-- provider-id?      te-global-id
```



```

    +-- client-id?      te-global-id
    +-- topology-id?   te-topology-id
grouping performance-metrics-one-way-delay-loss:
    +-- one-way-delay?      uint32
    +-- one-way-delay-normality?
        te-types:performance-metrics-normality
grouping performance-metrics-two-way-delay-loss:
    +-- two-way-delay?      uint32
    +-- two-way-delay-normality?
        te-types:performance-metrics-normality
grouping performance-metrics-one-way-bandwidth:
    +-- one-way-residual-bandwidth?
    |   rt-types:bandwidth-ieee-float32
    +-- one-way-residual-bandwidth-normality?
    |   te-types:performance-metrics-normality
    +-- one-way-available-bandwidth?
    |   rt-types:bandwidth-ieee-float32
    +-- one-way-available-bandwidth-normality?
    |   te-types:performance-metrics-normality
    +-- one-way-utilized-bandwidth?
    |   rt-types:bandwidth-ieee-float32
    +-- one-way-utilized-bandwidth-normality?
        te-types:performance-metrics-normality
grouping one-way-performance-metrics:
    +-- one-way-delay?      uint32
    +-- one-way-residual-bandwidth?
    |   rt-types:bandwidth-ieee-float32
    +-- one-way-available-bandwidth?
    |   rt-types:bandwidth-ieee-float32
    +-- one-way-utilized-bandwidth?
        rt-types:bandwidth-ieee-float32
grouping two-way-performance-metrics:
    +-- two-way-delay?      uint32
grouping performance-metrics-thresholds:
    +-- one-way-delay?      uint32
    +-- one-way-residual-bandwidth?
    |   rt-types:bandwidth-ieee-float32
    +-- one-way-available-bandwidth?
    |   rt-types:bandwidth-ieee-float32
    +-- one-way-utilized-bandwidth?
    |   rt-types:bandwidth-ieee-float32
    +-- two-way-delay?      uint32
grouping performance-metrics-attributes:
    +-- performance-metrics-one-way
    |   +-- one-way-delay?      uint32
    |   +-- one-way-delay-normality?
    |   |   te-types:performance-metrics-normality
    |   +-- one-way-residual-bandwidth?

```

```

|         rt-types:bandwidth-ieee-float32
+-- one-way-residual-bandwidth-normality?
|         te-types:performance-metrics-normality
+-- one-way-available-bandwidth?
|         rt-types:bandwidth-ieee-float32
+-- one-way-available-bandwidth-normality?
|         te-types:performance-metrics-normality
+-- one-way-utilized-bandwidth?
|         rt-types:bandwidth-ieee-float32
+-- one-way-utilized-bandwidth-normality?
|         te-types:performance-metrics-normality
+-- performance-metrics-two-way
+-- two-way-delay?          uint32
+-- two-way-delay-normality?
|         te-types:performance-metrics-normality
grouping performance-metrics-throttle-container:
+-- throttle
+-- one-way-delay-offset?          uint32
+-- measure-interval?             uint32
+-- advertisement-interval?       uint32
+-- suppression-interval?         uint32
+-- threshold-out
|   +-- one-way-delay?             uint32
|   +-- one-way-residual-bandwidth?
|   |         rt-types:bandwidth-ieee-float32
|   +-- one-way-available-bandwidth?
|   |         rt-types:bandwidth-ieee-float32
|   +-- one-way-utilized-bandwidth?
|   |         rt-types:bandwidth-ieee-float32
|   +-- two-way-delay?             uint32
+-- threshold-in
|   +-- one-way-delay?             uint32
|   +-- one-way-residual-bandwidth?
|   |         rt-types:bandwidth-ieee-float32
|   +-- one-way-available-bandwidth?
|   |         rt-types:bandwidth-ieee-float32
|   +-- one-way-utilized-bandwidth?
|   |         rt-types:bandwidth-ieee-float32
|   +-- two-way-delay?             uint32
+-- threshold-accelerated-advertisement
+-- one-way-delay?             uint32
+-- one-way-residual-bandwidth?
|   rt-types:bandwidth-ieee-float32
+-- one-way-available-bandwidth?
|   rt-types:bandwidth-ieee-float32
+-- one-way-utilized-bandwidth?
|   rt-types:bandwidth-ieee-float32
+-- two-way-delay?             uint32

```

```

grouping explicit-route-hop:
  +-- (type)?
    +---:(numbered-node-hop)
      |   +-- numbered-node-hop
      |     +-- node-id-uri?   nw:node-id
      |     +-- node-id?      te-node-id
      |     +-- hop-type?     te-hop-type
    +---:(numbered-link-hop)
      |   +-- numbered-link-hop
      |     +-- link-tp-id    te-tp-id
      |     +-- hop-type?    te-hop-type
      |     +-- direction?   te-link-direction
    +---:(unnumbered-link-hop)
      |   +-- unnumbered-link-hop
      |     +-- link-tp-id-uri? nt:tp-id
      |     +-- link-tp-id?    te-tp-id
      |     +-- node-id-uri?   nw:node-id
      |     +-- node-id?      te-node-id
      |     +-- hop-type?     te-hop-type
      |     +-- direction?    te-link-direction
    +---:(as-number)
      |   +-- as-number-hop
      |     +-- as-number    inet:as-number
      |     +-- hop-type?    te-hop-type
    +---:(label)
      |   +-- label-hop
      |     +-- te-label
      |       +-- (technology)?
      |         | +---:(generic)
      |         |   +-- generic?   rt-types:generalized-label
      |         +-- direction?    te-label-direction
grouping explicit-route-hop-with-srlg:
  +-- (type)?
    +---:(numbered-node-hop)
      |   +-- numbered-node-hop
      |     +-- node-id-uri?   nw:node-id
      |     +-- node-id?      te-node-id
      |     +-- hop-type?     te-hop-type
    +---:(numbered-link-hop)
      |   +-- numbered-link-hop
      |     +-- link-tp-id    te-tp-id
      |     +-- hop-type?    te-hop-type
      |     +-- direction?   te-link-direction
    +---:(unnumbered-link-hop)
      |   +-- unnumbered-link-hop
      |     +-- link-tp-id-uri? nt:tp-id
      |     +-- link-tp-id?    te-tp-id
      |     +-- node-id-uri?   nw:node-id

```

```

|      +-- node-id?          te-node-id
|      +-- hop-type?         te-hop-type
|      +-- direction?        te-link-direction
+---:(as-number)
|      +-- as-number-hop
|      +-- as-number          inet:as-number
|      +-- hop-type?         te-hop-type
+---:(label)
|      +-- label-hop
|      +-- te-label
|      |      +-- (technology)?
|      |      |      +---:(generic)
|      |      |      +-- generic?    rt-types:generalized-label
|      |      +-- direction?        te-label-direction
+---:(srlg)
|      +-- srlg
|      +-- srlg?      uint32
grouping record-route-state:
+-- index?              uint32
+-- (type)?
+---:(numbered-node-hop)
|      +-- numbered-node-hop
|      |      +-- node-id-uri?    nw:node-id
|      |      +-- node-id?        te-node-id
|      |      +-- flags*          path-attribute-flags
+---:(numbered-link-hop)
|      +-- numbered-link-hop
|      |      +-- link-tp-id      te-tp-id
|      |      +-- flags*          path-attribute-flags
+---:(unnumbered-link-hop)
|      +-- unnumbered-link-hop
|      |      +-- link-tp-id-uri?  nt:tp-id
|      |      +-- link-tp-id?      te-tp-id
|      |      +-- node-id-uri?     nw:node-id
|      |      +-- node-id?         te-node-id
|      |      +-- flags*           path-attribute-flags
+---:(label)
|      +-- label-hop
|      +-- te-label
|      |      +-- (technology)?
|      |      |      +---:(generic)
|      |      |      +-- generic?    rt-types:generalized-label
|      |      +-- direction?        te-label-direction
|      +-- flags*          path-attribute-flags
grouping label-restriction-info:
+-- restriction?        enumeration
+-- index?              uint32
+-- label-start

```

```

|   +-- te-label
|   |   +-- (technology)?
|   |   |   +---:(generic)
|   |   |   +-- generic?    rt-types:generalized-label
|   |   +-- direction?     te-label-direction
+-- label-end
|   +-- te-label
|   |   +-- (technology)?
|   |   |   +---:(generic)
|   |   |   +-- generic?    rt-types:generalized-label
|   |   +-- direction?     te-label-direction
+-- label-step
|   +-- (technology)?
|   |   +---:(generic)
|   |   +-- generic?    int32
+-- range-bitmap?    yang:hex-string
grouping label-set-info:
+-- label-restrictions
|   +-- label-restriction* [index]
|   |   +-- restriction?    enumeration
|   |   +-- index?         uint32
|   |   +-- label-start
|   |   |   +-- te-label
|   |   |   |   +-- (technology)?
|   |   |   |   |   +---:(generic)
|   |   |   |   |   +-- generic?    rt-types:generalized-label
|   |   |   |   +-- direction?     te-label-direction
|   |   +-- label-end
|   |   |   +-- te-label
|   |   |   |   +-- (technology)?
|   |   |   |   |   +---:(generic)
|   |   |   |   |   +-- generic?    rt-types:generalized-label
|   |   |   |   +-- direction?     te-label-direction
|   |   +-- label-step
|   |   |   +-- (technology)?
|   |   |   |   +---:(generic)
|   |   |   |   +-- generic?    int32
|   |   +-- range-bitmap?    yang:hex-string
grouping optimization-metric-entry:
+-- metric-type?          identityref
+-- weight?               uint8
+-- explicit-route-exclude-objects
|   +-- route-object-exclude-object* [index]
|   |   +-- index?         uint32
|   |   +-- (type)?
|   |   |   +---:(numbered-node-hop)
|   |   |   |   +-- numbered-node-hop
|   |   |   |   |   +-- node-id-uri?    nw:node-id

```

```

|         +-- node-id?          te-node-id
|         +-- hop-type?         te-hop-type
+---:(numbered-link-hop)
|   +-- numbered-link-hop
|   +-- link-tp-id             te-tp-id
|   +-- hop-type?             te-hop-type
|   +-- direction?            te-link-direction
+---:(unnumbered-link-hop)
|   +-- unnumbered-link-hop
|   +-- link-tp-id-uri?        nt:tp-id
|   +-- link-tp-id?            te-tp-id
|   +-- node-id-uri?           nw:node-id
|   +-- node-id?               te-node-id
|   +-- hop-type?              te-hop-type
|   +-- direction?             te-link-direction
+---:(as-number)
|   +-- as-number-hop
|   +-- as-number              inet:as-number
|   +-- hop-type?              te-hop-type
+---:(label)
|   +-- label-hop
|   +-- te-label
|   +-- (technology)?
|   |   +---:(generic)
|   |   |   +-- generic?        rt-types:generalized-label
|   +-- direction?            te-label-direction
+---:(srlg)
|   +-- srlg
|   +-- srlg?                  uint32
+-- explicit-route-include-objects
|   +-- route-object-include-object* [index]
|   |   +-- index?              uint32
|   |   +-- (type)?
|   |   +---:(numbered-node-hop)
|   |   |   +-- numbered-node-hop
|   |   |   +-- node-id-uri?     nw:node-id
|   |   |   +-- node-id?         te-node-id
|   |   |   +-- hop-type?        te-hop-type
|   |   +---:(numbered-link-hop)
|   |   |   +-- numbered-link-hop
|   |   |   +-- link-tp-id        te-tp-id
|   |   |   +-- hop-type?        te-hop-type
|   |   |   +-- direction?       te-link-direction
|   |   +---:(unnumbered-link-hop)
|   |   |   +-- unnumbered-link-hop
|   |   |   +-- link-tp-id-uri?   nt:tp-id
|   |   |   +-- link-tp-id?       te-tp-id
|   |   |   +-- node-id-uri?      nw:node-id

```

```

|      +-- node-id?          te-node-id
|      +-- hop-type?         te-hop-type
|      +-- direction?        te-link-direction
+---:(as-number)
|      +-- as-number-hop
|      +-- as-number          inet:as-number
|      +-- hop-type?         te-hop-type
+---:(label)
|      +-- label-hop
|      +-- te-label
|      +-- (technology)?
|      |      +---:(generic)
|      |      |      +-- generic?    rt-types:generalized-label
|      |      +-- direction?        te-label-direction
grouping common-constraints:
+-- te-bandwidth
|  +-- (technology)?
|  |      +---:(generic)
|  |      |      +-- generic?    te-bandwidth
+-- link-protection?    identityref
+-- setup-priority?     uint8
+-- hold-priority?      uint8
+-- signaling-type?     identityref
grouping tunnel-constraints:
+-- network-id?          nw:network-id
+-- te-topology-identifier
|  +-- provider-id?      te-global-id
|  +-- client-id?        te-global-id
|  +-- topology-id?      te-topology-id
+-- te-bandwidth
|  +-- (technology)?
|  |      +---:(generic)
|  |      |      +-- generic?    te-bandwidth
+-- link-protection?    identityref
+-- setup-priority?     uint8
+-- hold-priority?      uint8
+-- signaling-type?     identityref
grouping path-constraints-route-objects:
+-- explicit-route-objects
|  +-- route-object-exclude-always* [index]
|  |      +-- index?          uint32
|  |      +-- (type)?
|  |      |      +---:(numbered-node-hop)
|  |      |      |      +-- numbered-node-hop
|  |      |      |      |      +-- node-id-uri?    nw:node-id
|  |      |      |      |      +-- node-id?        te-node-id
|  |      |      |      |      +-- hop-type?        te-hop-type
|  |      |      +---:(numbered-link-hop)

```

```

|         +-- numbered-link-hop
|         |   +-- link-tp-id      te-tp-id
|         |   +-- hop-type?      te-hop-type
|         |   +-- direction?     te-link-direction
|         +---:(unnumbered-link-hop)
|         |   +-- unnumbered-link-hop
|         |   |   +-- link-tp-id-uri?  nt:tp-id
|         |   |   +-- link-tp-id?      te-tp-id
|         |   |   +-- node-id-uri?     nw:node-id
|         |   |   +-- node-id?        te-node-id
|         |   |   +-- hop-type?       te-hop-type
|         |   |   +-- direction?      te-link-direction
|         +---:(as-number)
|         |   +-- as-number-hop
|         |   |   +-- as-number      inet:as-number
|         |   |   +-- hop-type?     te-hop-type
|         +---:(label)
|         |   +-- label-hop
|         |   |   +-- te-label
|         |   |   |   +-- (technology)?
|         |   |   |   |   +---:(generic)
|         |   |   |   |   |   +-- generic?  rt-types:generalized-label
|         |   |   |   +-- direction?      te-label-direction
|         +-- route-object-include-exclude* [index]
|         +-- explicit-route-usage?      identityref
|         +-- index?                     uint32
|         +-- (type)?
|         +---:(numbered-node-hop)
|         |   +-- numbered-node-hop
|         |   |   +-- node-id-uri?  nw:node-id
|         |   |   +-- node-id?     te-node-id
|         |   |   +-- hop-type?    te-hop-type
|         +---:(numbered-link-hop)
|         |   +-- numbered-link-hop
|         |   |   +-- link-tp-id  te-tp-id
|         |   |   +-- hop-type?   te-hop-type
|         |   |   +-- direction?  te-link-direction
|         +---:(unnumbered-link-hop)
|         |   +-- unnumbered-link-hop
|         |   |   +-- link-tp-id-uri?  nt:tp-id
|         |   |   +-- link-tp-id?      te-tp-id
|         |   |   +-- node-id-uri?     nw:node-id
|         |   |   +-- node-id?        te-node-id
|         |   |   +-- hop-type?       te-hop-type
|         |   |   +-- direction?      te-link-direction
|         +---:(as-number)
|         |   +-- as-number-hop
|         |   |   +-- as-number      inet:as-number

```



```

    |      +-- hop-type?      te-hop-type
  +---:(label)
    |      +-- label-hop
    |      |      +-- te-label
    |      |      |      +-- (technology)?
    |      |      |      |      +---:(generic)
    |      |      |      |      |      +-- generic?      rt-types:generalized-label
    |      |      |      |      |      +-- direction?      te-label-direction
  +---:(srlg)
    |      +-- srlg
    |      |      +-- srlg?      uint32
grouping path-route-include-objects:
  +-- route-object-include-object* [index]
    +-- index?      uint32
    +-- (type)?
      +---:(numbered-node-hop)
        |      +-- numbered-node-hop
        |      |      +-- node-id-uri?      nw:node-id
        |      |      +-- node-id?      te-node-id
        |      |      +-- hop-type?      te-hop-type
      +---:(numbered-link-hop)
        |      +-- numbered-link-hop
        |      |      +-- link-tp-id      te-tp-id
        |      |      +-- hop-type?      te-hop-type
        |      |      +-- direction?      te-link-direction
      +---:(unnumbered-link-hop)
        |      +-- unnumbered-link-hop
        |      |      +-- link-tp-id-uri?      nt:tp-id
        |      |      +-- link-tp-id?      te-tp-id
        |      |      +-- node-id-uri?      nw:node-id
        |      |      +-- node-id?      te-node-id
        |      |      +-- hop-type?      te-hop-type
        |      |      +-- direction?      te-link-direction
      +---:(as-number)
        |      +-- as-number-hop
        |      |      +-- as-number      inet:as-number
        |      |      +-- hop-type?      te-hop-type
      +---:(label)
        |      +-- label-hop
        |      |      +-- te-label
        |      |      |      +-- (technology)?
        |      |      |      |      +---:(generic)
        |      |      |      |      |      +-- generic?      rt-types:generalized-label
        |      |      |      |      |      +-- direction?      te-label-direction
grouping path-route-exclude-objects:
  +-- route-object-exclude-object* [index]
    +-- index?      uint32
    +-- (type)?

```

```

+---:(numbered-node-hop)
|   +--- numbered-node-hop
|       +--- node-id-uri?    nw:node-id
|       +--- node-id?       te-node-id
|       +--- hop-type?      te-hop-type
+---:(numbered-link-hop)
|   +--- numbered-link-hop
|       +--- link-tp-id      te-tp-id
|       +--- hop-type?      te-hop-type
|       +--- direction?     te-link-direction
+---:(unnumbered-link-hop)
|   +--- unnumbered-link-hop
|       +--- link-tp-id-uri?  nt:tp-id
|       +--- link-tp-id?     te-tp-id
|       +--- node-id-uri?    nw:node-id
|       +--- node-id?       te-node-id
|       +--- hop-type?      te-hop-type
|       +--- direction?     te-link-direction
+---:(as-number)
|   +--- as-number-hop
|       +--- as-number       inet:as-number
|       +--- hop-type?      te-hop-type
+---:(label)
|   +--- label-hop
|       +--- te-label
|           +--- (technology)?
|               +---:(generic)
|                   +--- generic?    rt-types:generalized-label
|               +--- direction?     te-label-direction
+---:(srlg)
|   +--- srlg
|       +--- srlg?    uint32
grouping generic-path-metric-bounds:
+--- path-metric-bounds
+--- path-metric-bound* [metric-type]
+--- metric-type?    identityref
+--- upper-bound?    uint64
grouping generic-path-optimization:
+--- optimizations
|   +--- (algorithm)?
|       +---:(metric) {path-optimization-metric}?
|           +--- optimization-metric* [metric-type]
|               +--- metric-type?    identityref
|               +--- weight?         uint8
|               +--- explicit-route-exclude-objects
|                   +--- route-object-exclude-object* [index]
|                       +--- index?    uint32
|                       +--- (type)?

```

```

+---:(numbered-node-hop)
|   +-- numbered-node-hop
|       +--- node-id-uri?    nw:node-id
|       +--- node-id?       te-node-id
|       +--- hop-type?      te-hop-type
+---:(numbered-link-hop)
|   +-- numbered-link-hop
|       +--- link-tp-id     te-tp-id
|       +--- hop-type?     te-hop-type
|       +--- direction?    te-link-direction
+---:(unnumbered-link-hop)
|   +-- unnumbered-link-hop
|       +--- link-tp-id-uri? nt:tp-id
|       +--- link-tp-id?    te-tp-id
|       +--- node-id-uri?   nw:node-id
|       +--- node-id?       te-node-id
|       +--- hop-type?      te-hop-type
|       +--- direction?    te-link-direction
+---:(as-number)
|   +-- as-number-hop
|       +--- as-number      inet:as-number
|       +--- hop-type?      te-hop-type
+---:(label)
|   +-- label-hop
|       +--- te-label
|           +--- (technology)?
|               +---:(generic)
|                   +--- generic?
|                       rt-types:generalized\
|                           -label
|
|       +--- direction?
|           te-label-direction
+---:(srlg)
|   +-- srlg
|       +--- srlg?    uint32
+-- explicit-route-include-objects
+--- route-object-include-object* [index]
+--- index?                        uint32
+--- (type)?
+---:(numbered-node-hop)
|   +-- numbered-node-hop
|       +--- node-id-uri?    nw:node-id
|       +--- node-id?       te-node-id
|       +--- hop-type?      te-hop-type
+---:(numbered-link-hop)
|   +-- numbered-link-hop
|       +--- link-tp-id     te-tp-id

```

```

| | | | | hop-type? te-hop-type
| | | | | direction? te-link-direction
+---:(unnumbered-link-hop)
| | | | | unnumbered-link-hop
| | | | | link-tp-id-uri? nt:tp-id
| | | | | link-tp-id? te-tp-id
| | | | | node-id-uri? nw:node-id
| | | | | node-id? te-node-id
| | | | | hop-type? te-hop-type
| | | | | direction?
| | | | | te-link-direction
+---:(as-number)
| | | | | as-number-hop
| | | | | as-number inet:as-number
| | | | | hop-type? te-hop-type
+---:(label)
| | | | | label-hop
| | | | | te-label
| | | | | (technology)?
| | | | | | +---:(generic)
| | | | | | generic?
| | | | | rt-types:generalized\
| | | | | -label
| | | | | direction?
| | | | | te-label-direction
x-- tiebreakers
| x-- tiebreaker* [tiebreaker-type]
| x-- tiebreaker-type? identityref
+---:(objective-function)
| {path-optimization-objective-function}?
| +--- objective-function
| +--- objective-function-type? identityref
+--- tiebreaker? identityref
grouping generic-path-affinities:
+--- path-affinities-values
| +--- path-affinities-value* [usage]
| +--- usage? identityref
| +--- value? admin-groups
+--- path-affinity-names
+--- path-affinity-name* [usage]
+--- usage? identityref
+--- affinity-name* [name]
+--- name? string
grouping generic-path-srlgs:
+--- path-srlgs-lists
| +--- path-srlgs-list* [usage]
| +--- usage? identityref
| +--- values* srlg

```

```

+-- path-srlgs-names
  +-- path-srlgs-name* [usage]
    +-- usage? identityref
    +-- names* string
grouping generic-path-disjointness:
  +-- disjointness? te-path-disjointness
grouping common-path-constraints-attributes:
+-- te-bandwidth
  | +-- (technology)?
  |   +--:(generic)
  |     +-- generic? te-bandwidth
+-- link-protection? identityref
+-- setup-priority? uint8
+-- hold-priority? uint8
+-- signaling-type? identityref
+-- path-metric-bounds
  | +-- path-metric-bound* [metric-type]
  |   +-- metric-type? identityref
  |   +-- upper-bound? uint64
+-- path-affinities-values
  | +-- path-affinities-value* [usage]
  |   +-- usage? identityref
  |   +-- value? admin-groups
+-- path-affinity-names
  | +-- path-affinity-name* [usage]
  |   +-- usage? identityref
  |   +-- affinity-name* [name]
  |     +-- name? string
+-- path-srlgs-lists
  | +-- path-srlgs-list* [usage]
  |   +-- usage? identityref
  |   +-- values* srlg
+-- path-srlgs-names
  +-- path-srlgs-name* [usage]
    +-- usage? identityref
    +-- names* string
grouping generic-path-constraints:
+-- path-constraints
  +-- te-bandwidth
    | +-- (technology)?
    |   +--:(generic)
    |     +-- generic? te-bandwidth
+-- link-protection? identityref
+-- setup-priority? uint8
+-- hold-priority? uint8
+-- signaling-type? identityref
+-- path-metric-bounds
  | +-- path-metric-bound* [metric-type]

```

```

|         +-- metric-type?    identityref
|         +-- upper-bound?   uint64
+-- path-affinities-values
|   +-- path-affinities-value* [usage]
|   +-- usage?    identityref
|   +-- value?    admin-groups
+-- path-affinity-names
|   +-- path-affinity-name* [usage]
|   +-- usage?    identityref
|   +-- affinity-name* [name]
|   +-- name?     string
+-- path-srlgs-lists
|   +-- path-srlgs-list* [usage]
|   +-- usage?    identityref
|   +-- values*    srlg
+-- path-srlgs-names
|   +-- path-srlgs-name* [usage]
|   +-- usage?    identityref
|   +-- names*    string
+-- disjointness?          te-path-disjointness
grouping generic-path-properties:
+--ro path-properties
+--ro path-metric* [metric-type]
|   +--ro metric-type?    identityref
|   +--ro accumulative-value?  uint64
+--ro path-affinities-values
|   +--ro path-affinities-value* [usage]
|   +--ro usage?    identityref
|   +--ro value?    admin-groups
+--ro path-affinity-names
|   +--ro path-affinity-name* [usage]
|   +--ro usage?    identityref
|   +--ro affinity-name* [name]
|   +--ro name?     string
+--ro path-srlgs-lists
|   +--ro path-srlgs-list* [usage]
|   +--ro usage?    identityref
|   +--ro values*    srlg
+--ro path-srlgs-names
|   +--ro path-srlgs-name* [usage]
|   +--ro usage?    identityref
|   +--ro names*    string
+--ro path-route-objects
+--ro path-route-object* [index]
+--ro index?                                uint32
+--ro (type)?
+--:(numbered-node-hop)
|   +--ro numbered-node-hop

```

```

|         +--ro node-id-uri?    nw:node-id
|         +--ro node-id?       te-node-id
|         +--ro hop-type?      te-hop-type
+---:(numbered-link-hop)
|   +--ro numbered-link-hop
|   |   +--ro link-tp-id      te-tp-id
|   |   +--ro hop-type?      te-hop-type
|   |   +--ro direction?     te-link-direction
+---:(unnumbered-link-hop)
|   +--ro unnumbered-link-hop
|   |   +--ro link-tp-id-uri?  nt:tp-id
|   |   +--ro link-tp-id?     te-tp-id
|   |   +--ro node-id-uri?    nw:node-id
|   |   +--ro node-id?       te-node-id
|   |   +--ro hop-type?      te-hop-type
|   |   +--ro direction?     te-link-direction
+---:(as-number)
|   +--ro as-number-hop
|   |   +--ro as-number      inet:as-number
|   |   +--ro hop-type?     te-hop-type
+---:(label)
|   +--ro label-hop
|   |   +--ro te-label
|   |   |   +--ro (technology)?
|   |   |   |   +---:(generic)
|   |   |   |   |   +--ro generic?
|   |   |   |   |   |   rt-types:generalized-label
|   |   |   +--ro direction?    te-label-direction
grouping encoding-and-switching-type:
+-- encoding?      identityref
+-- switching-type? identityref
grouping te-generic-node-id:
+-- id?            union
+-- type?          enumeration

```

A.2. Packet TE Types Schema Tree

```
module: ietf-te-packet-types
```

```

grouping performance-metrics-attributes-packet:
+-- performance-metrics-one-way
|   +-- one-way-delay?                               uint32
|   +-- one-way-delay-normality?
|   |   te-types:performance-metrics-normality
|   +-- one-way-residual-bandwidth?
|   |   rt-types:bandwidth-ieee-float32
|   +-- one-way-residual-bandwidth-normality?
|   |   te-types:performance-metrics-normality

```

```

|   +-- one-way-available-bandwidth?
|   |   rt-types:bandwidth-ieee-float32
|   +-- one-way-available-bandwidth-normality?
|   |   te-types:performance-metrics-normality
|   +-- one-way-utilized-bandwidth?
|   |   rt-types:bandwidth-ieee-float32
|   +-- one-way-utilized-bandwidth-normality?
|   |   te-types:performance-metrics-normality
|   +-- one-way-min-delay?                               uint32
|   +-- one-way-min-delay-normality?
|   |   te-types:performance-metrics-normality
|   +-- one-way-max-delay?                               uint32
|   +-- one-way-max-delay-normality?
|   |   te-types:performance-metrics-normality
|   +-- one-way-delay-variation?                         uint32
|   +-- one-way-delay-variation-normality?
|   |   te-types:performance-metrics-normality
|   +-- one-way-packet-loss?                             decimal64
|   +-- one-way-packet-loss-normality?
|       te-types:performance-metrics-normality
+-- performance-metrics-two-way
|   +-- two-way-delay?                                   uint32
|   +-- two-way-delay-normality?
|   |   te-types:performance-metrics-normality
|   +-- two-way-min-delay?                               uint32
|   +-- two-way-min-delay-normality?
|   |   te-types:performance-metrics-normality
|   +-- two-way-max-delay?                               uint32
|   +-- two-way-max-delay-normality?
|   |   te-types:performance-metrics-normality
|   +-- two-way-delay-variation?                         uint32
|   +-- two-way-delay-variation-normality?
|   |   te-types:performance-metrics-normality
|   +-- two-way-packet-loss?                             decimal64
|   +-- two-way-packet-loss-normality?
|       te-types:performance-metrics-normality
grouping one-way-performance-metrics-packet:
|   +-- one-way-min-delay?                               uint32
|   +-- one-way-max-delay?                               uint32
|   +-- one-way-delay-variation?                         uint32
|   +-- one-way-packet-loss?                             decimal64
grouping one-way-performance-metrics-gauge-packet:
|   +-- one-way-min-delay?                               yang:gauge64
|   +-- one-way-max-delay?                               yang:gauge64
|   +-- one-way-delay-variation?                         yang:gauge64
|   +-- one-way-packet-loss?                             decimal64
grouping two-way-performance-metrics-packet:
|   +-- two-way-min-delay?                               uint32

```



```

+-- two-way-max-delay?          uint32
+-- two-way-delay-variation?    uint32
+-- two-way-packet-loss?       decimal64
grouping two-way-performance-metrics-gauge-packet:
+-- two-way-min-delay?          yang:gauge64
+-- two-way-max-delay?          yang:gauge64
+-- two-way-delay-variation?    yang:gauge64
+-- two-way-packet-loss?       decimal64
grouping performance-metrics-throttle-container-packet:
+-- throttle
+-- one-way-delay-offset?          uint32
+-- measure-interval?             uint32
+-- advertisement-interval?       uint32
+-- suppression-interval?        uint32
+-- threshold-out
|   +-- one-way-delay?            uint32
|   +-- one-way-residual-bandwidth?
|   |   rt-types:bandwidth-ieee-float32
|   +-- one-way-available-bandwidth?
|   |   rt-types:bandwidth-ieee-float32
|   +-- one-way-utilized-bandwidth?
|   |   rt-types:bandwidth-ieee-float32
|   +-- two-way-delay?            uint32
|   +-- one-way-min-delay?        uint32
|   +-- one-way-max-delay?        uint32
|   +-- one-way-delay-variation?  uint32
|   +-- one-way-packet-loss?      decimal64
|   +-- two-way-min-delay?        uint32
|   +-- two-way-max-delay?        uint32
|   +-- two-way-delay-variation?  uint32
|   +-- two-way-packet-loss?      decimal64
+-- threshold-in
|   +-- one-way-delay?            uint32
|   +-- one-way-residual-bandwidth?
|   |   rt-types:bandwidth-ieee-float32
|   +-- one-way-available-bandwidth?
|   |   rt-types:bandwidth-ieee-float32
|   +-- one-way-utilized-bandwidth?
|   |   rt-types:bandwidth-ieee-float32
|   +-- two-way-delay?            uint32
|   +-- one-way-min-delay?        uint32
|   +-- one-way-max-delay?        uint32
|   +-- one-way-delay-variation?  uint32
|   +-- one-way-packet-loss?      decimal64
|   +-- two-way-min-delay?        uint32
|   +-- two-way-max-delay?        uint32
|   +-- two-way-delay-variation?  uint32
|   +-- two-way-packet-loss?      decimal64

```

```

    +-- threshold-accelerated-advertisement
      +-- one-way-delay?          uint32
      +-- one-way-residual-bandwidth?
      |   rt-types:bandwidth-ieee-float32
      +-- one-way-available-bandwidth?
      |   rt-types:bandwidth-ieee-float32
      +-- one-way-utilized-bandwidth?
      |   rt-types:bandwidth-ieee-float32
      +-- two-way-delay?          uint32
      +-- one-way-min-delay?      uint32
      +-- one-way-max-delay?      uint32
      +-- one-way-delay-variation? uint32
      +-- one-way-packet-loss?    decimal64
      +-- two-way-min-delay?      uint32
      +-- two-way-max-delay?      uint32
      +-- two-way-delay-variation? uint32
      +-- two-way-packet-loss?    decimal64
grouping bandwidth-profile-parameters:
  +-- cir?      uint64
  +-- cbs?      uint64
  +-- eir?      uint64
  +-- ebs?      uint64
  +-- pir?      uint64
  +-- pbs?      uint64
grouping te-packet-path-bandwidth:
  +-- packet-bandwidth
    +-- specification-type?    te-bandwidth-requested-type
    +-- set-bandwidth?         bandwidth-kbps
    +-- bandwidth-profile
      |   +-- bandwidth-profile-name?    string
      |   +-- bandwidth-profile-type?    identityref
      |   +-- cir?                      uint64
      |   +-- cbs?                      uint64
      |   +-- eir?                      uint64
      |   +-- ebs?                      uint64
      |   +-- pir?                      uint64
      |   +-- pbs?                      uint64
    +-- class-type?            te-types:te-ds-class
    +--ro signaled-bandwidth?   te-packet-types:bandwidth-kbps
grouping te-packet-link-bandwidth:
  +-- packet-bandwidth?    uint64

```

Appendix B. Changes from RFC 8776

This version adds new common data types, identities, and groupings to the YANG modules. It also updates some of the existing data types, identities, and groupings in the YANG modules and fixes few bugs in [RFC8776].

The following new identities have been added to the 'ietf-te-types' module:

- * lsp-provisioning-error-reason;
- * association-type-diversity;
- * tunnel-admin-state-auto;
- * lsp-restoration-restore-none;
- * restoration-scheme-rerouting;
- * path-metric-optimization-type;
- * link-path-metric-type;
- * link-metric-type and its derived identities;
- * path-computation-error-reason and its derived identities;
- * protocol-origin-type and its derived identities;
- * svec-objective-function-type and its derived identities;
- * svec-metric-type and its derived identities.

The following new data types have been added to the 'ietf-te-types' module:

- * path-type.

The following new groupings have been added to the 'ietf-te-types' module:

- * explicit-route-hop-with-srlg;
- * encoding-and-switching-type;
- * te-generic-node-id.

The following new identities have been added to the 'ietf-te-packet-types' module:

- * bandwidth-profile-type;
- * link-metric-delay-variation;

- * link-metric-loss;
- * path-metric-delay-variation;
- * path-metric-loss.

The following new groupings have been added to the 'ietf-te-packet-types' module:

- * te-packet-path-bandwidth;
- * te-packet-link-bandwidth.

The following identities, already defined in [RFC8776], have been updated in the 'ietf-te-types' module:

- * objective-function-type (editorial);
- * action-exercise (bug fix);
- * path-metric-type:
 - new base identities have been added;
- * path-metric-te (bug fix);
- * path-metric-igp (bug fix);
- * path-metric-hop (bug fix);
- * path-metric-delay-average (bug fix);
- * path-metric-delay-minimum (bug fix);
- * path-metric-residual-bandwidth (bug fix);
- * path-metric-optimize-includes (bug fix);
- * path-metric-optimize-excludes (bug fix);
- * te-optimization-criterion (editorial).

The following data type, already defined in [RFC8776], has been updated in the 'ietf-te-types' module:

- * te-node-id;

The data type has been changed to be a union.

The following groupings, already defined in [RFC8776], have been updated in the 'ietf-te-types' module:

* explicit-route-hop

The following new leaves have been added to the 'explicit-route-hop' grouping:

- node-id-uri;
- link-tp-id-uri;

The following leaves, already defined in [RFC8776], have been updated in the 'explicit-route-hop':

- node-id;
- link-tp-id.

The mandatory true statements for the node-id and link-tp-id have been replaced by must statements that requires at least the presence of:

- o node-id or node-id-uri;
- o link-tp-id or link-tp-id-uri.

* explicit-route-hop

The following new leaves have been added to the 'explicit-route-hop' grouping:

- node-id-uri;
- link-tp-id-uri;

The following leaves, already defined in [RFC8776], have been updated in the 'explicit-route-hop':

- node-id;
- link-tp-id.

The mandatory true statements for the node-id and link-tp-id have been replaced by must statements that requires at least the presence of:

- o node-id or node-id-uri;

- o link-tp-id or link-tp-id-uri.

* optimization-metric-entry:

The following leaves, already defined in [RFC8776], have been updated in the 'optimization-metric-entry':

- metric-type;

The base identity has been updated without impacting the set of derived identities that are allowed.

* tunnel-constraints;

The following new leaf have been added to the 'tunnel-constraints' grouping:

- network-id;

* path-constraints-route-objects:

The following container, already defined in [RFC8776], has been updated in the 'path-constraints-route-objects':

- explicit-route-objects-always;

The container has been renamed as 'explicit-route-objects'. This change is not affecting any IETF standard YANG data models since this grouping has not yet been used by any YANG data model defined in existing IETF RFCs.

* generic-path-metric-bounds:

The following leaves, already defined in [RFC8776], have been updated in the 'generic-path-metric-bounds':

- metric-type;

The base identity has been updated to:

- o increase the set of derived identities that are allowed and;
- o remove from this set the 'path-metric-optimize-includes' and the 'path-metric-optimize-excludes' identities (bug fixing)

* generic-path-optimization

The following new leaf have been added to the 'generic-path-optimization' grouping:

- tiebreaker;

The following container, already defined in [RFC8776], has been deprecated:

- tiebreakers.

The following identities, already defined in [RFC8776], have been obsoleted in the 'ietf-te-types' module for bug fixing:

- * of-minimize-agg-bandwidth-consumption (the 'svec-of-minimize-agg-bandwidth-consumption' identity should be used instead);
- * of-minimize-load-most-loaded-link (the 'svec-of-minimize-load-most-loaded-link' identity should be used instead);
- * of-minimize-cost-path-set (the 'svec-of-minimize-cost-path-set' identity should be used instead);
- * lsp-protection-reroute-extra (the 'restoration-scheme-rerouting' identity should be used instead);
- * lsp-protection-reroute (the 'restoration-scheme-rerouting' identity should be used instead).

Acknowledgements

The authors would like to thank Robert Wilton, Lou Berger, Mahesh Jethanandani and Jeff Haas for their valuable input to the discussion about the process to follow to provide tiny updates to a YANG module already published as an RFC.

The authors would like to thank Mohamed Boucadair and Sergio Belotti for their valuable comments and suggestions on this document.

This document was prepared using kramdown.

Contributors

Vishnu Pavan Beeram
Juniper Networks
Email: vbeeram@juniper.net

Rakesh Gandhi
Cisco Systems, Inc.
Email: rgandhi@cisco.com

Authors' Addresses

Italo Busi
Huawei
Email: italo.busi@huawei.com

Aihua Guo
Futurewei Technologies
Email: aihuaguo.ietf@gmail.com

Xufeng Liu
Alef Edge
Email: xufeng.liu.ietf@gmail.com

Tarek Saad
Cisco Systems Inc.
Email: tsaad.net@gmail.com

Igor Bryskin
Individual
Email: i_bryskin@yahoo.com