

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: 10 October 2025

N. Karstens
Garmin International
S. Cheshire
Apple Inc.
M. McBride
Futurewei
8 April 2025

The Multicast Application Port
draft-karstens-intarea-multicast-application-port-02

Abstract

This document discusses the drawbacks of the current practice of assigning a UDP port to each multicast application. Such assignments are redundant because the multicast address already uniquely identifies the data. The document proposes assigning a UDP port specifically for use with multicast applications and lists requirements for using this port.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 10 October 2025.

Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components

extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	2
1.1. Requirements Language	3
2. Assignment	3
3. Host Requirements	3
4. Application Requirements	4
5. Security Considerations	4
6. IANA Considerations	4
7. Acknowledgement	5
8. References	5
8.1. Normative References	5
8.2. Informative References	5
Authors' Addresses	6

1. Introduction

The Internet community has recognized the need to be judicious when assigning port numbers (see [RFC7605], Section 6). With unicast applications, the need for explicit port assignment has been reduced by techniques such as locally assigning a dynamic port, combined with some mechanism for advertising that port (see [RFC7605], Section 7.1). Dynamic assignment does not work with multicast applications because it is impossible to guarantee that the port remains unused by all hosts that may want to join a given multicast group. The result is that each multicast application-layer protocol has had to have its own dedicated port assignment. Even worse, each different use of that multicast application-layer protocol has had to have a different unique port assigned.

In the TCP/IP model, the port number in the transport layer multiplexes applications within a host (see [RFC1122], Section 4.1.1 and [RFC7605], Section 5). With Any-Source Multicast, the use of a port number to multiplex applications is unnecessary because the destination multicast address already provides a unique identifier for the application. The same applies to Source-Specific Multicast if both source address and destination multicast address are considered.

Because of the desire to conserve port numbers and the fact that a port is not necessary to multiplex multicast applications, this document assigns a UDP port that may be used with multicast applications: the Multicast Application Port.

Use of this port is optional because there may be circumstances where assigning a port is preferred, such as when participants cannot meet the requirements in Section 3 and Section 4.

An application may use this port in conjunction with a unicast port to balance out deficiencies related to multicast distribution (see [RFC9119], for example).

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

2. Assignment

This document REQUESTS assignment of UDP port 49149 and gives it the service name "mcast-app-port". This port is near the end of the range of User ports [RFC6335], Section 6 to differentiate it from other port assignments.

The REQUESTED port may be used as a source port if the application exclusively uses multicast messages. If any application messages are unicast, then a dynamic port should be used as the source port. This allows receivers to know which port to send replies to.

3. Host Requirements

Hosts shall require applications using this port to use it non-exclusively. In practice, this means hosts using POSIX-like socket APIs would require applications to set the SO_REUSEADDR and/or SO_REUSEPORT socket options before binding the socket [POSIX]. This ensures that applications developed on a conformant host will also work on a non-conformant host.

Hosts shall prevent use of the port with the wildcard address (see [RFC3493], Section 3.8).

Hosts shall prevent applications from sending non-multicast packets to this destination port.

Hosts shall discard all incoming, non-multicast packets that use this destination port.

4. Application Requirements

Applications running on non-conformant hosts can ensure compatibility with conformant hosts by meeting the requirements in this section.

Applications running on a non-conformant host shall not prevent other applications from using this port. In practice, this means that applications using POSIX-like socket APIs would enable the `SO_REUSEADDR` and/or `SO_REUSEPORT` socket options before binding the socket [POSIX].

Applications running on a non-conformant host shall discard all datagrams that do not have the multicast address used by the application.

5. Security Considerations

Applications running on non-conformant hosts are vulnerable to a denial of service attack if another application claims exclusive access to the port.

Systems that use POSIX-like socket APIs typically have restrictions on binding multiple sockets to the same port. This can serve as a rudimentary security mechanism in that other local applications cannot eavesdrop on the multicast stream. A necessary side-effect of using the Multicast Application Port is that applications can no longer rely on these security mechanisms. These applications may want to incorporate additional security measures into their protocol. Note that the problem of local eavesdropping is typically no worse than eavesdropping in-flight, so it is likely that both attack vectors can be resolved by the same security measure.

6. IANA Considerations

IANA is REQUESTED to assign the following port:

Service Name	mcast-app-port
Transport Protocol	UDP
Assignee	IESG <iesg@ietf.org>
Contact	IETF Chair <chair@ietf.org>
Description	Multicast Application Port
Reference	This document
Port Number	49149

IANA is requested to update its "Application for Service Names and User Port Numbers" [IANA-APP] to reference this document, ask if the Multicast Application Port may be used, and require an explanation if not. This document does not prohibit future port assignments for multicast applications; the review team still has discretion to approve requests on a case-by-case basis.

7. Acknowledgement

Special thanks to the National Marine Electronics Association for their contributions in developing marine industry standards and their support for this research.

Thanks also to the members of the PIM and INT-AREA working groups for their review of this draft, to Lorenzo Colitti for his suggestions for host requirements, and to Dr. Joe Touch for consulting on port assignment.

8. References

8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

8.2. Informative References

- [IANA-APP] Internet Assigned Numbers Authority, "Application for Service Names and User Port Numbers", <<https://www.iana.org/form/ports-services>>.
- [POSIX] The Open Group, "The Open Group Base Specifications", Issue 7, 2018 edition", December 2001, <<https://pubs.opengroup.org/onlinepubs/9699919799/>>.
- [RFC1122] Braden, R., Ed., "Requirements for Internet Hosts - Communication Layers", STD 3, RFC 1122, DOI 10.17487/RFC1122, October 1989, <<https://www.rfc-editor.org/info/rfc1122>>.

- [RFC3493] Gilligan, R., Thomson, S., Bound, J., McCann, J., and W. Stevens, "Basic Socket Interface Extensions for IPv6", RFC 3493, DOI 10.17487/RFC3493, February 2003, <<https://www.rfc-editor.org/info/rfc3493>>.
- [RFC6335] Cotton, M., Eggert, L., Touch, J., Westerlund, M., and S. Cheshire, "Internet Assigned Numbers Authority (IANA) Procedures for the Management of the Service Name and Transport Protocol Port Number Registry", BCP 165, RFC 6335, DOI 10.17487/RFC6335, August 2011, <<https://www.rfc-editor.org/info/rfc6335>>.
- [RFC7605] Touch, J., "Recommendations on Using Assigned Transport Port Numbers", BCP 165, RFC 7605, DOI 10.17487/RFC7605, August 2015, <<https://www.rfc-editor.org/info/rfc7605>>.
- [RFC9119] Perkins, C., McBride, M., Stanley, D., Kumari, W., and JC. Z炭単 iga, "Multicast Considerations over IEEE 802 Wireless Media", RFC 9119, DOI 10.17487/RFC9119, October 2021, <<https://www.rfc-editor.org/info/rfc9119>>.

Authors' Addresses

Nate Karstens
Garmin International
Email: nate.karstens@gmail.com

Stuart Cheshire
Apple Inc.
Email: cheshire@apple.com

Mike McBride
Futurewei
Email: michael.mcbride@futurewei.com