

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: 7 May 2026

C. Lin
New H3C Technologies
Y. Liu
China Mobile
Y. Liu
ZTE
3 November 2025

Export of QUIC Information in IP Flow Information Export (IPFIX)
draft-lin-opsawg-ipfix-quic-header-03

Abstract

This document introduces new IP Flow Information Export (IPFIX) Information Elements to identify a set of QUIC related information, which contained in QUIC Header, QUIC Frame and Stream that traffic is being forwarded along with.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 7 May 2026.

Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	2
2. Terminology	3
3. New IPFIX QUIC Information Elements	4
4. Sample Use Cases	5
5. Security Considerations	6
6. IANA Considerations	6
6.1. New IPFIX QUIC Information Elements	6
6.1.1. quicHeaderFlag	7
6.1.2. quicVersion	7
6.1.3. quicDestinationConnectionID	8
6.1.4. quicSourceConnectionID	8
6.1.5. quicPacketNumber	9
6.1.6. quicFrameType	9
6.1.7. quicStreamID	9
7. Operational Considerations	10
8. References	10
8.1. Normative References	10
8.2. Informative References	11
Authors' Addresses	11

1. Introduction

QUIC Packets are carried in UDP datagrams and exchanged for communication of QUIC endpoints [RFC9000]. A QUIC packet normally consists of a QUIC Header and a QUIC Payload.

QUIC Header is divided into Long Header and Short Header. Long Headers are used for packets that are sent prior to the establishment of 1-RTT keys. The Long Header contains an 8-bit Public Flag, a 32-bit QUIC Version, a variable-length Destination Connection ID, a variable-length Source Connection ID and Type-Specific field which has different content based on the Packet type. The Packet types that use the Long Header contain Version Negotiation Packet, Initial Packet, 0-RTT Packet, Handshake Packet and Retry Packet. Once 1-RTT keys are available, a sender switches to sending 1-RTT packets using the Short Header. The Short Header includes an 8-bit Public Flag, a variable-length Destination Connection ID and a Packet Number.

QUIC payload MAY contain a sequence of Frames which begin with a Frame Type. In the generic Frame Layout, the Frame Type is followed by additional type-dependent fields. Since Stream in QUIC is the one core component to provide a lightweight, ordered byte-stream abstraction to an application, the Stream ID of Frames related to Stream is an important information that indicates the stream in which the Frame is located or that the Frame affects.

QUIC packets provide varying levels of cryptographic protection depending on their type [RFC9000]. While the entire QUIC payload MUST be encrypted, certain fields in the QUIC Header are not protected, as described in the Section 2.1 of [RFC9312]. For details on QUIC's packet protection mechanisms, refer to Section 5 of [RFC9001]. The protected fields of QUIC packets can only be accessed after successful decryption.

This document specifies several new IPFIX Information Elements (IEs) within the "IPFIX Information Elements" registry [RFC7012] for purposes of getting QUIC related information. These IEs are used to export the main fields of QUIC Header and Payload in QUIC packet. The protected values of some new IEs are accessible exclusively to devices capable of decrypting QUIC packets, specifically, the endpoints of a QUIC connection.

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

This document makes use of the terms defined in [RFC7011] and [RFC9000].

The following terms are used as defined in [RFC7011]:

- * IPFIX
- * IPFIX Information Elements

The following terms are used as defined in [RFC9000]:

- * QUIC
- * Endpoint
- * Server

- * QUIC packet
- * Connection ID
- * Frame
- * Stream

3. New IPFIX QUIC Information Elements

This section specifies the new IPFIX QUIC IEs.

quicHeaderFlag

8-bit flag defined in the QUIC Header (Section 17.2 and 17.3 of [RFC9000]), as the first byte of QUIC Packet. Base on the first four bits of the Long Header flag and the first three bits of the Short Header flag, the QUIC Packet Type can be obtained. the last four bits of the Long Header flag and last five bits of the Short Header flag are protected or encrypted, and the remaining bits are not protected.

quicVersion

32-bit QUIC Version that is in use or negotiation in QUIC Long Header Packets during connection establishment. For Version Negotiation Packet, This Version is used to indicate the Supported Version, because the Version field of a Version Negotiation Packet MUST be set to 0x00000000. The version field is not protected in QUIC packet.

quicDestinationConnectionID

The unprotected Destination Connection ID included in the Long Header or Short Header of QUIC Packet. The Destination Connection ID is chosen by the recipient of the packet and is used to provide consistent routing. Since the length of the Destination Connection ID is not included in 1-RTT Packet (Short Header), the Destination Connection ID of a 1-RTT Packet could be obtained by matching only if when the Destination Connection ID is known and preconfigured on the device.

quicSourceConnectionID

The unprotected Source Connection ID included by the Long Header of QUIC Packet. The Source Connection ID is used to set the Destination Connection ID used by the peer during connection establishment.

quicPacketNumber

The protected Packet Number that appears in some QUIC packet types such as Initial packet, 0-RTT packet and Handshake packet. The

underlying packet number increases with each packet sent in a given packet number space. The Packet Number is an integer in the range 0 to 262-1. When present in a Long or Short Header, packet numbers are reduced and encoded in 1 to 4 bytes.

quicFrameType

The protected Frame Type that indicates the type of Frame contained in the Payload of QUIC Packet. The Frame Type value uses a variable-length integer encoding which means that integers are encoded on 1, 2, 4, or 8 bytes and can encode 6-, 14-, 30-, or 62-bit values, respectively. Some Frame Types are defined in section 12.4 of [RFC9000].

quicStreamID

The protected Stream ID included in the Frame related to Stream such as RESET_STREAM frame, STOP_SENDING frame, STREAM frame and MAX_STREAM_DATA frame. A stream ID is a 62-bit integer (0 to 262-1) that is unique for all streams on a connection. Stream IDs are encoded as variable-length integers, which means that integers are encoded on 1, 2, 4, or 8 bytes and can encode 6-, 14-, 30-, or 62-bit values, respectively. The two least significant bits from a stream ID identify the stream types defined in section 2.1 of [RFC9000].

4. Sample Use Cases

The IPFIX IEs listed in the Section 3, forwardingStatus (89) [RFC7270] and some existing counter information [IANA-IPFIX] provide answers to the following questions (amongst others).

- * How many packets are forwarded or dropped using QUIC in a network?
- * If dropped, for which reasons?
- * What is the type of QUIC packet?
- * What is the QUIC version that is in use or negotiation?
- * What is the Destination or Source Connection ID of QUIC packet?
- * Have all the QUIC packets been fully received?
- * Which frames does the QUIC packet carry?
- * Which stream is the QUIC packet located in?

For Long Header Packet, the following parameters is used to represent a QUIC flow by IPFIX:

- * Five-tuple (protocol, source and destination IP address, source and destination port)
- * Source Connection ID.
- * Destination Connection ID.

Example:

When the Long Packet Type is observed in a Flow during a QUIC connection, Flow information includes:

Five-tuple + Source Connection ID + Destination Connection ID + Header Flag

For Short Header Packet, the following parameters is used to represent a QUIC flow:

- * Five-tuple (protocol, source and destination IP address, source and destination port)
- * Destination Connection ID.

Example:

When the Frame Type is observed in a Flow, Flow information includes:

Five-tuple + Destination Connection ID + Frame Type

When the Stream ID is observed in a Flow, Flow information includes:

Five-tuple + Destination Connection ID + Stream ID

5. Security Considerations

There exists no extra security considerations regarding allocation of these new IPFIX IEs compared to [RFC7012].

6. IANA Considerations

6.1. New IPFIX QUIC Information Elements

This document requests IANA to add new IPFIX QUIC IEs to the "IPFIX Information Elements" registry [RFC7012] available at [IANA-IPFIX].

Table 1 lists the new IPFIX QUIC IEs:

Element ID	Name	Reference
TBD1	quicHeaderFlag	This document
TBD2	quicVersion	This document
TBD3	quicDestinationConnectionID	This document
TBD4	quicSourceConnectionID	This document
TBD5	quicPacketNumber	This document
TBD6	quicFrameType	This document
TBD7	quicStreamID	This document

Table 1: New QUIC IEs in the "IPFIX Information Elements" Registry

6.1.1. quicHeaderFlag

Name: quicHeaderFlag

ElementID: TBD1

Description: The 8-bit flag defined in the QUIC Header (Section 17.2 and 17.3 of [RFC9000]). The meanings of the flag are provided in the first byte of the QUIC Header Packet [RFC9000].

Abstract Data Type: unsigned8

Data Type Semantics: flags

Additional Information: See RFC9000 for the QUIC Header first byte specification.

Reference: [this document]

6.1.2. quicVersion

Name: quicVersion

ElementID: TBD2

Description: 32-bit unsigned integer defining the number of Version, which is in use and negotiation. Its values are provided in the "QUIC Versions" IANA registry.

Abstract Data Type: unsigned32

Data Type Semantics: default

Additional Information: See the assignments in the "QUIC Versions" IANA registry at <https://www.iana.org/assignments/quic/quic.xhtml#quic-versions>. See also RFC9000 for the QUIC Versions specification.

Reference: [this document]

6.1.3. quicDestinationConnectionID

Name: quicDestinationConnectionID

ElementID: TBD3

Description: The Destination Connection ID as defined in Section 7.2 of [RFC9000] as a series of octets in IPFIX. In QUIC version 1, this value MUST NOT exceed 20 bytes.

Abstract Data Type: octetArray

Data Type Semantics: default

Additional Information: See Section 7.2 of [RFC9000] for more details about The Destination Connection ID.

Reference: [this document]

6.1.4. quicSourceConnectionID

Name: quicSourceConnectionID

ElementID: TBD4

Description: The Source Connection ID as defined in Section 7.2 of [RFC9000] as a series of octets in IPFIX. In QUIC version 1, this value MUST NOT exceed 20 bytes.

Abstract Data Type: octetArray

Data Type Semantics: default

Additional Information: See Section 7.2 of [RFC9000] for more details about The Source Connection ID.

Reference: [this document]

6.1.5. quicPacketNumber

Name: quicPacketNumber

ElementID: TBD5

Description: 8~32-bit unsigned integer defining the packet number of QUIC Header, which is used in determining the cryptographic nonce for packet protection.

Abstract Data Type: unsigned32

Data Type Semantics: default

Additional Information: See Section 12.3 of [RFC9000] for more details about The Packet Number.

Reference: [this document]

6.1.6. quicFrameType

Name: quicFrameType

ElementID: TBD6

Description: 62-bit unsigned integer defining the value of Frame Type, which indicates the type of QUIC Frame. Its values are provided in the "QUIC Frame Types" IANA registry.

Abstract Data Type: unsigned64

Data Type Semantics: default

Additional Information: See the assignments in the "QUIC FrameTypes" IANA registry at <https://www.iana.org/assignments/quic/quic.xhtml#quic-frame-types>. See also RFC9000 for the Frame Types specification of QUIC.

Reference: [this document]

6.1.7. quicStreamID

Name: quicStreamID

ElementID: TBD7

Description: 62-bit unsigned integer defining the value of Stream

ID, which identifies a Stream. The two least significant bits from a stream ID identify the stream types defined in section 2.1 of [RFC9000].

Abstract Data Type: unsigned64

Data Type Semantics: identifier

Additional Information: See Section 2.1 of [RFC9000] for more details about The Stream ID.

Reference: [this document]

7. Operational Considerations

The quicDestinationConnectionID can be used to track flow path consistency, but the Destination Connection ID in the Short Header Packet lacks a length indication, making it difficult to match on intermediate devices. Therefore, the Destination Connection ID or its length must be preconfigured on the intermediate devices.

The protected packet fields must be decrypted before they can be obtained. quicHeaderFlag, quicVersion, quicDestinationConnectionID, and quicSourceConnectionID can be obtained in all on-path devices. quicPacketNumber, quicFrameType, and quicStreamID can be obtained in endpoint devices or on-path devices which are capable of decrypting QUIC packets.

8. References

8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC7011] Claise, B., Ed., Trammell, B., Ed., and P. Aitken, "Specification of the IP Flow Information Export (IPFIX) Protocol for the Exchange of Flow Information", STD 77, RFC 7011, DOI 10.17487/RFC7011, September 2013, <<https://www.rfc-editor.org/info/rfc7011>>.
- [RFC7012] Claise, B., Ed. and B. Trammell, Ed., "Information Model for IP Flow Information Export (IPFIX)", RFC 7012, DOI 10.17487/RFC7012, September 2013, <<https://www.rfc-editor.org/info/rfc7012>>.

- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC9000] Iyengar, J., Ed. and M. Thomson, Ed., "QUIC: A UDP-Based Multiplexed and Secure Transport", RFC 9000, DOI 10.17487/RFC9000, May 2021, <<https://www.rfc-editor.org/info/rfc9000>>.
- [RFC9001] Thomson, M., Ed. and S. Turner, Ed., "Using TLS to Secure QUIC", RFC 9001, DOI 10.17487/RFC9001, May 2021, <<https://www.rfc-editor.org/info/rfc9001>>.

8.2. Informative References

- [IANA-IPFIX] "IANA, "IP Flow Information Export (IPFIX) Entities"", <<https://www.iana.org/assignments/ipfix/ipfix.xhtml>>.
- [RFC7270] Yourtchenko, A., Aitken, P., and B. Claise, "Cisco-Specific Information Elements Reused in IP Flow Information Export (IPFIX)", RFC 7270, DOI 10.17487/RFC7270, June 2014, <<https://www.rfc-editor.org/info/rfc7270>>.
- [RFC9312] Kuehlewind, M. and B. Trammell, "Manageability of the QUIC Transport Protocol", RFC 9312, DOI 10.17487/RFC9312, September 2022, <<https://www.rfc-editor.org/info/rfc9312>>.

Authors' Addresses

Changwang Lin
New H3C Technologies
8 Yongjia North Road
Beijing
Haidian District, 100094
China
Email: linchangwang.04414@h3c.com

Yisong Liu
China Mobile
32 Xuanwumen West Street
Beijing
Xicheng District, 100053
China
Email: liuyisong@chinamobile.com

Yao Liu
ZTE
Nanjing
China
Email: liu.yao71@zte.com.cn