

Internet Engineering Task Force
Internet-Draft
Intended status: Informational
Expires: 26 September 2026

ssw. Whited, Ed.
25 March 2026

Matroska Stem Files
draft-swhited-mka-stems-05

Abstract

This document defines a multi-track profile of the Matroska container format for storing stems for use by DJ applications while remaining backwards compatible with existing media players.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 26 September 2026.

Copyright Notice

Copyright (c) 2026 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

Table of Contents

1. Introduction	2
1.1. Requirements Language	2
2. Requirements	2
3. Track Layout	3
3.1. Audio Streams	3
4. Digital Signal Processor	4
4.1. Compressor Metadata	5
4.2. Limiter Metadata	5
5. IANA Considerations	5
6. Security Considerations	6
7. Normative References	6
8. Informative References	6
Acknowledgements	7
Author's Address	7

1. Introduction

Stem are recordings of individual instruments, or clusters of instruments, used by DJs and music producers for live mixing of music. Historically stem files have been stored as individual audio files, or using patent-encumbered or vendor specific proprietary container formats. The Matroska container format formally specified in [RFC9559] is ideally situated as a container for stems.

This specification documents a profile for the Matroska container format that allows it to store lossless or lossy stems as well as metadata about the stems and mastering information in a single file for use in DJ applications.

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

2. Requirements

STEM files have a few basic requirements:

- * Backwards compatibility with existing media players
- * The ability to store multiple audio track
- * The ability to store file-level metadata and track-level metadata

- * Backwards compatibility when additional tracks have unknown formats that cannot be decoded

3. Track Layout

3.1. Audio Streams

Each stem file may contain an arbitrary number of tracks containing audio and MUST include at least three audio tracks (the mixed audio and at least two stems). For stem files meant for live DJ use, it is RECOMMENDED that four or fewer stem tracks be used (as opposed to stem files meant for music production where a DAW may have a significantly larger number of tracks). For ease of decoding each track SHOULD be encoded using the same codec with the same parameters including bitrate, channel layout, and sample rate. Stems are often recorded with a single channel and only the final mix is in stereo. Stems MAY have a different channel count or layout than the main audio track.

The first track containing audio data MUST be the final post-mix audio in the default language. All tracks containing the final post-mix audio regardless of language MUST have the Matroska "Default" flag set to "1" ([RFC9559], Section 18.1, 5.1.4.1.5). This helps preserve backwards compatibility in media players which do not support this format which typically play the first audio stream found or may select based on the default flag. In addition, the "Enabled" flag for any main tracks MUST be set to "1" ([RFC9559], Section 5.1.4.1.4).

The remaining audio tracks will be individual stems and MUST have the same effective length as the first track such that playing each stem track from the beginning would result in the same audio (excluding mastering) as the final mix present in the first track. For example, if the original track is three minutes long and the stem file includes a percussion track but the percussion does not start until minute two the percussion stem would still be three minutes long but would contain a minute of silence at the start of the track, or would have a block timestamp ([RFC9559], Section 10) that sets the effective start time to one minute.

Each stem track MUST NOT have the Matroska "Default" flag set to "1" (it MAY be set to "0" or unset) and MUST have the "Enabled" flag set to "0".

The stem tracks SHOULD NOT have any gain normalization applied. Instead they should retain the same levels as they would have in the final mix present in the first track so that if all stems were played at unity gain the levels would be equivalent to the final mix.

Each stem track (ie. all tracks that are not the first track) MUST set the value of the \Segment\Tracks\TrackEntry\Name field ([RFC9559], Section 5.1.4.1.18) to a human-readable track name for the stem, for example "Percussion" or "Vocals".

For each stem track a \Segment\Tags\Tag ([RFC9559], Section 5.1.8) SHOULD also be set with its target set to the stem track. The tag, if present, MUST contain a SimpleTag element with the TagName field set to "STEM_COLOR" and the TagString field set to a color representing the track in RGB hex format (ie. "#145374").

4. Digital Signal Processor

Because mastering happens post-mix and the stems are pre-mix audio the stem tracks SHOULD NOT have any mastering steps applied. Instead, metadata for configuring a compressor and limiter SHOULD be included in the file's global metadata as simple tags (see Section 5.1.8.1.2 of [RFC9559]). After mixing, playback applications MAY choose to feed the mix through a Digital Signal Processor (DSP) configured with the limiter and compressor settings read from the metadata.

Each binary setting for the compressor or limiter is stored as a floating-point number in the 32-bit and 64-bit binary interchange format, as defined in [IEEE_754_2019] with the additional restriction that they are limited to a minimum value of 0.0 and a maximum value of 1.0. Because different DSPs may use different ranges or scales for each value the playback software SHOULD interpret the 0-1 values as a linear scale and map them to the range and scale required by the DSP when configuring the DSP for playback. This may result in a loss of fidelity on some DSPs, but this is deemed an acceptable trade off for stem playback which would not normally be able to have a mastering step at all.

During production of a stem track, vendor specific metadata MAY be embedded in the Matroska file for more accurately configuring a specific DSP, but if such metadata is included the scaled values SHOULD also be present for those without access to the specific DSP used for the track and such metadata MUST select tag names in such a way that they do not conflict with the tag names defined for the generic compressor or limiter.

4.1. Compressor Metadata

Tag Name	Type	Values
COMPRESSOR_ENABLED	UTF-8	"TRUE" or "FALSE"
COMPRESSOR_RATIO	binary	0.0-1.0
COMPRESSOR_OUTPUT_GAIN	binary	0.0-1.0
COMPRESSOR_THRESHOLD	binary	0.0-1.0
COMPRESSOR_ATTACK	binary	0.0-1.0
COMPRESSOR_INPUT_GAIN	binary	0.0-1.0
COMPRESSOR_RELEASE	binary	0.0-1.0
COMPRESSOR_HP_CUTOFF	binary	0.0-1.0
COMPRESSOR_HP_DRY_WET	binary	0.0-1.0

Table 1: Compressor metadata tags

4.2. Limiter Metadata

Tag Name	Type	Values
LIMITER_ENABLED	UTF-8	"TRUE" or "FALSE"
LIMITER_RELEASE	binary	0.0-1.0
LIMITER_THRESHOLD	binary	0.0-1.0
LIMITER_CEILING	binary	0.0-1.0

Table 2: Limiter metadata tags

5. IANA Considerations

This memo modifies the "Matroska Tag Names" registry to add the following values:

Tag Name	Tag Type	Reference
STEM_COLOR	UTF-8	This document, Section 3.1
COMPRESSOR_ENABLED	UTF-8	This document, Section 4.1
COMPRESSOR_RATIO	binary	This document, Section 4.1
COMPRESSOR_OUTPUT_GAIN	binary	This document, Section 4.1
COMPRESSOR_THRESHOLD	binary	This document, Section 4.1
COMPRESSOR_ATTACK	binary	This document, Section 4.1
COMPRESSOR_INPUT_GAIN	binary	This document, Section 4.1
COMPRESSOR_RELEASE	binary	This document, Section 4.1
COMPRESSOR_HP_CUTOFF	binary	This document, Section 4.1
COMPRESSOR_HP_DRY_WET	binary	This document, Section 4.1
LIMITER_ENABLED	UTF-8	This document, Section 4.2
LIMITER_RELEASE	binary	This document, Section 4.2
LIMITER_THRESHOLD	binary	This document, Section 4.2
LIMITER_CEILING	binary	This document, Section 4.2

Table 3: Additions to the "Matroska Tag Names" Registry

6. Security Considerations

This document should not affect the security of the Internet.

7. Normative References

- [RFC9559] Lhomme, S., Bunkus, M., and D. Rice, "Matroska Media Container Format Specification", RFC 9559, DOI 10.17487/RFC9559, October 2024, <<https://www.rfc-editor.org/info/rfc9559>>.

8. Informative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [IEEE_754_2019] IEEE, "IEEE Standard for Floating-Point Arithmetic", IEEE IEEE 754-2019, DOI 10.1109/IEEESTD.2019.8766229, 18 July 2019, <<https://ieeexplore.ieee.org/document/8766229>>.

Acknowledgements

Thanks to the members of #matroska, and mosu in particular, on the libera.chat IRC network for patiently explaining the basics of the format to me. Also to the members of the IETF CELLAR working group, especially Steve Lhomme, for their feedback.

Author's Address

Sam Whited (editor)
Email: sam@samwhited.com
URI: <https://blog.samwhited.com>