

Network Working Group

Internet-Draft

Updates: rfc4007, rfc5889, rfc6724 (if approved)

Intended status: Standards Track

Expires: 5 May 2026

F. L. Templin, Ed.

Boeing Research & Technology

1 November 2025

IPv6 Addresses for Ad Hoc Networks
draft-templin-6man-mla-29

Abstract

Ad Hoc networks present an IPv6 addressing challenge due to the undetermined neighborhood properties of their interfaces. IPv6 nodes must assign locally-unique and topology-independent IPv6 addresses when topology-oriented IPv6 address delegation services are either absent or only intermittently available. This document introduces a new IPv6 address type (termed the "Multilink Local Address (MLA)") that nodes can autonomously assign to interfaces to support Ad Hoc network operations.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 5 May 2026.

Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components

extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	2
2. IPv6 Ad Hoc Network Local Addressing	4
3. Assigning an MLA to an Interface	5
4. MLAs in the Scoped Addressing Architecture	5
5. MLAs for Ad Hoc Networks	6
6. Address Selection	7
7. Requirements	7
8. Implementation Status	8
9. IANA Considerations	8
10. Security Considerations	8
11. Acknowledgements	8
12. References	9
12.1. Normative References	9
12.2. Informative References	9
Appendix A. Change Log	11
Author's Address	12

1. Introduction

When two or more IPv6 [RFC8200] nodes come together to form an Ad Hoc network, they must be able to assign unique addresses to their interfaces and exchange IPv6 packets with peers even if there is no Internetworking infrastructure present. A classical example is a Mobile Ad-hoc Network (MANET) where wireless nodes within a common radio frequency locality discover multihop routes to support peer-to-peer communications. However, arbitrary collections of fixed nodes interconnected by sparse collections of physical links also qualify. See [RFC5889] for further characteristics of Ad Hoc networks.

Ad Hoc networks often include IPv6 nodes that configure interface attachments to links with undetermined connectivity properties such that multihop traversal may be necessary to span the network. The transitive property of connectivity for conventional shared media links is therefore not assured, while nodes must still be able to configure IPv6 addresses that are unique within the local Ad Hoc network. This is true even for nodes that configure multiple interface attachments to the same Ad Hoc network as a localized multihop/multilink forwarding domain.

By its nature, the term "Ad Hoc network" implies logical groupings whereas the historical term "site" suggested physical boundaries such as a building or a campus. In particular, Ad Hoc networks can self-

organize autonomously even if they overlap with other (logical) networks, split apart to form multiple smaller networks or join together to form larger networks. Clustering has been suggested as a means to organize these logical groupings, noting that Ad Hoc network ecosystems are often in a constant state of flux and likely to change over time. An address type that can be used by nodes that roam freely between logical Ad Hoc network boundaries is therefore necessary.

The term "Ad Hoc" used throughout this document extends to include isolated local IPv6 networks where peer to peer communications may require multihop and/or multilink traversal regardless of whether the network is particularly mobile or spontaneously organized. For any such isolated network (i.e., one for which Internetworking proxy/servers are either absent or only intermittently available), a topology-independent IPv6 addressing scheme that allows peer nodes to communicate internally is necessary. Therefore, all nodes that connect to such isolated IPv6 networks should be prepared to operate according to this multilink Ad Hoc addressing model when necessary. Each node then coordinates multihop forwarding services at an IPv6-based architectural sublayer termed the "adaptation layer" below the Internetworking layer but above the true link layer.

Section 6 of the "IP Addressing Model in Ad Hoc Networks" [RFC5889] states that: "an IP address configured on this (Ad Hoc) interface should be unique, at least within the routing domain" and: "no on-link subnet prefix is configured on this (Ad Hoc) interface". The section then continues to explain why IPv6 Link-Local Addresses (LLAs) are of limited utility on links with undetermined connectivity, to the point that they cannot be used exclusively within Ad Hoc network domains. (Note that [RFC5498] provides IANA allocations for MANET protocols as a complementary publication.)

[RFC5889] suggests Global Unicast [RFC4291] (aka "GUA") and Unique-Local [RFC4193] (aka "ULA") addresses as Ad Hoc network addressing candidates. However, GUAs and ULAs are topology-oriented address types that must be obtained through either administrative actions or an address autoconfiguration service based on IPv6 proxy/servers that connect Ad Hoc networks to larger Internetworks. (In particular topology-oriented address types are typically obtained through DHCPv6 messages and/or Router Advertisement Prefix Information Options with prefix length shorter than 128.) Since such Internetworking services may not always be available, however, this document asserts that a topology-independent and unique Ad Hoc network local IPv6 address type is needed. The address type may include multiple sub-types, some of which may be coordinated with address registration services and others that may be partially or fully self-generated.

The key feature of these Ad Hoc network adaptation layer IPv6 addresses is that they must have excellent statistical uniqueness properties such that there is little/no chance of conflicting with an address assigned by another node. The addresses need not include topology-oriented prefixes, since the (newly-formed) Ad Hoc networks may not (yet) connect to established Internetworking topologies.

Ad Hoc network nodes must be able to use adaptation layer IPv6 addresses for continuous local communications and/or to coordinate topology-oriented addresses for assignment on other interfaces. A new "Multilink Local" scope for the IPv6 scoped addressing architecture [RFC4007] with scope greater than LLA but lesser than ULA/GUA is therefore needed. This document therefore defines a new unique local unicast address variant known as the "Multilink Local Address (MLA)".

Candidate MLA examples are found in [RFC7343][RFC9374][RFC9602]. The IPv6 address assignment policy is clarified in [RFC9812].

2. IPv6 Ad Hoc Network Local Addressing

The IPv6 addressing architecture specified in [RFC4007], [RFC4193] and [RFC4291] defines the supported IPv6 unicast/multicast/anycast address types with various scopes. ULAs and GUAs are typically obtained through Stateless Address AutoConfiguration (SLAAC) [RFC4862] and/or the Dynamic Host Configuration Protocol for IPv6 (DHCPv6) [RFC8415], but these services require the presence of IPv6 Internetworking infrastructure which may not be continuously or even intermittently available in spontaneously-formed Ad Hoc networks.

Interface attachments to Ad Hoc networks have the interesting property that a multihop router R will often need to forward packets between nodes A and B even though R uses the same interface in the inbound and outbound directions. Since nodes A and B may not be able to communicate directly even though both can communicate directly with R, the transitive property for link connectivity does not apply and the IPv6 Neighbor Discovery (ND) Redirect service cannot be used. Conversely, R may need to forward packets between nodes A and B via different interfaces within an Ad Hoc network that includes multiple distinct links/regions. Due to these indeterminant multilink properties, exclusive use of IPv6 LLAs is also out of scope.

This document therefore introduces a new IPv6 MLA address type based on one or more well-formed IPv6 prefixes "TBD::/N" (see: IANA Considerations). After a node creates an MLA, it can use the address within the context of spontaneously-organized Ad Hoc networks in which two or more nodes come together in the absence of stable supporting infrastructure and can still exchange IPv6 packets with

little or no chance of address collisions. The node can limit MLA usage to bootstrapping the assignment of topology-oriented IPv6 addresses through other means mentioned earlier. The node can instead extend its MLA usage to longer term patterns such as sustained communications with single-hop neighbors on a local link or even between Ad Hoc network multihop peers.

3. Assigning an MLA to an Interface

IPv6 MLAs are topology-independent and can therefore be assigned to a virtual interface of the node with a /128 prefix length (i.e., as a singleton address). The node can then begin to use an MLA as the Source/Destination Address of IPv6 packets that are forwarded over an interface attachment to an Ad Hoc network multihop forwarding region.

A node can specifically assign an MLA to a loopback interface to support the operation of Ad Hoc network routing protocols and also to an Overlay Multilink Network (OMNI) Interface [I-D.templin-6man-omni3] to support extended communications with remote peers over an OMNI virtual link.

MLAs may then serve as a basis for multihop forwarding and/or for local neighborhood discovery over other IPv6 interface types. Due to their uniqueness properties, the node can assign MLAs as optimistic addresses per [RFC4429], however it should take actions to deconflict if it detects in-service duplication.

4. MLAs in the Scoped Addressing Architecture

With reference to a debate that concluded in the earliest years of the third millennium, a case could be made for reclaiming the deprecated site-local address prefix "fec0::/10" for use as a top-level MLA prefix. However, some implementations still honor the deprecation and continue to regard the prefix as a defunct historical artifact.

[RFC3879] documents the deprecation rationale including the assertion that "Site is an Ill-Defined Concept". However, the concept of an Ad Hoc network is a coherent logical one based on time-varying (multilink) connectivity and not necessarily one constrained by physical boundaries. Especially in Ad Hoc networks that employ a proactive local routing protocol the list of available adaptation layer addresses in each network is continuously updated for temporal consistency.

For example, an IPv6 node may connect to multiple distinct Ad Hoc networks with a first set of interfaces connected to network "A", a second set of interfaces connected to network "B", etc. According to

the scoped IPv6 addressing architecture [RFC4007], the node would assign a separate MLA to virtual interfaces associated with each Ad Hoc network interface set A, B, etc. and maintain separate Ad Hoc network multihop routing protocol instances for each set. MLAs A, B, etc. then provide a basis for unique router IDs for the separate routing protocol instances, but the IPv6 node may elect to redistribute discovered adaptation layer routes between the instances. The uniqueness properties of MLAs must therefore transcend logical Ad Hoc network boundaries but without "leaking" into external networks.

A means for entering Ad Hoc network local IPv6 Zone Identifiers in user interfaces is necessary according to [RFC9844]. Examples of an Ad Hoc network local unicast address qualified by a zone identifier are as follows:

```
TBD::884e:9d2a:73fc:2d94%netA
```

```
TBD::c63d:9724:fca:1237%netB
```

This document updates the IPv6 scoped addressing architecture [RFC4007] by introducing a "Multilink-Local" unicast addressing scope. In particular, this document adds a third unicast address scope to Section 4 of [RFC4007] as follows:

- * Multilink-Local scope, for uniquely identifying a node's attached Ad Hoc networks.

The size relationship among scopes is further updated as:

- * For unicast scopes, link-local is a smaller scope than Multilink-Local, which is a smaller scope than global.

In [RFC4007], Section 5 under: "Zones of the different scopes are instantiated as follows", add the new bullet:

- * Each Ad Hoc network and the interfaces attached to that Ad Hoc network comprise a single zone of Multilink-Local scope (for unicast).

5. MLAs for Ad Hoc Networks

This document updates [RFC5889] to add a new address type "Multilink-Local" to the list of IPv6 address types found in Section 1 as:

- * For IPv6, these addresses may be global [RFC3587], Unique-Local [RFC4193], Multilink-Local [RFCXXXX] or Link-Local [RFC4291].

6. Address Selection

"Default Address Selection for Internet Protocol Version 6 (IPv6)" [RFC6724] provides a policy table that specifies precedence values and preferred Source Address prefixes for specific Destination Addresses. "Preference for IPv6 ULAs over IPv4 addresses in RFC6724" [I-D.ietf-6man-rfc6724-update] updates the policy table entries for ULAs, IPv4 Addresses and the 6to4 prefix (2002::/16).

This document proposes a further update to the policy table for IPv6 MLAs. The proposed update appears in the table below:

draft-ietf-6man-rfc6724-update			Updated		
Prefix	Precedence	Label	Prefix	Precedence	Label
::1/128	50	0	::1/128	50	0
::/0	40	1	::/0	40	1
::ffff:0:0/96	20	4	::ffff:0:0/96	20	4
2002::/16	5	2	2002::/16	5	2
2001::/32	5	5	2001::/32	5	5
fc00::/7	30	13	fc00::/7	30	13
::/96	1	3	::/96	1	3
fec0::/10	1	11	fec0::/10	1	11
3ffe::/16	1	12	3ffe::/16	1	12
			TBD::/N	4	14 (*)

(*) value(s) changed in update

Figure 1: Policy Table Update for Multilink Local Addresses

With the proposed updates, this new MLA address type appears as a lesser precedence than IPv6 GUAs, IPv6 ULAs and IPv4 addresses but as a greater precedence than deprecated IPv6 prefixes.

7. Requirements

IPv6 nodes assign unique MLAs to an IPv6 virtual interface (e.g., an OMNI interface) configured over underlying interface attachments to Ad Hoc networks. If the node becomes aware that a tentative self-generated MLA is already in use by another node, it instead generates and assigns a new MLA. If the node becomes aware that an MLA for which it holds a certificate through an official registration service is already in use by another node, it should log and report the incident to the registration service authority.

IPv6 routers MAY forward IPv6 packets with adaptation layer MLA Source or Destination Addresses over multiple hops within the same Ad Hoc network as an adaptation layer function.

IPv6 routers MUST NOT forward packets with adaptation layer MLA Source or Destination Addresses to a link outside the packet's Ad Hoc network of origin, although MLAs MAY occur as network layer IPv6 Source or Destination Addresses in packets forwarded between disjoint MANETs via the virtual overlay.

8. Implementation Status

In progress.

9. IANA Considerations

IANA considerations will be updated with specific requirements for MLA delegations prior to publication.

10. Security Considerations

IPv6 MLAs include very large uniquely-assigned bit strings in both the prefix and interface identifier components which together provide ample uniqueness properties.

With the random generation procedures expected for the various MLA types, the only apparent opportunity for MLA duplication would be through either intentional or unintentional misconfiguration.

Certain MLA types may have cryptographically generated portions tied to a certificate with the node's public key while other portions of the address identify a registration service where address proof-of-ownership can be confirmed. This stands in contrast to autonomously assigned and fully self-generated MLAs while relying entirely on statistical uniqueness properties.

An IPv6 node that configures an MLA and assigns it to a virtual interface with an optimistic expectation of uniqueness should therefore be prepared to deconflict legitimate duplications.

11. Acknowledgements

This work was inspired by continued investigations into 5G MANET operations in cooperation with the Virginia Tech National Security Institute (VTNSI).

Emerging discussions both in-person and on the IPv6 maintenance (6man) and MANET mailing lists continue to shape updated versions of this document. The author acknowledges all those whose useful comments have helped further the understanding of this proposal.

Honoring life, liberty and the pursuit of happiness.

12. References

12.1. Normative References

- [RFC4007] Deering, S., Haberman, B., Jinmei, T., Nordmark, E., and B. Zill, "IPv6 Scoped Address Architecture", RFC 4007, DOI 10.17487/RFC4007, March 2005, <<https://www.rfc-editor.org/info/rfc4007>>.
- [RFC4193] Hinden, R. and B. Haberman, "Unique Local IPv6 Unicast Addresses", RFC 4193, DOI 10.17487/RFC4193, October 2005, <<https://www.rfc-editor.org/info/rfc4193>>.
- [RFC4291] Hinden, R. and S. Deering, "IP Version 6 Addressing Architecture", RFC 4291, DOI 10.17487/RFC4291, February 2006, <<https://www.rfc-editor.org/info/rfc4291>>.
- [RFC5889] Baccelli, E., Ed. and M. Townsley, Ed., "IP Addressing Model in Ad Hoc Networks", RFC 5889, DOI 10.17487/RFC5889, September 2010, <<https://www.rfc-editor.org/info/rfc5889>>.
- [RFC6724] Thaler, D., Ed., Draves, R., Matsumoto, A., and T. Chown, "Default Address Selection for Internet Protocol Version 6 (IPv6)", RFC 6724, DOI 10.17487/RFC6724, September 2012, <<https://www.rfc-editor.org/info/rfc6724>>.
- [RFC8200] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", STD 86, RFC 8200, DOI 10.17487/RFC8200, July 2017, <<https://www.rfc-editor.org/info/rfc8200>>.

12.2. Informative References

- [I-D.ietf-6man-rfc6724-update] Buraglio, N., Chown, T., and J. Duncan, "Prioritizing known-local IPv6 ULAs through address selection policy", Work in Progress, Internet-Draft, draft-ietf-6man-rfc6724-update-25, 11 August 2025, <<https://datatracker.ietf.org/doc/html/draft-ietf-6man-rfc6724-update-25>>.
- [I-D.templin-6man-aero3] Templin, F., "Automatic Extended Route Optimization (AERO)", Work in Progress, Internet-Draft, draft-templin-6man-aero3-47, 20 October 2025, <<https://datatracker.ietf.org/doc/html/draft-templin-6man-aero3-47>>.

`[I-D.templin-6man-omni3]`

Templin, F. L., "Transmission of IP Packets over Overlay Multilink Network (OMNI) Interfaces", Work in Progress, Internet-Draft, draft-templin-6man-omni3-66, 1 November 2025, <<https://datatracker.ietf.org/doc/html/draft-templin-6man-omni3-66>>.

- [RFC3879] Huitema, C. and B. Carpenter, "Deprecating Site Local Addresses", RFC 3879, DOI 10.17487/RFC3879, September 2004, <<https://www.rfc-editor.org/info/rfc3879>>.
- [RFC4429] Moore, N., "Optimistic Duplicate Address Detection (DAD) for IPv6", RFC 4429, DOI 10.17487/RFC4429, April 2006, <<https://www.rfc-editor.org/info/rfc4429>>.
- [RFC4862] Thomson, S., Narten, T., and T. Jinmei, "IPv6 Stateless Address Autoconfiguration", RFC 4862, DOI 10.17487/RFC4862, September 2007, <<https://www.rfc-editor.org/info/rfc4862>>.
- [RFC5498] Chakeres, I., "IANA Allocations for Mobile Ad Hoc Network (MANET) Protocols", RFC 5498, DOI 10.17487/RFC5498, March 2009, <<https://www.rfc-editor.org/info/rfc5498>>.
- [RFC6296] Wasserman, M. and F. Baker, "IPv6-to-IPv6 Network Prefix Translation", RFC 6296, DOI 10.17487/RFC6296, June 2011, <<https://www.rfc-editor.org/info/rfc6296>>.
- [RFC7343] Laganier, J. and F. Dupont, "An IPv6 Prefix for Overlay Routable Cryptographic Hash Identifiers Version 2 (ORCHIDv2)", RFC 7343, DOI 10.17487/RFC7343, September 2014, <<https://www.rfc-editor.org/info/rfc7343>>.
- [RFC8415] Mrugalski, T., Siodelski, M., Volz, B., Yourtchenko, A., Richardson, M., Jiang, S., Lemon, T., and T. Winters, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", RFC 8415, DOI 10.17487/RFC8415, November 2018, <<https://www.rfc-editor.org/info/rfc8415>>.
- [RFC9374] Moskowitz, R., Card, S., Wiethuechter, A., and A. Gurtov, "DRIP Entity Tag (DET) for Unmanned Aircraft System Remote ID (UAS RID)", RFC 9374, DOI 10.17487/RFC9374, March 2023, <<https://www.rfc-editor.org/info/rfc9374>>.
- [RFC9602] Krishnan, S., "Segment Routing over IPv6 (SRv6) Segment Identifiers in the IPv6 Addressing Architecture", RFC 9602, DOI 10.17487/RFC9602, October 2024, <<https://www.rfc-editor.org/info/rfc9602>>.

- [RFC9812] Carpenter, B., Krishnan, S., and D. Farmer, "Clarification of IPv6 Address Allocation Policy", BCP 242, RFC 9812, DOI 10.17487/RFC9812, October 2025, <<https://www.rfc-editor.org/info/rfc9812>>.
- [RFC9844] Carpenter, B. and R. Hinden, "Entering IPv6 Zone Identifiers in User Interfaces", RFC 9844, DOI 10.17487/RFC9844, August 2025, <<https://www.rfc-editor.org/info/rfc9844>>.

Appendix A. Change Log

<< RFC Editor - remove prior to publication >>

Differences from earlier versions:

Draft -28 to -29

- * Updated abstract, introduction and references.

Draft -27 to -28

- * Removed section on "Obtaining and Assigning IPv6 ULAs/GUAs" as out of scope for this document.
- * Version update.

Draft -26 to -27

- * Significant updates to requirements.
- * Relaxed "1x1" assignment of MLAs to a single MANET.
- * Included references for candidate MLA types.

Draft -24 to -26

- * Stress address deconfliction instead of deprecation when address duplication is detected.
- * Security considerations for MLA types that support remote attestation.
- * Discussion of site as an ill-defined concept in contrast to "Multilink Local Scope".

Draft -23 to -24

- * Change reference to RFC6296.
- * Added more explanation about Ad Hoc Networks.

- * MLAs now assigned only to a virtual interface associated with the Ad-Hoc network and not the physical interfaces themselves.
- * Added specifics of how this document updates other RFCs.

Author's Address

Fred L. Templin (editor)
Boeing Research & Technology
P.O. Box 3707
Seattle, WA 98124
United States of America
Email: fltemplin@acm.org