

IVY Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: 12 July 2026

C. Yu  
Huawei  
A. Guo  
Futurewei  
I. Busi  
Huawei  
M. Boroon  
Highstreet  
S. Belotti  
T.V. Caenegem  
S.I. S.  
S. B.  
Nokia  
N. Davis  
Ciena  
M. Tilocca  
FiberCop  
B. Peters  
NBN  
B.Y. Yun  
ETRI  
Y. Liu  
Y. Zhao  
China Mobile  
A. Sakalabhaktula  
Radisys  
8 January 2026

A YANG Data Model for Passive Network Inventory  
draft-ygb-ivy-passive-network-inventory-03

Abstract

This document presents a YANG data model for tracking and managing passive network inventory. The model enhances the base model outlined in [I-D.draft-ietf-ivy-network-inventory-yang] and is intended for use in the northbound interface of a domain controller as defined in [RFC8453].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 12 July 2026.

## Copyright Notice

Copyright (c) 2026 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

## Table of Contents

1. Introduction . . . . .	3
2. Examples of Passive Network Inventory . . . . .	3
2.1. Passive Infrastructure in Optical Transport Networks . . . . .	4
2.2. Passive Infrastructure in Optical Access Networks . . . . .	5
2.3. Passive Infrastructure in Microwave Networks . . . . .	6
3. Terminology and Notations . . . . .	6
3.1. Requirements Notations . . . . .	6
3.2. Terminology . . . . .	6
3.3. Tree Diagram . . . . .	7
3.4. Prefixes in Data Node Names . . . . .	8
4. Modeling Considerations . . . . .	8
4.1. Relationship with Network Inventory . . . . .	8
4.2. Relationship with Topology . . . . .	8
5. YANG Model Overview . . . . .	8
6. Model Tree Diagram . . . . .	8
7. YANG Modules . . . . .	10
7.1. YANG Data Model for Passive Device Inventory . . . . .	10
8. Manageability Considerations . . . . .	21
9. Security Considerations . . . . .	21
10. IANA Considerations . . . . .	22

11. Normative References . . . . .	22
Authors' Addresses . . . . .	24

## 1. Introduction

Passive infrastructure refers to the underlying infrastructure of a telecommunication network that is not actively detectable or manageable. It typically includes non-powered, non-communicating devices and components, such as cabinets, cables, connectors, splitters, antennas, distribution frames, etc., that are either hosted within an actively managed device or deployed along the physical pathway between active devices. Passive infrastructure serves as physical connections between active network devices, forming the backbone for network topology. As a crucial part of communication networks, the inventory information for these devices is also essential for inventory management.

[I-D.draft-ietf-ivy-network-inventory-yang] incorporates the component concept from [RFC8348] to detail the equipment and holder information of a NE. This encompasses chassis, slot/sub-slot, board/sub-board, port, and transceiver. As these items are recognized by the NE through internal protocols, the passive devices that cannot be discovered by the NE are thus not included in the modeling and needs to be addressed.

[I-D.draft-ietf-ivy-network-inventory-location] emphasizes the relative and geographic location, e.g. equipment room, geo-location for NE. A passive device is deployed in a certain location visible by the operator, and thus can reference the location defined by [I-D.draft-ietf-ivy-network-inventory-location].

This document focuses on modeling passive device inventory. The scope of this model is intended to be applicable to a variety types of networks, including but not limited to, IP/MPLS, optical access, optical transport and microwave networks. The methods for learning about these devices are implementation-specific and fall outside the scope of this document.

## 2. Examples of Passive Network Inventory

Network segments built on different technologies share many common passive infrastructure components across the system. To explore the practical applications of these components, we can examine example scenarios for optical access networks, optical transport systems, and microwave networks.

## 2.1. Passive Infrastructure in Optical Transport Networks

Passive infrastructure in optical transport networks serves as the backbone for high-capacity data transmission. Key components include fiber optic cables, which act as the primary medium of long distance transmission. Optical connectors, patch panels, and splice enclosures are crucial for joining and managing fiber links. Couplers and splitters are used for signal distribution and combining.

Within a physical network element (NE) there are also presence of passive components. For example, fiber optic cables are used to connect the ports of different modules within the same or between different chassis. Attenuators, on the other hand, are placed at places through connectors or built-in modules for reducing optical power.

Figure 1 illustrates a typical passive infrastructure for a point-to-point optical transport network.




Figure 1: Passive Infrastructure for Optical Transport Networks



Figure 2: Passive Infrastructure for Optical Access Networks

### 2.3. Passive Infrastructure in Microwave Networks

To be developed.

## 3. Terminology and Notations

### 3.1. Requirements Notations

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

### 3.2. Terminology

The following terms are defined in [RFC7950] and are not redefined here:

- \* client
- \* server
- \* augment
- \* data model
- \* data node

The following terms are defined in [RFC6241] and are not redefined here:

- \* configuration data
- \* state data

The following terms are defined and used in this document.

- \* **Passive device:** refers to a physical device within a network that does not require external power to function, and simply manipulates signals through processes like transmission, reflection, splitting, filtering, or attenuation without actively amplifying or generating the signal. Examples include optical fibers, splitters, couplers, and optical filters, all of which are used to direct signals within a system without needing power. A passive device typically does not have management interfaces and is typically deployed in a location tracked by the network operator.
- \* **Active device:** refers to a physical device that contains hardware and software and is manageable through communication interfaces. Network elements defined by [I-D.draft-ietf-ivy-network-inventory-yang] are examples of active device.
- \* **Guiding media:** refers to physical transmission pathways - such as optical fiber cables, electrical cables, and coaxial cables - that direct and confine electromagnetic signals along a specific route. These media provide a bounded channel for data transmission, ensuring signal integrity, minimizing interference, and enabling high-speed communication over varying distances. This category is also commonly known as guided media or wired transmission media. Guiding media can be concatenated to form longer guiding media.
- \* **Optical Cable:** refers to a type of guiding media that uses optical fiber as media to transmit optical signals. An optical cable can contain one or multiple fiber cores, also known as fiber strands, each serving as an independent guiding media for data transmission. Optical cables can be spliced or fused through joint boxes, optical distribution frames (ODF), or fiber jumpers.
- \* **Electrical Cable:** refers to a type of guiding media that uses metal conductors (such as copper or aluminum wires) as a medium to carry electrical signals for communication or power distribution. Common examples include twisted-pair cables (such as CAT-5/6 and DSL cables), and coaxial cables, which feature a single-core conductor commonly used in DOCSIS and MoCA-based broadband access networks. Electrical cables can be connected through splicing, connectors, or junction boxes.

### 3.3. Tree Diagram

Tree diagrams used in this document follow the notation defined in [RFC8340].

### 3.4. Prefixes in Data Node Names

In this document, names of data nodes and other data model objects are prefixed using the standard prefix associated with the corresponding YANG imported modules, as shown in Table 1.

Prefix	YANG Module	Reference
nwi	ietf-network-inventory	RFC XXXX
nil	ietf-ni-location	RFC YYYY

Table 1: Prefixes and Corresponding YANG Modules

RFC Editor Note: Please replace XXXX with the RFC number assigned to [I-D.draft-ietf-ivy-network-inventory-yang]. Please replace YYYY with the RFC number assigned to [I-D.draft-ietf-ivy-network-inventory-location]. Please remove this note.

## 4. Modeling Considerations

### 4.1. Relationship with Network Inventory

TBD

### 4.2. Relationship with Topology

TBD

## 5. YANG Model Overview

The YANG data model in this draft augments the model defined in [I-D.draft-ietf-ivy-network-inventory-yang] with the following information: - Passive devices: a list of passive devices with extended attributed reported by the domain controller. - Cables: a list of cables with each containing an optional list of child cables.

## 6. Model Tree Diagram



```

module: ietf-nwi-passive-inventory

augment /nwi:network-inventory:
  +--rw cable* [id]
  |   +--rw id                string
  |   +--rw length?          uint32
  |   +--rw a-end
  |   |   +--rw device-type?    identityref
  |   |   +--rw (connected-device-type)?
  |   |   |   +---:(passive)
  |   |   |   |   +--rw device-id?    string
  |   |   |   +---:(active)
  |   |   |   |   +--rw ne-ref?      leafref
  |   |   |   |   +--rw component-ref? leafref
  |   +--rw z-end
  |   |   +--rw device-type?    identityref
  |   |   +--rw (connected-device-type)?
  |   |   |   +---:(passive)
  |   |   |   |   +--rw device-id?    string
  |   |   |   +---:(active)
  |   |   |   |   +--rw ne-ref?      leafref
  |   |   |   |   +--rw component-ref? leafref
  |   +--ro uuid?            yang:uuid
  |   +--rw name?            string
  |   +--rw description?     string
  |   +--rw alias?           string
  |   +--rw cable-type?      identityref
  |   +--rw cable-role?      identityref
  |   +--rw optical-cable
  |   |   +--rw fiber-core-num?  uint32
  |   |   +--rw fiber-type?      identityref
  |   |   +--rw attenuation?    decimal64
  |   +--rw child-cable* [index]
  |   |   +--rw index          uint8
  |   |   +--rw id?            string
  |   |   +--rw length?        uint32
  |   |   +--rw a-end
  |   |   |   +--rw device-type?    identityref
  |   |   |   +--rw (connected-device-type)?
  |   |   |   |   +---:(passive)
  |   |   |   |   |   +--rw device-id?    string
  |   |   |   |   +---:(active)
  |   |   |   |   |   +--rw ne-ref?      leafref
  |   |   |   |   |   +--rw component-ref? leafref
  |   |   +--rw z-end
  |   |   |   +--rw device-type?    identityref
  |   |   |   +--rw (connected-device-type)?
  |   |   |   |   +---:(passive)

```

```

|           |  +--rw device-id?      string
|           |  +--:(active)
|           |    +--rw ne-ref?       leafref
|           |    +--rw component-ref? leafref
+--rw passive-device* [id]
  +--rw id          string
  +--ro uuid?       yang:uuid
  +--rw name?       string
  +--rw description? string
  +--rw alias?      string
  +--rw device-type? identityref
  +--rw custom-tags* string
  +--rw location-ref? nil:ni-location-ref
  +--rw passive-port* [id]
    +--rw id          string
    +--ro uuid?       yang:uuid
    +--rw name?       string
    +--rw description? string
    +--rw alias?      string
    +--rw port-type?  identityref
    +--rw fiber-core-num? uint32

```

Figure 3: Tree diagram for passive network inventory

## 7. YANG Modules

### 7.1. YANG Data Model for Passive Device Inventory

```

<CODE BEGINS> file "ietf-nwi-passive-inventory@2025-07-07.yang"
module ietf-nwi-passive-inventory {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-nwi-passive-inventory";
  prefix nwi-passive;

  import ietf-network-inventory {
    prefix nwi;
    reference
    "RFCXXXX: A YANG Data Model for Network Inventory";
    //RFC Editor: replace XXXX with actual RFC number
    //and remove this note
  }
  import ietf-ni-location {
    prefix nil;
    reference
    "RFCYYYY: A YANG Data Model for Network Inventory Location";
    //RFC Editor: replace YYYY with actual RFC number
    //and remove this note
  }
}

```

## organization

"IETF Network Inventory YANG (ivy) Working Group";

## contact

"WG Web: <<https://datatracker.ietf.org/wg/ivy/>>

WG List: <<mailto:inventory-yang@ietf.org>>

Editor: Chaode Yu  
<[yuchaode@huawei.com](mailto:yuchaode@huawei.com)>

Editor: Aihua Guo  
<[aihuaguo.ietf@gmail.com](mailto:aihuaguo.ietf@gmail.com)>

Editor: Italo Busi  
<[italo.busi@huawei.com](mailto:italo.busi@huawei.com)>"

## description

"This YANG module specifies a data model for passive devices, such as fibers, cables, and passive sites, deployed within and between network elements.

The model fully conforms to the Network Management Datastore Architecture (NMDA).

Copyright (c) 2023 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Revised BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.

The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED', 'MAY', and 'OPTIONAL' in this document are to be interpreted as described in BCP 14 (RFC 2119) (RFC 8174) when, and only when, they appear in all capitals, as shown here.";

// RFC Ed.: replace XXXX with actual RFC number and remove this  
// note.  
// RFC Ed.: update the date below with the date of RFC publication  
// and remove this note.

revision 2025-07-07 {

```
description
  "Initial version";
reference
  "RFC XXXX: A YANG Data Model for Passive Device Info in
  Network Inventory.";
  //RFC Editor: replace XXXX with actual RFC number, update date
  //information and remove this note
}

/* Identities */
identity fiber-type {
  description
    "Base identity for fiber types.";
}
identity G652A {
  base fiber-type;
  description
    "ITU-T G.652A fiber.";
}
identity G652B {
  base fiber-type;
  description
    "ITU-T G.652B fiber.";
}
identity G652C {
  base fiber-type;
  description
    "ITU-T G.652C fiber.";
}
identity G652D {
  base fiber-type;
  description
    "ITU-T G.652D fiber.";
}
identity G653 {
  base fiber-type;
  description
    "ITU-T G.653 fiber.";
}
identity G654 {
  base fiber-type;
  description
    "ITU-T G.654 fiber.";
}
identity G655 {
  base fiber-type;
  description
    "ITU-T G.655 fiber.";
```

```
}
identity G656 {
  base fiber-type;
  description
    "ITU-T G.656 fiber.";
}
identity G657A1 {
  base fiber-type;
  description
    "ITU-T G.657A1 fiber.";
}
identity G657A2 {
  base fiber-type;
  description
    "ITU-T G.657A2 fiber.";
}
identity G657B {
  base fiber-type;
  description
    "ITU-T G.657B fiber.";
}
identity other {
  base fiber-type;
  description
    "Other type of fiber.";
}

identity cable-type {
  description
    "Base identity for cable types.";
}
identity optical-fiber {
  base cable-type;
  description
    "Fiber optic cable.";
}
identity electrical-cable {
  base cable-type;
  description
    "Electrical cable.";
}
identity coaxial-cable {
  base electrical-cable;
  description
    "Coaxial cable.";
}

identity cable-role {
```

```
    description
        "Base identity for cable roles.";
}
identity backbone {
    base cable-role;
    description
        "Backbone cable.";
}
identity aggregation {
    base cable-role;
    description
        "Aggregation cable.";
}
identity access {
    base cable-role;
    description
        "Access cable.";
}
identity trunk {
    base cable-role;
    description
        "Trunk cable.";
}
identity distribution {
    base cable-role;
    description
        "Distribution cable.";
}
identity branch {
    base cable-role;
    description
        "Branch cable.";
}

identity passive-port-type {
    description
        "Base identity for passive port types.";
}
identity service-port {
    base passive-port-type;
    description
        "Service port.";
}
identity input-port {
    base passive-port-type;
    description
        "Input port.";
}
```

```
identity output-port {
  base passive-port-type;
  description
    "Output port.";
}
identity p2mp-port {
  base passive-port-type;
  description
    "Input port.";
}

identity connected-device-type {
  description
    "Base identity for connected device types.";
}
identity passive-device {
  base connected-device-type;
  description
    "Passive/unmanaged device.";
}
identity active-device {
  base connected-device-type;
  description
    "Active device, e.g. network element.";
}

identity passive-device-type {
  description
    "Base identity for passive device types.";
}
identity ODF {
  base passive-device-type;
  description
    "Optical Distribution Frame.";
}
identity WDM {
  base passive-device-type;
  description
    "Wavelength Division Multiplexer.";
}
identity FAT {
  base passive-device-type;
  description
    "Fiber Access Terminal.";
}
identity FDT {
  base passive-device-type;
  description
```

```
        "Fiber Distribution Terminal.";
    }
    identity ATB {
        base passive-device-type;
        description
            "Access Terminal Box.";
    }

/* Groupings */
    grouping connected-device-end {
        description
            "Attributes applicable to connected device end.";

        leaf device-type {
            type identityref {
                base connected-device-type;
            }
            description
                "Type of connected device.";
        }

        choice connected-device-type {
            description
                "Device end based on the type of connected device.";
            case passive {
                leaf device-id {
                    type string;
                    must "derived-from-or-self(..device-type,
                        'nwi-passive:passive-device')";
                    description
                        "Connected passive device identifier.";
                }
            }
            case active {
                leaf ne-ref {
                    type leafref {
                        path "/nwi:network-inventory/nwi:network-elements"
                            + "/nwi:network-element/nwi:ne-id";
                    }
                    must "derived-from-or-self(..device-type,
                        'nwi-passive:active-device')";
                    description
                        "Referenced Network Element (NE).";
                }
                leaf component-ref {
                    type leafref {
                        path "/nwi:network-inventory/nwi:network-elements"
                            + "/nwi:network-element[nwi:ne-id=current()]/.."
                    }
                }
            }
        }
    }
}
```



```
        + "/ne-ref]/nwi:components/nwi:component"
        + "/nwi:component-id";
    }
    must "derived-from-or-self(..../device-type,
        'nwi-passive:active-device');"
    description
        "Referenced connected active device's component,
        e.g. port component."
    }
}
}
}

grouping connected-device-ref {
    description
        "Attributes applicable to connected devices.";

    container a-end {
        description
            "A-end device reference";
        uses connected-device-end;
    }

    container z-end {
        description
            "Z-end device reference";
        uses connected-device-end;
    }
}

grouping common-cable-attributes {
    description
        "Common attributes of cables applicable to the cable
        and its child cables.";

    leaf id {
        type string;
        description
            "Cable identifier.";
    }

    leaf length {
        type uint32;
        units "meter";
        description
            "Length of the cable in meter.";
    }
}
```

```
    uses connected-device-ref;
  }

  grouping optical-cable-attributes {
    description
      "Attributes applicable to fiber optic cables.";

    container optical-cable {
      when
        "derived-from-or-self(.. /cable-type, 'optical-fiber')";

      description
        "Container for attributes associated with fiber
        optic cables.";

      leaf fiber-core-num {
        type uint32;
        description
          "Number of fiber cores within the cable.";
      }
      leaf fiber-type {
        type identityref {
          base fiber-type;
        }
        description
          "Type of fiber contained in the cable.";
      }
      leaf attenuation {
        type decimal64 {
          fraction-digits 2;
        }
        units "dB";
        description
          "The fiber attenuation in dB.";
      }
    }
  }

  grouping cable-attributes {
    description
      "Attributes of cables.";

    uses common-cable-attributes;
    uses nwi:basic-common-entity-attributes;

    leaf cable-type {
      type identityref {
        base cable-type;
      }
    }
  }
}
```

```
    }
    description
      "Type of cable.";
  }

  leaf cable-role {
    type identityref {
      base cable-role;
    }
    description
      "Role of cable.";
  }

  uses optical-cable-attributes;
}

grouping child-cables {
  description
    "Attributes applicable to child cables that are concatnated
    to form the cable.";

  list child-cable {
    key "index";
    min-elements 2;
    description
      "Ordered list of concatenated child cables.";

    leaf index {
      type uint8;
      description
        "An index number used to identify the concatenation
        order of the child cables.";
    }

    uses common-cable-attributes;
  }
}

grouping cables {
  description
    "Attributes applicable to cables.";

  list cable {
    key "id";
    description
      "List of cables.";

    uses cable-attributes;
  }
}
```

```
    uses child-cables;
  }
}

grouping passive-device-ports {
  description
    "Attributes applicable to passive device ports.";

  list passive-port {
    key "id";
    description
      "List of ports on a passive device.";

    leaf id {
      type string;
      description
        "Port identifier.";
    }
    uses nwi:basic-common-entity-attributes;
    leaf port-type {
      type identityref {
        base passive-port-type;
      }
      description
        "Type of passive port.";
    }
    leaf fiber-core-num {
      type uint32;
      description
        "Number of fiber cores within the port.";
    }
  }
}

grouping passive-devices {
  description
    "Attributes applicable to passive devices.";

  list passive-device {
    key "id";
    description
      "List of passive devices.";

    leaf id {
      type string;
      description
        "Cable identifier.";
    }
  }
}
```

```
    uses nwi:basic-common-entity-attributes;
    leaf device-type {
        type identityref {
            base passive-device-type;
        }
        description
            "Type of passive device.";
    }
    leaf-list custom-tags {
        type string;
        description
            "Customized tags, e.g. RFID, QR code that are
             attached to the device.";
    }
    leaf location-ref {
        type nil:ni-location-ref;
        description
            "Referenced location for the passive device.";
    }
    uses passive-device-ports;
}

/* Augmentation */
augment "/nwi:network-inventory" {
    description
        "Augment network inventory with information
         for optical cables and passive devices.";
    uses cables;
    uses passive-devices;
}
}
<CODE ENDS>
```

Figure 4: YANG model for passive network inventory

## 8. Manageability Considerations

TBD.

## 9. Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF [RFC6241] or RESTCONF [RFC8040]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [RFC6242]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS

[RFC8446].

The NETCONF access control model [RFC8341] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. Considerations in Section 8 of [RFC8795] are also applicable to their subtrees in the module defined in this document.

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. Considerations in Section 8 of [RFC8795] are also applicable to their subtrees in the module defined in this document.

## 10. IANA Considerations

It is proposed to IANA to assign new URIs from the "IETF XML Registry" [RFC3688] as follows:

URI: urn:ietf:params:xml:ns:yang:ietf-nwi-passive-inventory  
Registrant Contact: The IESG  
XML: N/A; the requested URI is an XML namespace.

This document registers the following YANG module in the YANG Module Names registry [RFC6020].

name: ietf-nwi-passive-inventory  
namespace: urn:ietf:params:xml:ns:yang:ietf-nwi-passive-inventory  
prefix: nwi-passive  
reference: RFC XXXX

## 11. Normative References

- [I-D.draft-ietf-ivy-network-inventory-location]  
Wu, B., Belotti, S., Bouquier, J., Peruzzini, F., and P. Bedard, "A YANG Data Model for Network Inventory Location", Work in Progress, Internet-Draft, draft-ietf-ivy-network-inventory-location-03, 7 July 2025, <<https://datatracker.ietf.org/doc/html/draft-ietf-ivy-network-inventory-location-03>>.
- [I-D.draft-ietf-ivy-network-inventory-yang]  
Yu, C., Belotti, S., Bouquier, J., Peruzzini, F., and P. Bedard, "A Base YANG Data Model for Network Inventory", Work in Progress, Internet-Draft, draft-ietf-ivy-network-inventory-yang-12, 22 December 2025, <<https://datatracker.ietf.org/doc/html/draft-ietf-ivy-network-inventory-yang-12>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", RFC 6242, DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.

- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, RFC 8341, DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8348] Bierman, A., Bjorklund, M., Dong, J., and D. Romascanu, "A YANG Data Model for Hardware Management", RFC 8348, DOI 10.17487/RFC8348, March 2018, <<https://www.rfc-editor.org/info/rfc8348>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.
- [RFC8453] Ceccarelli, D., Ed. and Y. Lee, Ed., "Framework for Abstraction and Control of TE Networks (ACTN)", RFC 8453, DOI 10.17487/RFC8453, August 2018, <<https://www.rfc-editor.org/info/rfc8453>>.
- [RFC8795] Liu, X., Bryskin, I., Beeram, V., Saad, T., Shah, H., and O. Gonzalez de Dios, "YANG Data Model for Traffic Engineering (TE) Topologies", RFC 8795, DOI 10.17487/RFC8795, August 2020, <<https://www.rfc-editor.org/info/rfc8795>>.

#### Authors' Addresses

Chaode Yu  
Huawei  
Email: [yuchaode@huawei.com](mailto:yuchaode@huawei.com)

Aihua Guo  
Futurewei  
Email: [aihuaguo.ietf@gmail.com](mailto:aihuaguo.ietf@gmail.com)

Italo Busi  
Huawei  
Email: [italo.busi@huawei.com](mailto:italo.busi@huawei.com)



Mohammad Boroon  
Highstreet  
Email: mohammad.boroon@highstreet-technologies.com

Sergio Belotti  
Nokia  
Email: sergio.belotti@nokia.com

Tom Van Caenegem  
Nokia  
Email: tom.van\_caenegem@nokia.com

Swaminathan 1. S.  
Nokia  
Email: swaminathan.1.s@nokia.com

Swaminathan B.  
Nokia  
Email: swaminathan.b@nokia.com

Nigel Davis  
Ciena  
Email: ndavis@ciena.com

Mauro Tilocca  
FiberCop  
Email: mauro.tilocca@fibercop.it

Brad Peters  
NBN  
Email: bradpeters@nbnco.com.au

Bin Yu Yun  
ETRI  
Email: byyun@etri.re.kr

Yucong Liu  
China Mobile  
Email: liuyucongyjy@chinamobile.com

Yang Zhao  
China Mobile  
Email: zhaoyangyjy@chinamobile.com

Avinash Sakalabhaktula  
Radisys  
Email: Avinash.Sakalabhaktula@radisys.com