

CCAMP Working Group
Internet-Draft
Intended status: Standards Track
Expires: 16 October 2025

C. Yu
H. Zheng
Huawei Technologies
A. Guo
Futurewei
I. Busi
Huawei Technologies
Y. Xu
CAICT
Y. Zhao
China Mobile
X. Liu
Alef Edge
14 April 2025

A YANG Data Model for Client-layer Tunnel
draft-zheng-ccamp-client-tunnel-yang-17

Abstract

A transport network is a server-layer network to provide connectivity services to its client. In this draft the tunnel of client is described, with the definition of client tunnel YANG model.

About This Document

This note is to be removed before publishing as an RFC.

The latest revision of this draft can be found at <https://italobusi.github.io/eth-te-tunnel/draft-zheng-ccamp-client-tunnel-yang.html>. Status information for this document may be found at <https://datatracker.ietf.org/doc/draft-zheng-ccamp-client-tunnel-yang/>.

Discussion of this document takes place on the Common Control and Measurement Plane Working Group mailing list (<mailto:ccamp@ietf.org>), which is archived at <https://mailarchive.ietf.org/arch/browse/ccamp/>. Subscribe at <https://www.ietf.org/mailman/listinfo/ccamp/>.

Source for this draft and an issue tracker can be found at <https://github.com/italobusi/eth-te-tunnel>.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 16 October 2025.

Copyright Notice

Copyright (c) 2025 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

1. Introduction	3
2. Terminology and Notations	3
3. YANG Model for Client-layer Tunnel	3
3.1. YANG Tree for Ethernet Tunnel	4
3.2. YANG Tree for Tunnel of other Client Signal Model	4
4. YANG Code for Client-layer Tunnel	4
4.1. The ETH Tunnel YANG Code	4
4.2. Other Client-layer Tunnel YANG Code	6
5. Considerations and Open Issue	6
6. IANA Considerations	6
7. Manageability Considerations	6
8. Security Considerations	6
9. References	7
9.1. Normative References	7
9.2. Informative References	7
Acknowledgments	8
Contributors	8
Authors' Addresses	8

1. Introduction

A transport network is a server-layer network designed to provide connectivity services for a client-layer network to carry the client traffic transparently across the server-layer network resources. The tunnel model in Traffic-Engineered network has been defined in both generic way and technology-specific way. The generic model, which is the base TE tunnel YANG model, can be found at [I-D.ietf-teas-yang-te]. Technology-specific models, such as OTN/WSON tunnel model, have also been defined in [I-D.ietf-ccamp-otn-tunnel-model] and [I-D.ietf-ccamp-wson-tunnel-model] respectively. Corresponding tunnel on client-layer is also required, to have a complete topology view from the perspective of network controllers.

This document defines a data model of all client-layer tunnel, using YANG language defined in [RFC7950]. The model is augmenting the generic TE tunnel model, and can be used by applications exposing to a network controller via a REST interface. Furthermore, it can be used by an application to describe the client tunnel that constructed above the server-layer network. It is also worth noting that the client layer network will only need the tunnel model when there is a demand for switching techniques, such as Carrier Ethernet and MPLS-TP. The transparent signals do not need this model.

2. Terminology and Notations

A simplified graphical representation of the data model is used in this document. The meaning of the symbols in the YANG data tree presented later in this document is defined in [RFC8340]. They are provided below for reference.

- * Brackets "[" and "]" enclose list keys.
- * Abbreviations before data node names: "rw" means configuration (read-write) and "ro" state data (read-only).
- * Symbols after data node names: "?" means an optional node, "!" means a presence container, and "*" denotes a list and leaf-list.
- * Parentheses enclose choice and case nodes, and case nodes are also marked with a colon (":").
- * Ellipsis ("...") stands for contents of subtrees that are not shown.

3. YANG Model for Client-layer Tunnel

3.1. YANG Tree for Ethernet Tunnel

```

module: ietf-eth-te-tunnel

augment /te:te/te:tunnels/te:tunnel:
  +--rw src-eth-tunnel-endpoint
  |   +--rw vlanid?      etht-types:vlanid
  |   +--rw tag-type?    etht-types:eth-tag-type
  +--rw dst-eth-tunnel-endpoint
  |   +--rw vlanid?      etht-types:vlanid
  |   +--rw tag-type?    etht-types:eth-tag-type
  +--rw bandwidth-profile
  |   +--rw bandwidth-profile-type?
  |       etht-types:bandwidth-profile-type
  +--rw CIR?              uint64
  +--rw CBS?              uint64
  +--rw EIR?              uint64
  +--rw EBS?              uint64
  +--rw color-aware?      boolean
  +--rw coupling-flag?    boolean

```

Figure 1: Ethernet TE Tunnel YANG tree

3.2. YANG Tree for Tunnel of other Client Signal Model

This section will be completed later.

4. YANG Code for Client-layer Tunnel

4.1. The ETH Tunnel YANG Code

```

<CODE BEGINS> file "ietf-eth-te-tunnel@2018-03-01.yang"
module ietf-eth-te-tunnel {

    namespace "urn:ietf:params:xml:ns:yang:ietf-eth-te-tunnel";

    prefix "eth-tunnel";

    import ietf-te {
        prefix "te";
    }

    import ietf-eth-tran-types {
        prefix "etht-types";
    }

    organization
        "Internet Engineering Task Force (IETF) CCAMP WG";

```

```
contact
  "
    WG List: <mailto:ccamp@ietf.org>

    ID-draft editor:
      Haomian Zheng (zhenghaomian@huawei.com);
      Italo Busi (italo.busi@huawei.com);
      Aihua Guo (aihuaguo.ietf@gmail.com);
      Yunbin Xu (xuyunbin@caict.ac.cn);
      Yang Zhao (zhaoyangyjy@chinamobile.com);
      Xufeng Liu (xufeng.liu.ietf@gmail.com);
  ";

description
  "This module defines a model for ETH transport tunnel";

revision 2018-03-01 {
  description
    "Initial revision";
  reference
    "draft-zheng-ccamp-client-tunnel-yang";
}

grouping eth-tunnel-endpoint {
  description "Parameters for ETH tunnel.";

  leaf vlanid {
    type eth-types:vlanid;
    description
      "VLAN tag id.";
  }

  leaf tag-type {
    type eth-types:eth-tag-type;
    description "VLAN tag type.";
  }
}

augment "/te:te/te:tunnels/te:tunnel" {
  description
    "Augment with additional parameters required for ETH
    service.";

  container src-eth-tunnel-endpoint {
    description
      "Source ETH tunnel endpoint.";

    uses eth-tunnel-endpoint;
  }
}
```

```
    }
    container dst-eth-tunnel-endpoint {
        description
            "Destination ETH tunnel endpoint.";

        uses eth-tunnel-endpoint;
    }

    container bandwidth-profile {
        description
            "ETH tunnel bandwidth profile specification.";

        uses etht-types:etht-bandwidth-profiles;
    }
}
<CODE ENDS>
```

Figure 2: Ethernet TE Tunnel YANG module

4.2. Other Client-layer Tunnel YANG Code

TBD.

5. Considerations and Open Issue

Editor Notes: This section is used to note temporary discussion/ conclusion that to be fixed in the future version, and will be removed before publication. This is a part of L2 work, need to discuss how to go with other L2 network models. The expectation is to include all potential L2 TE part in this work.

6. IANA Considerations

TBD.

7. Manageability Considerations

TBD.

8. Security Considerations

The data following the model defined in this document is exchanged via, for example, the interface between an orchestrator and a transport network controller. The security concerns mentioned in [I-D.ietf-teas-yang-te] also applies to this document.

The YANG module defined in this document can be accessed via the RESTCONF protocol defined in [RFC8040], or maybe via the NETCONF protocol [RFC6241].

9. References

9.1. Normative References

[I-D.ietf-teas-yang-te]

Saad, T., Gandhi, R., Liu, X., Beeram, V. P., and I. Bryskin, "A YANG Data Model for Traffic Engineering Tunnels, Label Switched Paths and Interfaces", Work in Progress, Internet-Draft, draft-ietf-teas-yang-te-37, 9 October 2024, <<https://datatracker.ietf.org/doc/html/draft-ietf-teas-yang-te-37>>.

[RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/rfc/rfc6241>>.

[RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/rfc/rfc7950>>.

[RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/rfc/rfc8040>>.

9.2. Informative References

[I-D.ietf-ccamp-otn-tunnel-model]

Zheng, H., Busi, I., Belotti, S., Lopez, V., and Y. Xu, "A YANG Data Model for Optical Transport Network (OTN) Tunnels and Label Switched Paths", Work in Progress, Internet-Draft, draft-ietf-ccamp-otn-tunnel-model-22, 3 December 2024, <<https://datatracker.ietf.org/doc/html/draft-ietf-ccamp-otn-tunnel-model-22>>.

[I-D.ietf-ccamp-wson-tunnel-model]

Lee, Y., Zheng, H., Guo, A., Lopez, V., King, D., Yoon, B. Y., and R. Vilalta, "A Yang Data Model for WSON Tunnel", Work in Progress, Internet-Draft, draft-ietf-ccamp-wson-tunnel-model-09, 9 July 2023, <<https://datatracker.ietf.org/doc/html/draft-ietf-ccamp-wson-tunnel-model-09>>.

[RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams",
BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018,
<<https://www.rfc-editor.org/rfc/rfc8340>>.

Acknowledgments

We would like to thank Igor Bryskin and Daniel King for their
comments and discussions.

Contributors

Zhe Liu
Huawei Technologies
Email: liuzhe123@huawei.com

Sergio Belotti
Nokia
Email: sergio.belotti@nokia.com

Yingxi Yao
Shanghai Bell
Email: yingxi.yao@nokia-sbell.com

Giuseppe Fioccola
Huawei Technologies
Email: giuseppe.fioccola@huawei.com

Yanlei Zheng
China Unicom
Email: zhengyanlei@chinaunicom.cn

Authors' Addresses

Chaode Yu
Huawei Technologies
Email: yuchaode@huawei.com

Haomian Zheng
Huawei Technologies
H1, Huawei Xiliu Beipo Village, Songshan Lake
Dongguan
Guangdong, 523808
China
Email: zhenghaomian@huawei.com

Aihua Guo
Futurewei
Email: aihuaguo@futurewei.com

Italo Busi
Huawei Technologies
Email: italo.busi@huawei.com

Yunbin Xu
CAICT
Email: xuyunbin@caict.ac.cn

Yang Zhao
China Mobile
Email: zhaoyangyjy@chinamobile.com

Xufeng Liu
Alef Edge
Email: xufeng.liu.ietf@gmail.com