

Network Working Group  
Request for Comments: 3383  
BCP: 64  
Category: Best Current Practice

K. Zeilenga  
OpenLDAP Foundation  
September 2002

## Internet Assigned Numbers Authority (IANA) Considerations for the Lightweight Directory Access Protocol (LDAP)

### Status of this Memo

This document specifies an Internet Best Current Practices for the Internet Community, and requests discussion and suggestions for improvements. Distribution of this memo is unlimited.

### Copyright Notice

Copyright (C) The Internet Society (2002). All Rights Reserved.

### Abstract

This document provides procedures for registering extensible elements of the Lightweight Directory Access Protocol (LDAP). This document also provides guidelines to the Internet Assigned Numbers Authority (IANA) describing conditions under which new values can be assigned.

### 1. Introduction

The Lightweight Directory Access Protocol (LDAP) [RFC3377] is an extensible protocol. LDAP supports:

- addition of new operations,
- extension of existing operations, and
- extensible schema.

This document details procedures for registering values of used to unambiguously identify extensible elements of the protocol including:

- LDAP message types;
- LDAP extended operations and controls;
- LDAP result codes;
- LDAP authentication methods;
- LDAP attribute description options; and
- Object Identifier descriptors.

These registries are maintained by the Internet Assigned Numbers Authority (IANA).

In addition, this document provides guidelines to IANA describing the conditions under which new values can be assigned.

## 2. Terminology and Conventions

This section details terms and conventions used in this document.

### 2.1. Policy Terminology

The terms "IESG Approval", "Standards Action", "IETF Consensus", "Specification Required", "First Come First Served", "Expert Review", and "Private Use" are used as defined in BCP 26 [RFC2434].

### 2.2. Requirement Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119]. In this case, "the specification" as used by BCP 14 refers to the processing of protocols being submitted to the IETF standards process.

### 2.3. Common ABNF Productions

A number of syntaxes in this document are described using ABNF [RFC2234]. These syntaxes rely on the following common productions:

ALPHA = %x41-5A / %x61-7A ; A-Z / a-z

LDIGIT = %x31-39 ; 1-9

DIGIT = %x30 / LDIGIT ; 0-9

HYPHEN = %x2D ; "-"

DOT = %x2E ; "."

number = DIGIT / ( LDIGIT 1\*DIGIT )

keychar = ALPHA / DIGIT / HYPHEN

leadkeychar = ALPHA

keystring = leadkeychar \*keychar

A keyword is a case-insensitive string of UTF-8 [RFC2279] encoded characters from the Universal Character Set (UCS) [ISO10646] restricted to the <keystring> production.

### 3. IANA Considerations for LDAP

This section details each kind of protocol value which can be registered and provides IANA guidelines on how to assign new values.

IANA may reject obviously bogus registration requests.

#### 3.1. Object Identifiers

Numerous LDAP schema and protocol elements are identified by Object Identifiers. Specifications which assign OIDs to elements SHOULD state who delegated the OIDs for its use.

For IETF developed elements, specifications SHOULD use OIDs under "Internet Directory Numbers" (1.3.6.1.1.x). Numbers under this OID arc will be assigned upon Expert Review with Specification Required. Only one OID per specification will be assigned. The specification MAY then assign any number of OIDs within this arc without further coordination with IANA.

For elements developed by others, any properly delegated OID can be used, including those under "Internet Private Enterprise Numbers" (1.3.6.1.4.1.x) assigned by IANA  
<<http://www.iana.org/cgi-bin/enterprise.pl>>.

To avoid interoperability problems between early implementations of "works in progress" and implementations of the published specification (e.g., the RFC), experimental OIDs SHOULD be used in "works in progress" and early implementations. OIDs under the Internet Experimental OID arc (1.3.6.1.3.x) may be used for this purpose.

Experimental OIDs are not to used in published specifications (e.g., RFCs).

Practices for IANA assignment of Internet Enterprise and Experimental OIDs are detailed in STD 16 [RFC1155].

#### 3.2 Protocol Mechanisms

LDAP provides a number of Root DSE attributes for discovery of protocol mechanisms identified by OIDs, including:

- supportedControl [RFC2252] and
- supportedExtension [RFC2252].

A registry of OIDs used for discover of protocol mechanisms is provided to allow implementors and others to locate the technical specification for these protocol mechanisms. Future specifications of additional Root DSE attributes holding values identifying protocol mechanisms MAY extend this registry for their values.

OIDs associated with discoverable protocol mechanisms SHOULD be registered. These are to be considered on a First Come First Served with Specification Required basis.

OIDs associated with Standard Track mechanisms MUST be registered and require Standards Action.

### 3.3. Object Identifier Descriptors

LDAP allows short descriptive names (or descriptors) to be used instead of a numeric Object Identifier to identify protocol extensions [RFC2251], schema elements [RFC2252], LDAP URL [RFC2255] extensions, and other objects. Descriptors are restricted to strings of UTF-8 encoded UCS characters restricted by the following ABNF:

name = kestring

Descriptors are case-insensitive.

Multiple names may be assigned to a given OID. For purposes of registration, an OID is to be represented in numeric OID form conforming to the ABNF:

numericoid = number \*( DOT number ) ; e.g., 1.1.0.23.40

While the protocol places no maximum length restriction upon descriptors, they should be short. Descriptors longer than 48 characters may be viewed as too long to register.

A values ending with a hyphen ("-") reserve all descriptors which start with the value. For example, the registration of the option "descrFamily-" reserves all options which start with "descrFamily-" for some related purpose.

Descriptors beginning with "x-" are for Private Use and cannot be registered.

Descriptors beginning with "e-" are reserved for experiments and will be registered on a First Come First Served basis.

All other descriptors require Expert Review to be registered.

The registrant need not "own" the OID being named.

The OID namespace is managed by The ISO/IEC Joint Technical Committee 1 - Subcommittee 6.

### 3.4. AttributeDescription Options

An AttributeDescription [RFC2251, Section 4.1.5] can contain zero or more options specifying additional semantics. An option SHALL be restricted to a string UTF-8 encoded UCS characters limited by the following ABNF:

```
option = kestring
```

Options are case-insensitive.

While the protocol places no maximum length restriction upon option strings, they should be short. Options longer than 24 characters may be viewed as too long to register.

Values ending with a hyphen ("-") reserve all option names which start with the name. For example, the registration of the option "optionFamily-" reserves all options which start with "optionFamily-" for some related purpose.

Options beginning with "x-" are for Private Use and cannot be registered.

Options beginning with "e-" are reserved for experiments and will be registered on a First Come First Served basis.

All other options require Standards Action or Expert Review with Specification Required to be registered.

### 3.5. LDAP Message Types

Each protocol message is encapsulated in an LDAPMessage envelope [RFC2251, Section 4.1.1]. The protocolOp CHOICE indicates the type of message encapsulated. Each message type consists of a keyword and a non-negative choice number is combined with the class (APPLICATION) and data type (CONSTRUCTED or PRIMITIVE) to construct the BER tag in the message's encoding. The choice numbers for existing protocol messages are implicit in the protocol's ASN.1 defined in [RFC2251].

New values will be registered upon Standards Action.

Note: LDAP provides extensible messages which reduces, but does not eliminate, the need to add new message types.

### 3.6. LDAP Result Codes

LDAP result messages carry an resultCode enumerated value to indicate the outcome of the operation [RFC2251, Section 4.1.10]. Each result code consists of a keyword and a non-negative integer.

New resultCode integers in the range 0-1023 require Standards Action to be registered. New resultCode integers in the range 1024-4095 require Expert Review with Specification Required. New resultCode integers in the range 4096-16383 will be registered on a First Come First Served basis. Keywords associated with integers in the range 0-4095 SHALL NOT start with "e-" or "x-". Keywords associated with integers in the range 4096-16383 SHALL start with "e-". Values greater than or equal to 16384 and keywords starting with "x-" are for Private Use and cannot be registered.

### 3.7. LDAP Authentication Method

The LDAP Bind operation supports multiple authentication methods [RFC2251, Section 4.2]. Each authentication choice consists of a keyword and a non-negative integer.

The registrant SHALL classify the authentication method usage using one of the following terms:

- COMMON           - method is appropriate for common use on the Internet,
- LIMITED USE     - method is appropriate for limited use,
- OBSOLETE        - method has been deprecated or otherwise found to be inappropriate for any use.

Methods without publicly available specifications SHALL NOT be classified as COMMON. New registrations of class OBSOLETE cannot be registered.

New authentication method integers in the range 0-1023 require Standards Action to be registered. New authentication method integers in the range 1024-4095 require Expert Review with Specification Required. New authentication method integers in the range 4096-16383 will be registered on a First Come First Served basis. Keywords associated with integers in the range 0-4095 SHALL NOT start with "e-" or "x-". Keywords associated with integers in the range 4096-16383 SHALL start with "e-". Values greater than or equal to 16384 and keywords starting with "x-" are for Private Use and cannot be registered.

Note: LDAP supports SASL [RFC2222] as an Authentication CHOICE. SASL is an extensible LDAP authentication method.

### 3.8. Directory Systems Names

The IANA-maintained "Directory Systems Names" registry [IANADSN] of valid keywords for well known attributes used in the LDAPv2 string representation of a distinguished name [RFC1779]. RFC 1779 was obsoleted by RFC 2253.

Directory systems names are not known to be used in any other context. LDAPv3 uses Object Identifier Descriptors [Section 3.2] (which have a different syntax than directory system names).

New Directory System Names will no longer be accepted. For historical purposes, the current list of registered names should remain publicly available.

### 4. Registration Procedure

The procedure given here MUST be used by anyone who wishes to use a new value of a type described in Section 3 of this document.

The first step is for the requester to fill out the appropriate form. Templates are provided in Appendix A.

If the policy is Standards Action, the completed form SHOULD be provided to the IESG with the request for Standards Action. Upon approval of the Standards Action, the IESG SHALL forward the request (possibly revised) to IANA. The IESG SHALL be viewed as the owner of all values requiring Standards Action.

If the policy is Expert Review, the requester SHALL post the completed form to the <directory@apps.ietf.org> mailing list for public review. The review period is two (2) weeks. If a revised form is later submitted, the review period is restarted. Anyone may subscribe to this list by sending a request to <directory-request@apps.ietf.org>. During the review, objections may be raised by anyone (including the Expert) on the list. After completion of the review, the Expert, based upon public comments, SHALL either approve the request and forward it to the IESG OR deny the request. In either case, the Expert SHALL promptly notify the requester of the action. Actions of the Expert may be appealed [RFC2026]. The Expert is appointed by Applications Area Director(s). The requester is viewed as the owner of values registered under Expert Review.

If the policy is First Come First Served, the requester SHALL submit the completed form directly to the IANA: <iana@iana.org>. The requester is viewed as the owner of values registered under First Come First Served.

Neither the Expert nor IANA will take position on the claims of copyright or trademarks issues regarding completed forms.

Prior to submission of the Internet Draft (I-D) to the RFC Editor but after IESG review and tentative approval, the document editor SHOULD revise the I-D to use registered values.

## 5. Registration Maintenance

This section discusses maintenance of registrations.

### 5.1. Lists of Registered Values

IANA makes lists of registered values readily available to the Internet community on their web site: <http://www.iana.org/>.

### 5.2. Change Control

The registration owner MAY update the registration subject to the same constraints and review as with new registrations. In cases where the owner is not unable or unwilling to make necessary updates, the IESG MAY assert ownership in order to update the registration.

### 5.3. Comments

For cases where others (anyone other than the owner) have significant objections to the claims in a registration and the owner does not agree to change the registration, comments MAY be attached to a registration upon Expert Review. For registrations owned by the IESG, the objections SHOULD be addressed by initiating a request for Expert Review.

The form of these requests is ad hoc, but MUST include the specific objections to be reviewed and SHOULD contain (directly or by reference) materials supporting the objections.

## 6. Security Considerations

The security considerations detailed in [RFC2434] are generally applicable to this document. Additional security considerations specific to each namespace are discussed in Section 3 where appropriate.

Security considerations for LDAP are discussed in documents comprising the technical specification [RFC3377].

## 7. Acknowledgment

This document is a product of the IETF LDAP Revision (LDAPbis) Working Group. Some text was borrowed from "Guidelines for Writing an IANA Considerations Section in RFCs" [RFC2434] by Thomas Narten and Harald Alvestrand.

## 8. Normative References

- [RFC1155] Rose, M. and K. McCloghrie, "Structure and Identification of Management Information for TCP/IP-based Internets", STD 16, RFC 1155, May 1990.
- [RFC2026] Bradner, S., "The Internet Standards Process -- Revision 3", BCP 9, RFC 2026, October 1996.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2234] Crocker, D. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", RFC 2234, November 1997.
- [RFC2251] Wahl, M., Howes, T. and S. Kille, "Lightweight Directory Access Protocol (v3)", RFC 2251, December 1997.
- [RFC2252] Wahl, M., Coulbeck, A., Howes, T. and S. Kille, "Lightweight Directory Access Protocol (v3): Attribute Syntax Definitions", RFC 2252, December 1997.
- [RFC2255] Howes, T. and M. Smith, "The LDAP URL Format", RFC 2255, December, 1997.
- [RFC2256] Wahl, M., "A Summary of the X.500(96) User Schema for use with LDAPv3", RFC 2256, December 1997.
- [RFC2279] Yergeau, F., "UTF-8, a transformation format of ISO 10646", RFC 2279, January 1998.
- [RFC2434] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", BCP 26, RFC 2434, October 1998.
- [RFC3377] Hodges, J. and R. Morgan, "Lightweight Directory Access Protocol (v3): Technical Specification", RFC 3377, September 2002.
- [IANADSN] IANA, "Directory Systems Names",  
<http://www.iana.org/assignments/directory-system-names>

[ISO10646] Universal Multiple-Octet Coded Character Set (UCS) - Architecture and Basic Multilingual Plane, ISO/IEC 10646-1: 1993.

#### 10. Informative References

[RFC1779] Kille, S., "A String Representation of Distinguished Names", RFC 1779, March 1995.

[RFC2222] Myers, J., "Simple Authentication and Security Layer (SASL)", RFC 2222, October 1997.

## Appendix A. Registration Templates

This appendix provides registration templates for registering new LDAP values.

### A.1. LDAP Object Identifier Registration Template

Subject: Request for LDAP OID Registration

Person & email address to contact for further information:

Specification: (I-D)

Author/Change Controller:

Comments:

(Any comments that the requester deems relevant to the request)

### A.2. LDAP Protocol Mechanism Registration Template

Subject: Request for LDAP Protocol Mechanism Registration

Object Identifier:

Description:

Person & email address to contact for further information:

Usage: (One of Control or Extension)

Specification: (I-D)

Author/Change Controller:

Comments:

(Any comments that the requester deems relevant to the request)

### A.3. LDAP Descriptor Registration Template

Subject: Request for LDAP Descriptor Registration

Descriptor (short name):

Object Identifier:

Person & email address to contact for further information:

Usage: (One of attribute type, URL extension,  
object class, or other)

Specification: (RFC, I-D, URI)

Author/Change Controller:

Comments:

(Any comments that the requester deems relevant to the request)

### A.4. LDAP Attribute Description Option Registration Template

Subject: Request for LDAP Attribute Description Option Registration

Option Name:

Family of Options: (YES or NO)

Person & email address to contact for further information:

Specification: (RFC, I-D, URI)

Author/Change Controller:

Comments:

(Any comments that the requester deems relevant to the request)

#### A.5. LDAP Message Type Registration Template

Subject: Request for LDAP Message Type Registration

LDAP Message Name:

Person & email address to contact for further information:

Specification: (Approved I-D)

Comments:

(Any comments that the requester deems relevant to the request)

#### A.6. LDAP Result Code Registration Template

Subject: Request for LDAP Result Code Registration

Result Code Name:

Person & email address to contact for further information:

Specification: (RFC, I-D, URI)

Author/Change Controller:

Comments:

(Any comments that the requester deems relevant to the request)

#### A.7. LDAP Authentication Method Registration Template

Subject: Request for LDAP Authentication Method Registration

Authentication Method Name:

Person & email address to contact for further information:

Specification: (RFC, I-D, URI)

Intended Usage: (One of COMMON, LIMITED-USE, OBSOLETE)

Author/Change Controller:

Comments:

(Any comments that the requester deems relevant to the request)

## Appendix B. Assigned Values

The following values are currently assigned.

### B.1. Object Identifiers

Currently registered "Internet Private Enterprise Numbers" can be found at <<http://www.iana.org/assignments/enterprise-numbers>>.

Currently registered "Internet Directory Numbers" can be found at <<http://www.iana.org/assignments/smi-numbers>>.

### B.2. Protocol Mechanisms

| Object Identifier          | Type | Description     | Reference |
|----------------------------|------|-----------------|-----------|
| 1.2.840.113556.1.4.473     | C    | Sort Request    | [RFC2891] |
| 1.2.840.113556.1.4.474     | C    | Sort Response   | [RFC2891] |
| 1.3.6.1.4.1.1466.101.119.1 | E    | Dynamic Refresh | [RFC2589] |
| 1.3.6.1.4.1.1466.20037     | E    | Start TLS       | [RFC2830] |
| 1.3.6.1.4.1.4203.1.11.1    | E    | Modify Password | [RFC3062] |
| 2.16.840.1.113730.3.4.2    | C    | ManageDsaIT     | [RFC3296] |

#### Legend

C => supportedControl  
E => supportedExtension

### B.3. Object Identifier Descriptors

| NAME                      | Type | OID [REF]                            |
|---------------------------|------|--------------------------------------|
| account                   | O    | 0.9.2342.19200300.100.4.5 [RFC1274]  |
| alias                     | O    | 2.5.6.1 [RFC2256]                    |
| aliasedEntryName          | A    | 2.5.4.1 [X.501]                      |
| aliasedObjectName         | A    | 2.5.4.1 [RFC2256]                    |
| altServer                 | A    | 1.3.6.1.4.1.1466.101.120.6 [RFC2252] |
| applicationEntity         | O    | 2.5.6.12 [RFC2256]                   |
| applicationProcess        | O    | 2.5.6.11 [RFC2256]                   |
| aRecord                   | A    | 0.9.2342.19200300.100.1.26 [RFC1274] |
| associatedDomain          | A    | 0.9.2342.19200300.100.1.37 [RFC1274] |
| associatedInternetGateway | A    | 1.3.6.1.4.1.453.7.2.8 [RFC2164]      |
| associatedName            | A    | 0.9.2342.19200300.100.1.38 [RFC1274] |
| associatedORAddress       | A    | 1.3.6.1.4.1.453.7.2.6 [RFC2164]      |
| associatedX400Gateway     | A    | 1.3.6.1.4.1.453.7.2.3 [RFC2164]      |
| attributeTypes            | A    | 2.5.21.5 [RFC2252]                   |
| audio                     | A    | 0.9.2342.19200300.100.1.55 [RFC1274] |
| authorityRevocationList   | A    | 2.5.4.38 [RFC2256]                   |

|                             |  |
|-----------------------------|--|
| bitStringMatch              | M 2.5.13.16 [RFC2252]                  |
| buildingName                | A 0.9.2342.19200300.100.1.48 [RFC1274] |
| businessCategory            | A 2.5.4.15 [RFC2256]                   |
| C                           | A 2.5.4.6 [RFC2256]                    |
| cACertificate               | A 2.5.4.37 [RFC2256]                   |
| calCalAdrURI                | A 1.2.840.113556.1.4.481 [RFC2739]     |
| calCalURI                   | A 1.2.840.113556.1.4.478 [RFC2739]     |
| calCAPURI                   | A 1.2.840.113556.1.4.480 [RFC2739]     |
| calEntry                    | O 1.2.840.113556.1.5.87 [RFC2739]      |
| calFBURL                    | A 1.2.840.113556.1.4.479 [RFC2739]     |
| calOtherCalAdrURIs          | A 1.2.840.113556.1.4.485 [RFC2739]     |
| calOtherCalURIs             | A 1.2.840.113556.1.4.482 [RFC2739]     |
| calOtherCAPURIs             | A 1.2.840.113556.1.4.484 [RFC2739]     |
| calOtherFBURLs              | A 1.2.840.113556.1.4.483 [RFC2739]     |
| caseExactIA5Match           | M 1.3.6.1.4.1.1466.109.114.1 [RFC2252] |
| caseIgnoreIA5Match          | M 1.3.6.1.4.1.1466.109.114.2 [RFC2252] |
| caseIgnoreListMatch         | M 2.5.13.11 [RFC2252]                  |
| caseIgnoreMatch             | M 2.5.13.2 [RFC2252]                   |
| caseIgnoreOrderingMatch     | M 2.5.13.3 [RFC2252]                   |
| caseIgnoreSubstringsMatch   | M 2.5.13.4 [RFC2252]                   |
| certificateRevocationList   | A 2.5.4.39 [RFC2256]                   |
| certificationAuthority      | O 2.5.6.16 [RFC2256]                   |
| certificationAuthority-V2   | O 2.5.6.16.2 [RFC2256]                 |
| CN                          | A 2.5.4.3 [RFC2256]                    |
| cNAMERecord                 | A 0.9.2342.19200300.100.1.31 [RFC1274] |
| co                          | A 0.9.2342.19200300.100.1.43 [RFC1274] |
| commonName                  | A 2.5.4.3 [RFC2256]                    |
| country                     | O 2.5.6.2 [RFC2256]                    |
| countryName                 | A 2.5.4.6 [RFC2256]                    |
| createTimestamp             | A 2.5.18.1 [RFC2252]                   |
| creatorsName                | A 2.5.18.3 [RFC2252]                   |
| cRLDistributionPoint        | O 2.5.6.19 [RFC2256]                   |
| crossCertificatePair        | A 2.5.4.40 [RFC2256]                   |
| DC                          | A 0.9.2342.19200300.100.1.25 [RFC2247] |
| dcObject                    | O 1.3.6.1.4.1.1466.344 [RFC2247]       |
| deltaCRL                    | O 2.5.6.23 [RFC2587]                   |
| deltaRevocationList         | A 2.5.4.53 [RFC2256]                   |
| description                 | A 2.5.4.13 [RFC2256]                   |
| destinationIndicator        | A 2.5.4.27 [RFC2256]                   |
| device                      | O 2.5.6.14 [RFC2256]                   |
| distinguishedName           | A 2.5.4.49 [RFC2256]                   |
| distinguishedNameMatch      | M 2.5.13.1 [RFC2252]                   |
| distinguishedNameTableEntry | O 1.3.6.1.4.1.453.7.1.5 [RFC2293]      |
| distinguishedNameTableKey   | A 1.3.6.1.4.1.453.7.2.3 [RFC2293]      |
| dITContentRules             | A 2.5.21.2 [RFC2252]                   |
| dITRedirect                 | A 0.9.2342.19200300.100.1.54 [RFC1274] |
| dITStructureRules           | A 2.5.21.1 [RFC2252]                   |
| dmd                         | O 2.5.6.20 [RFC2256]                   |

|                              |  |
|------------------------------|--|
| dmdName                      | A 2.5.4.54 [RFC2256]                     |
| dnQualifier                  | A 2.5.4.46 [RFC2256]                     |
| dNSDomain                    | O 0.9.2342.19200300.100.4.15 [RFC1274]   |
| document                     | O 0.9.2342.19200300.100.4.6 [RFC1274]    |
| documentAuthor               | A 0.9.2342.19200300.100.1.14 [RFC1274]   |
| documentIdentifier           | A 0.9.2342.19200300.100.1.11 [RFC1274]   |
| documentLocation             | A 0.9.2342.19200300.100.1.15 [RFC1274]   |
| documentPublisher            | A 0.9.2342.19200300.100.1.56 [RFC1274]   |
| documentSeries               | O 0.9.2342.19200300.100.4.8 [RFC1274]    |
| documentTitle                | A 0.9.2342.19200300.100.1.12 [RFC1274]   |
| documentVersion              | A 0.9.2342.19200300.100.1.13 [RFC1274]   |
| domain                       | O 0.9.2342.19200300.100.4.13 [RFC2247]   |
| domainComponent              | A 0.9.2342.19200300.100.1.25 [RFC2247]   |
| domainNameForm               | N 1.3.6.1.4.1.1466.345 [RFC2247]         |
| domainRelatedObject          | O 0.9.2342.19200300.100.4.17 [RFC1274]   |
| drink                        | A 0.9.2342.19200300.100.1.5 [RFC1274]    |
| dSA                          | O 2.5.6.13 [RFC2256]                     |
| dSAQuality                   | A 0.9.2342.19200300.100.1.49 [RFC1274]   |
| dynamicObject                | O 1.3.6.1.4.1.1466.101.119.2 [RFC2589]   |
| dynamicSubtrees              | A 1.3.6.1.4.1.1466.101.119.4 [RFC2589]   |
| enhancedSearchGuide          | A 2.5.4.47 [RFC2256]                     |
| entryTtl                     | A 1.3.6.1.4.1.1466.101.119.3 [RFC2589]   |
| extensibleObject             | O 1.3.6.1.4.1.1466.101.120.111 [RFC2252] |
| facsimileTelephoneNumber     | A 2.5.4.23 [RFC2256]                     |
| favouriteDrink               | A 0.9.2342.19200300.100.1.5 [RFC1274]    |
| friendlyCountry              | O 0.9.2342.19200300.100.4.18 [RFC1274]   |
| friendlyCountryName          | A 0.9.2342.19200300.100.1.43 [RFC1274]   |
| generalizedTimeMatch         | M 2.5.13.27 [RFC2252]                    |
| generalizedTimeOrderingMatch | M 2.5.13.28 [RFC2252]                    |
| generationQualifier          | A 2.5.4.44 [RFC2256]                     |
| givenName                    | A 2.5.4.42 [RFC2256]                     |
| GN                           | A 2.5.4.42 [RFC2256]                     |
| groupOfNames                 | O 2.5.6.9 [RFC2256]                      |
| groupOfUniqueNames           | O 2.5.6.17 [RFC2256]                     |
| homePhone                    | A 0.9.2342.19200300.100.1.20 [RFC1274]   |
| homePostalAddress            | A 0.9.2342.19200300.100.1.39 [RFC1274]   |
| homeTelephone                | A 0.9.2342.19200300.100.1.20 [RFC1274]   |
| host                         | A 0.9.2342.19200300.100.1.9 [RFC1274]    |
| houseIdentifier              | A 2.5.4.51 [RFC2256]                     |
| info                         | A 0.9.2342.19200300.100.1.4 [RFC1274]    |
| initials                     | A 2.5.4.43 [RFC2256]                     |
| integerFirstComponentMatch   | M 2.5.13.29 [RFC2252]                    |
| integerMatch                 | M 2.5.13.14 [RFC2252]                    |
| internationaliSDNNumber      | A 2.5.4.25 [RFC2256]                     |
| janetMailbox                 | A 0.9.2342.19200300.100.1.46 [RFC1274]   |
| jpegPhoto                    | A 0.9.2342.19200300.100.1.60 [RFC1488]   |
| knowledgeInformation         | A 2.5.4.2 [RFC2256]                      |
| L                            | A 2.5.4.7 [RFC2256]                      |

|                                     |   |
|-------------------------------------|---|
| labeledURI                          | A 1.3.6.1.4.1.250.1.57 [RFC2079]        |
| labeledURIObject                    | A 1.3.6.1.4.1.250.3.15 [RFC2079]        |
| lastModifiedBy                      | A 0.9.2342.19200300.100.1.24 [RFC1274]  |
| lastModifiedTime                    | A 0.9.2342.19200300.100.1.23 [RFC1274]  |
| ldapSyntaxes                        | A 1.3.6.1.4.1.1466.101.120.16 [RFC2252] |
| locality                            | O 2.5.6.3 [RFC2256]                     |
| localityName                        | A 2.5.4.7 [RFC2256]                     |
| mail                                | A 0.9.2342.19200300.100.1.3 [RFC2798]   |
| mailPreferenceOption                | A 0.9.2342.19200300.100.1.47 [RFC1274]  |
| manager                             | A 0.9.2342.19200300.100.1.10 [RFC1274]  |
| matchingRules                       | A 2.5.21.4 [RFC2252]                    |
| matchingRuleUse                     | A 2.5.21.8 [RFC2252]                    |
| mcmTables                           | A 1.3.6.1.4.1.453.7.2.9 [RFC2164]       |
| mDRecord                            | A 0.9.2342.19200300.100.1.27 [RFC1274]  |
| member                              | A 2.5.4.31 [RFC2256]                    |
| mixerGateway                        | O 1.3.6.1.4.1.453.7.1.4 [RFC2164]       |
| mobile                              | A 0.9.2342.19200300.100.1.41 [RFC1274]  |
| mobileTelephoneNumber               | A 0.9.2342.19200300.100.1.41 [RFC1274]  |
| modifiersName                       | A 2.5.18.4 [RFC2252]                    |
| modifyTimestamp                     | A 2.5.18.2 [RFC2252]                    |
| mXRecord                            | A 0.9.2342.19200300.100.1.28 [RFC1274]  |
| name                                | A 2.5.4.41 [RFC2256]                    |
| nameForms                           | A 2.5.21.7 [RFC2252]                    |
| namingContexts                      | A 1.3.6.1.4.1.1466.101.120.5 [RFC2252]  |
| nSRecord                            | A 0.9.2342.19200300.100.1.29 [RFC1274]  |
| numericStringMatch                  | M 2.5.13.8 [RFC2252]                    |
| numericStringSubstringsMatch        | M 2.5.13.10 [RFC2252]                   |
| O                                   | A 2.5.4.10 [RFC2256]                    |
| objectClass                         | A 2.5.4.0 [RFC2256]                     |
| objectClasses                       | A 2.5.21.6 [RFC2252]                    |
| objectIdentifierFirstComponentMatch | M 2.5.13.30 [RFC2252]                   |
| objectIdentifiersMatch              | M 2.5.13.0 [RFC2252]                    |
| octetStringMatch                    | M 2.5.13.17 [RFC2252]                   |
| omittedORAddressComponent           | O 1.3.6.1.4.1.453.7.1.3 [RFC2164]       |
| oRAddressComponentType              | A 1.3.6.1.4.1.453.7.2.7 [RFC2164]       |
| organization                        | O 2.5.6.4 [RFC2256]                     |
| organizationalPerson                | O 2.5.6.7 [RFC2256]                     |
| organizationalRole                  | O 2.5.6.8 [RFC2256]                     |
| organizationalStatus                | A 0.9.2342.19200300.100.1.45 [RFC1274]  |
| organizationalUnit                  | O 2.5.6.5 [RFC2256]                     |
| organizationalUnitName              | A 2.5.4.11 [RFC2256]                    |
| organizationName                    | A 2.5.4.10 [RFC2256]                    |
| otherMailbox                        | A 0.9.2342.19200300.100.1.22 [RFC1274]  |
| OU                                  | A 2.5.4.11 [RFC2256]                    |
| owner                               | A 2.5.4.32 [RFC2256]                    |
| pager                               | A 0.9.2342.19200300.100.1.42 [RFC1274]  |
| pagerTelephoneNumber                | A 0.9.2342.19200300.100.1.42 [RFC1274]  |
| person                              | O 2.5.6.6 [RFC2256]                     |

|                            |  |
|----------------------------|--|
| personalSignature          | A 0.9.2342.19200300.100.1.53 [RFC1274] |
| personalTitle              | A 0.9.2342.19200300.100.1.40 [RFC1274] |
| photo                      | A 0.9.2342.19200300.100.1.7 [RFC1274]  |
| physicalDeliveryOfficeName | A 2.5.4.19 [RFC2256]                   |
| pilotDSA                   | O 0.9.2342.19200300.100.4.21 [RFC1274] |
| pilotObject                | O 0.9.2342.19200300.100.4.3 [RFC1274]  |
| pilotOrganization          | O 0.9.2342.19200300.100.4.20 [RFC1274] |
| pilotPerson                | O 0.9.2342.19200300.100.4.4 [RFC1274]  |
| pkiCA                      | O 2.5.6.22 [RFC2587]                   |
| pkiUser                    | O 2.5.6.21 [RFC2587]                   |
| postalAddress              | A 2.5.4.16 [RFC2256]                   |
| postalCode                 | A 2.5.4.17 [RFC2256]                   |
| postOfficeBox              | A 2.5.4.18 [RFC2256]                   |
| preferredDeliveryMethod    | A 2.5.4.28 [RFC2256]                   |
| presentationAddress        | A 2.5.4.29 [RFC2256]                   |
| presentationAddressMatch   | M 2.5.13.22 [RFC2252]                  |
| protocolInformation        | A 2.5.4.48 [RFC2256]                   |
| protocolInformationMatch   | M 2.5.13.24 [RFC2252]                  |
| qualityLabelledData        | O 0.9.2342.19200300.100.4.22 [RFC1274] |
| ref                        | A 2.16.840.1.113730.3.1.34 [RFC3296]   |
| referral                   | O 2.16.840.1.113730.3.2.6 [RFC3296]    |
| registeredAddress          | A 2.5.4.26 [RFC2256]                   |
| residentialPerson          | O 2.5.6.10 [RFC2256]                   |
| RFC822LocalPart            | O 0.9.2342.19200300.100.4.14 [RFC1274] |
| RFC822Mailbox              | A 0.9.2342.19200300.100.1.3 [RFC1274]  |
| rFC822ToX400Mapping        | O 1.3.6.1.4.1.453.7.1.1 [RFC2164]      |
| roleOccupant               | A 2.5.4.33 [RFC2256]                   |
| room                       | O 0.9.2342.19200300.100.4.7 [RFC1274]  |
| roomNumber                 | A 0.9.2342.19200300.100.1.6 [RFC1274]  |
| searchGuide                | A 2.5.4.14 [RFC2256]                   |
| secretary                  | A 0.9.2342.19200300.100.1.21 [RFC1274] |
| seeAlso                    | A 2.5.4.34 [RFC2256]                   |
| serialNumber               | A 2.5.4.5 [RFC2256]                    |
| simpleSecurityObject       | O 0.9.2342.19200300.100.4.19 [RFC1274] |
| singleLevelQuality         | A 0.9.2342.19200300.100.1.50 [RFC1274] |
| SN                         | A 2.5.4.4 [RFC2256]                    |
| sOARcord                   | A 0.9.2342.19200300.100.1.30 [RFC1274] |
| ST                         | A 2.5.4.8 [RFC2256]                    |
| stateOrProvinceName        | A 2.5.4.8 [RFC2256]                    |
| street                     | A 2.5.4.9 [RFC2256]                    |
| streetAddress              | A 2.5.4.9 [RFC2256]                    |
| strongAuthenticationUser   | O 2.5.6.15 [RFC2256]                   |
| subschema                  | O 2.5.20.1 [RFC2252]                   |
| subschemaSubentry          | A 2.5.18.10 [RFC2252]                  |
| subtree                    | O 1.3.6.1.4.1.453.7.1.1 [RFC2293]      |
| subtreeMaximumQuality      | A 0.9.2342.19200300.100.1.52 [RFC1274] |
| subtreeMinimumQuality      | A 0.9.2342.19200300.100.1.51 [RFC1274] |
| supportedAlgorithms        | A 2.5.4.52 [RFC2256]                   |

|                                |   |
|--------------------------------|---|
| supportedApplicationContext    | A 2.5.4.30 [RFC2256]                    |
| supportedControl               | A 1.3.6.1.4.1.1466.101.120.13 [RFC2252] |
| supportedExtension             | A 1.3.6.1.4.1.1466.101.120.7 [RFC2252]  |
| supportedLDAPVersion           | A 1.3.6.1.4.1.1466.101.120.15 [RFC2252] |
| supportedSASLMechanisms        | A 1.3.6.1.4.1.1466.101.120.14 [RFC2252] |
| surname                        | A 2.5.4.4 [RFC2256]                     |
| table                          | O 1.3.6.1.4.1.453.7.1.2 [RFC2293]       |
| tableEntry                     | O 1.3.6.1.4.1.453.7.1.3 [RFC2293]       |
| telephoneNumber                | A 2.5.4.20 [RFC2256]                    |
| telephoneNumberMatch           | M 2.5.13.20 [RFC2252]                   |
| telephoneNumberSubstringsMatch | M 2.5.13.21 [RFC2252]                   |
| teletexTerminalIdentifier      | A 2.5.4.22 [RFC2256]                    |
| telexNumber                    | A 2.5.4.21 [RFC2256]                    |
| textEncodedORAddress           | A 0.9.2342.19200300.100.1.2 [RFC1274]   |
| textTableEntry                 | O 1.3.6.1.4.1.453.7.1.4 [RFC2293]       |
| textTableKey                   | A 1.3.6.1.4.1.453.7.2.1 [RFC2293]       |
| textTableValue                 | A 1.3.6.1.4.1.453.7.2.2 [RFC2293]       |
| title                          | A 2.5.4.12 [RFC2256]                    |
| top                            | O 2.5.6.0 [RFC2256]                     |
| uid                            | A 0.9.2342.19200300.100.1.1 [RFC2253]   |
| uniqueIdentifier               | A 0.9.2342.19200300.100.1.44 [RFC1274]  |
| uniqueMember                   | A 2.5.4.50 [RFC2256]                    |
| uniqueMemberMatch              | M 2.5.13.23 [RFC2252]                   |
| userCertificate                | A 2.5.4.36 [RFC2256]                    |
| userClass                      | A 0.9.2342.19200300.100.1.8 [RFC1274]   |
| userId                         | A 0.9.2342.19200300.100.1.1 [RFC1274]   |
| userPassword                   | A 2.5.4.35 [RFC2256]                    |
| userSecurityInformation        | O 2.5.6.18 [RFC2256]                    |
| x121Address                    | A 2.5.4.24 [RFC2256]                    |
| x400ToRFC822Mapping            | O 1.3.6.1.4.1.453.7.1.2 [RFC2164]       |
| x500UniqueIdentifier           | A 2.5.4.45 [RFC2256]                    |

#### Legend

-----  
A => Attribute Type  
C => DIT Content Rule  
E => LDAP URL Extension  
M => Matching Rule  
N => Name Form  
O => Object Class

## B.4. Attribute Description Options

| Option | Owner | Reference |
|--------|-------|-----------|
| -----  | ----- | -----     |
| binary | IESG  | [RFC2251] |
| lang-* | IESG  | [RFC2596] |

\* family of options

## B.5. LDAPMessage types

| Name            | Code  | Owner | Reference |
|-----------------|-------|-------|-----------|
| -----           | ----- | ----- | -----     |
| bindRequest     | 0     | IESG  | [RFC2251] |
| bindResponse    | 1     | IESG  | [RFC2251] |
| unbindRequest   | 2     | IESG  | [RFC2251] |
| searchRequest   | 3     | IESG  | [RFC2251] |
| searchResEntry  | 4     | IESG  | [RFC2251] |
| searchResDone   | 5     | IESG  | [RFC2251] |
| modifyRequest   | 6     | IESG  | [RFC2251] |
| modifyResponse  | 7     | IESG  | [RFC2251] |
| addRequest      | 8     | IESG  | [RFC2251] |
| addResponse     | 9     | IESG  | [RFC2251] |
| delRequest      | 10    | IESG  | [RFC2251] |
| delResponse     | 11    | IESG  | [RFC2251] |
| modDNRequest    | 12    | IESG  | [RFC2251] |
| modDNResponse   | 13    | IESG  | [RFC2251] |
| compareRequest  | 14    | IESG  | [RFC2251] |
| compareResponse | 15    | IESG  | [RFC2251] |
| abandonRequest  | 16    | IESG  | [RFC2251] |
| reserved        | 17-18 | IESG  |           |
| searchResRef    | 19    | IESG  | [RFC2251] |
| reserved        | 20-22 | IESG  |           |
| extendedReq     | 23    | IESG  | [RFC2251] |
| extendedResp    | 24    | IESG  | [RFC2251] |

## B.6. resultCode values

| Name                   | Code  | Owner | Reference |
|------------------------|-------|-------|-----------|
| -----                  | ----- | ----- | -----     |
| success                | 0     | IESG  | [RFC2251] |
| operationsError        | 1     | IESG  | [RFC2251] |
| protocolError          | 2     | IESG  | [RFC2251] |
| timeLimitExceeded      | 3     | IESG  | [RFC2251] |
| sizeLimitExceeded      | 4     | IESG  | [RFC2251] |
| compareFalse           | 5     | IESG  | [RFC2251] |
| compareTrue            | 6     | IESG  | [RFC2251] |
| authMethodNotSupported | 7     | IESG  | [RFC2251] |

|                              |       |      |           |
|------------------------------|-------|------|-----------|
| strongAuthRequired           | 8     | IESG | [RFC2251] |
| reserved (partialResults)    | 9     | IESG | [RFC2251] |
| referral                     | 10    | IESG | [RFC2251] |
| adminLimitExceeded           | 11    | IESG | [RFC2251] |
| unavailableCriticalExtension | 12    | IESG | [RFC2251] |
| confidentialityRequired      | 13    | IESG | [RFC2251] |
| saslBindInProgress           | 14    | IESG | [RFC2251] |
| noSuchAttribute              | 16    | IESG | [RFC2251] |
| undefinedAttributeType       | 17    | IESG | [RFC2251] |
| inappropriateMatching        | 18    | IESG | [RFC2251] |
| constraintViolation          | 19    | IESG | [RFC2251] |
| attributeOrValueExists       | 20    | IESG | [RFC2251] |
| invalidAttributeSyntax       | 21    | IESG | [RFC2251] |
| noSuchObject                 | 32    | IESG | [RFC2251] |
| aliasProblem                 | 33    | IESG | [RFC2251] |
| invalidDNyntax               | 34    | IESG | [RFC2251] |
| reserved (isLeaf)            | 35    | IESG | [RFC2251] |
| aliasDereferencingProblem    | 36    | IESG | [RFC2251] |
| reserved                     | 37-47 | IESG |           |
| inappropriateAuthentication  | 48    | IESG | [RFC2251] |
| invalidCredentials           | 49    | IESG | [RFC2251] |
| insufficientAccessRights     | 50    | IESG | [RFC2251] |
| busy                         | 51    | IESG | [RFC2251] |
| unavailable                  | 52    | IESG | [RFC2251] |
| unwillingToPerform           | 53    | IESG | [RFC2251] |
| loopDetect                   | 54    | IESG | [RFC2251] |
| reserved                     | 55-63 | IESG |           |
| namingViolation              | 64    | IESG | [RFC2251] |
| objectClassViolation         | 65    | IESG | [RFC2251] |
| notAllowedOnNonLeaf          | 66    | IESG | [RFC2251] |
| notAllowedOnRDN              | 67    | IESG | [RFC2251] |
| entryAlreadyExists           | 68    | IESG | [RFC2251] |
| objectClassModsProhibited    | 69    | IESG | [RFC2251] |
| reserved (resultsTooLarge)   | 70    | IESG | [RFC2251] |
| reserved                     | 71-79 | IESG |           |
| other                        | 80    | IESG | [RFC2251] |
| reserved (APIs)              | 81-90 | IESG | [RFC2251] |

## B.7. Bind Authentication Method

| Method     | Value | Owner | Usage       | Reference         |
|------------|-------|-------|-------------|-------------------|
| -----      | ----- | ----- | -----       | -----             |
| simple     | 0     | IESG  | LIMITED USE | [RFC2251,RFC2829] |
| krbv42LDAP | 1     | IESG  | OBSOLETE*   | [RFC1777]         |
| krbv42DSA  | 2     | IESG  | OBSOLETE*   | [RFC1777]         |
| sasl       | 3     | IESG  | COMMON      | [RFC2251,RFC2829] |

\* These LDAPv2-only mechanisms were deprecated in favor of the LDAPv3 SASL authentication method, specifically the GSSAPI mechanism.

## Author's Address

Kurt D. Zeilenga  
OpenLDAP Foundation

EMail: Kurt@OpenLDAP.org

#### Full Copyright Statement

Copyright (C) The Internet Society (2002). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

#### Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.

