

Management Information Base for
Intermediate System to Intermediate System (IS-IS)

Status of This Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

Copyright Notice

Copyright (C) The Internet Society (2006).

Abstract

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. Specifically, this document describes a MIB for the Intermediate System to Intermediate System (IS-IS) Routing protocol when it is used to construct routing tables for IP networks.

Table of Contents

1. The Internet-Standard Management Framework	2
2. Overview	2
3. Conventions	5
4. Definition of IS-IS MIB.	6
5. IANA Considerations.	96
6. Acknowledgements	96
7. Security Considerations.	96
8. Normative References	101
9. Informative References	102

1. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

2. Overview

This document describes a management information base for the Intermediate System to Intermediate System (IS-IS) Routing protocol, as described in ISO 10589 [ISO10589], when it is used to construct routing tables for IP networks, as described in RFC 1195 [RFC1195]. The objects are mainly derived from the Guidelines for Definition of Managed Objects (GDMO) definitions in ISO 10589 and from the GDMO definitions in ISO 10733 [ISO10733]. There are also additional objects for managing the IP-specific functionality of Integrated IS-IS operation.

This MIB imports definitions from SNMPv2-TC [RFC2579], SNMPv2-SMI [RFC2578], SNMPv2-CONF [RFC2580], SNMP-FRAMEWORK-MIB [RFC3411], DIFFSERV-MIB [RFC3289], IF-MIB [RFC2863], and INET-ADDRESS-MIB [RFC4001]. See the imports section of the MIB for the specific items imported.

This MIB defines some objects to manage Mesh Groups, described in [RFC2973], and a three-way handshake for point-to-point adjacencies, described in [RFC3373].

The IS-IS MIB defines the following objects:

System-Wide Attributes

- isisSystem

This table contains information specific to a single instance of the IS-IS protocol running on a router.

- isisManAreaAddr

This table includes area addresses that are manually configured, which are used to control the associations formed between Level 1 Intermediate Systems.

- isisAreaAddr

This table includes area addresses reported in relevant L1 LSPs.

- isisSummAddr

This table holds summary addresses configured for each Level 2 instance of the IS-IS protocol running on a router.

- isisRedistributeAddr

This table provides criteria to decide whether a route should be leaked from L2 to L1 when Domain Wide Prefix leaking is enabled.

- isisRouter

This table holds the hostname and router ID for Intermediate Systems in the network.

- isisSysLevel

This table contains information specific to a domain (Level 2) or an area (Level 1) of the IS-IS protocol.

- isisNextCircIndex

This scalar is used to provide a unique circuit index.

Circuit-specific Attributes

- isisCirc

This table contains information specific to a point-to-point or a broadcast interface in the system.

- isisCircLevel

This table contains information specific to Level 1 or Level 2 of an interface.

Counters

- isisSystemCounter

Counters in the System table, such as number of times we have wrapped a sequence counter on one of our Link State PDUs.

- isisCircuitCounter

Counters of events particular to a circuit, such as PDUs with an illegal value of the System ID field length.

- isisPacketCounter

Counts of IS-IS Protocol PDUs broken down into packet type.

Attributes associated with an Adjacency

- isisISAdj

This table contains information about adjacencies to routers maintained by the protocol. Entries in this table cannot be created by management action: they are established through the Hello protocol.

- isisISAdjAreaAddr

This table contains the set of Area Addresses of neighboring Intermediate Systems, as reported in IIH PDUs.

- isisISAdjIPAddr

This table contains the set of IP Addresses of neighboring Intermediate Systems, as reported in received IIH PDUs.

- isisISAdjProtSupp

This table contains the set of protocols supported by neighboring Intermediate Systems, as reported in received IIH PDUs.

Attributes Associated with Addresses

- isisRA

The Reachable Address Table.

This table contains information about an address prefix manually configured on the system or learned through another protocol.

- isisIPRA

The IP Reachable Address Table.

This table contains information about an IP reachable address manually configured on this system or learned from another protocol.

Attributes Associated with Link State PDU Table

- isisLSPSummaryTable

The Link State PDU Summary Table.

This table contains information contained in the headers of Link State PDUs stored by the system.

- isisLSPTLVTable

The Link State PDU TLV Table.

This table holds the sequence of TLVs that make up an LSP fragment.

Attributes Associated with a Notification

- isisNotification

This table defines attributes that will be included when reporting IS-IS notifications.

3. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL", when they appear in this document, are to be interpreted as described in BCP 14, RFC 2119 [RFC2119].

4. Definition of IS-IS MIB

ISIS-MIB DEFINITIONS ::= BEGIN

IMPORTS

```
    TEXTUAL-CONVENTION, RowStatus, TruthValue, TimeStamp
        FROM SNMPv2-TC -- RFC2579
    MODULE-IDENTITY, OBJECT-TYPE, NOTIFICATION-TYPE,
        Unsigned32, Counter32, mib-2
        FROM SNMPv2-SMI -- RFC2578
    MODULE-COMPLIANCE, OBJECT-GROUP, NOTIFICATION-GROUP
        FROM SNMPv2-CONF -- RFC2580
    SnmpAdminString
        FROM SNMP-FRAMEWORK-MIB -- RFC2571
    IndexInteger, IndexIntegerNextFree
        FROM DIFFSERV-MIB -- RFC3289
    InterfaceIndex
        FROM IF-MIB -- RFC2863
    InetAddressType, InetAddress, InetAddressPrefixLength
        FROM INET-ADDRESS-MIB; -- RFC3291
```

isisMIB MODULE-IDENTITY

```
    LAST-UPDATED "200604040000Z" -- April 4, 2006, midnight
    ORGANIZATION "IETF IS-IS for IP Internets Working Group"
    CONTACT-INFO
```

```
    "IS-IS for IP Internets working Group
    http://www.ietf.org/html.charters/isis-charter.html
    isis-wg@ietf.org
```

```
    Jeff Parker
    Department of Computer Science
    Middlebury College,
    Middlebury, Vermont 05753
    jeffp at middlbury dot edu"
```

DESCRIPTION

```
"This document describes a management information base for
the IS-IS Routing protocol, as described in ISO 10589,
when it is used to construct routing tables for IP
networks, as described in RFC 1195.
```

```
This document is based on a 1994 IETF document by Chris
Gunner. This version has been modified to include
current syntax, to exclude portions of the protocol that
are not relevant to IP, and to add management support for
current practice.
```

Copyright (C) The Internet Society (2006). This version of this MIB module is part of RFC 4444; see the RFC itself for full legal notices."

REVISION "200604040000Z" -- April 4, 2006, midnight

DESCRIPTION

"Initial version, published as RFC 4444."

::= { mib-2 138 }

-- Top-level structure of the MIB

isisNotifications OBJECT IDENTIFIER ::= { isisMIB 0 }
isisObjects OBJECT IDENTIFIER ::= { isisMIB 1 }
isisConformance OBJECT IDENTIFIER ::= { isisMIB 2 }

-- OBJECT IDENTIFIER definitions

-- System wide attributes.

isisSystem OBJECT IDENTIFIER ::= { isisObjects 1 }

-- Attributes associated with the domain or with the area.

isisSysLevel OBJECT IDENTIFIER ::= { isisObjects 2 }

-- Attributes associated with one Circuit

isisCirc OBJECT IDENTIFIER ::= { isisObjects 3 }

-- Attributes associated with area or domain relevant within a Circuit.

isisCircLevelValues OBJECT IDENTIFIER ::= { isisObjects 4 }

-- System and circuit counters.

isisCounters OBJECT IDENTIFIER ::= { isisObjects 5 }

-- Attributes associated with an adjacent Protocol Peer.

isisISAdj OBJECT IDENTIFIER ::= { isisObjects 6 }

-- Attributes associated with a configured address.

isisReachAddr OBJECT IDENTIFIER ::= { isisObjects 7 }

-- Attributes associated with IP routes learned by

-- configuration or through another protocol.

isisIPReachAddr OBJECT IDENTIFIER ::= { isisObjects 8 }

-- The collection of Link State PDUs known to the Intermediate System

isisLSPDataBase OBJECT IDENTIFIER ::= { isisObjects 9 }

-- Objects included in Notifications.

isisNotification OBJECT IDENTIFIER ::= { isisObjects 10 }

-- Type definitions

```
IsisOSINSAddress ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "OSI Network Service Address, e.g., NSAP, SNPA, or Network
        Entity Title"
    SYNTAX OCTET STRING (SIZE(0..20))
```

```
IsisSystemID ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "The ID for an Intermediate System. This should
        be unique within a network, and is included
        in all PDUs originated by an Intermediate System.
        The protocol does not place any meanings upon
        the bits, other than using ordering to break
        ties in electing a Designated IS on a LAN."
    REFERENCE "{ISIS.aoi systemId (119)}"
    SYNTAX OCTET STRING (SIZE(6))
```

```
IsisLinkStatePDUID ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "The 8-byte Link State PDU (LSP) ID,
        consisting of the 6-byte SystemID of the
        originating IS; a one-byte PseudoNode ID,
        which is 0 unless the LSP represents the
        topology of a LAN; and a one-byte LSP
        fragment number that is issued in sequence,
        starting with 0. Non-zero PseudoNode IDs
        need to be unique to the IS but need not
        match the IfIndex."
    REFERENCE "{See section 9.8 of ISO 10589}"
    SYNTAX OCTET STRING (SIZE(8))
```

```
IsisAdminState ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "Type used in enabling and disabling a row."
    SYNTAX INTEGER
        {
            on(1),
            off(2)
        }
```

```
IsisLSPBuffSize ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d"
```


STATUS current
DESCRIPTION
 "Integer sub-range for maximum LSP size."
SYNTAX Unsigned32 (512..16000)

IsisLevelState ::= TEXTUAL-CONVENTION

STATUS current
DESCRIPTION
 "States of the IS-IS protocol."
SYNTAX INTEGER
 {
 off (1),
 on (2),
 waiting (3),
 overloaded(4)
 }

IsisSupportedProtocol ::= TEXTUAL-CONVENTION

STATUS current
DESCRIPTION
 "Types of network protocol supported by Integrated IS-IS.
 The values for ISO8473 and IP are those registered for
 these protocols in ISO TR9577."
REFERENCE "{See section 5.3.1 of RFC 1195}"
SYNTAX INTEGER
 {
 iso8473(129),
 ipV6(142),
 ip(204)
 }

IsisDefaultMetric ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"
STATUS current
DESCRIPTION
 "Integer sub-range for default metric for single hop.
 ISO 10589 provides for 4 types of metric. Only the
 'default' metric is used in practice."
REFERENCE "{See section 7.2.2 of ISO 10589}"
SYNTAX Unsigned32 (0..63)

IsisWideMetric ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"
STATUS current
DESCRIPTION
 "Wide metric for IS Neighbors. ISO 10589 provides a
 6-bit metric. Traffic Engineering extensions provide
 24-bit metrics."

```
REFERENCE "{See section 3 of RFC 3784}"
SYNTAX Unsigned32 (0..16777215)
```

```
IsisFullMetric ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "d"
    STATUS current
    DESCRIPTION
        "Full metric for IP Routes.  Traffic Engineering extensions
        provide 32-bit metrics."
    REFERENCE "{See section 4 of RFC 3784}"
    SYNTAX Unsigned32
```

```
IsisMetricType ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "Is this an Internal or External Metric?"
    REFERENCE "{See section 7.2.2 of ISO 10589}"
    SYNTAX INTEGER
        {
            internal(1),
            external(2)
        }
```

```
IsisMetricStyle ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "Do we use RFC 1195 style metrics or wide metrics?"
    REFERENCE "{See section 5 of RFC 3787}"
    SYNTAX INTEGER
        {
            narrow(1),
            wide(2),
            both(3)
        }
```

```
IsisISLevel ::= TEXTUAL-CONVENTION
    STATUS current
    DESCRIPTION
        "Identifies a level."
    REFERENCE "{See definitions 3.6.1 and 3.6.11 of ISO 10589}"
    SYNTAX INTEGER
        {
            area(1),          -- L1
            domain(2)         -- L2
        }
```

```
IsisLevel ::= TEXTUAL-CONVENTION
    STATUS current
```

DESCRIPTION

"Identifies one or more levels."

REFERENCE "{See definitions 3.6.1 and 3.6.11 of ISO 10589}"

SYNTAX INTEGER

```
{
    level1(1),
    level2(2),
    levelland2(3)
}
```

IsisPDUHeader ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"A block to contain the header from a PDU."

SYNTAX OCTET STRING (SIZE(0..64))

IsisCircuitID ::= TEXTUAL-CONVENTION

STATUS current

DESCRIPTION

"ID for a circuit."

REFERENCE "{See section 7.2.7 of ISO 10589}"

SYNTAX OCTET STRING (SIZE(0|7))

IsisISPriority ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS current

DESCRIPTION

"Integer sub-range for IS-IS priority."

REFERENCE "{See section 9.5 of ISO 10589}"

SYNTAX Unsigned32 (0..127)

IsisUnsigned16TC ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS current

DESCRIPTION

"An Unsigned32 further restricted to 16 bits. Note that the ASN.1 BER encoding may still require 24 bits for some values."

SYNTAX Unsigned32 (0..65535)

IsisUnsigned8TC ::= TEXTUAL-CONVENTION

DISPLAY-HINT "d"

STATUS current

DESCRIPTION

"An Unsigned32 further restricted to 8 bits. Note that the ASN.1 BER encoding may still require 16 bits for some values."

SYNTAX Unsigned32 (0..255)

```
-- Behavior Definitions

-- ResettingTimer behavior definition
--
-- "This behavior applies to objects that specify the interval
-- between events in the operation of the protocol state machine.
-- If the value of such an object is set to a new value while
-- the protocol state machine is in operation, the implementation
-- shall take the necessary steps to ensure that for any time
-- interval that was in progress when the value of the
-- corresponding object was changed, the next expiration of that
-- interval takes place the specified time after the original
-- start of that interval, or immediately, whichever is later.
-- The precision with which this time shall be implemented shall
-- be the same as that associated with the basic operation of
-- the timer object."

-- ReplaceOnlyWhileDisabled behavior definition
-- "This behavior applies to objects that may not be modified
-- while the corresponding table row's variable of type
-- IsisAdminState is in state on."

-- ManualOrAutomatic behavior definition
-- "This behavior applies to objects that are read-write
-- if the object was created manually. Objects that were
-- created automatically that have this behavior are
-- read-only.

isisSysObject OBJECT IDENTIFIER ::= { isisSystem 1 }

isisSysVersion OBJECT-TYPE
    SYNTAX INTEGER
        {
            unknown(0),
            one(1)
        }
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The version number of the IS-IS protocol that
        is implemented."
    REFERENCE "{ISIS.aoi version (1)}"
    DEFVAL { one }
    ::= { isisSysObject 1 }

isisSysLevelType OBJECT-TYPE
    SYNTAX IsisLevel
```

```
MAX-ACCESS read-write
STATUS current
DESCRIPTION
    "At which levels is the Intermediate System
    running? This object may not be modified when
    the isisSysAdminState variable is in state 'on'
    for this Intermediate System.

    Configured values MUST survive an agent reboot."
REFERENCE "{ISIS.aoi iSType (2)}"
DEFVAL { levelland2 }
::= { isisSysObject 2 }

isisSysID OBJECT-TYPE
    SYNTAX IsisSystemID
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The ID for this Intermediate System.
        This value is appended to each of the
        area addresses to form the Network Entity Titles.
        The derivation of a value for this object is
        implementation specific. Some implementations may
        automatically assign values and not permit an
        SNMP write, while others may require the value
        to be set manually.

        Configured values MUST survive an agent reboot."
REFERENCE "{ISIS.aoi systemId (119)}"
::= { isisSysObject 3 }

isisSysMaxPathSplits OBJECT-TYPE
    SYNTAX Unsigned32 (1..32)
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "Maximum number of paths with equal routing metric value
        which it is permitted to split between. This object
        may not be modified when the isisSysAdminState variable
        is in state 'on' for this Intermediate System.

        Configured values MUST survive an agent reboot."
REFERENCE "{ISIS.aoi maximumPathSplits (3)}"
DEFVAL { 2 }
::= { isisSysObject 4 }

isisSysMaxLSPGenInt OBJECT-TYPE
    SYNTAX Unsigned32 (1..65235)
```

```
UNITS "seconds"
MAX-ACCESS read-write
STATUS current
DESCRIPTION
    "Maximum interval, in seconds, between generated LSPs
    by this Intermediate System. This object follows
    the ResettingTimer behavior. The value must be
    greater than any value configured for
    isisSysLevelMinLSPGenInt, and should be at least 300
    seconds less than isisSysMaxAge.

    Configured values MUST survive an agent reboot."
REFERENCE "{ISIS.aoi maximumLSPGenerationInterval (6)}"
DEFVAL { 900 }
 ::= { isisSysObject 5 }

isisSysPollESHelloRate OBJECT-TYPE
    SYNTAX IsisUnsigned16TC (1..65535)
    UNITS "seconds"
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The value, in seconds, to be used for the suggested ES
        configuration timer in ISH PDUs when soliciting the ES
        configuration.

        Configured values MUST survive an agent reboot."
    REFERENCE "{ISIS.aoi pollESHelloRate (13)}"
    DEFVAL { 50 }
 ::= { isisSysObject 6 }

isisSysWaitTime OBJECT-TYPE
    SYNTAX IsisUnsigned16TC (1..65535)
    UNITS "seconds"
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "Number of seconds to delay in state 'waiting' before
        entering the state 'on'. This object follows the
        ResettingTimer behavior.

        Configured values MUST survive an agent reboot."
    REFERENCE "{ISIS.aoi waitingTime (15)}"
    DEFVAL { 60 }
 ::= { isisSysObject 7 }

isisSysAdminState OBJECT-TYPE
    SYNTAX IsisAdminState
```

```
MAX-ACCESS read-write
STATUS current
DESCRIPTION
    "The administrative state of this Intermediate
    System. Setting this object to the value 'on'
    when its current value is 'off' enables
    the Intermediate System.

    Configured values MUST survive an agent reboot."
DEFVAL { off }
 ::= { isisSysObject 8 }

isisSysL2toL1Leaking OBJECT-TYPE
    SYNTAX TruthValue
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "If true, allow the router to leak L2 routes into L1.

        Configured values MUST survive an agent reboot."
    DEFVAL { false }
 ::= { isisSysObject 9 }

isisSysMaxAge OBJECT-TYPE
    SYNTAX IsisUnsigned16TC (350..65535)
    UNITS "seconds"
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "Value to place in RemainingLifeTime field of
        the LSPs we generate.
        This should be at least 300 seconds greater than
        isisSysMaxLSPGenInt.

        Configured values MUST survive an agent reboot."
    DEFVAL { 1200 }
 ::= { isisSysObject 10 }

isisSysReceiveLSPBufferSize OBJECT-TYPE
    SYNTAX IsisUnsigned16TC (1492..16000)
    UNITS "bytes"
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "Size of the largest buffer we are designed or
        configured to store. This should be at least
        as big as the maximum isisSysLevelOrigLSPBuffSize
        supported by the system."
```

If resources allow, we will store and flood LSPs larger than `isisSysReceiveLSPBufferSize`, as this can help avoid problems in networks with different values for `isisSysLevelOrigLSPBuffSize`.

Configured values MUST survive an agent reboot."

```
DEFVAL { 1492 }
::= { isisSysObject 11 }
```

`isisSysProtSupported` OBJECT-TYPE

```
SYNTAX BITS {
    iso8473 (0),
    ipv4 (1),
    ipv6 (2)
}
```

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This attribute contains the set of protocols supported by this Intermediate System."

```
::= { isisSysObject 12 }
```

`isisSysNotificationEnable` OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"If this object is set to true(1), then it enables the emission of IS-IS Notifications. If it is set to false(2), these notifications are not sent."

Configured values MUST survive an agent reboot."

```
DEFVAL { true }
::= { isisSysObject 13 }
```

-- The Level 1 Manual Area Address Table

`isisManAreaAddrTable` OBJECT-TYPE

SYNTAX SEQUENCE OF `IsisManAreaAddrEntry`

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The set of manual area addresses configured on this Intermediate System."

At least one row in which the value of `isisManAreaAddrExistState` is active must be present.
The maximum number of rows in this table for

which the object isisManAreaAddrExistState has the value active is 3.

An attempt to create more than 3 rows of isisManAreaAddrEntry with state 'active' in one instance of the IS-IS protocol should return inconsistentValue."

```
REFERENCE "{ISIS.aoi manualAreaAddresses (10)}"
::= { isisSystem 2 }
```

isisManAreaAddrEntry OBJECT-TYPE

SYNTAX IsisManAreaAddrEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Each entry contains one area address manually configured on this system.

Dynamically created rows MUST survive an agent reboot."

```
INDEX { isisManAreaAddr }
::= { isisManAreaAddrTable 1 }
```

IsisManAreaAddrEntry ::=

```
SEQUENCE {
    isisManAreaAddr
        IsisOSINSAddress,
    isisManAreaAddrExistState
        RowStatus
}
```

isisManAreaAddr OBJECT-TYPE

SYNTAX IsisOSINSAddress

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"A manually configured area address for this system.

Note: An index for the entry {1, {49.0001} active} in this table would be the ordered pair

(1, (0x03 0x49 0x00 0x01)), as the length of an octet string is part of the OID."

```
::= { isisManAreaAddrEntry 1 }
```

isisManAreaAddrExistState OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The state of the isisManAreaAddrEntry. If the isisSysAdminState for this Intermediate System is 'on' and an attempt is made to set this object to the value 'destroy' or 'notInService' when this is the only isisManAreaAddrEntry in state 'active' for this Intermediate System should return inconsistentValue.

A row entry cannot be modified when the value of this object is 'active'."

::= { isisManAreaAddrEntry 2 }

-- The Level 1 Area Address Table

-- The Level 1 Area Address Table contains the
 -- union of the sets of relevant area addresses configured
 -- or learned from Level 1 LSPs received by this Intermediate System.

isisAreaAddrTable OBJECT-TYPE

SYNTAX SEQUENCE OF IsisAreaAddrEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The union of the sets of area addresses reported in all Level 1 LSPs with fragment number zero generated by this Intermediate System, or received from other Intermediate Systems that are reachable via Level 1 routing."

REFERENCE "{ISIS.aoi areaAddresses (18)}"

::= { isisSystem 3 }

isisAreaAddrEntry OBJECT-TYPE

SYNTAX IsisAreaAddrEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Each entry contains one area address reported in a Level 1 LSP generated or received by this Intermediate System.

Dynamically learned rows do not survive an agent reboot."

INDEX { isisAreaAddr }

::= { isisAreaAddrTable 1 }

IsisAreaAddrEntry ::=

SEQUENCE {

isisAreaAddr

IsisOSINSAddress

}

```

isisAreaAddr OBJECT-TYPE
    SYNTAX IsisOSINSAddress
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "An area address reported in a Level 1 LSP."
    ::= { isisAreaAddrEntry 1 }

```

-- The Summary Address Table

-- The Summary Address Table contains the set of summary
 -- addresses manually configured for the Intermediate System.
 --
 -- This is used to control leaking L1 routes into L2.

```

isisSummAddrTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisSummAddrEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The set of IP summary addresses to use in forming
        summary TLVs originated by this Intermediate System.

        An administrator may use a summary address to combine
        and modify IP Reachability announcements. If the
        Intermediate system can reach any subset of the summary
        address, the summary address MUST be announced instead,
        at the configured metric."
    ::= { isisSystem 4 }

```

```

isisSummAddrEntry OBJECT-TYPE
    SYNTAX IsisSummAddrEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each entry contains one IP summary address.

        Dynamically created rows MUST survive an agent reboot.

        Implementers need to be aware that if the total number
        of elements (octets or sub-identifiers) in
        isisSummAddress and isisSummAddrPrefixLen is too great,
        then OIDs of column instances in this table will have
        more than 128 subidentifiers and cannot be accessed
        using SNMPv1, SNMPv2c, or SNMPv3."
    INDEX { isisSummAddressType,
            isisSummAddress,
            isisSummAddrPrefixLen }

```

```
::= { isisSummAddrTable 1 }
```

```
IsisSummAddrEntry ::=
```

```
    SEQUENCE {  
        isisSummAddressType  
            InetAddressType,  
        isisSummAddress  
            InetAddress,  
        isisSummAddrPrefixLen  
            InetAddressPrefixLength,  
        isisSummAddrExistState  
            RowStatus,  
        isisSummAddrMetric  
            IsisDefaultMetric,  
        isisSummAddrFullMetric  
            IsisFullMetric  
    }
```

```
isisSummAddressType OBJECT-TYPE
```

```
    SYNTAX InetAddressType
```

```
    MAX-ACCESS not-accessible
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "The Type of IP address for this summary address."
```

```
::= { isisSummAddrEntry 1 }
```

```
isisSummAddress OBJECT-TYPE
```

```
    SYNTAX InetAddress
```

```
    MAX-ACCESS not-accessible
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "The IP Address value for this summary address.
```

```
        The address must not contain any set host bits  
        (bits set after the address prefix determined by  
        isisSummAddrPrefixLen).
```

```
        The type of this address is determined by the value of  
        the isisSummAddressType object."
```

```
::= { isisSummAddrEntry 2 }
```

```
isisSummAddrPrefixLen OBJECT-TYPE
```

```
    SYNTAX InetAddressPrefixLength
```

```
    MAX-ACCESS not-accessible
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "The Length of the IP NetMask for this summary address.
```

```
        The values for the index objects isisSummAddress and
```

isisSummAddrPrefixLen must be consistent. When the value of isisSummAddress (excluding the zone index, if one is present) is x, then the bitwise logical-AND of x with the value of the mask formed from the corresponding index object isisSummAddrPrefixLen MUST be equal to x. If not, then the index pair is not consistent, and an inconsistentName error must be returned on SET or CREATE requests."

```
::= { isisSummAddrEntry 3 }
```

isisSummAddrExistState OBJECT-TYPE

SYNTAX RowStatus

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The existence state of this summary address. Support for 'createAndWait' and 'notInService' is not required.

A row entry cannot be modified when the value of this object is 'active'."

```
::= { isisSummAddrEntry 4 }
```

isisSummAddrMetric OBJECT-TYPE

SYNTAX IsisDefaultMetric

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The metric value to announce this summary address within LSPs generated by this system."

DEFVAL { 20 }

```
::= { isisSummAddrEntry 5 }
```

isisSummAddrFullMetric OBJECT-TYPE

SYNTAX IsisFullMetric

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The wide metric value to announce this summary address within LSPs generated by this system."

DEFVAL { 20 }

```
::= { isisSummAddrEntry 6 }
```

```
-- The Redistribution table defines addresses that should be
-- leaked from L2 to L1 if isisSysL2toL1Leaking is enabled.
```

isisRedistributeAddrTable OBJECT-TYPE

SYNTAX SEQUENCE OF IsisRedistributeAddrEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table provides criteria to decide if a route should be leaked from L2 to L1 when Domain Wide Prefix leaking is enabled.

Addresses that match the summary mask in the table MUST be announced at L1 by routers when isisSysL2toL1Leaking is enabled. Routes that fall into the ranges specified are announced as is, without being summarized. Routes that do not match a summary mask are not announced."

::= { isisSystem 5 }

isisRedistributeAddrEntry OBJECT-TYPE

SYNTAX IsisRedistributeAddrEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Each entry contains one configured IP summary address to manage leaking L2 addresses into L1.

Dynamically created rows MUST survive an agent reboot.

Implementers need to be aware that if the total number of elements (octets or sub-identifiers) in isisRedistributeAddrAddress and isisRedistributeAddrPrefixLen is too great, then OIDs of column instances in this table will have more than 128 subidentifiers and cannot be accessed using SNMPv1, SNMPv2c, or SNMPv3."

INDEX { isisRedistributeAddrType,
isisRedistributeAddrAddress,
isisRedistributeAddrPrefixLen }

::= { isisRedistributeAddrTable 1 }

IsisRedistributeAddrEntry ::=

SEQUENCE {

isisRedistributeAddrType

InetAddressType,

isisRedistributeAddrAddress

InetAddress,

isisRedistributeAddrPrefixLen

InetAddressPrefixLength,

isisRedistributeAddrExistState

RowStatus

}

isisRedistributeAddrType OBJECT-TYPE

```

SYNTAX InetAddressType
MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
    "The Type of IP address for this summary address."
::= { isisRedistributeAddrEntry 1 }

isisRedistributeAddrAddress OBJECT-TYPE
    SYNTAX InetAddress
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The IP Address value for this summary address.
        The type of this address is determined by the
        value of the isisRedistributeAddrType object.
        The address must not contain any set host bits -
        bits set after the address prefix determined by
        isisRedistributeAddrPrefixLen."

::= { isisRedistributeAddrEntry 2 }

isisRedistributeAddrPrefixLen OBJECT-TYPE
    SYNTAX InetAddressPrefixLength
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The Length of the IP NetMask for this summary address.

        The values for the index objects
        isisRedistributeAddrAddress and
        isisRedistributeAddrPrefixLen must be consistent.
        When the value of isisRedistributeAddrAddress
        (excluding the zone index, if one is present) is x,
        then the bitwise logical-AND of x with the value of
        the mask formed from the corresponding index object
        isisRedistributeAddrPrefixLen MUST be equal to x.
        If not, then the index pair is not consistent, and an
        inconsistentName error must be returned on SET or
        CREATE requests."

::= { isisRedistributeAddrEntry 3 }

isisRedistributeAddrExistState OBJECT-TYPE
    SYNTAX RowStatus
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The existence state of this summary address.  Support

```

for createAndWait and notInService is not required.

A row entry cannot be modified when the value of this object is 'active'."

```
::= { isisRedistributeAddrEntry 4 }
```

```
-- The Router Table keeps track of hostnames and router IDs
-- associated with Intermediate Systems in the area and domain.
```

```
isisRouterTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisRouterEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The set of hostnames and router ID."
    ::= { isisSystem 6 }
```

```
isisRouterEntry OBJECT-TYPE
    SYNTAX IsisRouterEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each entry tracks information about one Intermediate
        System at one level.

        Dynamically learned rows do not survive an agent reboot."
    INDEX { isisRouterSysID,
            isisRouterLevel }
    ::= { isisRouterTable 1 }
```

```
IsisRouterEntry ::=
    SEQUENCE {
        isisRouterSysID
            IsisSystemID,
        isisRouterLevel
            IsisISLevel,
        isisRouterHostName
            SnmpAdminString,
        isisRouterID
            Unsigned32
    }
```

```
isisRouterSysID OBJECT-TYPE
    SYNTAX IsisSystemID
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The System ID of the Intermediate System."
```



```
::= { isisRouterEntry 1 }

isisRouterLevel OBJECT-TYPE
    SYNTAX IsisISLevel
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The level at which the information about this
        Intermediate System was received."
 ::= { isisRouterEntry 2 }

isisRouterHostName OBJECT-TYPE
    SYNTAX SnmpAdminString
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The hostname listed in the LSP, or a zero-length
        string if none."
 ::= { isisRouterEntry 3 }

isisRouterID OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The Router ID found in the LSP, or zero if none."
 ::= { isisRouterEntry 4 }

-- The System Level Table
-- This table captures level-specific information about the system

isisSysLevelTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisSysLevelEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Level specific information about the System."
 ::= { isisSysLevel 1 }

isisSysLevelEntry OBJECT-TYPE
    SYNTAX IsisSysLevelEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each row describes variables configured for Area or Domain.

        Configured values MUST survive an agent reboot."
    INDEX { isisSysLevelIndex }
```

```
::= { isisSysLevelTable 1 }
```

```
IsisSysLevelEntry ::=
```

```
    SEQUENCE {
        isisSysLevelIndex
            IsisISLevel,
        isisSysLevelOrigLSPBuffSize
            IsisLSPBuffSize,
        isisSysLevelMinLSPGenInt
            IsisUnsigned16TC,
        isisSysLevelState
            IsisLevelState,
        isisSysLevelSetOverload
            TruthValue,
        isisSysLevelSetOverloadUntil
            Unsigned32,
        isisSysLevelMetricStyle
            IsisMetricStyle,
        isisSysLevelSPFConsiders
            IsisMetricStyle,
        isisSysLevelTEEnabled
            TruthValue
    }
```

```
isisSysLevelIndex OBJECT-TYPE
```

```
    SYNTAX IsisISLevel
```

```
    MAX-ACCESS not-accessible
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "The level that this entry describes."
```

```
::= { isisSysLevelEntry 1 }
```

```
isisSysLevelOrigLSPBuffSize OBJECT-TYPE
```

```
    SYNTAX IsisLSPBuffSize
```

```
    MAX-ACCESS read-write
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "The maximum size of LSPs and SNPs originated by
        this Intermediate System at this level.  This
        object may not be modified when the isisSysAdminState
        variable is in state 'on' for this Intermediate System."
```

```
    REFERENCE "{ISIS.aoi originatingL1LSPBufferSize (9)}"
```

```
    DEFVAL { 1492 }
```

```
::= { isisSysLevelEntry 2 }
```

```
isisSysLevelMinLSPGenInt OBJECT-TYPE
```

```
    SYNTAX IsisUnsigned16TC (1..65535)
```

```
    UNITS "seconds"
```

```
MAX-ACCESS read-write
STATUS current
DESCRIPTION
    "Minimum interval, in seconds, between successive
    generation of LSPs with the same LSPID at this level
    by this Intermediate System."
REFERENCE "{ISIS.aoi minimumLSPGenerationInterval (11)}"
DEFVAL { 30 }
 ::= { isisSysLevelEntry 3 }

isisSysLevelState OBJECT-TYPE
SYNTAX IsisLevelState
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The state of the database at this level.
    The value 'off' indicates that IS-IS is not active at
    this level.
    The value 'on' indicates that IS-IS is active at this
    level and is not overloaded.
    The value 'waiting' indicates a database that is low on
    an essential resource, such as memory.
    The administrator may force the state to 'overloaded'
    by setting the object isisSysLevelSetOverload.
    If the state is 'waiting' or 'overloaded', we
    originate LSPs with the overload bit set."
REFERENCE "{ISIS.aoi llState (17)}"
 ::= { isisSysLevelEntry 4 }

isisSysLevelSetOverload OBJECT-TYPE
SYNTAX TruthValue
MAX-ACCESS read-write
STATUS current
DESCRIPTION
    "Administratively set the overload bit for the level.
    The overload bit MUST continue to be set if the
    implementation runs out of memory, independent of
    this variable. It may also be set manually independent
    of this variable, using the isisSysLevelSetOverloadUntil
    object."
DEFVAL { false }
 ::= { isisSysLevelEntry 5 }

isisSysLevelSetOverloadUntil OBJECT-TYPE
SYNTAX Unsigned32
UNITS "Seconds until clearing manually set Overload Bit"
MAX-ACCESS read-write
STATUS current
```

DESCRIPTION

"If this object is non-zero, the overload bit is set at this level when the isisSysAdminState variable goes to state 'on' for this Intermediate System. The overload bit remains set for isisSysLevelSetOverloadUntil seconds. When isisSysLevelSetOverloadUntil seconds have elapsed, the overload flag remains set if the implementation has run out of memory, or if it is set manually using the isisSysLevelSetOverload object.

If isisSysLevelSetOverload is false, the system clears the overload bit when isisSysLevelSetOverloadUntil seconds have elapsed, if the system has not run out of memory."

::= { isisSysLevelEntry 6 }

isisSysLevelMetricStyle OBJECT-TYPE

SYNTAX IsisMetricStyle

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Which style of metric do we generate in our LSPs at this level?"

DEFVAL { narrow }

::= { isisSysLevelEntry 7 }

isisSysLevelSPFConsiders OBJECT-TYPE

SYNTAX IsisMetricStyle

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Which style of metric do we consider in our SPF computation at this level?"

DEFVAL { narrow }

::= { isisSysLevelEntry 8 }

isisSysLevelTEEnabled OBJECT-TYPE

SYNTAX TruthValue

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Do we do Traffic Engineering at this level?"

DEFVAL { false }

::= { isisSysLevelEntry 9 }

-- Static to provide next CircIndex

isisNextCircIndex OBJECT-TYPE

SYNTAX IndexIntegerNextFree

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"This object is used to assist a management application in creating new rows in the isisCircTable. If it is possible to create a new instance of isisCircEntry, then this object will contain a non-zero value that is not in use as the index of any row in the isisCircTable. The network manager reads the value of this object and then (if the value read is non-zero) attempts to create the corresponding instance of isisCircEntry. If the set request fails with the code 'inconsistentValue', then the process must be repeated; if the set request succeeds, then the agent will change the value of this object according to an implementation-specific algorithm."

::= { isisCirc 1 }

-- The Circuit Table

-- Each broadcast or point-to-point interface on the system

-- corresponds to one entry in the Circuit table. However, there

-- may be multiple X.25 DA circuit entries in the Circuit table

-- for a given X.25 interface.

isisCircTable OBJECT-TYPE

SYNTAX SEQUENCE OF IsisCircEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The table of circuits used by this Intermediate System."

::= { isisCirc 2 }

isisCircEntry OBJECT-TYPE

SYNTAX IsisCircEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An isisCircEntry exists for each circuit configured for Integrated IS-IS on this system.

Dynamically created rows MUST survive an agent reboot."

INDEX { isisCircIndex }

::= { isisCircTable 1 }

```
IsisCircEntry ::=
    SEQUENCE {
        isisCircIndex
            IndexInteger,
        isisCircIfIndex
            InterfaceIndex,
        isisCircAdminState
            IsisAdminState,
        isisCircExistState
            RowStatus,
        isisCircType
            INTEGER,
        isisCircExtDomain
            TruthValue,
        isisCircLevelType
            IsisLevel,
        isisCircPassiveCircuit
            TruthValue,
        isisCircMeshGroupEnabled
            INTEGER,
        isisCircMeshGroup
            Unsigned32,
        isisCircSmallHellos
            TruthValue,
        isisCircLastUpTime
            TimeStamp,
        isisCirc3WayEnabled
            TruthValue,
        isisCircExtendedCircID
            Unsigned32
    }

isisCircIndex OBJECT-TYPE
    SYNTAX IndexInteger
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "An index used to uniquely identify this circuit.
        When creating a row in this table, the
        isisNextCircIndex object should be retrieved,
        and its value should be specified as the value
        of this index using a SET operation.  A retrieved
        value of zero(0) indicates that no rows can be
        created at this time."
    ::= { isisCircEntry 1 }

isisCircIfIndex OBJECT-TYPE
    SYNTAX InterfaceIndex
```

```
MAX-ACCESS read-create
STATUS current
DESCRIPTION
    "The value of ifIndex for the interface to which this
    circuit corresponds. This object cannot be modified
    after creation."
 ::= { isisCircEntry 2 }

isisCircAdminState OBJECT-TYPE
    SYNTAX IsisAdminState
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The administrative state of the circuit."
    DEFVAL { off }
 ::= { isisCircEntry 3 }

isisCircExistState OBJECT-TYPE
    SYNTAX RowStatus
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The existence state of this circuit. Setting the state
        to 'notInService' halts the generation and processing of
        IS-IS protocol PDUs on this circuit. Setting the state
        to destroy will also erase any configuration associated
        with the circuit. Support for 'createAndWait' and
        'notInService' is not required.

        A row entry cannot be modified when the value of this
        object is 'active'."
 ::= { isisCircEntry 4 }

isisCircType OBJECT-TYPE
    SYNTAX INTEGER
        {
            broadcast(1),
            ptToPt(2),
            staticIn(3),
            staticOut(4),
            dA(5)
        }
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The type of the circuit. This object follows the
        ReplaceOnlyWhileDisabled behavior. The type specified
        must be compatible with the type of the interface defined
```

```
        by the value of isisCircIfIndex."
REFERENCE "{ISIS.aoi type (33)}"
 ::= { isisCircEntry 5 }

isisCircExtDomain OBJECT-TYPE
    SYNTAX TruthValue
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "If true, suppress normal transmission of and
        interpretation of Intra-domain IS-IS PDUs on this
        circuit."
    REFERENCE "{ISIS.aoi externalDomain (46)}"
    DEFVAL { false }
 ::= { isisCircEntry 6 }

isisCircLevelType OBJECT-TYPE
    SYNTAX IsisLevel
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "Indicates which type of packets will be sent and
        accepted on this circuit. The values set will be
        saved, but the values used will be modified by
        the settings of isisSysLevelType. Thus, if the
        isisSysType is level2 and the isisCircLevelType
        for a circuit is level1, the circuit will not send
        or receive IS-IS packets. This object follows the
        ReplaceOnlyWhileDisabled behavior."
    DEFVAL { levelland2 }
 ::= { isisCircEntry 7 }

isisCircPassiveCircuit OBJECT-TYPE
    SYNTAX TruthValue
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "Should we include this interface in LSPs, even if
        it is not running the IS-IS Protocol?"
    DEFVAL { false }
 ::= { isisCircEntry 8 }

isisCircMeshGroupEnabled OBJECT-TYPE
    SYNTAX INTEGER
    {
        inactive(1),
        blocked(2),
        set(3)
    }
```



```

    }
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "Is this port a member of a mesh group, or is it
        blocked?  Circuits in the same mesh group act as a
        virtual multiaccess network.  LSPs seen on one circuit
        in a mesh group will not be flooded to another circuit
        in the same mesh group."
    REFERENCE "{ RFC 2973 }"
    DEFVAL { inactive }
 ::= { isisCircEntry 9 }

isisCircMeshGroup OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "Circuits in the same mesh group act as a virtual
        multiaccess network.  LSPs seen on one circuit in
        a mesh group will not be flooded to another circuit
        in the same mesh group.  If isisCircMeshGroupEnabled
        is inactive or blocked, this value is ignored."
    REFERENCE "{ RFC 2973 }"
 ::= { isisCircEntry 10 }

isisCircSmallHellos OBJECT-TYPE
    SYNTAX TruthValue
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "Can we send unpadded hellos on LAN circuits?  False
        means the LAN Hellos must be padded.
        Implementations should allow the administrator to read
        this value.  An implementation need not be able to
        support unpadded hellos to be conformant."
    DEFVAL { false }
 ::= { isisCircEntry 11 }

isisCircLastUpTime OBJECT-TYPE
    SYNTAX TimeStamp
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "How long the circuit has been enabled, measured in
        hundredths of seconds since the last re-initialization
        of the network management subsystem; 0 if the
        circuit has never been 'on'."

```

```

 ::= { isisCircEntry 12 }

isisCirc3WayEnabled OBJECT-TYPE
    SYNTAX TruthValue
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "Is this circuit enabled to run 3Way handshake?"
    DEFVAL { true }
 ::= { isisCircEntry 13 }

isisCircExtendedCircID OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The value to be used as the extended circuit ID in
        3Way handshake. This value is only used if
        isisCirc3WayEnabled is true, and it must be unique
        across all circuits on this IS."
 ::= { isisCircEntry 14 }

-- The Circuit Level Table
-- This table captures level-specific information about a circuit

isisCircLevelTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisCircLevelEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Level specific information about circuits used by IS-IS."
 ::= { isisCircLevelValues 1 }

isisCircLevelEntry OBJECT-TYPE
    SYNTAX IsisCircLevelEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "An isisCircLevelEntry exists for each level on
        each circuit configured for Integrated IS-IS on
        this system.

        Configured values MUST survive an agent reboot."
    INDEX { isisCircIndex,
            isisCircLevelIndex }
 ::= { isisCircLevelTable 1 }

IsisCircLevelEntry ::=

```

```

SEQUENCE {
    isisCircLevelIndex
        IsisISLevel,
    isisCircLevelMetric
        IsisDefaultMetric,
    isisCircLevelWideMetric
        IsisWideMetric,
    isisCircLevelISPriority
        IsisISPriority,
    isisCircLevelIDOctet
        Unsigned32,
    isisCircLevelID
        IsisCircuitID,
    isisCircLevelDesIS
        IsisCircuitID,
    isisCircLevelHelloMultiplier
        Unsigned32,
    isisCircLevelHelloTimer
        Unsigned32,
    isisCircLevelDRHelloTimer
        Unsigned32,
    isisCircLevelLSPThrottle
        IsisUnsigned16TC,
    isisCircLevelMinLSPRetransInt
        Unsigned32,
    isisCircLevelCSNPInterval
        Unsigned32,
    isisCircLevelPartSNPInterval
        Unsigned32
}

isisCircLevelIndex OBJECT-TYPE
    SYNTAX IsisISLevel
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The level that this entry describes."
    ::= { isisCircLevelEntry 1 }

isisCircLevelMetric OBJECT-TYPE
    SYNTAX IsisDefaultMetric
    MAX-ACCESS read-write
    STATUS current
    DESCRIPTION
        "The metric value of this circuit for this level."
    REFERENCE "{ISIS.aoi 11DefaultMetric (35)}"
    DEFVAL { 10 }
    ::= { isisCircLevelEntry 2 }

```

isisCircLevelWideMetric OBJECT-TYPE

SYNTAX IsisWideMetric

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The wide metric value of this circuit for this level."

DEFVAL { 10 }

::= { isisCircLevelEntry 3 }

isisCircLevelISPriority OBJECT-TYPE

SYNTAX IsisISPriority

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"The priority for becoming the LAN-Designated
Intermediate System at this level."

REFERENCE "{ISIS.aoi l2IntermediateSystemPriority (73)}"

DEFVAL { 64 }

::= { isisCircLevelEntry 4 }

isisCircLevelIDOctet OBJECT-TYPE

SYNTAX Unsigned32(0..255)

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"A one-byte identifier for the circuit selected by the
Intermediate System.

On point-to-point circuits, the value is used as the Local
Circuit ID in point-to-point IIH PDUs transmitted on this
circuit. In this case, values of isisCircLevelIDOctet do
not need to be unique.

For broadcast circuits, the value is used to generate the
LAN ID that will be used if this Intermediate System is
elected as the Designated IS on this circuit. The value
is required to differ on LANs where the Intermediate System
is the Designated Intermediate System."

::= { isisCircLevelEntry 5 }

isisCircLevelID OBJECT-TYPE

SYNTAX IsisCircuitID

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"On a point-to-point circuit with a fully initialized
adjacency to a peer IS, the value of this object is
the circuit ID negotiated during adjacency initialization.

On a point to point circuit without such an adjacency, the value is the concatenation of the local system ID and the one-byte isisCircLevelIDOctet for this circuit, i.e., the value that would be proposed for the circuit ID. On other circuit types, the value returned is the zero-length OCTET STRING."

```
REFERENCE "{ISIS.aoi ptPtCircuitID (51)}"
::= { isisCircLevelEntry 6 }
```

isisCircLevelDesIS OBJECT-TYPE

SYNTAX IsisCircuitID

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The ID of the LAN-Designated Intermediate System on this circuit at this level. If, for any reason, this system is not partaking in the relevant Designated Intermediate System election process, then the value returned is the zero-length OCTET STRING."

```
REFERENCE "{ISIS.aoi l2DesignatedIntermediateSystem (75)}"
::= { isisCircLevelEntry 7 }
```

isisCircLevelHelloMultiplier OBJECT-TYPE

SYNTAX Unsigned32 (2..100)

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"This value is multiplied by the corresponding HelloTimer, and the result in seconds (rounded up) is used as the holding time in transmitted hellos, to be used by receivers of hello packets from this IS."

```
REFERENCE "{ISIS.aoi iSISHelloTimer (45)}"
DEFVAL { 10 }
::= { isisCircLevelEntry 8 }
```

isisCircLevelHelloTimer OBJECT-TYPE

SYNTAX Unsigned32 (10..600000)

UNITS "milliseconds"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Maximum period, in milliseconds, between IIH PDUs on multiaccess networks at this level for LANs. The value at L1 is used as the period between Hellos on L1L2 point-to-point circuits. Setting this value at level 2 on an L1L2 point-to-point circuit will result in an error of InconsistentValue."

This object follows the ResettingTimer behavior."

REFERENCE "{ISIS.aoi iSISHelloTimer (45)}"

DEFVAL { 3000 }

::= { isisCircLevelEntry 9 }

isisCircLevelDRHelloTimer OBJECT-TYPE

SYNTAX Unsigned32 (10..120000)

UNITS "milliseconds"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Period, in milliseconds, between Hello PDUs on multiaccess networks when this IS is the Designated Intermediate System. This object follows the ResettingTimer behavior."

REFERENCE "{ISIS.aoi iSISHelloTimer (45)}"

DEFVAL { 1000 }

::= { isisCircLevelEntry 10 }

isisCircLevelLSPThrottle OBJECT-TYPE

SYNTAX IsisUnsigned16TC (1..65535)

UNITS "milliseconds"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Minimal interval of time, in milliseconds, between transmissions of LSPs on an interface at this level."

REFERENCE

"{ISIS.aoi minimumBroadcastLSPTransmissionInterval (5)}"

DEFVAL { 30 }

::= { isisCircLevelEntry 11 }

isisCircLevelMinLSPRetransInt OBJECT-TYPE

SYNTAX Unsigned32 (1..300)

UNITS "seconds"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Minimum interval, in seconds, between re-transmission of an LSP at this level. This object follows the ResettingTimer behavior."

Note that isisCircLevelLSPThrottle controls how fast we send back-to-back LSPs. This variable controls how fast we re-send the same LSP."

REFERENCE "{ISIS.aoi minimumLSPTransmissionInterval (5)}"

DEFVAL { 5 }

::= { isisCircLevelEntry 12 }

isisCircLevelCSNPInterval OBJECT-TYPE

SYNTAX Unsigned32 (1..600)

UNITS "seconds"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Interval of time, in seconds, between periodic transmission of a complete set of CSNPs on multiaccess networks if this router is the designated router at this level.

This object follows the ResettingTimer behavior."

REFERENCE "{ISIS.aoi completeSNPInterval (8)}"

DEFVAL { 10 }

::= { isisCircLevelEntry 13 }

isisCircLevelPartSNPInterval OBJECT-TYPE

SYNTAX Unsigned32 (1..120)

UNITS "seconds"

MAX-ACCESS read-write

STATUS current

DESCRIPTION

"Minimum interval, in seconds, between sending Partial Sequence Number PDUs at this level. This object follows the ResettingTimer behavior."

REFERENCE "{ISIS.aoi partialSNPInterval (14)}"

DEFVAL { 2 }

::= { isisCircLevelEntry 14 }

-- isisSystemCounterTable keeps track of system-wide events.

isisSystemCounterTable OBJECT-TYPE

SYNTAX SEQUENCE OF IsisSystemCounterEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"System-wide counters for this Intermediate System."

::= { isisCounters 1 }

isisSystemCounterEntry OBJECT-TYPE

SYNTAX IsisSystemCounterEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"System-wide IS-IS counters."

INDEX { isisSysStatLevel }

::= { isisSystemCounterTable 1 }

IsisSystemCounterEntry ::=

```

SEQUENCE {
    isisSysStatLevel
        IsisISLevel,
    isisSysStatCorrLSPs
        Counter32,
    isisSysStatAuthTypeFails
        Counter32,
    isisSysStatAuthFails
        Counter32,
    isisSysStatLSPDbaseOloads
        Counter32,
    isisSysStatManAddrDropFromAreas
        Counter32,
    isisSysStatAttmptToExMaxSeqNums
        Counter32,
    isisSysStatSeqNumSkips
        Counter32,
    isisSysStatOwnLSPPurges
        Counter32,
    isisSysStatIDFieldLenMismatches
        Counter32,
    isisSysStatPartChanges
        Counter32,
    isisSysStatSPFRuns
        Counter32,
    isisSysStatLSPErrors
        Counter32
}

```

```

isisSysStatLevel OBJECT-TYPE
    SYNTAX IsisISLevel
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The level that this entry describes."
 ::= { isisSystemCounterEntry 1 }

```

```

isisSysStatCorrLSPs OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of corrupted in-memory frames"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of corrupted in-memory LSPs detected.

        LSPs received from the wire with a bad checksum
        are silently dropped and are not counted.

```



```
        LSPs received from the wire with parse errors
        are counted by isisSysStatLSPErrors."
    REFERENCE "{ISIS.aoi corruptedLSPsDetected (19)}"
 ::= { isisSystemCounterEntry 2 }

isisSysStatAuthTypeFails OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of frames with authentication type mismatches"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of authentication type mismatches recognized
        by this Intermediate System."
 ::= { isisSystemCounterEntry 3 }

isisSysStatAuthFails OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of frames with authentication key failures"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of authentication key failures recognized
        by this Intermediate System."
 ::= { isisSystemCounterEntry 4 }

isisSysStatLSPDbaseOloads OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of times the LSP database has become
        overloaded."
    REFERENCE "{ISIS.aoi lSPL1DatabaseOverloads (20)}"
 ::= { isisSystemCounterEntry 5 }

isisSysStatManAddrDropFromAreas OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of times a manual address has been dropped from
        the area."
    REFERENCE "{ISIS.aoi manualAddressesDroppedFromArea (21)}"
 ::= { isisSystemCounterEntry 6 }

isisSysStatAttmptToExMaxSeqNums OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
```

```
STATUS current
DESCRIPTION
    "Number of times the IS has attempted to exceed the
    maximum sequence number."
REFERENCE
    "{ISIS.aoi attemptsToExceedmaximumSequenceNumber (22)}"
::= { isisSystemCounterEntry 7 }

isisSysStatSeqNumSkips OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of times a sequence number skip has occurred."
    REFERENCE "{ISIS.aoi sequenceNumberSkips (23)}"
::= { isisSystemCounterEntry 8 }

isisSysStatOwnLSPPurges OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of times a zero-aged copy of the system's own LSP
        is received from some other node."
    REFERENCE "{ISIS.aoi ownLSPPurges (24)}"
::= { isisSystemCounterEntry 9 }

isisSysStatIDFieldLenMismatches OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of frames with ID length mismatches"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of times a PDU is received with a different value
        for ID field length from that of the receiving system."
    REFERENCE "{ISIS.aoi idFieldLengthMismatches (25)}"
::= { isisSystemCounterEntry 10 }

isisSysStatPartChanges OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Partition changes."
::= { isisSystemCounterEntry 11 }

isisSysStatSPFRuns OBJECT-TYPE
    SYNTAX Counter32
```

```

    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of times we ran SPF at this level."
 ::= { isisSystemCounterEntry 12 }

isisSysStatLSPErrors OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of frames with errors that we have received"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Number of LSPs with errors we have received."
 ::= { isisSystemCounterEntry 13 }

-- isisCircuitCounterTable keeps track of events
-- specific to a circuit and a level

isisCircuitCounterTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisCircuitCounterEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Circuit specific counters for this
         Intermediate System."
 ::= { isisCounters 2 }

isisCircuitCounterEntry OBJECT-TYPE
    SYNTAX IsisCircuitCounterEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "An isisCircuitCounterEntry exists for each circuit
         used by Integrated IS-IS on this system."
    INDEX { isisCircIndex,
            isisCircuitType }
 ::= { isisCircuitCounterTable 1 }

IsisCircuitCounterEntry ::= SEQUENCE {
    isisCircuitType
        INTEGER,
    isisCircAdjChanges
        Counter32,
    isisCircNumAdj
        Unsigned32,
    isisCircInitFails
        Counter32,
    isisCircRejAdjs

```

```

        Counter32,
isisCircIDFieldLenMismatches
        Counter32,
isisCircMaxAreaAddrMismatches
        Counter32,
isisCircAuthTypeFails
        Counter32,
isisCircAuthFails
        Counter32,
isisCircLANDesISChanges
        Counter32
    }
isisCircuitType OBJECT-TYPE
    SYNTAX INTEGER
    {
        lanlevel1(1),
        lanlevel2(2),
        p2pcircuit(3)
    }
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "What type of circuit saw these counts?

        The point-to-point Hello PDU includes
        both L1 and L2, and ISs form a single
        adjacency on point-to-point links.
        Thus, we combine counts on
        point-to-point links into one group."
 ::= { isisCircuitCounterEntry 1 }

isisCircAdjChanges OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of times an adjacency state change has
        occurred on this circuit."
    REFERENCE "{ISIS.aoi changesInAdjacencyState (40)}"
 ::= { isisCircuitCounterEntry 2 }

isisCircNumAdj OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of adjacencies on this circuit."

```

```
REFERENCE "{ISIS.aoi changesInAdjacencyState (40)}"
 ::= { isisCircuitCounterEntry 3 }

isisCircInitFails OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of times initialization of this circuit has
         failed. This counts events such as PPP NCP failures.
         Failures to form an adjacency are counted by
         isisCircRejAdjs."
 ::= { isisCircuitCounterEntry 4 }

isisCircRejAdjs OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of times an adjacency has been rejected on
         this circuit."
    REFERENCE "{ISIS.aoi rejectedAdjacencies (42)}"
 ::= { isisCircuitCounterEntry 5 }

isisCircIDFieldLenMismatches OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of frames with ID field length mismatch"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of times an IS-IS control PDU with an ID
         field length different from that for this system has been
         received."
    REFERENCE "{ISIS.aoi idFieldLengthMismatches (25)}"
 ::= { isisCircuitCounterEntry 6 }

isisCircMaxAreaAddrMismatches OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of times an IS-IS control PDU with a
         max area length address field different from that for this
         system has been received."
    REFERENCE "{ISIS.aoi idFieldLengthMismatches (25)}"
 ::= { isisCircuitCounterEntry 7 }

isisCircAuthTypeFails OBJECT-TYPE
```

```
SYNTAX Counter32
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of times an IS-IS control PDU with
    an auth type field different from that for this
    system has been received."
 ::= { isisCircuitCounterEntry 8 }

isisCircAuthFails OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of times an IS-IS control PDU with
        the correct auth type has failed to pass authentication
        validation."
 ::= { isisCircuitCounterEntry 9 }

isisCircLANDesISChanges OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of times the Designated IS has changed
        on this circuit at this level.  If the circuit is
        point to point, this count is zero."
 ::= { isisCircuitCounterEntry 10 }

-- isisPacketCounterTable keeps track of the number of IS-IS
-- control packets sent and received at each level

isisPacketCounterTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisPacketCounterEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Information about IS-IS protocol traffic at one level,
        on one circuit, in one direction."
 ::= { isisCounters 3 }

isisPacketCounterEntry OBJECT-TYPE
    SYNTAX IsisPacketCounterEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Information about IS-IS protocol traffic at one level,
        on one circuit, in one direction."
```

```

    INDEX { isisCircIndex,
             isisPacketCountLevel,
             isisPacketCountDirection }
 ::= { isisPacketCounterTable 1 }

IsisPacketCounterEntry ::=
    SEQUENCE {
        isisPacketCountLevel
            IsisISLevel,
        isisPacketCountDirection
            INTEGER,
        isisPacketCountIIHello
            Counter32,
        isisPacketCountISHello
            Counter32,
        isisPacketCountESHello
            Counter32,
        isisPacketCountLSP
            Counter32,
        isisPacketCountCSNP
            Counter32,
        isisPacketCountPSNP
            Counter32,
        isisPacketCountUnknown
            Counter32
    }

isisPacketCountLevel OBJECT-TYPE
    SYNTAX IsisISLevel
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The level at which these PDU counts have been collected."
 ::= { isisPacketCounterEntry 1 }

isisPacketCountDirection OBJECT-TYPE
    SYNTAX INTEGER
    {
        sending(1),
        receiving(2)
    }
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Were we sending or receiving these PDUs?"
 ::= { isisPacketCounterEntry 2 }

isisPacketCountIIHello OBJECT-TYPE

```

```
SYNTAX Counter32
UNITS "Number of IS-IS Hellos frames seen in this direction
      at this level"
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of IS-IS Hello PDUs seen in this
    direction at this level.

    Point-to-Point IIH PDUs are counted at
    the lowest enabled level: at L1 on L1 or L1L2 circuits,
    and at L2 otherwise."
REFERENCE "{ISIS.aoi iSISControlPDUsSent (43)}"
 ::= { isisPacketCounterEntry 3 }

isisPacketCountISHello OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of ES-IS frames seen in this direction at
          this level."
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of ES-IS Hello PDUs seen in this
        direction. ISH PDUs are counted at the
        lowest enabled level: at L1 on L1 or L1L2
        circuits, and at L2 otherwise."
    ::= { isisPacketCounterEntry 4 }

isisPacketCountESHello OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of ES Hello frames seen in this direction at
          this level"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of ES Hello PDUs seen in this
        direction. ESH PDUs are counted at the
        lowest enabled level: at L1 on L1 or L1L2
        circuits, and at L2 otherwise."
    ::= { isisPacketCounterEntry 5 }

isisPacketCountLSP OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of IS-IS LSP frames seen in this direction at
          this level"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
```



```

        "The number of IS-IS LSPs seen in this
        direction at this level."
    REFERENCE "{ISIS.aoi iSISControlPDUsSent (43)}"
 ::= { isisPacketCounterEntry 6 }

```

```

isisPacketCountCSNP OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of IS-IS CSNP frames seen in this direction at
        this level"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of IS-IS CSNPs seen in this
        direction at this level."
    REFERENCE "{ISIS.aoi iSISControlPDUsSent (43)}"
 ::= { isisPacketCounterEntry 7 }

```

```

isisPacketCountPSNP OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of IS-IS PSNP frames seen in this direction at
        this level"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of IS-IS PSNPs seen in this
        direction at this level."
    REFERENCE "{ISIS.aoi iSISControlPDUsSent (43)}"
 ::= { isisPacketCounterEntry 8 }

```

```

isisPacketCountUnknown OBJECT-TYPE
    SYNTAX Counter32
    UNITS "Number of unknown IS-IS frames seen at this level"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of unknown IS-IS PDUs seen
        at this level."
    REFERENCE "{ISIS.aoi iSISControlPDUsSent (43)}"
 ::= { isisPacketCounterEntry 9 }

```

```

-- The IS Adjacency Table
--
-- Each adjacency to an IS corresponds to one entry in this
-- table.

```

```

isisISAdjTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisISAdjEntry
    MAX-ACCESS not-accessible

```

```
STATUS current
DESCRIPTION
    "The table of adjacencies to Intermediate Systems."
 ::= { isisISAdj 1 }

isisISAdjEntry OBJECT-TYPE
    SYNTAX IsisISAdjEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each entry corresponds to one adjacency to an
         Intermediate System on this system.

         Dynamically learned rows do not survive an agent reboot."
    INDEX { isisCircIndex,
            isisISAdjIndex }
 ::= { isisISAdjTable 1 }

IsisISAdjEntry ::=
    SEQUENCE {
        isisISAdjIndex
            Unsigned32,
        isisISAdjState
            INTEGER,
        isisISAdj3WayState
            INTEGER,
        isisISAdjNeighSNPAAAddress
            IsisOSINSAddress,
        isisISAdjNeighSysType
            INTEGER,
        isisISAdjNeighSysID
            IsisSystemID,
        isisISAdjNbrExtendedCircID
            Unsigned32,
        isisISAdjUsage
            IsisLevel,
        isisISAdjHoldTimer
            IsisUnsigned16TC,
        isisISAdjNeighPriority
            IsisISPriority,
        isisISAdjLastUpTime
            TimeStamp
    }

isisISAdjIndex OBJECT-TYPE
    SYNTAX Unsigned32(1..4294967295)
    MAX-ACCESS not-accessible
    STATUS current
```

```

DESCRIPTION
    "A unique value identifying the IS adjacency from all
    other such adjacencies on this circuit. This value is
    automatically assigned by the system when the adjacency
    is created."
 ::= { isisISAdjEntry 1 }

isisISAdjState OBJECT-TYPE
    SYNTAX INTEGER
        {
            down (1),
            initializing (2),
            up (3),
            failed(4)
        }
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The state of the adjacency."
    REFERENCE "{ISIS.aoi adjacencyState (78)}"
 ::= { isisISAdjEntry 2 }

isisISAdj3WayState OBJECT-TYPE
    SYNTAX INTEGER
        {
            up (0),
            initializing (1),
            down (2),
            failed (3)
        }
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The 3Way state of the adjacency. These are picked
        to match the historical on-the-wire representation
        of the 3Way state and are not intended to match
        isisISAdjState."
    REFERENCE "{ RFC 3373 }"
 ::= { isisISAdjEntry 3 }

isisISAdjNeighSNPAAAddress OBJECT-TYPE
    SYNTAX IsisOSINSAddress
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The SNPA address of the neighboring system."
    REFERENCE "{ISIS.aoi neighbourSNPAAAddress (79)}"
 ::= { isisISAdjEntry 4 }

```

isisISAdjNeighSysType OBJECT-TYPE

SYNTAX INTEGER

```
{
    l1IntermediateSystem(1),
    l2IntermediateSystem(2),
    l1L2IntermediateSystem(3),
    unknown(4)
}
```

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The type of the neighboring system."

REFERENCE "{ISIS.aoi neighbourSystemType (80)}"

::= { isisISAdjEntry 5 }

isisISAdjNeighSysID OBJECT-TYPE

SYNTAX IsisSystemID

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The system ID of the neighboring Intermediate System."

REFERENCE "{ISIS.aoi neighbourSystemIds (83)}"

::= { isisISAdjEntry 6 }

isisISAdjNbrExtendedCircID OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The 4-byte Extended Circuit ID learned from the Neighbor during 3-way handshake, or 0."

::= { isisISAdjEntry 7 }

isisISAdjUsage OBJECT-TYPE

SYNTAX IsisLevel

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"How is the adjacency used? On a point-to-point link, this might be levelland2, but on a LAN, the usage will be levell1 on the adjacency between peers at L1, and level2 for the adjacency between peers at L2."

REFERENCE "{ISIS.aoi adjacencyUsage (82)}"

::= { isisISAdjEntry 8 }

isisISAdjHoldTimer OBJECT-TYPE

SYNTAX IsisUnsigned16TC (1..65535)

```

    UNITS "seconds"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The holding time, in seconds, for this adjacency.
        This value is based on received IIH PDUs and
        the elapsed time since receipt."
    REFERENCE "{ISIS.aoi holdingTimer (85)}"
 ::= { isisISAdjEntry 9 }

isisISAdjNeighPriority OBJECT-TYPE
    SYNTAX IsisISPriority
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Priority of the neighboring Intermediate System for
        becoming the Designated Intermediate System."
    REFERENCE "{ISIS.aoi LANPriority (86)}"
 ::= { isisISAdjEntry 10 }

isisISAdjLastUpTime OBJECT-TYPE
    SYNTAX TimeStamp
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "When the adjacency most recently entered the state 'up',
        measured in hundredths of a second since the last
        re-initialization of the network management subsystem.
        Holds 0 if the adjacency has never been in state 'up'."
 ::= { isisISAdjEntry 11 }

-- The IS Adjacency Area Address Table

-- The IS Adjacency Area Address Table contains the set of
-- Area Addresses of neighboring
-- Intermediate Systems as reported in IIH PDUs.

isisISAdjAreaAddrTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisISAdjAreaAddrEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "This table contains the set of Area Addresses of
        neighboring Intermediate Systems as reported in received
        IIH PDUs."
    REFERENCE "{ISIS.aoi areaAddressesOfNeighbour (84)}"
 ::= { isisISAdj 2 }

```

```

isisISAdjAreaAddrEntry OBJECT-TYPE
    SYNTAX IsisISAdjAreaAddrEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each entry contains one Area Address reported by a
        neighboring Intermediate System in its IIH PDUs.

        Dynamically learned rows do not survive an agent reboot."
    INDEX { isisCircIndex,
            isisISAdjIndex,
            isisISAdjAreaAddrIndex }
    ::= { isisISAdjAreaAddrTable 1 }

IsisISAdjAreaAddrEntry ::=
    SEQUENCE {
        isisISAdjAreaAddrIndex
            Unsigned32,
        isisISAdjAreaAddress
            IsisOSINSAddress
    }

isisISAdjAreaAddrIndex OBJECT-TYPE
    SYNTAX Unsigned32(1..4294967295)
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "An index for the areas associated with one neighbor.
        This provides a simple way to walk the table."
    ::= { isisISAdjAreaAddrEntry 1 }

isisISAdjAreaAddress OBJECT-TYPE
    SYNTAX IsisOSINSAddress
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "One Area Address as reported in IIH PDUs received from
        the neighbor."
    ::= { isisISAdjAreaAddrEntry 2 }

-- The IS Adjacency IP Address Table

-- The IS Adjacency IP Address Table contains the
-- set of IP Addresses of neighboring Intermediate Systems
-- as reported in received IIH PDUs.

isisISAdjIPAddrTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisISAdjIPAddrEntry

```

```

MAX-ACCESS not-accessible
STATUS current
DESCRIPTION
    "This table contains the set of IP Addresses of
    neighboring Intermediate Systems as reported in received
    IIH PDUs."
 ::= { isisISAdj 3 }

isisISAdjIPAddrEntry OBJECT-TYPE
    SYNTAX IsisISAdjIPAddrEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each entry contains one IP Address reported by a
        neighboring Intermediate System in its IIH PDUs.

        Dynamically learned rows do not survive an agent reboot."
    INDEX { isisCircIndex,
            isisISAdjIndex,
            isisISAdjIPAddrIndex
          }
 ::= { isisISAdjIPAddrTable 1 }

IsisISAdjIPAddrEntry ::=
    SEQUENCE {
        isisISAdjIPAddrIndex
            Unsigned32,
        isisISAdjIPAddrType
            InetAddressType,
        isisISAdjIPAddrAddress
            InetAddress
    }

isisISAdjIPAddrIndex OBJECT-TYPE
    SYNTAX Unsigned32(1..4294967295)
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "An index to this table that identifies the IP addresses
        to which this entry belongs."
 ::= { isisISAdjIPAddrEntry 1 }

isisISAdjIPAddrType OBJECT-TYPE
    SYNTAX InetAddressType
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The type of one IP Address as reported in IIH PDUs

```

```

        received from the neighbor."
 ::= { isisISAdjIPAddrEntry 2 }

isisISAdjIPAddrAddress OBJECT-TYPE
    SYNTAX InetAddress
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "One IP Address as reported in IIH PDUs received from the
        neighbor.

        The type of this address is determined by the value of
        the isisISAdjIPAddrType object."
 ::= { isisISAdjIPAddrEntry 3 }

-- The IS Adjacency Protocol Supported Table
--
-- The IS Adjacency Protocol Supported Table contains the set of
-- protocols supported by neighboring
-- Intermediate Systems as reported in received IIH PDUs.

isisISAdjProtSuppTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisISAdjProtSuppEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "This table contains the set of protocols supported by
        neighboring Intermediate Systems as reported in received
        IIH PDUs."
 ::= { isisISAdj 4 }

isisISAdjProtSuppEntry OBJECT-TYPE
    SYNTAX IsisISAdjProtSuppEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each entry contains one protocol supported by a
        neighboring Intermediate System as reported in its IIH
        PDUs.

        Dynamically learned rows do not survive an agent reboot."
    INDEX { isisCircIndex,
            isisISAdjIndex,
            isisISAdjProtSuppProtocol }
 ::= { isisISAdjProtSuppTable 1 }

IsisISAdjProtSuppEntry ::=
    SEQUENCE {
```



```

        isisISAdjProtSuppProtocol
            IsisSupportedProtocol
    }

isisISAdjProtSuppProtocol OBJECT-TYPE
    SYNTAX IsisSupportedProtocol
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "One supported protocol as reported in IIH PDUs received
        from the neighbor."
    ::= { isisISAdjProtSuppEntry 1 }

-- The Reachable Address Group
--
-- The Reachable Address Table
-- Each entry records information about a reachable address
-- (NSAP or address prefix) manually configured on the system
-- or learned through another protocol.

isisRATable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisRAEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The table of Reachable Addresses to NSAPs or Address
        Prefixes."
    ::= { isisReachAddr 1 }

isisRAEntry OBJECT-TYPE
    SYNTAX IsisRAEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each entry defines a configured Reachable Address
        to an NSAP or Address Prefix.

        Dynamically created rows MUST survive an agent reboot."
    INDEX { isisCircIndex,
            isisRAIndex }
    ::= { isisRATable 1 }

IsisRAEntry ::=
    SEQUENCE {
        isisRAIndex
            Unsigned32,
        isisRAExistState
            RowStatus,

```

```

isisRAAdminState
    IsisAdminState,
isisRAAddrPrefix
    IsisOSINSAddress,
isisRAMapType
    INTEGER,
isisRAMetric
    IsisDefaultMetric,
isisRAMetricType
    IsisMetricType,
isisRASNPAddress
    IsisOSINSAddress,
isisRASNPAMask
    IsisOSINSAddress,
isisRASNPAPrefix
    IsisOSINSAddress,
isisRAType
    INTEGER
}

isisRAIndex OBJECT-TYPE
    SYNTAX Unsigned32(1..4294967295)
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The identifier for this isisRAEntry. This value must be
        unique amongst all Reachable Addresses on the same parent
        Circuit."
 ::= { isisRAEntry 1 }

isisRAExistState OBJECT-TYPE
    SYNTAX RowStatus
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The existence state of this Reachable Address. This
        object follows the ManualOrAutomatic behaviors. Support
        for 'createAndWait' and 'notInService' is not required.

        A row entry cannot be modified when the value of this
        object is 'active'."
 ::= { isisRAEntry 2 }

isisRAAdminState OBJECT-TYPE
    SYNTAX IsisAdminState
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION

```

"The administrative state of the Reachable Address. This object follows the ManualOrAutomatic behaviors."

DEFVAL { off }

::= { isisRAEntry 3 }

isisRAAddrPrefix OBJECT-TYPE

SYNTAX IsisOSINSAddress

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The destination of this Reachable Address. This is an Address Prefix. This object follows the ReplaceOnlyWhileDisabled and ManualOrAutomatic behaviors."

REFERENCE "{ISIS.aoi addressPrefix (98)}"

::= { isisRAEntry 4 }

isisRAMapType OBJECT-TYPE

SYNTAX INTEGER

```
{
    none (1),
    explicit (2),
    extractIDI (3),
    extractDSP (4)
}
```

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The type of mapping to be employed to ascertain the SNPA Address that should be used in forwarding PDUs for this Reachable Address prefix. This object follows the ManualOrAutomatic behavior. The following values of mapping type are defined:

none: The mapping is null because the neighbor SNPA is implicit by nature of the subnetwork (e.g., a point-to-point linkage).

explicit: The subnetwork addresses in the object isisRASNPAAAddress are to be used.

extractIDI: The SNPA is embedded in the IDI of the destination NSAP Address. The mapping algorithm extracts the SNPA to be used according to the format and encoding rules of ISO8473/Add2. This SNPA extraction algorithm can be used in conjunction with Reachable Address prefixes from the X.121, F.69, E.163, and E.164

addressing subdomains.

extractDSP: All, or a suffix, of the SNPA is embedded in the DSP of the destination address. This SNPA extraction algorithm extracts the embedded subnetwork addressing information by performing a logical AND of the isisRASNPAMask object value with the destination address. The part of the SNPA extracted from the destination NSAP is appended to the isisRASNPAPrefix object value to form the next hop subnetwork addressing information."

REFERENCE "{ISO10589-ISIS.aoi mappingType (107)}"
::= { isisRAEntry 5 }

isisRAMetric OBJECT-TYPE

SYNTAX IsisDefaultMetric

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The metric value for reaching the specified prefix over this circuit. This object follows the ManualOrAutomatic behavior."

REFERENCE "{ISIS.aoi DefaultMetric (99)}"

DEFVAL { 20 }

::= { isisRAEntry 6 }

isisRAMetricType OBJECT-TYPE

SYNTAX IsisMetricType

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"Indicates whether the metric is internal or external. This object follows the ManualOrAutomatic behavior."

REFERENCE "{ISIS.aoi DefaultMetricType (103)}"

DEFVAL { internal }

::= { isisRAEntry 7 }

isisRASNPAAAddress OBJECT-TYPE

SYNTAX IsisOSINSAddress

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The SNPA Address to which a PDU may be forwarded in order to reach a destination that matches the address prefix of the Reachable Address. This object follows the

```

        ManualOrAutomatic behavior."
    REFERENCE "{ISIS.aoi sNPAAAddresses (109)}"
-- Note only one address may be specified per Reachable Address
-- in the MIB
    DEFVAL { 'H }
    ::= { isisRAEntry 8 }

isisRASNPAMask OBJECT-TYPE
    SYNTAX IsisOSINSAddress
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "A bit mask with 1 bit indicating the positions in the
        effective destination address from which embedded SNPA
        information is to be extracted.  For the extraction, the
        first octet of the isisRASNPAMask object value is aligned
        with the first octet (AFI) of the NSAP Address.  If the
        isisRASNPAMask object value and NSAP Address are of
        different lengths, the shorter of the two is logically
        padded with zeros before performing the extraction.  This
        object follows the ManualOrAutomatic behavior."
    REFERENCE "{ISIS.aoi sNPAMask (122)}"
    DEFVAL { '00'H }
    ::= { isisRAEntry 9 }

isisRASNPAPrefix OBJECT-TYPE
    SYNTAX IsisOSINSAddress
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "A fixed SNPA prefix for use when the isisRAMapType is
        extractDSP.  The SNPA Address to use is formed by
        concatenating the fixed SNPA prefix with a variable SNPA
        part that is extracted from the effective destination
        address.  For Reachable Address prefixes in which the
        entire SNPA is embedded in the DSP, the SNPA Prefix shall
        be null.  This object follows the ManualOrAutomatic
        behavior."
    REFERENCE "{ISIS.aoi sNPAPrefix (123)}"
    DEFVAL { '00'H }
    ::= { isisRAEntry 10 }

isisRAType OBJECT-TYPE
    SYNTAX INTEGER
    {
        manual (1),
        automatic (2)
    }

```

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The type of Reachable address. Those of type manual are created by the network manager. Those of type automatic are created through propagation of routing information from another routing protocol (e.g., IDRP). "

DEFVAL {manual}

::= {isisRAEntry 11 }

-- The IP Reachable Address Table

-- Each entry records information about one IP reachable
 -- address manually configured on this system or learned from
 -- another protocol.

isisIPRATable OBJECT-TYPE

SYNTAX SEQUENCE OF IsisIPRAEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"The table of IP Reachable Addresses to networks, subnetworks, or hosts either manually configured or learned from another protocol."

::= { isisIPReachAddr 1 }

isisIPRAEntry OBJECT-TYPE

SYNTAX IsisIPRAEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"Each entry defines an IP Reachable Address to a network, subnetwork, or host.

Each IP Reachable Address may have multiple entries in the table, one for each equal cost path to the reachable address.

Dynamically created rows MUST survive an agent reboot.

Implementers need to be aware that if the total number of elements (octets or sub-identifiers) in isisIPRADestr, isisIPRADestPrefixLen, and isisIPRANextHopIndex is too great, then OIDs of column instances in this table will have more than 128 subidentifiers and cannot be accessed using SNMPv1,

```

        SNMPv2c, or SNMPv3."
INDEX {  isisSysLevelIndex,
         isisIPRADestType,
         isisIPRADest,
         isisIPRADestPrefixLen,
         isisIPRANextHopIndex }
 ::= { isisIPRATable 1 }

IsisIPRAEntry ::=
    SEQUENCE {
        isisIPRADestType
            InetAddressType,
        isisIPRADest
            InetAddress,
        isisIPRADestPrefixLen
            InetAddressPrefixLength,
        isisIPRANextHopIndex
            Unsigned32,
        isisIPRANextHopType
            InetAddressType,
        isisIPRANextHop
            InetAddress,
        isisIPRAType
            INTEGER,
        isisIPRAExistState
            RowStatus,
        isisIPRAAdminState
            IsisAdminState,
        isisIPRAMetric
            IsisDefaultMetric,
        isisIPRAMetricType
            IsisMetricType,
        isisIPRAFullMetric
            IsisFullMetric,
        isisIPRASNPAAAddress
            IsisOSINSAddress,
        isisIPRASourceType
            INTEGER
    }

isisIPRADestType OBJECT-TYPE
    SYNTAX InetAddressType
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The type of this IP Reachable Address."
    ::= { isisIPRAEntry 1 }

```

```
isisIPRADest OBJECT-TYPE
    SYNTAX InetAddress
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The destination of this IP Reachable Address. This is
        a network address, subnetwork address, or host
        address.

        The type of this address is determined by the value of
        the isisIPRADestType object."

 ::= { isisIPRAEntry 2 }

isisIPRADestPrefixLen OBJECT-TYPE
    SYNTAX InetAddressPrefixLength
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The length of the IP Netmask for Reachability Address.

        The values for the index objects isisIPRADest and
        isisIPRADestPrefixLen must be consistent. When the value
        of isisIPRADest (excluding the zone index, if one
        is present) is x, then the bitwise logical-AND
        of x with the value of the mask formed from the
        corresponding index object isisIPRADestPrefixLen MUST be
        equal to x. If not, then the index pair is not
        consistent, and an inconsistentName error must be
        returned on SET or CREATE requests."

 ::= { isisIPRAEntry 3 }

isisIPRANextHopIndex OBJECT-TYPE
    SYNTAX Unsigned32(1..4294967295)
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Index of next hop. Used when there are multiple Equal
        Cost Multipath alternatives for the same destination."

 ::= { isisIPRAEntry 4 }

isisIPRANextHopType OBJECT-TYPE
    SYNTAX InetAddressType
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The type of the IP next hop address."

 ::= { isisIPRAEntry 5 }
```



```
isisIPRANextHop OBJECT-TYPE
    SYNTAX InetAddress
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The IP next hop to this destination.

        The type of this address is determined by the value of
        the isisIPRANextHopType object."
 ::= { isisIPRAEntry 6 }

isisIPRAType OBJECT-TYPE
    SYNTAX INTEGER
        {
            manual (1),
            automatic (2)
        }
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The type of this IP Reachable Address. Those of type
        manual are created by the network manager. Those of type
        automatic are created through propagation of routing
        information from another routing protocol. This object
        follows the ManualOrAutomatic behavior."
 ::= { isisIPRAEntry 7 }

isisIPRAExistState OBJECT-TYPE
    SYNTAX RowStatus
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The state of this IP Reachable Address. This object
        follows the ExistenceState and ManualOrAutomatic
        behaviors. Support for 'createAndWait' and
        'notInService' is not required.

        A row entry cannot be modified when the value of this
        object is 'active'."
 ::= { isisIPRAEntry 8 }

isisIPRAAdminState OBJECT-TYPE
    SYNTAX IsisAdminState
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The administrative state of the IP Reachable Address. This
        object follows the IsisAdminState and ManualOrAutomatic
```

```
        behaviors."
    DEFVAL { off }
 ::= { isisIPRAEntry 9 }

isisIPRAMetric OBJECT-TYPE
    SYNTAX IsisDefaultMetric
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The metric value for reaching the specified
        destination over this circuit.  This object follows the
        ManualOrAutomatic behavior."
    DEFVAL { 10 }
 ::= { isisIPRAEntry 10 }

isisIPRAMetricType OBJECT-TYPE
    SYNTAX IsisMetricType
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "Indicates whether the metric is internal or
        external.  This object follows the ManualOrAutomatic
        behavior."
    DEFVAL { internal }
 ::= { isisIPRAEntry 11 }

isisIPRAFullMetric OBJECT-TYPE
    SYNTAX IsisFullMetric
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The wide metric value for reaching the specified
        destination over this circuit.  This object follows the
        ManualOrAutomatic behavior."
    DEFVAL { 10 }
 ::= { isisIPRAEntry 12 }

isisIPRASNPAAAddress OBJECT-TYPE
    SYNTAX IsisOSINSAddress
    MAX-ACCESS read-create
    STATUS current
    DESCRIPTION
        "The SNPA Address to which a PDU may be forwarded in
        order to reach a destination that matches this IP
        Reachable Address.  This object follows the
        ManualOrAutomatic behavior."
    DEFVAL { ''H }
 ::= { isisIPRAEntry 13 }
```

```

isisIPRASourceType OBJECT-TYPE
    SYNTAX INTEGER
        {
            static (1),
            direct (2),
            ospfv2 (3),
            ospfv3 (4),
            isis (5),
            rip (6),
            igrp (7),
            eigrp (8),
            bgp (9),
            other (10)
        }
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The origin of this route."
    ::= { isisIPRAEntry 14 }

```

-- The LSP Database Table

--

-- The first table provides Summary Information about LSPs

-- The next table provides a complete record

```

isisLSPSummaryTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisLSPSummaryEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The table of LSP Headers."
    ::= { isisLSPDataBase 1 }

```

```

isisLSPSummaryEntry OBJECT-TYPE
    SYNTAX IsisLSPSummaryEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each entry provides a summary describing an
        LSP currently stored in the system.

        Dynamically learned rows will not survive an
        agent reboot."
    INDEX { isisLSPLevel,
            isisLSPID }
    ::= { isisLSPSummaryTable 1 }

```

```

IsisLSPSummaryEntry ::=

```

```
SEQUENCE {
    isisLSPLevel
        IsisISLevel,
    isisLSPID
        IsisLinkStatePDUID,
    isisLSPSeq
        Unsigned32,
    isisLSPZeroLife
        TruthValue,
    isisLSPChecksum
        IsisUnsigned16TC,
    isisLSPLifetimeRemain
        IsisUnsigned16TC,
    isisLSPPDULength
        IsisUnsigned16TC,
    isisLSPAttributes
        IsisUnsigned8TC
}

isisLSPLevel OBJECT-TYPE
    SYNTAX IsisISLevel
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "At which level does this LSP appear?"
    ::= { isisLSPSummaryEntry 1 }

isisLSPID OBJECT-TYPE
    SYNTAX IsisLinkStatePDUID
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The 8-byte LSP ID for this Link State PDU."
    ::= { isisLSPSummaryEntry 2 }

isisLSPSeq OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The sequence number for this LSP."
    ::= { isisLSPSummaryEntry 3 }

isisLSPZeroLife OBJECT-TYPE
    SYNTAX TruthValue
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
```

```
        "Is this LSP being purged by this system?"
 ::= { isisLSPSummaryEntry 4 }

isisLSPChecksum OBJECT-TYPE
    SYNTAX IsisUnsigned16TC
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The 16-bit Fletcher Checksum for this LSP."
 ::= { isisLSPSummaryEntry 5 }

isisLSPLifetimeRemain OBJECT-TYPE
    SYNTAX IsisUnsigned16TC
    UNITS "seconds"
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The remaining lifetime, in seconds, for this LSP."
 ::= { isisLSPSummaryEntry 6 }

isisLSPPDULength OBJECT-TYPE
    SYNTAX IsisUnsigned16TC
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The length of this LSP."
 ::= { isisLSPSummaryEntry 7 }

isisLSPAttributes OBJECT-TYPE
    SYNTAX IsisUnsigned8TC
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "Flags carried by the LSP."
 ::= { isisLSPSummaryEntry 8 }

-- LSP Table
--
-- The full LSP as a sequence of {Type, Len, Value} tuples
-- Since the underlying LSP may have changed while downloading
-- TLVs, we provide the Sequence number and Checksum for each
-- LSP TLV, so the network manager may verify that they are
-- still working on the same version of the LSP.

isisLSPTLVTable OBJECT-TYPE
    SYNTAX SEQUENCE OF IsisLSPTLVEntry
    MAX-ACCESS not-accessible
    STATUS current
```

```
DESCRIPTION
    "The table of LSPs in the database."
 ::= { isisLSPDataBase 2 }

isisLSPTLVEntry OBJECT-TYPE
    SYNTAX IsisLSPTLVEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "Each entry describes a TLV within
         an LSP currently stored in the system.

         Dynamically learned rows will not survive an
         agent reboot."
    INDEX { isisLSPLevel,
            isisLSPID,
            isisLSPTLVIndex }
 ::= { isisLSPTLVTable 1 }

IsisLSPTLVEntry ::=
    SEQUENCE {
        isisLSPTLVIndex
            Unsigned32,
        isisLSPTLVSeq
            Unsigned32,
        isisLSPTLVChecksum
            IsisUnsigned16TC,
        isisLSPTLVType
            IsisUnsigned8TC,
        isisLSPTLVLen
            IsisUnsigned8TC,
        isisLSPTLVValue
            OCTET STRING
    }

isisLSPTLVIndex OBJECT-TYPE
    SYNTAX Unsigned32(1..4294967295)
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The index of this TLV in the LSP. The first TLV has
         index 1, and the Nth TLV has an index of N."
 ::= { isisLSPTLVEntry 1 }

isisLSPTLVSeq OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS read-only
    STATUS current
```

```
DESCRIPTION
    "The sequence number for this LSP."
 ::= { isisLSPTLVEntry 2 }

isisLSPTLVChecksum OBJECT-TYPE
    SYNTAX IsisUnsigned16TC
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The 16-bit Fletcher Checksum for this LSP."
 ::= { isisLSPTLVEntry 3 }

isisLSPTLVType OBJECT-TYPE
    SYNTAX IsisUnsigned8TC
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The type of this TLV."
 ::= { isisLSPTLVEntry 4 }

isisLSPTLVLen OBJECT-TYPE
    SYNTAX IsisUnsigned8TC
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The length of this TLV."
 ::= { isisLSPTLVEntry 5 }

isisLSPTLVValue OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE(0..255))
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The value of this TLV."
 ::= { isisLSPTLVEntry 6 }
```

-- The IS-IS Notification Table

-- The IS-IS Notification Table records fields that are
-- required for notifications

```
isisNotificationEntry OBJECT IDENTIFIER
    ::= { isisNotification 1 }

isisNotificationSysLevelIndex OBJECT-TYPE
    SYNTAX IsisLevel
    MAX-ACCESS accessible-for-notify
```

```
STATUS current
DESCRIPTION
    "The system level for this notification."
 ::= { isisNotificationEntry 1 }

isisNotificationCircIfIndex OBJECT-TYPE
    SYNTAX Unsigned32 (1..2147483647)
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "The identifier of this circuit relevant to
         this notification."
 ::= { isisNotificationEntry 2 }

isisPduLspId OBJECT-TYPE
    SYNTAX IsisLinkStatePDUID
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "An Octet String that uniquely identifies
         a Link State PDU."
 ::= { isisNotificationEntry 3 }

isisPduFragment OBJECT-TYPE
    SYNTAX IsisPDUHeader
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds up to 64 initial bytes of a PDU that
         triggered the notification."
 ::= { isisNotificationEntry 4 }

isisPduFieldLen OBJECT-TYPE
    SYNTAX IsisUnsigned8TC
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds the System ID length reported in PDU we received."
 ::= { isisNotificationEntry 5 }

isisPduMaxAreaAddress OBJECT-TYPE
    SYNTAX IsisUnsigned8TC
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds the Max Area Addresses reported in a PDU
         we received."
 ::= { isisNotificationEntry 6 }
```



```
isisPduProtocolVersion OBJECT-TYPE
    SYNTAX IsisUnsigned8TC
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds the Protocol version reported in PDU we received."
 ::= { isisNotificationEntry 7 }

isisPduLspSize OBJECT-TYPE
    SYNTAX Unsigned32 (0..2147483647)
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds the size of LSP we received that is too
         big to forward."
 ::= { isisNotificationEntry 8 }

isisPduOriginatingBufferSize OBJECT-TYPE
    SYNTAX IsisUnsigned16TC (0..16000)
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds the size of isisSysLevelOrigLSPBuffSize advertised
         by the peer in the originatingLSPBufferSize TLV.
         If the peer does not advertise this TLV, this
         value is set to 0."
 ::= { isisNotificationEntry 9 }

isisPduBufferSize OBJECT-TYPE
    SYNTAX IsisUnsigned16TC (0..16000)
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "Holds the size of LSP received from peer."
 ::= { isisNotificationEntry 10 }

isisPduProtocolsSupported OBJECT-TYPE
    SYNTAX OCTET STRING (SIZE(0..255))
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "The list of protocols supported by an
         adjacent system. This may be empty."
 ::= { isisNotificationEntry 11 }

isisAdjState OBJECT-TYPE
    SYNTAX INTEGER
    {
```

```

        down (1),
        initializing (2),
        up (3),
        failed(4)
    }
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "The current state of an adjacency."
 ::= { isisNotificationEntry 12 }

isisErrorOffset OBJECT-TYPE
    SYNTAX Unsigned32
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "An offset to a problem in a PDU.  If the problem
         is a malformed TLV, this points to the beginning
         of the TLV.  If the problem is in the header, this
         points to the byte that is suspicious."
 ::= { isisNotificationEntry 13 }

isisErrorTLVType OBJECT-TYPE
    SYNTAX Unsigned32 (0..255)
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "The type for a malformed TLV."
 ::= { isisNotificationEntry 14 }

isisNotificationAreaAddress OBJECT-TYPE
    SYNTAX IsisOSINSAddress
    MAX-ACCESS accessible-for-notify
    STATUS current
    DESCRIPTION
        "An Area Address."
 ::= { isisNotificationEntry 15 }

-- Notification definitions
--
-- Note that notifications can be disabled by setting
--     isisSysNotificationEnable false

isisDatabaseOverload NOTIFICATION-TYPE
    OBJECTS {
        isisNotificationSysLevelIndex,
        isisSysLevelState
    }

```

```
STATUS current
DESCRIPTION
    "This notification is generated when the system
    enters or leaves the Overload state. The number
    of times this has been generated and cleared is kept
    track of by isisSysStatLSPDbaseOloads."
 ::= { isisNotifications 1 }

isisManualAddressDrops NOTIFICATION-TYPE
    OBJECTS {
        isisNotificationAreaAddress
    }
    STATUS current
    DESCRIPTION
        "This notification is generated when one of the
        manual areaAddresses assigned to this system is
        ignored when computing routes. The object
        isisNotificationAreaAddress describes the area that
        has been dropped.

        The number of times this event has been generated
        is counted by isisSysStatManAddrDropFromAreas.

        The agent must throttle the generation of
        consecutive isisManualAddressDrops notifications
        so that there is at least a 5-second gap between
        notifications of this type. When notifications
        are throttled, they are dropped, not queued for
        sending at a future time."
 ::= { isisNotifications 2 }

isisCorruptedLSPDetected NOTIFICATION-TYPE
    OBJECTS {
        isisNotificationSysLevelIndex,
        isisPduLspId
    }
    STATUS current
    DESCRIPTION
        "This notification is generated when we find that
        an LSP that was stored in memory has become
        corrupted. The number of times this has been
        generated is counted by isisSysCorrLSPs.

        We forward an LSP ID. We may have independent
        knowledge of the ID, but in some implementations
        there is a chance that the ID itself will be
        corrupted."
```

```
::= { isisNotifications 3 }
```

```
isisAttemptToExceedMaxSequence NOTIFICATION-TYPE
```

```
  OBJECTS {  
    isisNotificationSysLevelIndex,  
    isisPduLspId  
  }
```

```
  STATUS current
```

```
  DESCRIPTION
```

"When the sequence number on an LSP we generate wraps the 32-bit sequence counter, we purge and wait to re-announce this information. This notification describes that event. Since these should not be generated rapidly, we generate an event each time this happens.

While the first 6 bytes of the LSPID are ours, the other two contain useful information."

```
::= { isisNotifications 4 }
```

```
isisIDLenMismatch NOTIFICATION-TYPE
```

```
  OBJECTS {  
    isisNotificationSysLevelIndex,  
    isisPduFieldLen,  
    isisNotificationCircIfIndex,  
    isisPduFragment  
  }
```

```
  STATUS current
```

```
  DESCRIPTION
```

"A notification sent when we receive a PDU with a different value for the System ID Length. This notification includes an index to identify the circuit where we saw the PDU and the header of the PDU, which may help a network manager identify the source of the confusion.

The agent must throttle the generation of consecutive isisIDLenMismatch notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

```
::= { isisNotifications 5 }
```

```
isisMaxAreaAddressesMismatch NOTIFICATION-TYPE
```

```
  OBJECTS {
```

```
    isisNotificationSysLevelIndex,  
    isisPduMaxAreaAddress,  
    isisNotificationCircIfIndex,  
    isisPduFragment  
}
```

STATUS current

DESCRIPTION

"A notification sent when we receive a PDU with a different value for the Maximum Area Addresses. This notification includes the header of the packet, which may help a network manager identify the source of the confusion.

The agent must throttle the generation of consecutive isisMaxAreaAddressesMismatch notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

```
::= { isisNotifications 6 }
```

isisOwnLSPPurge NOTIFICATION-TYPE

```
    OBJECTS {  
        isisNotificationSysLevelIndex,  
        isisNotificationCircIfIndex,  
        isisPduLspId  
    }
```

STATUS current

DESCRIPTION

"A notification sent when we receive a PDU with our systemID and zero age. This notification includes the circuit Index and router ID from the LSP, if available, which may help a network manager identify the source of the confusion."

```
::= { isisNotifications 7 }
```

isisSequenceNumberSkip NOTIFICATION-TYPE

```
    OBJECTS {  
        isisNotificationSysLevelIndex,  
        isisNotificationCircIfIndex,  
        isisPduLspId  
    }
```

STATUS current

DESCRIPTION

"When we receive an LSP with our System ID and different contents, we may need to reissue the LSP with a higher sequence number.

We send this notification if we need to increase the sequence number by more than one. If two Intermediate Systems are configured with the same System ID, this notification will fire."

::= { isisNotifications 8 }

isisAuthenticationTypeFailure NOTIFICATION-TYPE

OBJECTS {
 isisNotificationSysLevelIndex,
 isisNotificationCircIfIndex,
 isisPduFragment
}

STATUS current

DESCRIPTION

"A notification sent when we receive a PDU with the wrong authentication type field. This notification includes the header of the packet, which may help a network manager identify the source of the confusion.

The agent must throttle the generation of consecutive isisAuthenticationTypeFailure notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

::= { isisNotifications 9 }

isisAuthenticationFailure NOTIFICATION-TYPE

OBJECTS {
 isisNotificationSysLevelIndex,
 isisNotificationCircIfIndex,
 isisPduFragment
}

STATUS current

DESCRIPTION

"A notification sent when we receive a PDU with an incorrect authentication information field. This notification includes the header of the packet, which may help a network manager identify the source of the confusion.

The agent must throttle the generation of consecutive isisAuthenticationFailure notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

::= { isisNotifications 10 }

isisVersionSkew NOTIFICATION-TYPE

OBJECTS {
 isisNotificationSysLevelIndex,
 isisNotificationCircIfIndex,
 isisPduProtocolVersion,
 isisPduFragment
}

STATUS current

DESCRIPTION

"A notification sent when we receive a Hello PDU from an IS running a different version of the protocol. This notification includes the header of the packet, which may help a network manager identify the source of the confusion.

The agent must throttle the generation of consecutive isisVersionSkew notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

::= { isisNotifications 11 }

isisAreaMismatch NOTIFICATION-TYPE

OBJECTS {
 isisNotificationCircIfIndex,
 isisPduFragment
}

STATUS current

DESCRIPTION

"A notification sent when we receive a Hello PDU from an IS that does not share any area address. This notification includes the header of the packet, which may help a network manager identify the source of the confusion.

The agent must throttle the generation of consecutive isisAreaMismatch notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

::= { isisNotifications 12 }

isisRejectedAdjacency NOTIFICATION-TYPE

OBJECTS {
 isisNotificationSysLevelIndex,
 isisNotificationCircIfIndex,
 isisPduFragment
}

STATUS current

DESCRIPTION

"A notification sent when we receive a Hello PDU from an IS but do not establish an adjacency for some reason.

The agent must throttle the generation of consecutive isisRejectedAdjacency notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

::= { isisNotifications 13 }

isisLSPTooLargeToPropagate NOTIFICATION-TYPE

OBJECTS {
 isisNotificationSysLevelIndex,
 isisNotificationCircIfIndex,
 isisPduLspSize,
 isisPduLspId
}

STATUS current

DESCRIPTION

"A notification sent when we attempt to propagate an LSP that is larger than the dataLinkBlockSize for the circuit.

The agent must throttle the generation of consecutive isisLSPTooLargeToPropagate notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not

queued for sending at a future time."

::= { isisNotifications 14 }

isisOrigLSPBuffSizeMismatch NOTIFICATION-TYPE

OBJECTS {
 isisNotificationSysLevelIndex,
 isisNotificationCircIfIndex,
 isisPduLspId,
 isisPduOriginatingBufferSize,
 isisPduBufferSize
}

STATUS current

DESCRIPTION

"A notification sent when a Level 1 LSP or Level 2 LSP is received that is larger than the local value for isisSysLevelOrigLSPBuffSize, or when an LSP is received that contains the supported Buffer Size option and the value in the PDU option field does not match the local value for isisSysLevelOrigLSPBuffSize. We pass up the size from the option field and the size of the LSP when one of them exceeds our configuration.

The agent must throttle the generation of consecutive isisOrigLSPBuffSizeMismatch notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

::= { isisNotifications 15 }

isisProtocolsSupportedMismatch NOTIFICATION-TYPE

OBJECTS {
 isisNotificationSysLevelIndex,
 isisNotificationCircIfIndex,
 isisPduProtocolsSupported,
 isisPduLspId,
 isisPduFragment
}

STATUS current

DESCRIPTION

"A notification sent when a non-pseudonode segment 0 LSP is received that has no matching protocols supported. This may be because the system does not generate the field, or because there are no common elements. The list of protocols supported should be included in the notification: it may be

empty if the TLV is not supported, or if the TLV is empty.

The agent must throttle the generation of consecutive isisProtocolsSupportedMismatch notifications so that there is at least a 5-second gap between notifications of this type. When notifications are throttled, they are dropped, not queued for sending at a future time."

::= { isisNotifications 16 }

isisAdjacencyChange NOTIFICATION-TYPE

OBJECTS {
 isisNotificationSysLevelIndex,
 isisNotificationCircIfIndex,
 isisPduLspId,
 isisAdjState
}

STATUS current

DESCRIPTION

"A notification sent when an adjacency changes state, entering or leaving state up.

The first 6 bytes of the isisPduLspId are the SystemID of the adjacent IS.

The isisAdjState is the new state of the adjacency."

::= { isisNotifications 17 }

isisLSPErrorDetected NOTIFICATION-TYPE

OBJECTS {
 isisNotificationSysLevelIndex,
 isisPduLspId,
 isisNotificationCircIfIndex,
 isisPduFragment,
 isisErrorOffset,
 isisErrorTLVType
}

STATUS current

DESCRIPTION

"This notification is generated when we receive an LSP with a parse error. The isisCircIfIndex holds an index of the circuit on which the PDU arrived. The isisPduFragment holds the start of the LSP, and the isisErrorOffset points to the problem.

If the problem is a malformed TLV, isisErrorOffset points to the start of the TLV, and isisErrorTLVType

holds the value of the type.

If the problem is with the LSP header, `isisErrorOffset` points to the suspicious byte.

The number of such LSPs is accumulated in `isisSysStatLSPErrors`."

```
::= { isisNotifications 18 }
```

```
-- Agent Conformance Definitions
```

```
-- We define the objects a conformant agent must define
```

```
isisCompliances OBJECT IDENTIFIER ::= { isisConformance 1 }
```

```
isisGroups      OBJECT IDENTIFIER ::= { isisConformance 2 }
```

```
-- compliance statements
```

```
isisCompliance MODULE-COMPLIANCE
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "The compliance statement for agents that support  
        the IS-IS MIB.
```

```
        There are a number of INDEX objects that cannot be  
        represented in the form of OBJECT clauses in SMIV2,  
        but for which there are compliance requirements.  
        Those requirements and similar requirements for  
        related objects are expressed below, in  
        pseudo-OBJECT clause form, in this description:
```

```
        -- OBJECT isisSummAddressType
```

```
        -- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
```

```
        --
```

```
        -- DESCRIPTION
```

```
        --     The MIB requires support for IPv4 Summary  
        --     Addresses and anticipates the support of  
        --     IPv6 addresses.
```

```
        --
```

```
        --
```

```
        -- OBJECT isisRedistributeAddrType
```

```
        -- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
```

```
        --
```

```
        -- DESCRIPTION
```

```
        --     The MIB requires support for IPv4  
        --     Redistribution Addresses and anticipates  
        --     the support of IPv6 addresses."
```

```
        --
```

```

--
-- OBJECT isisISAdjIPAddrType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
--
-- DESCRIPTION
--     The MIB requires support for IPv4
--     Adjacency Addresses and anticipates the
--     support of IPv6 addresses.
MODULE -- this module
    MANDATORY-GROUPS {
        isisSystemGroup,
        isisCircuitGroup,
        isisISAdjGroup,
        isisNotificationObjectGroup,
        isisNotificationGroup
    }
::= { isisCompliances 1 }

-- List of all groups, mandatory and optional
isisAdvancedCompliance MODULE-COMPLIANCE
    STATUS current
    DESCRIPTION
        "The compliance statement for agents that fully
        support the IS-IS MIB.

        There are a number of INDEX objects that cannot be
        represented in the form of OBJECT clauses in SMIV2,
        but for which there are compliance requirements.
        Those requirements and similar requirements for
        related objects are expressed below, in
        pseudo-OBJECT clause form, in this description:

        -- OBJECT isisSummAddressType
        -- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
        --
        -- DESCRIPTION
        --     The MIB requires support for IPv4 Summary
        --     Addresses and anticipates the support of
        --     IPv6 addresses.
        --
        --
        -- OBJECT isisRedistributeAddrType
        -- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
        --
        -- DESCRIPTION
        --     The MIB requires support for IPv4
        --     Redistribution Addresses and anticipates
        --     the support of IPv6 addresses."

```

```

--
--
-- OBJECT isisISAdjIPAddrType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
--
-- DESCRIPTION
--     The MIB requires support for IPv4
--     Adjacency Addresses and anticipates the
--     support of IPv6 addresses.
--
--
-- OBJECT isisIPRADestType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
--
-- DESCRIPTION
--     The MIB requires support for IPv4 RA
--     Addresses and anticipates the support of
--     IPv6 addresses.
--
--
-- OBJECT isisIPRANextHopType
-- SYNTAX InetAddressType { ipv4(1), ipv6(2) }
--
-- DESCRIPTION
--     The MIB requires support for IPv4 NextHop
--     Addresses and anticipates the support of
--     IPv6 addresses.
MODULE -- this module
    MANDATORY-GROUPS {
        isisSystemGroup,
        isisCircuitGroup,
        isisISAdjGroup,
        isisNotificationObjectGroup,
        isisNotificationGroup,
        isisISPDUCounterGroup,
        isisRATableGroup,
        isisISIPRADestGroup,
        isisLSPGroup
    }
::= { isisCompliances 2 }

isisReadOnlyCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION
        "When this MIB is implemented without support for
        read-create (i.e., in read-only mode), the
        implementation can claim read-only compliance.  Such
        a device can then be monitored but cannot be

```

```
        configured with this MIB."
MODULE -- this module
    MANDATORY-GROUPS {
        isisSystemGroup,
        isisCircuitGroup,
        isisISAdjGroup
    }

OBJECT isisSysLevelType
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysID
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysMaxPathSplits
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysMaxLSPGenInt
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysPolleSHelloRate
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysWaitTime
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysAdminState
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT isisSysL2toL1Leaking
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."
```

OBJECT isisSysMaxAge
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisManAreaAddrExistState
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisSysLevelOrigLSPBuffSize
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisSysLevelMinLSPGenInt
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisSysLevelSetOverload
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisSysLevelSetOverloadUntil
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisSysLevelMetricStyle
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisSysLevelSPFConsiders
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisSysLevelTEEnabled
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisSysReceiveLSPBufferSize
MIN-ACCESS read-only
DESCRIPTION

"Write access is not required."

OBJECT isisSummAddrExistState

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT isisSummAddrMetric

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT isisSummAddrFullMetric

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT isisRedistributeAddrExistState

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT isisCircAdminState

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT isisCircExistState

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT isisCircType

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT isisCircExtDomain

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT isisCircLevelType

MIN-ACCESS read-only

DESCRIPTION

"Write access is not required."

OBJECT isisCircPassiveCircuit

MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisCircMeshGroupEnabled
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisCircMeshGroup
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisCircSmallHellos
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisCircExtendedCircID
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisCircIfIndex
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisCirc3WayEnabled
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisCircLevelMetric
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisCircLevelWideMetric
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

OBJECT isisCircLevelISPriority
MIN-ACCESS read-only
DESCRIPTION
 "Write access is not required."

```
OBJECT isisCircLevelHelloMultiplier
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."
```

```
OBJECT isisCircLevelHelloTimer
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."
```

```
OBJECT isisCircLevelDRHelloTimer
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."
```

```
OBJECT isisCircLevelLSPThrottle
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."
```

```
OBJECT isisCircLevelMinLSPRetransInt
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."
```

```
OBJECT isisCircLevelCSNPInterval
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."
```

```
OBJECT isisCircLevelPartSNPInterval
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."
```

```
::= { isisCompliances 3 }
```

```
-- MIB Grouping
```

```
isisSystemGroup OBJECT-GROUP
    OBJECTS {
        isisSysVersion,
        isisSysLevelType,
        isisSysID,
        isisSysMaxPathSplits,
        isisSysMaxLSPGenInt,
        isisSysPollESHelloRate,
        isisSysWaitTime,
```

```

isisSysAdminState,
isisSysL2toL1Leaking,
isisSysMaxAge,
isisSysProtSupported,
isisSysNotificationEnable,
isisManAreaAddrExistState,
isisSysLevelOrigLSPBuffSize,
isisSysLevelMinLSPGenInt,
isisSysLevelState,
isisSysLevelSetOverload,
isisSysLevelSetOverloadUntil,
isisSysLevelMetricStyle,
isisSysLevelSPFConsiders,
isisSysLevelTEEnabled,
isisSysReceiveLSPBufferSize,
isisSummAddrExistState,
isisSummAddrMetric,
isisAreaAddr,
isisSummAddrFullMetric,
isisRedistributeAddrExistState,
isisRouterHostName,
isisRouterID,
isisSysStatCorrLSPs,
isisSysStatLSPDbaseOloads,
isisSysStatManAddrDropFromAreas,
isisSysStatAttmptToExMaxSeqNums,
isisSysStatSeqNumSkips,
isisSysStatOwnLSPPurges,
isisSysStatIDFieldLenMismatches,
isisSysStatPartChanges,
isisSysStatSPFRuns,
isisSysStatAuthTypeFails,
isisSysStatAuthFails,
isisSysStatLSPErrors
}
STATUS current
DESCRIPTION
    "The collections of objects used to manage an
    IS-IS router."
 ::= { isisGroups 1 }

isisCircuitGroup OBJECT-GROUP
    OBJECTS {
        isisNextCircIndex,
        isisCircAdminState,
        isisCircExistState,
        isisCircType,
        isisCircExtDomain,

```

```
isisCircLevelType,
isisCircAdjChanges,
isisCircNumAdj,
isisCircInitFails,
isisCircRejAdjs,
isisCircIDFieldLenMismatches,
isisCircMaxAreaAddrMismatches,
isisCircAuthTypeFails,
isisCircAuthFails,
isisCircLANDesISChanges,
isisCircPassiveCircuit,
isisCircMeshGroupEnabled,
isisCircMeshGroup,
isisCircSmallHellos,
isisCircLastUpTime,
isisCirc3WayEnabled,
isisCircExtendedCircID,
isisCircIfIndex,
isisCircLevelMetric,
isisCircLevelWideMetric,
isisCircLevelISPriority,
isisCircLevelIDOctet,
isisCircLevelID,
isisCircLevelDesIS,
isisCircLevelHelloMultiplier,
isisCircLevelHelloTimer,
isisCircLevelDRHelloTimer,
isisCircLevelLSPThrottle,
isisCircLevelMinLSPRetransInt,
isisCircLevelCSNPInterval,
isisCircLevelPartSNPInterval
}
STATUS current
DESCRIPTION
    "The collections of objects used to describe an
    IS-IS Circuit."
 ::= { isisGroups 2 }

isisISAdjGroup OBJECT-GROUP
OBJECTS {
    isisISAdjState,
    isisISAdj3WayState,
    isisISAdjNeighSNPAAAddress,
    isisISAdjNeighSysType,
    isisISAdjNeighSysID,
    isisISAdjNbrExtendedCircID,
    isisISAdjUsage,
    isisISAdjHoldTimer,
```

```
        isisISAdjNeighPriority,
        isisISAdjLastUpTime,
        isisISAdjAreaAddress,
        isisISAdjIPAddrType,
        isisISAdjIPAddrAddress,
        isisISAdjProtSuppProtocol
    }
    STATUS current
    DESCRIPTION
        "The collections of objects used to manage an
        IS-IS Adjacency."
 ::= { isisGroups 3 }

isisNotificationObjectGroup OBJECT-GROUP
    OBJECTS {
        isisNotificationSysLevelIndex,
        isisNotificationCircIfIndex,
        isisPduLspId,
        isisPduFragment,
        isisPduFieldLen,
        isisPduMaxAreaAddress,
        isisPduProtocolVersion,
        isisPduLspSize,
        isisPduOriginatingBufferSize,
        isisPduBufferSize,
        isisPduProtocolsSupported,
        isisAdjState,
        isisErrorOffset,
        isisErrorTLVType,
        isisNotificationAreaAddress
    }
    STATUS current
    DESCRIPTION
        "The objects used to record notification parameters."
 ::= { isisGroups 4 }

isisNotificationGroup NOTIFICATION-GROUP
    NOTIFICATIONS {
        isisDatabaseOverload,
        isisManualAddressDrops,
        isisCorruptedLSPDetected,
        isisAttemptToExceedMaxSequence,
        isisIDLenMismatch,
        isisMaxAreaAddressesMismatch,
        isisOwnLSPPurge,
        isisSequenceNumberSkip,
        isisAuthenticationTypeFailure,
```

```
        isisAuthenticationFailure,
        isisVersionSkew,
        isisAreaMismatch,
        isisRejectedAdjacency,
        isisLSPTooLargeToPropagate,
        isisOrigLSPBuffSizeMismatch,
        isisProtocolsSupportedMismatch,
        isisAdjacencyChange,
        isisLSPErrorDetected
    }
    STATUS current
    DESCRIPTION
        "The collections of notifications sent by an IS."
 ::= { isisGroups 5 }

isisISPDUCounterGroup OBJECT-GROUP
    OBJECTS {
        isisPacketCountIIHello,
        isisPacketCountISHello,
        isisPacketCountESHello,
        isisPacketCountLSP,
        isisPacketCountCSNP,
        isisPacketCountPSNP,
        isisPacketCountUnknown
    }
    STATUS current
    DESCRIPTION
        "The collections of objects used to count protocol PDUs."
 ::= { isisGroups 6 }

isisRATableGroup OBJECT-GROUP
    OBJECTS {
        isisRAExistState,
        isisRAAdminState,
        isisRAAddrPrefix,
        isisRAMapType,
        isisRAMetric,
        isisRAMetricType,
        isisRASNPAddress,
        isisRASNPAMask,
        isisRASNPAPrefix,
        isisRAType
    }
    STATUS current
    DESCRIPTION
        "The collections of objects used to manage the
```

```
        reachable NSAP prefixes."
 ::= { isisGroups 7 }

isisISIPRADestGroup OBJECT-GROUP
    OBJECTS {
        isisIPRANextHopType,
        isisIPRANextHop,
        isisIPRAType,
        isisIPRAExistState,
        isisIPRAAdminState,
        isisIPRAMetric,
        isisIPRAFullMetric,
        isisIPRAMetricType,
        isisIPRASNPAAAddress,
        isisIPRASourceType
    }
    STATUS current
    DESCRIPTION
        "The collections of objects used to manage configured
        IP addresses."
 ::= { isisGroups 8 }

isisLSPGroup OBJECT-GROUP
    OBJECTS {
        isisLSPSeq,
        isisLSPZeroLife,
        isisLSPChecksum,
        isisLSPLifetimeRemain,
        isisLSPPDULength,
        isisLSPAttributes,
        isisLSPTLVSeq,
        isisLSPTLVChecksum,
        isisLSPTLVType,
        isisLSPTLVLen,
        isisLSPTLVValue
    }
    STATUS current
    DESCRIPTION
        "The collections of objects used to observe the LSP
        Database."
 ::= { isisGroups 9 }
```

END

5. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER values recorded in the SMI Numbers registry:

Descriptor -----	OBJECT IDENTIFIER value -----
isisMIB	{ mib-2 138 }

6. Acknowledgements

This MIB is based on a March 1994 document by Chris Gunner, who should be held blameless for the errors introduced since then. This version has been modified to include MIB-II syntax, to exclude portions of the protocol that are not relevant to IP, such as the ES-IS protocol, and to add management support for current practice.

We would like to thank the following individuals for constructive and valuable comments: Mike Bartlett, Neal Castagnoli, Ken Chapman, Joan Cucchiara, Satish Dattatri, Nagi Jonnala, Adrian Farrel, Shamik Ganguly, Les Ginsberg, Don Goodspeed, Jeff Gross, Jim Halpin, Jon Harrison, Dimitri Haskin, C. M. Heard, Peter Higginson, Christian Hopps, Laura Liu, Gavin McPherson, Kay Noguchi, Serge Maskalik, Z. Opalka, Jeff Pickering, Sundar Ramachandran, Swaminatha Ramalingam, Aravind Ravikumar, Juergen Schoenwaelder, Koen Vermeulen, Hans De Vleeschouwer, Bert Wijnen, and Bingzhang Zhao.

7. Security Considerations

Management information defined in this MIB may be considered sensitive in some network environments.

7.1. Discussion

This MIB may be used to manage an IP router, which is used to direct network traffic. The control of network traffic allows an attacker to deny service to a region of the network or to forward traffic to adversaries. By raising or lowering metrics, traffic may be directed to insecure portions of the network. By disabling the protocol on an interface, the network may be partitioned. Changes to the network topology will force all routers to recompute their routes. Periodic route changes have brought down networks in the past by subjecting routers to stressful recomputations.

There are a number of management objects defined in this MIB that have a MAX-ACCESS clause of read-write and/or read-create. Such objects may be considered sensitive or vulnerable in some network

environments. The support for SET operations in a non-secure environment without proper protection can have a negative effect on network operations. Authentication of received SNMP requests and controlled access to management information should be employed in such environments.

We identify a set of threats and then list attributes that can be used in each form of attack. We discuss the effects that can be obtained by a single change to the variable in each class.

7.2. Threats

- Drop an Adjacency
- Drop all Peers
- Drop Subnetwork
- Split the Network
- Intermittent Outages
- Redirect Traffic
- Delay Convergence
- Avoid Detection
- Prevent Updates
- Hijack LAN
- Create Problems for CLNS Networks

7.2.1. Drop an Adjacency

By changing attributes that are used to peer, we can disrupt an adjacency and bring a link down.

```
isisCirc3WayEnabled
isisCircAdminState
isisCircExistState
isisCircLevelDRHelloTimer
isisCircLevelHelloTimer
isisCircLevelType
isisCircSmallHellos
```

7.2.2. Drop All Adjacencies

These attributes can be used to break some or all of a router's adjacencies. In the case of System ID, the adjacency may be restored. However, it will subject the network to additional stress.

```
isisSysLevelType
isisManAreaAddrExistState
isisSysAdminState
isisSysID
```

7.2.3. Drop Subnetwork

This attribute can be used to stop advertisement of a subnetwork reachable through a single interface.

isisCircPassiveCircuit

7.2.4. Split the Network

If the network design depends upon Wide Metrics or TE, we can use these attributes to prevent traffic from passing through a router.

isisSysLevelMetricStyle
isisSysLevelOrigLSPBuffSize
isisSysLevelSPFConsiders
isisSysLevelTEEnabled
isisSysReceiveLSPBufferSize

7.2.5. Intermittent Outages

We can use these attributes to subject the network to a series of topology changes, or otherwise force extensive recomputations of routes.

isisSysLevelMinLSPGenInt
isisSysLevelSetOverload
isisSysLevelSetOverloadUntil
isisSysMaxAge
isisSysMaxLSPGenInt
isisSysL2toL1Leaking
isisSysID

7.2.6. Redirect Traffic

By changing attributes such as metrics, we can push traffic to different parts of the network. This may allow an intruder to observe data traffic from otherwise remote parts of the network.

We may also use these attributes to deny service to parts of the network.

isisSysMaxPathSplits
isisCircLevelMetric
isisCircLevelWideMetric
isisIPRAAdminState
isisIPRAExistState
isisIPRAFullMetric
isisIPRAMetric

```
isisIPRAMetricType
isisIPRANextHop
isisIPRANextHopType
isisIPRASNPAddress
isisIPRAType
isisRedistributeAddrExistState
isisSummAddrExistState
isisSummAddrFullMetric
isisSummAddrMetric
isisSysL2toL1Leaking
```

7.2.7. Delay Convergence

These attributes can be used to slow convergence by increasing the minimal interval required to update a packet.

```
isisCircLevelCSNPInterval
isisCircLevelLSPThrottle
isisCircLevelMinLSPRetransInt
isisCircLevelPartSNPInterval
isisSysWaitTime
isisCircPassiveCircuit
```

7.2.8. Avoid Detection

By turning off traps, we can prevent a Network Management station from observing problems in the network caused by other aspects of an attack.

```
isisSysNotificationEnable
```

7.2.9. Prevent Updates

Mesh Groups can be used to prevent the transmission of Link State PDUs on certain interfaces, delaying or preventing the propagation of updates.

```
isisCircMeshGroup
isisCircMeshGroupEnabled
```

7.2.10. Hijack LAN

If we have compromised a router, we can use this attribute to become the designated router and lie about the topology of a LAN.

```
isisCircLevelISPriority
```

7.2.11. Create Problems for CLNS Networks

This attribute can be used to modify the handling of CLNS traffic.

- isisRAAddrPrefix
- isisRAAdminState
- isisRAExistState
- isisRAMapType
- isisRAMetric
- isisRAMetricType
- isisRASNPAddress
- isisRASNPAMask
- isisRASNPAPrefix
- isisRAType
- isisSysPolleSHelloRate

7.2.12. Mostly Harmless

The following writable attributes do not pose a known security risk.

- isisCircExtDomain
- isisCircExtendedCircID
- isisCircIfIndex
- isisCircLevelHelloMultiplier
- isisCircType

7.2.13. Recommendations

Much of the MIB is used to set or read attributes which are readily visible to any intruder who has access to traffic. None of the security attributes are setable or visible through the MIB. Read access to the MIB does not pose additional risks or vulnerabilities.

If write access is to be provided, it is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [RFC3410], section 8), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPSec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

Deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an

instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

8. Normative References

- [ISO10589] ISO 10589, "Intermediate system to Intermediate system routeing information exchange protocol for use in conjunction with the Protocol for providing the Connectionless-mode Network Service (ISO 8473)," ISO/IEC 10589:2002.
- [ISO10733] ISO 10733, "Information Processing Systems - Open Systems Interconnection - Specification of the elements of Management Information related to OSI Network layer Standards", September 1998.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC1195] Callon, R., "Use of OSI IS-IS for routing in TCP/IP and dual environments", RFC 1195, December 1990.
- [RFC2863] McCloghrie, K. and F. Kastenholtz, "The Interfaces Group MIB", RFC 2863, June 2000.
- [RFC3289] Baker, F., Chan, K., and A. Smith, "Management Information Base for the Differentiated Services Architecture", RFC 3289, May 2002.
- [RFC3411] Harrington, D., Presuhn, R., and B. Wijnen, "An Architecture for Describing Simple Network Management Protocol (SNMP) Management Frameworks", STD 62, RFC 3411, December 2002.
- [RFC2578] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999.
- [RFC2579] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Textual Conventions for SMIv2", STD 58, RFC 2579, April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, RFC 2580, April 1999.

- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", RFC 4001, February 2005.

9. Informative References

- [RFC2973] Balay, R., Katz, D., and J. Parker, "IS-IS Mesh Groups", RFC 2973, October 2000.
- [RFC3373] Katz, D. and R. Saluja, "Three-Way Handshake for Intermediate System to Intermediate System (IS-IS) Point-to-Point Adjacencies", RFC 3373, September 2002.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002.

Authors' Address

Jeff Parker
Department of Computer Science
Middlebury College,
Middlebury, Vermont 05753

EMail: jeffp@middlebury.edu

Full Copyright Statement

Copyright (C) The Internet Society (2006).

This document is subject to the rights, licenses and restrictions contained in BCP 78, and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in BCP 78 and BCP 79.

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Acknowledgement

Funding for the RFC Editor function is provided by the IETF Administrative Support Activity (IASA).

