

Internet Engineering Task Force (IETF)
Request for Comments: 6670
Category: Informational
ISSN: 2070-1721

N. Sprecher
Nokia Siemens Networks
KY. Hong
Cisco Systems
July 2012

The Reasons for Selecting a Single Solution for MPLS Transport Profile (MPLS-TP) Operations, Administration, and Maintenance (OAM)

Abstract

The MPLS Transport Profile (MPLS-TP) is a profile of the MPLS technology for use in transport network deployments. The work on MPLS-TP has extended the MPLS technology with additional architectural elements and functions that can be used in any MPLS deployment. MPLS-TP is a set of functions and features selected from the extended MPLS toolset and applied in a consistent way to meet the needs and requirements of operators of packet transport networks.

During the process of development of the profile, additions to the MPLS toolset have been made to ensure that the tools available met the requirements. These additions were motivated by MPLS-TP, but form part of the wider MPLS toolset such that any of them could be used in any MPLS deployment.

One major set of additions provides enhanced support for Operations, Administration, and Maintenance (OAM). This enables fault management and performance monitoring to the level needed in a transport network. Many solutions and protocol extensions have been proposed to address the requirements for MPLS-TP OAM, and this document sets out the reasons for selecting a single, coherent set of solutions for standardization.

Status of This Memo

This document is not an Internet Standards Track specification; it is published for informational purposes.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Not all documents approved by the IESG are a candidate for any level of Internet Standard; see Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc6670>.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	4
1.1. Background	5
1.2. The Development of a Parallel MPLS-TP OAM Solution	7
2. Terminology	8
2.1. Acronyms	8
3. Motivations for a Single OAM Solution in MPLS-TP	9
3.1. MPLS-TP Is an MPLS Technology	9
3.2. MPLS-TP Is a Convergence Technology	9
3.3. There Is an End-to-End Requirement for OAM	10
3.4. The Complexity Sausage	10
3.5. Interworking Is Expensive and Has Deployment Issues	11
3.6. Selection of a Single OAM Solution When There Is a Choice	13
3.7. Migration Issues	14
4. Potential Models for Coexistence	15
4.1. Protocol Incompatibility	15
4.2. Inevitable Coexistence	16
4.3. Models for Coexistence	16
4.3.1. The Integrated Model	17
4.3.2. The Island Model	18
5. The Argument for Two Solutions	20
5.1. Progress of the IETF Solution	20
5.2. Commonality with Ethernet OAM	21
5.3. Different Application Scenarios	21
5.4. Interaction between Solutions	22
5.5. Letting the Market Decide	23
6. Security Considerations	24
7. Acknowledgments	24
8. References	24
8.1. Normative References	24
8.2. Informative References	25
Appendix A. Examples of Interworking Issues in the Internet	27
A.1. IS-IS/OSPF	27
A.2. Time Division Multiplexing Pseudowires	28
A.3. Codecs	28
A.4. MPLS Signaling Protocols	29
A.5. IPv4 and IPv6	29
Appendix B. Other Examples of Interworking Issues	30
B.1. SONET and SDH	30
B.2. IEEE 802.16d and IEEE 802.16e	32
B.3. CDMA and GSM	32

1. Introduction

The MPLS Transport Profile (MPLS-TP) is a profile of MPLS technology for use in transport network deployments. Note that "transport" in this document is used in the context of transport networks as discussed in Section 1.3 of [RFC5654] and in [RFC5921]. The work on MPLS-TP has extended the MPLS toolset with additional architectural elements and functions that can be used in any MPLS deployment. MPLS-TP is a set of functions and features selected from the extended MPLS toolset and applied in a consistent way to meet the needs and requirements of operators of packet transport networks.

Operations, Administration, and Maintenance (OAM) plays a significant role in carrier networks, providing methods for fault management and performance monitoring in both the transport and service layers, and enabling these layers to support services with guaranteed and strict Service Level Agreements (SLAs) while reducing their operational costs.

OAM provides a comprehensive set of capabilities that operate in the data plane. Network-oriented mechanisms are used to monitor the network's infrastructure in order to enhance the network's general behavior and level of performance. Service-oriented mechanisms are used to monitor the services offered to end customers. Such mechanisms enable rapid response to a failure event and facilitate the verification of some SLA parameters. Fault management mechanisms are used for fault detection and localization as well as for diagnostics and notification. Performance management mechanisms enable monitoring of the quality of service with regard to key SLA criteria (e.g., jitter, latency, and packet loss).

During the process of development of MPLS-TP, additions to the MPLS toolset have been made to ensure that the tools available meet the requirements. These additions were motivated by MPLS-TP, but form part of the wider MPLS toolset, such that any of them could be used in any MPLS deployment.

One major set of additions provides enhanced support for OAM. Many solutions and protocol extensions have been proposed to address these OAM requirements. This document sets out the reasons for selecting a single, coherent set of OAM solutions for standardization.

The content of this document should be read in the context of [RFC1958]. In particular, Section 3.2 of [RFC1958] says:

If there are several ways of doing the same thing, choose one. If a previous design, in the Internet context or elsewhere, has successfully solved the same problem, choose the same solution unless there is a good technical reason not to. Duplication of the same protocol functionality should be avoided as far as possible, without of course using this argument to reject improvements.

1.1. Background

The ITU-T and the IETF jointly commissioned a Joint Working Team (JWT) to examine the feasibility of a collaborative solution to support OAM requirements for MPLS transport networks known as the MPLS Transport Profile (MPLS-TP). The JWT reported that it is possible to extend the MPLS technology to fully satisfy the requirements [RFC5317]. The investigation by the JWT laid the foundations for the work to extend MPLS, but a thorough technical analysis was subsequently carried out within the IETF with strong input from the ITU-T to ensure that the MPLS-TP OAM requirements provided by the ITU-T and the IETF would be met.

The report of the JWT [RFC5317] as accepted by the ITU-T was documented in [TD7] and was communicated to the IETF in a liaison statement [LS26]. In particular, the ITU-T stated that any extensions to MPLS technology will be progressed via the IETF standards process using the procedures defined in [RFC4929].

[RFC5317] includes the analysis that "it is technically feasible that the existing MPLS architecture can be extended to meet the requirements of a Transport profile, and that the architecture allows for a single OAM technology for LSPs, PWs, and a deeply nested network". This provided a starting point for the work on MPLS-TP.

[RFC5654] in general, and [RFC5860] in particular, define a set of requirements for OAM functionality in MPLS-TP that are applicable to MPLS-TP Label Switched Paths (LSPs), Pseudowires (PWs), and MPLS-TP links. These documents are the results of a joint effort by the ITU-T and the IETF to include an MPLS Transport Profile within the IETF MPLS and Pseudowire Emulation Edge-to-Edge (PWE3) architectures to enable the deployment of a packet transport network that supports the capabilities and functionalities of a transport network as defined by the ITU-T. The OAM requirements are derived from those specified by the ITU-T in [Y.Sup4].

An analysis of the technical options for OAM solutions was carried out by a design team (the MEAD team) consisting of experts from both the ITU-T and the IETF. The team reached an agreement on the principles of the design and the direction for the development of an MPLS-TP OAM toolset. A report was subsequently submitted to the IETF MPLS working group at the Stockholm IETF meeting in July 2009 [DesignReport]. The guidelines drawn up by the design team have played an important role in the creation of a coherent MPLS-TP OAM solution.

The MPLS working group has modularized the function of MPLS-TP OAM, allowing for separate and prioritized development of solutions. This has given rise to a number of documents each describing a different part of the solution toolset. At the time of this writing, the most important of these documents have completed development within the MPLS working group and are advancing through the IETF process toward publication as RFCs. These documents cover the following OAM features:

- o Continuity Check
- o Connection Verification
- o On-Demand Connection Verification
- o Route Tracing
- o Remote Defect Indication
- o Packet Loss Measurement
- o Packet Delay Measurement
- o Lock Instruction
- o Loopback Testing
- o Fault Management

The standardization process within the IETF allows for the continued analysis of whether the OAM solutions under development meet the documented requirements, and facilitates the addition of new requirements if any are discovered. It is not the purpose of this document to analyze the correctness of the selection of specific OAM solutions. This document is intended to explain why it would be unwise to standardize multiple solutions for MPLS-TP OAM, and to show

how the existence of multiple solutions would complicate MPLS-TP development and deployment, making networks more expensive to build, less stable, and more costly to operate.

1.2. The Development of a Parallel MPLS-TP OAM Solution

It has been suggested that a second (i.e., different) OAM solution should also be developed and documented in an ITU-T Recommendation. Various arguments have been presented for this duplication of effort, including the following:

- o Similarity to OAM encodings and mechanisms used in Ethernet.
- o The existence of two distinct MPLS-TP deployment environments: Packet Switched Networks (PSNs) and Packet Transport Networks (PTNs).
- o The need for similar operational experience in MPLS-TP networks and in pre-existing transport networks (especially Synchronous Optical Network/Synchronous Digital Hierarchy (SONET/SDH) networks).

The first of these was discussed within the IETF's MPLS working group where precedence was given to adherence to the JWT's recommendation to select a solution that reused as far as possible pre-existing MPLS tools. Additionally, it was decided that consistency with encodings and mechanisms used in MPLS was of greater importance.

The second argument has not been examined in great detail because substantive evidence of the existence of two deployment environments has not been documented or presented. Indeed, one of the key differences cited between the two allegedly distinct environments is the choice of MPLS-TP OAM solution, which makes a circular argument.

The third argument contains a very important point: network operators want to achieve a smooth migration from legacy technologies such as SONET/SDH to their new packet transport networks. This transition can be eased if the new networks offer similar OAM features and can be managed using tools with similar look and feel. The requirements specifications [RFC5654] and [RFC5860] capture the essential issues that must be resolved to allow the same look and feel to be achieved. Since the OAM solutions developed within the IETF meet the documented requirements, Network Management Systems (NMSs) can easily be built to give the same type of control of MPLS-TP networks as is seen in other transport networks. Indeed, it should be understood that the construction of an NMS is not dependent on the protocols and packet formats within the OAM but on the high-level features and functions offered by the OAM.

This document does not debate the technical merits of any specific solution. That discussion, and the documentation of MPLS-TP OAM specifications, was delegated by the IETF and ITU-T to the MPLS working group and can be conducted using the normal consensus-driven IETF process. [OAM-OVERVIEW] presents an overview of the OAM mechanisms that have already been defined and that are currently being defined by the IETF, as well as a comparison with other OAM mechanisms that were defined by the IEEE and ITU-T.

This document focuses on an examination of the consequences of the existence of two MPLS-TP OAM solutions.

2. Terminology

2.1. Acronyms

This document uses the following acronyms:

ANSI	American National Standards Institute
CESoPSN	Circuit Emulation Service over Packet Switched Network
ETSI	European Telecommunications Standards Institute
FPGA	Field-Programmable Gate Array
GFP	Generic Framing Procedure
IEEE	Institute of Electrical and Electronics Engineers
ITU-T	International Telecommunication Union - Telecommunication Standardization Sector
JWT	Joint Working Team
LSP	Label Switched Path
MPLS-TP	MPLS Transport Profile
NMS	Network Management System
OAM	Operations, Administration, and Maintenance
PDH	Plesiochronous Digital Hierarchy
PSN	Packet Switched Network
PTN	Packet Transport Network
PW	Pseudowire
PWE3	Pseudowire Emulation Edge-to-Edge
SAToP	Structure-Agnostic Time Division Multiplexing over Packet
SDH	Synchronous Digital Hierarchy
SLA	Service Level Agreement
SONET	Synchronous Optical Network
TDM	Time Division Multiplexing
TDMoIP	Time Division Multiplexing over IP

3. Motivations for a Single OAM Solution in MPLS-TP

This section presents a discussion of the implications of the development and deployment of more than one MPLS OAM protocol. The summary is that it can be seen that there are strong technical, operational, and economic reasons to avoid the development and deployment of anything other than a single MPLS OAM protocol.

3.1. MPLS-TP Is an MPLS Technology

MPLS-TP is an MPLS technology. It is designed to apply MPLS to a new application. The original proposers of the concept assumed that the transport variant of MPLS would always exist in a disjoint network, and indeed their first attempt at the technology (Transport MPLS (T-MPLS)) had a number of significant incompatibilities with MPLS that were irreconcilable. When it was established that coexistence in the same layer network could and would occur, T-MPLS development was stopped and the development of MPLS-TP was begun. In MPLS-TP, MPLS was extended to satisfy the transport network requirements in a way that was compatible both with MPLS as has already been deployed, and with MPLS as the IETF envisioned it would develop in the future.

Given this intention for compatibility, it follows that the MPLS-TP OAM protocols should be designed according to the design philosophies that were applied for the existing deployed MPLS OAM and that have led to the current widespread adoption of MPLS. Key elements here are scalability and hardware independence, i.e., that the trade-off between scaling to large numbers of monitored objects and the performance of the monitoring system should be a matter for vendors and operators to resolve, and that the trade-off should be a soft transition rather than an abrupt one. Furthermore, there should be no requirement to execute any component (other than packet forwarding) in hardware to achieve usable performance.

3.2. MPLS-TP Is a Convergence Technology

It is possible to argue that using MPLS for transport is only a stepping stone in the middle of a longer transition. Quite clearly, all communication applications are being moved to operate over the Internet protocol stack of TCP/IP/MPLS, and the various layers that have existed in communications networks are gradually being collapsed into the minimum necessary set of layers. Thus, for example, we no longer run IP over X.25 over High-Level Data Link Control (HDLC) over multi-layered Time Division Multiplexing (TDM) networks.

Increasingly, the entire point of transport networks is to support the transmission of TCP/IP/MPLS. Using MPLS to construct a transport network may be a relatively short-term stepping stone toward running

IP and MPLS directly over fiber optics. MPLS has been deployed in operational networks for approximately a decade, and the existing MPLS OAM techniques have seen wide deployment. Service providers are not going to stop using the MPLS-based OAM techniques that they have been using for years, and no one has proposed that they would. Thus, the question is not which OAM to use for transport networks; the question is whether service providers want to use two different sets of OAM tools in the future converged network. If we arrive at a destination where TCP/IP/MPLS runs directly over fiber, the operators will use MPLS OAM tools to make this work.

3.3. There Is an End-to-End Requirement for OAM

The purpose of OAM is usually to execute a function that operates end to end on the monitored object (such as an LSP or PW). Since LSPs and PWs provide edge-to-edge connectivity and can cross network operator boundaries, the OAM must similarly operate across network operator boundaries. This is particularly the case with the continuity check and connection verification functions that are needed to test the end-to-end connectivity of LSPs and PWs. It is, therefore, necessary that any two pieces of equipment that could ever be a part of an end-to-end communications path have a common OAM. This necessity is emphasized in the case of equipment executing an edge function, since with a global technology such as MPLS it could be interconnected with edge equipment deployed by any other operator in any part of the global network.

This leads to the conclusion that it is desirable for any network-layer protocol in all equipment to be able to execute or to interwork with a canonical form of the OAM. As discussed in Section 4, interworking between protocols adds significant complexity; thus, a single default OAM is strongly preferred.

3.4. The Complexity Sausage

A frequent driver for the replacement of an established technology is a perception that the new technology is simpler and thus of greater economic benefit to the user. In an isolated system, this may be the case; however, as is usually the case with communications technologies, simplification in one element of the system introduces an increase (possibly a non-linear one) in complexity elsewhere.

This creates the "squashed sausage" effect, where reduction in complexity at one place leads to significant increase in complexity at a remote location. When we drive complexity out of hardware by placing complexity in the control plane, there is frequently an economic benefit, as illustrated by MPLS itself.

Some motivation for the second OAM solution is the simplicity of operation at a single node in conjunction with other transport OAM mechanisms. However, when we drive OAM complexity out of one network element at the cost of increased complexity at a peer network element, we lose out economically and, more importantly, we lose out in terms of the reliability of this important network functionality. Due to the need to ensure compatibility of an interworking function between the two MPLS-TP OAM solutions (in order to achieve end-to-end OAM), we create a situation where neither of two disjoint protocol developments is able to make technical advances. Such a restriction is unacceptable within the context of the Internet.

3.5. Interworking Is Expensive and Has Deployment Issues

The issue of OAM interworking can easily be illustrated by considering an analogy with people speaking different languages. Interworking is achieved through the use of an interpreter. The interpreter introduces cost, slows down the rate of information exchange, and may require transition through an intermediate language. There is considerable risk of translation errors and semantic ambiguities. These considerations also apply to computer protocols, particularly given the ultra-pedantic nature of such systems. In all cases, the availability of a single working language dramatically simplifies the system, reduces cost, and speeds reliable communication.

If two MPLS OAM protocols were to be deployed, we would have to consider three possible scenarios:

1. Isolation of the network into two incompatible and unconnected islands.
2. Universal use of both OAM protocols.
3. Placement of interworking (translation) functions or gateways.

We have many existence proofs that isolation is not a viable approach, and the reader is referred to the early T-MPLS discussions for examples. In summary, the purpose of the Internet is to achieve an integrated universal connectivity. Partition of the Internet into incompatible and unconnected islands is neither desirable nor acceptable.

Universal deployment of both OAM protocols requires the sum of the costs associated with each protocol. This manifests as implementation time, development costs, memory requirements, hardware components, and management systems. It introduces additional testing requirements to ensure there are no conflicts (processing state,

fault detection, code path, etc.) when both protocols are run on a common platform. It also requires code and the processes to deal with the negotiation of which protocol to use and to deal with conflict resolution (which may be remote and multi-party) when an inconsistent choice is made. In short, this option results in more than double the cost, increases the complexity of the resulting system, risks the stability of the deployed network, and makes the networks more expensive and more complicated to operate.

The third possibility is the use of some form of interworking function. This is not a simple solution and inevitably leads to cost and complexity in implementation, deployment, and operation. Where there is a chain of communication (end-to-end messages passed through a series of transit nodes), a choice must be made about where to apply the translation and interworking.

- o In a layered architecture, interworking can be achieved through tunneling with the translation points at the end-points of the tunnels. In simple network diagrams, this can look very appealing, and only one end-node is required to be able to perform the translation function (effectively speaking both OAM languages). But in the more complex reality of the Internet, nearly every network node performs the function of an end-node, and so the result is that nearly every node must be implemented with the capability to handle both OAM protocols and to translate between them. This turns out to be even more complex than the universal deployment of both protocols discussed above.
- o In a flat architecture, interworking is performed at a "gateway" between islands implementing different protocols. Gateways are substantially complex entities that usually have to maintain end-to-end state within the network (something that is against one of the fundamental design principles of the Internet) and must bridge the differences in state machines, message formats, and information elements in the two protocols. The complexity of gateways makes them expensive, fragile, and unstable; hard to update when new revisions of protocols are released; and difficult to manage.

To deploy an interworking function, it is necessary to determine whether the OAM protocol on the arriving segment of the OAM is identical to the OAM protocol on the departing segment. Where the protocols are not the same, it is necessary to determine which party will perform the translation. It is then necessary to route the LSP or PW through a translation point that has sufficient translation capacity and sufficient data bandwidth, as well as adequate path

diversity. When an upgraded OAM function is required, the problem changes from a two-party negotiation to an n-party negotiation with commercial and deployment issues added to the mix.

Note that when an end-to-end LSP or PW is deployed, it may transit many networks, and the OAM might require repeated translation back and forth between the OAM protocols. The consequent loss of information and potential for error is similar to the children's game of "telephone".

3.6. Selection of a Single OAM Solution When There Is a Choice

When there is a choice of protocols for deployment or operation, a network operator must make a choice. Choice can be a good thing when it provides for selection between different features and functions, but it is a burden when the protocols offer essentially the same functions but are incompatible.

In this case, the elements of the choice include the following:

- o Which protocol will continue to be developed by its Standards Development Organization (SDO)?
- o Which protocol is most stable in implementations?
- o How does a network operator test and evaluate the two protocols?
- o Which vendors support and will continue to support which protocol?
- o What equipment from different vendors is compatible?
- o Which management tools support which protocols?
- o What protocols are supported by peer operators, and what interworking function is needed?
- o Which protocols are engineers experienced with and trained in?
- o What are the consequences of a wrong choice?
- o Will it be possible to migrate from one protocol to another in the future?
- o How is integration with other functions already present in the network accomplished?
- o How does a network operator future-proof against the inclusion of new functions in the network?

At the very least, the evaluation of these questions constitutes a cost and introduces delay for the operator. The consequence of a wrong choice could be very expensive, and it is likely that any comparative testing will more than double the lab-test costs prior to deployment.

From a vendor's perspective, the choice is even harder. A vendor does not want to risk not offering a product for which there is considerable demand, so both protocols may need to be developed, leading to more than doubled development costs. Indeed, code complexity and defect rates have often been shown to increase more than linearly with code size, and (as noted in Section 3.5) the need to test for coexistence and interaction between the protocols adds to the cost and complexity.

It should be noted that, in the long run, it is the end-users who pay the price for the additional development costs and any network instability that arises.

3.7. Migration Issues

Deployment of a technology that is subsequently replaced or obsoleted often leads to the need to migrate from one technology to another. Such a situation might arise if an operator deploys one of the two OAM protocol solutions and discovers that he needs to migrate to the other one. A specific case would be when two operators merge their networks but are using different OAM solutions.

When the migration is between versions of a protocol, it may be that the new version is defined to support the old version. If the implementation is in software (including FPGAs), upgrades can be managed centrally. However, neither of these would be the case with MPLS-TP OAM mechanisms, and hardware components would need to be upgraded in the field using expensive call-out services.

Hardware upgrades are likely to affect service, even with sophisticated devices with redundant hardware components. Furthermore, since it would be impractical to upgrade every device in the network at the same time, there is a need for either a significantly large maintenance period across the whole network or for a rolling plan that involves upgrading nodes one at a time with new hardware that has dual capabilities. Such hardware is, of course, more expensive and more complex to configure than hardware dedicated to just one OAM protocol.

Additionally, the transition phase of migration leads to dual-mode networks as described in Section 4.3. Such networks are not desirable because of their cost and complexity.

In short, the potential for future migration will need to be part of the deployment planning exercise when there are two OAM protocols to choose between. This issue will put pressure on making the "right" choice when performing the selection described in Section 3.6.

4. Potential Models for Coexistence

This section expands upon the discussion in Section 3 by examining three questions:

- o What does it mean for two protocols to be incompatible?
- o Why can't we assume that the two solutions will never coexist in the same network?
- o What models could we support for coexistence?

4.1. Protocol Incompatibility

Protocol incompatibility comes in a range of grades of seriousness. At the most extreme, the operation of one protocol will prevent the safe and normal operation of the other protocol. This was the case with the original T-MPLS, where MPLS labels that could be used for data in a native MPLS system were assigned special meaning in T-MPLS such that data packets would be intercepted and mistaken for OAM packets.

A lesser incompatibility arises where the packets of one protocol are recognized as "unknown" or "not valid" by implementations of the other protocol. In this case, the rules of one protocol require that the packets of the other protocol be discarded and may result in the LSP or PW being torn down.

The least serious level of incompatibility is where the packets of one protocol are recognized as "unknown" by implementations of the other protocol, but where the rules of one protocol allow the packets of the other protocol to be ignored; in this case, such packets are either silently discarded or forwarded untouched.

These are issues with all of these grades of incompatibility; these issues range from disruption or corruption of user data, through connection failure, to the inability to provide end-to-end OAM function without careful planning and translation functions.

4.2. Inevitable Coexistence

Networks expand and merge. For example, one service provider may acquire another and wish to merge the operation of the two networks. This makes partitioning networks by protocol deployment a significant issue for future-proofing commercial interactions. Although a network operator may wish to present difficulties in order to disincentivize hostile takeover (a poison pill), most operators are interested in future options to grow their networks.

As described in Section 3.2, MPLS is a convergence technology. That means that there is a tendency for an ever-increasing number of services to be supported by MPLS and for MPLS to be deployed in an increasing number of environments. It would be an unwise operator who deployed a high-function convergence technology in such a way that the network could never be expanded to offer new services or to integrate with other networks or technologies.

As described in Section 3.3, there is a requirement for end-to-end OAM. That means that where LSPs and PWs span multiple networks, there is a need for OAM to span multiple networks.

All of this means that, if two different OAM protocol technologies are deployed, there will inevitably come a time when some form of coexistence is required, no matter how carefully the separation is initially planned.

4.3. Models for Coexistence

Two models for coexistence can be considered:

1. An integrated model based on the "ships-in-the-night" approach. In this model, there is no protocol translation or mapping. This model can be decomposed as follows:
 - * A non-integrated mixed network, where some nodes support just one protocol, some support just the other, and no node supports both protocols.
 - * Partial integration, where some nodes support just one protocol, some support just the other, and some support both protocols.
 - * Fully integrated dual mode, where all nodes support both protocols.

2. An "island" model, where groups of similar nodes are deployed together. In this model, there may be translation or mapping, but it is not always required. This model can be further decomposed as follows:

- * "Islands in a sea", where connectivity between islands of the same type is achieved across a sea of a different type.
- * "Border crossings", where connectivity between different islands is achieved at the borders between them.

4.3.1. The Integrated Model

The integrated model assumes that nodes of different capabilities coexist within a single network. Dual-mode nodes supporting both OAM solutions may coexist in the same network. Interworking is not required in this model, and no nodes are capable of performing translation or gateway function (see Section 4.3.2 for operational modes including translation and gateways).

In this model, protocol messages pass as "ships in the night" unaware of each other and without perturbing each other.

As noted above, there are several sub-models.

4.3.1.1. Mixed Network without Integration

In a mixed network with no integration, some nodes support one protocol and other nodes support the other protocol. There are no nodes that have dual capabilities.

All nodes on the path of an LSP or PW that are required to play an active part in OAM must support the same OAM protocol. Nodes that do not support the OAM protocol will silently ignore (and possibly discard) OAM packets from the other protocol and cannot form part of the OAM function for the LSP or PW.

In order to provision an end-to-end connection that benefits from the full OAM functionality, the planning and path-computation tool must know the capabilities of each network node and must select a path that includes only nodes with the same OAM protocol capability. This can result in considerably suboptimal paths and may lead to the network being partitioned. In the most obvious case, connectivity can only be achieved between end-points with the same OAM capability. This leads to considerable operational complexity and expense, as well as the inability to provide a fully flexible mesh of services.

In the event of dynamic network changes (such as fast reroute) or if misconnectivity occurs, nodes of mismatched OAM capabilities may become interconnected. This will disrupt traffic delivery because end-to-end continuity checks may be disrupted, and it may be hard or impossible to diagnose the problem because connectivity verification and route trace functions will not work properly.

4.3.1.2. Partial Integration

In a partially integrated network, the network described in Section 4.3.1.1 is enhanced by the addition of a number of nodes with dual capabilities. These nodes do not possess gateway or translation capabilities (this is covered in Section 4.3.2), but each such node can act as a transit point or end-node for an LSP or PW that uses either OAM protocol.

Complexity of network operation is not eased, but there is greater connectivity potential in the network.

4.3.1.3. Dual Mode

Dual mode is a development of partial integration (Section 4.3.1.2) such that all nodes in the network are capable of both OAM protocols. As in that section, these nodes do not possess gateway or translation capabilities (this is covered in Section 4.3.2), but each such node can act as a transit point or end-node for an LSP or PW that uses either OAM protocol. Thus, every LSP or PW in the network can be configured to use either of the OAM protocols.

However, it seems unlikely that an operator would choose which OAM protocol to use on a per-LSP or per-PW basis. That would lead to additional complexity in the management system and potential confusion if additional diagnostic analytics need to be performed. This mode increases the complexity of implementation, deployment, and operation without adding to the function within the network (since both OAM solutions provide the same level of function), so this mode would not be selected for deployment except, perhaps, during migration of the network from one OAM protocol to the other.

4.3.2. The Island Model

In the island model, regions or clusters of nodes with the same OAM capabilities are grouped together. Tools to interconnect the technologies are deployed based on layered networking or on interworking between the protocols. These lead to the two sub-models described in the sections that follow.

4.3.2.1. Islands in a Sea

One way to view clusters of nodes supporting one OAM protocol is as an island in a sea of nodes supporting the other protocol. In this view, tunnels are used to carry LSPs or PWs using one OAM type across the sea and into another island of a compatible OAM type. The tunnel in this case is an LSP utilizing the OAM protocol supported by the nodes in the sea. Theoretically, an island can be as small as one node, and the strait between two islands can be as narrow as just one node.

Layering in this way is an elegant solution to operating two protocols simultaneously and is, of course, used to support different technologies (such as MPLS over optical). However, in such layering deployments, there is no simple integration of OAM between the layers, and the OAM in the upper layer must regard the tunnel as a single hop with no visibility into the OAM of the lower layer. Diagnostics within the upper layer are complicated by this "hiding" of the nodes along the path of the tunnel in the lower layer.

In the scenarios described so far, both ends of each connection have been placed in islands of compatible OAM types. It is possible to achieve connectivity between a node in an island and a node in the sea if the end-point in the sea has dual capabilities (i.e., can be viewed as a single-node island).

A number of islands may lie along the path between end-points, necessitating the use of more than one tunnel. To further complicate matters, the islands may lie in an inland sea so that it is necessary to nest tunnels.

Regardless of the scenario, operating such tunnels/layers adds to the management complexity and expense. Furthermore, it should be noted that in an MPLS network there is often a call for any-to-any connectivity. That is, any node in the network may need to establish an LSP or a PW to any other node in the network. As previously noted, the end-points of any LSP or PW must support the same OAM type in the islands-in-a-sea model, so this tends to imply that all, or nearly all, nodes will end up needing to support both OAM protocols.

The use of tunnels can also degrade network services unless carefully coordinated. For example, a service in the upper layer may be provisioned with protection so that a working and backup path is constructed using diverse paths to make them robust against a single failure. However, the paths of the tunnels (in the lower layer) are not visible to the path computation in the upper layer, with the risk that the upper layer working and protection paths share a single point of failure in the lower layer. Traffic engineering techniques

have been developed to resolve this type of issue, but they add significant complexity to a system that would be a simple flat network if only one OAM technology was used.

4.3.2.2. Border Crossings

Instead of connecting islands with tunnels across the sea, islands of different types can be connected directly so that the LSP or PW transits the series of islands without tunneling. In this case, protocol translation is performed each time the LSP/PW crosses a border between islands that use a different OAM protocol.

In principle, this makes for a straightforward end-to-end connection. However, protocol translation presents a number of issues, as described in Section 3. The complexity is that in planning the end-to-end connection, gateways with protocol translation capabilities must be selected to lie on the path.

5. The Argument for Two Solutions

The decision to define and develop an alternative MPLS-TP OAM solution was based on several assertions:

- o The IETF solution is taking too long to standardize.
- o Commonality with Ethernet solutions is beneficial.
- o There are two different application scenarios.
- o There is no risk of interaction between the solutions.
- o The market should be allowed to decide between competing solutions.

The following sections look briefly at each of these claims.

5.1. Progress of the IETF Solution

The MPLS-TP OAM work carried out within the IETF is the product of joint work within the IETF and ITU-T communities. That is, all interested parties share the responsibility for progressing this work as quickly as possible. Since the work is contribution-driven, there is no reason to assume that consensus on the technical content of the work could be reached any more quickly.

Opening discussions on a second solution seems certain to increase the workload and will only slow down the speed at which consensus is reached.

The core work on MPLS-TP OAM within the IETF was completed, and the specifications were published as RFCs. For more information, see [ISOCAnnounce].

5.2. Commonality with Ethernet OAM

Ethernet can be used to build packet transport networks, and so there is an argument that Ethernet and MPLS-TP networks will be operated as peers. Examining the issues of end-to-end connections across mixed networks, many of the same issues as those discussed in Section 4 arise. If a peer networking gateway model (see Section 4.3.2.2) is applied, there is a strong argument for making the OAM technologies as similar as possible.

While this might be a valid discussion point when selecting the single OAM solution for MPLS-TP, it is countered by the need to achieve OAM consistency between MPLS and MPLS-TP networks. One might make the counter-argument that if there is a strong need to make MPLS-TP as similar as possible to Ethernet, it would be better to go the full distance and simply deploy Ethernet.

Furthermore, the approach of a second MPLS-TP OAM protocol does not resolve anything. Since MPLS-TP is not Ethernet, a gateway will still be needed. This would constitute a second MPLS-TP OAM, so additional gateways or interworking functions will be needed because coexistence is inevitable, as described in the rest of this document.

Additionally, it may be claimed that implementation can be simplified if the OAM solution developed for MPLS-TP is similar to Ethernet OAM. This would apply both in the hardware/software implementing the OAM, and at the server-to-client interface where OAM-induced fault status is reported. The questions here are very much implementation dependent, as the necessary function is contained within individual nodes. The counter-argument is that implementation simplicity can also be achieved by making MPLS-TP OAM similar to MPLS OAM, especially since the client technology may well be IP/MPLS and since MPLS is an end-to-end technology.

5.3. Different Application Scenarios

It has been suggested that two different applications of MPLS-TP exist: Packet Switched Networks (PSNs) and Packet Transport Networks (PTNs). These applications have not been documented in the IETF, and most of the support for this idea has been documented by the ITU-T [TD522].

One of the stated differences between these applications lies in the OAM tools that are required to support the distinct operational scenarios. The OAM used in a PSN should be similar to that used in an MPLS network (and so should be the MPLS-TP OAM defined in the IETF), while the OAM used in a PTN should provide the same operational experience as that found in SONET/SDH and Optical Transport Networks (OTNs).

The basic MPLS-TP OAM requirements in [RFC5654] make this point as follows:

Furthermore, for carriers it is important that operation of such packet transport networks should preserve the look-and-feel to which carriers have become accustomed in deploying their optical transport networks, while providing common, multi-layer operations, resiliency, control, and multi-technology management.

Thus, the look and feel of the OAM has been a concern in the design of MPLS-TP from the start, and the solutions that have been defined in the IETF were designed to comply with the requirements and to provide operational behavior, functionality, and processes similar to those available in existing transport networks. In particular, the toolset supports the same controls and indications as those present in other transport networks, and the same management information model can be used to support the MPLS-TP OAM tools (in areas where the technology type is irrelevant).

It is important to note that the operational look and feel does not determine the way in which OAM function is achieved. There are multiple ways of achieving the required functionality while still providing the same operational experience and supporting the same management information model. Thus, the OAM protocol solution does not dictate the look and feel, and the demand for a particular operational experience does not necessitate the development of a second OAM protocol.

5.4. Interaction between Solutions

Section 3 of this document discusses how network convergence occurs and indicates that where two MPLS-TP solutions exist, they are in fact very likely to appear either in the same network or at gateways between networks in order to provide end-to-end OAM functionality.

Indeed, since nodes offering either solution are likely to both be branded as "MPLS-TP", and since network interoperation (as described in Section 4) demands the existence of some nodes that are either dual-mode or act as protocol translators/gateways, there is considerable likelihood of the two OAM solutions interacting through

design or through accident. When a node is capable of supporting both OAM protocols, it must be configured to support the correct protocol for each interface and LSP/PW. When a device has interfaces that offer different MPLS-TP OAM functions, the risk of misconfiguration is significant. When a device is intended to support end-to-end connections, it may need to translate, map, or tunnel to accommodate both protocols.

Thus, the very existence of two OAM protocols within the common MPLS-TP family makes copresence and integration most likely.

5.5. Letting the Market Decide

When two technologies compete, it is common to let the market decide which one will survive. Sometimes the resolution is quite fast, and one technology dominates the other before there is widespread deployment. Sometimes it takes considerable time before one technology overcomes the other, perhaps because one technology has become entrenched before the emergence of the other, as in the case of MPLS replacing ATM. In more cases, however, the market does not select in favor of one technology or the other -- as in many of the cases described in Sections 4 and 5 of this document, sometimes both technologies continue to live in the network.

Letting the market decide is not a cheap option. Even when the resolution is rapid, equipment vendors and early adopters pay the price of both technologies. When it takes longer to determine which technology is correct, there will be a period of coexistence followed by the need to transition equipment from the losing solution to the winning one. In the cases where no choice is made, the network is permanently complicated by the existence of the competing technologies.

In fact, the only time when allowing the market to decide can be easily supported is when the competing technologies do not overlap. In those cases -- for example, different applications in the user space -- the core network is not perturbed by the decision-making process, and transition from one technology to the other is relatively painless. This is not the case for MPLS-TP OAM; coexistence while the market determines the correct approach would be expensive, while the necessary transition after the decision has been made would be difficult and costly.

6. Security Considerations

This informational document does not introduce any security issues.

However, it should be noted that the existence of two OAM protocols raises a number of security concerns:

- o Each OAM protocol must be secured. This leads to the existence of two security solutions that each need configuration and management. The increased complexity of operating security mechanisms tends to reduce the likelihood of them being used in the field and so increases the vulnerability of the network. Similarly, the existence of two security mechanisms raises the risk of misconfiguration.
- o One OAM protocol may be used as a vector to attack the other. Inserting an OAM message of the other OAM protocol onto a link may cause the service to be disrupted and, because some nodes may support both OAM protocols, it may be possible to cause the disruption at a remote point in the network.
- o Securing a network protocol is not a trivial matter for protocol designers. Duplicating design effort is unlikely to result in a stronger solution and runs the risk of diluting the effort and creating two less-secure solutions.

7. Acknowledgments

Thanks to Brian Carpenter, Tom Petch, Rolf Winter, Alexander Vainshtein, Ross Callon, Malcolm Betts, and Martin Vigoureux for their review and useful comments.

Thanks to Huub van Helvoort for supplying text and history about SONET/SDH.

8. References

8.1. Normative References

- [RFC5654] Niven-Jenkins, B., Ed., Brungard, D., Ed., Betts, M., Ed., Sprecher, N., and S. Ueno, "Requirements of an MPLS Transport Profile", RFC 5654, September 2009.
- [RFC5860] Vigoureux, M., Ed., Ward, D., Ed., and M. Betts, Ed., "Requirements for Operations, Administration, and Maintenance (OAM) in MPLS Transport Networks", RFC 5860, May 2010.

8.2. Informative References

- [RFC1958] Carpenter, B., Ed., "Architectural Principles of the Internet", RFC 1958, June 1996.
- [RFC4553] Vainshtein, A., Ed., and YJ. Stein, Ed., "Structure-Agnostic Time Division Multiplexing (TDM) over Packet (SAToP)", RFC 4553, June 2006.
- [RFC4929] Andersson, L., Ed., and A. Farrel, Ed., "Change Process for Multiprotocol Label Switching (MPLS) and Generalized MPLS (GMPLS) Protocols and Procedures", BCP 129, RFC 4929, June 2007.
- [RFC5086] Vainshtein, A., Ed., Sasson, I., Metz, E., Frost, T., and P. Pate, "Structure-Aware Time Division Multiplexed (TDM) Circuit Emulation Service over Packet Switched Network (CESoPSN)", RFC 5086, December 2007.
- [RFC5087] Stein, Y(J)., Shashoua, R., Insler, R., and M. Anavi, "Time Division Multiplexing over IP (TDMoIP)", RFC 5087, December 2007.
- [RFC5317] Bryant, S., Ed., and L. Andersson, Ed., "Joint Working Team (JWT) Report on MPLS Architectural Considerations for a Transport Profile", RFC 5317, February 2009.
- [RFC5921] Bocci, M., Ed., Bryant, S., Ed., Frost, D., Ed., Levrau, L., and L. Berger, "A Framework for MPLS in Transport Networks", RFC 5921, July 2010.
- [OAM-OVERVIEW]
Mizrahi, T., Sprecher, N., Bellagamba, E., and Y. Weingarten, "An Overview of Operations, Administration, and Maintenance (OAM) Mechanisms", Work in Progress, March 2012.
- [Y.Sup4] "Supplement on transport requirements for T-MPLS OAM and considerations for the application of IETF MPLS technology", ITU-T Y.1300-series Supplement 4, January 2008.
- [G.707] "Network node interface for the synchronous digital hierarchy (SDH)", ITU-T Recommendation G.707, January 2007.

- [TD7] "IETF and ITU-T cooperation on extensions to MPLS for transport network functionality", ITU-T TD7 (WP3/SG15), December 2008.
- [TD522] "Clarification of the PTN/solution X environment", ITU-T TD522 (WP3/SG15), February 2011.
- [LS26] "Cooperation Between IETF and ITU-T on the Development of MPLS-TP", ITU-T COM 15-LS26-E, December 2008, <<http://datatracker.ietf.org/documents/LIAISON/file596.pdf>>.
- [DesignReport] "MPLS-TP OAM Analysis", Proc. IETF 75, Stockholm, Sweden, July 2009, <http://www.ietf.org/proceedings/75/slides/mppls-17/mppls-17_files/frame.htm>.
- [ISOCAnnounce] "Milestone Achieved in Internet Carrier Network Standards - Multiprotocol Label Switching Transport Profile (MPLS-TP) Specifications Published", Internet Society, December 2011, <<http://www.isoc.org/standards/mppls.shtml>>.

Appendix A. Examples of Interworking Issues in the Internet

It is, of course, right to observe that there are a number of instances of multiple protocols serving the same purpose that have arisen within the Internet. It is valuable to examine these examples to understand what issues they have caused and how they have been mitigated.

A.1. IS-IS/OSPF

IS-IS and OSPF are two competing link-state IGP routing protocols that derive from the same root technology and that, for political and personality reasons, were never reconciled prior to wide-scale deployment. It is an accident of history that one of these protocols did not gain overwhelming deployment and so force the other into retirement.

The existence of these two widely deployed and highly functional competing IGPs doubles the cost of link-state IGP maintenance and deployment in the Internet. This is a situation that will almost certainly continue for the lifetime of the Internet. Although the Internet is clearly successful and operates well, the existence of these two IGPs forces router vendors to implement both protocols (doubling the protocol cost of all routers even when an operator only wants to deploy one of the protocols), forcing the operator to make an active choice between IGPs during deployment and requiring a gateway function between the islands of protocol use.

A mitigating factor in this specific case is that, owing to the way networks are partitioned for administrative and scaling reasons, there already existed a gateway routing protocol called BGP that propagates a summarized form of the IGP reachability information throughout the Internet. BGP means that there is actually no requirement for IS-IS and OSPF to interwork directly: that is, there is no need for a translation function between OSPF and IS-IS, and the two IGPs can continue to exist without impacting the function of the Internet. Thus, unlike the situation with MPLS OAM, the choice of IGP protocol is truly a local decision; however, there is a cost to BGP implementations that must support interactions with both OSPF and IS-IS.

A.2. Time Division Multiplexing Pseudowires

The IETF's PWE3 working group has published the specification of three different TDM PW types. This happened after considerable effort to reach a compromise failed to reduce the set of options.

- o SAToP is a relatively simple design. It is a Proposed Standard RFC [RFC4553] and is the mandatory-to-implement, default mode of operation.
- o CESoPSN [RFC5086] and TDMoIP [RFC5087] are more complex approaches with different degrees of bandwidth efficiency optimized for different applications. They are both published as Informational RFCs.

In this case, all implementations must include the default mode of operation (SAToP). This means that end-to-end operation is guaranteed: an operator can select equipment from any vendor in the knowledge that he will be able to build and operate an end-to-end TDM PW service.

If an operator wishes to deploy a TDM PW optimized for a specific application, he may select equipment from a vendor offering CESoPSN or TDMoIP in addition to SAToP. Provided that all of his equipment and his management system can handle the optimized approach, he can run this in his network, but he has to carry the cost of selecting, purchasing, configuring, and operating the extended mode of operation.

This situation is far from ideal, and it is possible that long-distance, multi-operator optimized TDM PWs cannot be achieved. However, the existence of a default mode implemented in all devices helps to reduce pain for the operator and ensures that simpler end-to-end operation is always available. Additionally, the growth of other protocols is acting to diminish the use of long-distance TDM circuits, making this a self-limiting problem.

A.3. Codecs

The n-squared codec interworking problem was brought to the attention of the IETF by the ITU-T when the IETF started its work on a royalty-free codec suitable for use in the Internet. Every time a new codec is deployed, translation between it and all other deployed codecs must be available within the network; each participating node must be able to handle the new codec. Translation between codecs is expensive and can lead to reduced quality.

This problem seriously constrains the addition of new codecs to the available set, and new codecs are only designed and released when there is a well-established need (such as a major difference in functionality).

The application layer of the Internet is, however, predicated on a business model that allows for the use of shared, free, and open-source software; this model requires the existence of a royalty-free codec. This, together with the specific characteristics of transmission over lossy packet networks, comprised requirements equivalent to a major difference in functionality and led to work in the IETF to specify a new codec.

The complexity, economic, and quality costs associated with interworking with this new codec will need to be factored into the deployment model. This, in turn, may adversely affect its adoption and the viability of its use in the Internet.

A.4. MPLS Signaling Protocols

There are three MPLS signaling control protocols used for distributing labels to set up LSPs and PWs in MPLS networks: LDP, RSVP - Traffic Engineering (RSVP-TE), and GMPLS.

The application domain for each of these protocols is different, and unlike the OAM situation, there is limited requirement for interworking between the protocols. For example, although one provider may use LDP to set up LSPs while its peer uses RSVP-TE, connectivity between the two providers usually takes place at the IP layer.

It should be noted that the IETF initially worked on another signaling protocol called Constraint-based Routed LDP (CR-LDP) with variants applicable to MPLS and GMPLS. The development of this protocol was allowed to progress in parallel with RSVP-TE. However, once it was possible to determine that the solution preferred by the community of vendors and operators was RSVP-TE, the IETF terminated all further work on CR-LDP. No translation function or gateway point interfacing RSVP-TE to CR-LDP was ever proposed.

A.5. IPv4 and IPv6

If there were ever an example of why protocol interworking is to be avoided if at all possible, it is the transition from IPv4 to IPv6.

The reasons for introducing IPv6 into the Internet are well known and don't need discussion here. IPv6 was not introduced as a competitor to IPv4 but rather as a planned replacement. The need for the

transition to IPv6 arose from the expansion of the network size beyond the wildest dreams of the creators of the Internet and from the consequent depletion of the IPv4 address space.

This transition has proved to be the hardest problem that the IETF has ever addressed. The invention and standardization of IPv6 were straightforward by comparison, but it has been exceptionally difficult to migrate networks from one established protocol to a new protocol.

The early assumption that by the time the IPv4 address space was exhausted IPv6 would be universally deployed failed to materialize due to (understandable) short-term economic constraints. Early migration would have been simpler and less costly than the current plans. The Internet is now faced with the considerable complexity of implementing and deploying interworking functions.

If anything can be learned from the IPv4/IPv6 experience, it is that every effort should be applied to avoid the need to migrate or jointly operate two protocols within one network. Adding to the mix, a number of issues caused by OAM interworking of MPLS, one of the Internet's core protocols, would be most unwelcome and would complicate matters still further.

Appendix B. Other Examples of Interworking Issues

B.1. SONET and SDH

SONET and SDH were defined as competing standards that basically provided the same functionality (simultaneous transport of multiple circuits of differing origin within a single framing protocol). SONET was developed first by ANSI, based on the 24-channel PDH hierarchy existing in North America and Japan. The basic rate is based on DS3. Some time later, ETSI developed SDH based on the 30-channel PDH deployed in Europe. The basic rate is based on E4 (3x DS3). The key difference between PDH and SDH is that the "S" stands for "synchronous" and the "P" for "plesiochronous". Thus, the difference between the technologies is timing related.

SONET was adopted in the U.S., Canada, and Japan, and SDH in the rest of the world.

Until 1988, the standards were unpublished and under development.

- o The SONET standard ANSI T1.105-1988 was published in 1988.
- o The SDH standard ETSI EN 300 417 was first published in 1992.
- o The compromise SDH/SONET standard ITU-T G.707 was published in 1988 (see below for the nature of this compromise).

Some implementers were confused by this situation. Equipment manufacturers initially needed to select the market segment they intended to address. The cost of chipsets for a limited market increased, and only a limited number of equipment manufacturers were available for selection in each market.

Obviously, most equipment vendors wanted to sell their equipment in both regions. Hence, today most chips support both SONET and SDH, and the selection is a matter of provisioning. The impact of the additional function to support both markets has had a mixed impact on cost. It has enabled a higher volume of production, which reduced cost, but it has required increased development and complexity, which increased cost.

Because the regions of applicability of SONET and SDH are well known, service providers do not need to consider the merits of the two standards and their long-term role in the industry when examining their investment options.

To be able to deploy SONET and SDH worldwide, the regional SDO experts came together in the ITU-T to define a frame structure and a frame rate that would allow interconnection of SONET and SDH. A compromise was agreed upon and approved in an ITU-T meeting in Seoul in 1988.

The SDH standard supports both the North American and Japanese 24-channel/T1/T3 hierarchy and the European 30-channel/E1/E4-based hierarchy within a single multiplexing structure. SDH has options for payloads at VC-4 (150 Mb/s) and above. SDH allows T1/T3 services to be delivered in Europe and E1 services to be delivered in North America using a common infrastructure.

Deployment of an E1-only standard in North America would have required the conversion of all of the 24-channel/T1 deployed equipment and services into the 30-channel/E1 format. Similarly, deployment of a T1-only standard in Europe would have required the conversion of all of the 30-channel/E1 equipment and services into

the 24-channel/T1 format. Clearly, given the existing network deployments (in 1988), this was not a practical proposition and was the principal reason why a compromise was reached.

The result of the compromise is documented in ITU-T Recommendation G.707 [G.707], which includes the frame definition and frame rates and also documents how SONET and SDH can interconnect.

An extensive interworking function had to be implemented in order to provide global connectivity (e.g., throughout the U.S. and Europe), and this resulted in an increase in operational overhead. The interworking function has to be performed before the SDH-based segment is reached. The reason for placing the interworking function on the SONET side was that in a previous agreement on interconnection the functionality was placed on the European side.

B.2. IEEE 802.16d and IEEE 802.16e

IEEE 802.16d and IEEE 802.16e were two different, incompatible iterations of the Worldwide Interoperability for Microwave Access (WiMAX) standards. In addition to the issues described for SONET/SDH, developers who implemented IEEE 802.16d found that they could not reuse their equipment design when developing the IEEE 802.16e variant. This increased the cost of development and lengthened the time to market.

B.3. CDMA and GSM

Code Division Multiple Access (CDMA) and the Global System for Mobile Communications (GSM) are two competing technologies for mobile connectivity.

In addition to all the undesirable effects described above, the existence of these two technologies adversely affected customers who used roaming when overseas. Sometimes, customers were obliged to obtain an additional device from their service providers in order to roam when traveling abroad (for example, when traveling from Europe to the U.S.).

Authors' Addresses

Nurit Sprecher
Nokia Siemens Networks
3 Hanagar St. Neve Ne'eman B
Hod Hasharon 45241
Israel

EMail: nurit.sprecher@nsn.com

Kyung-Yeop Hong
Cisco Systems
300 Beaver Brook Road
Boxborough, Massachusetts 01719
USA

EMail: hongk@cisco.com

