

Internet Engineering Task Force (IETF)  
Request for Comments: 7388  
Category: Standards Track  
ISSN: 2070-1721

J. Schoenwaelder  
A. Sehgal  
Jacobs University  
T. Tsou  
C. Zhou  
Huawei Technologies  
October 2014

Definition of Managed Objects for  
IPv6 over Low-Power Wireless Personal Area Networks (6LoWPANs)

Abstract

This document defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it defines objects for managing IPv6 over Low-Power Wireless Personal Area Networks (6LoWPANs).

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 5741.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc7388>.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction .....	2
2. The Internet-Standard Management Framework .....	2
3. Conventions .....	3
4. Overview .....	3
5. Relationship to Other MIB Modules .....	7
6. Definitions .....	7
7. Security Considerations .....	24
8. IANA Considerations .....	25
9. References .....	25
9.1. Normative References .....	25
9.2. Informative References .....	26
Acknowledgements .....	27
Authors' Addresses .....	27

## 1. Introduction

This document defines a portion of the Management Information Base (MIB) for use with network management protocols. In particular it defines objects for managing IPv6 over Low-Power Wireless Personal Area Networks (6LoWPANs) [RFC4944].

While a MIB module provides a direct binding for accessing data via the Simple Network Management Protocol (SNMP) [RFC3410], supporting SNMP may not always be affordable on constrained devices. Other protocols to access data modeled in MIB modules are possible and proposals have been made recently to provide bindings to the Constrained Application Protocol (CoAP) [RFC7252].

## 2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to section 7 of RFC 3410 [RFC3410].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This document specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, RFC 2578 [RFC2578], STD 58, RFC 2579 [RFC2579] and STD 58, RFC 2580 [RFC2580].

### 3. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14, RFC 2119 [RFC2119].

### 4. Overview

The left part of Figure 1 provides an overview of the IETF protocols designed for constrained devices. The right part lists the MIB modules providing monitoring and troubleshooting support ([RFC4113], [RFC4292], [RFC4293], and [RFC2863]). The LOWPAN-MIB defined in this document fills a hole by providing monitoring and troubleshooting support for the 6LoWPAN layer.

Protocol Layer	MIB Modules
+-----+	+-----+
CoAP [RFC7252]	UDP-MIB [RFC4113]
+-----+	+-----+
UDP [RFC0768]	IP-MIB [RFC4293]
+-----+	+-----+
IPv6 [RFC2460]	IP-FORWARD-MIB [RFC4292]
ICMPv6 [RFC4443]	+-----+
+-----+	LOWPAN-MIB [RFC7388]
6LoWPAN [RFC4944]	+-----+
+-----+	IF-MIB [RFC2863]
IEEE 802.15.4, ...	+-----+
+-----+	

Figure 1: Protocol Layers and MIB Modules

The LOWPAN-MIB module is primarily a collection of counters that reflect how 6LoWPAN datagrams are processed by the 6LoWPAN layer. The objects are defined twice: once to report the global statistics as seen by the 6LoWPAN layer and once to report per-interface 6LoWPAN layer statistics. The per-interface statistics are optional to implement. The object identifier registration tree has the following structure:

```

---- lowpanMIB(1.3.6.1.2.1.226)
+---- lowpanNotifications(0)
+---- lowpanObjects(1)
+---- lowpanStats(1)
+---r- lowpanReasmTimeout(1)           Unsigned32
+---r- lowpanInReceives(2)             Counter32
+---r- lowpanInHdrErrors(3)            Counter32
+---r- lowpanInMeshReceives(4)         Counter32
+---r- lowpanInMeshForwds(5)           Counter32
+---r- lowpanInMeshDelivers(6)         Counter32
+---r- lowpanInReasmReqds(7)           Counter32
+---r- lowpanInReasmFails(8)           Counter32
+---r- lowpanInReasmOKs(9)             Counter32
+---r- lowpanInCompReqds(10)           Counter32
+---r- lowpanInCompFails(11)          Counter32
+---r- lowpanInCompOKs(12)            Counter32
+---r- lowpanInDiscards(13)           Counter32
+---r- lowpanInDelivers(14)           Counter32
+---r- lowpanOutRequests(15)          Counter32
+---r- lowpanOutCompReqds(16)          Counter32
+---r- lowpanOutCompFails(17)         Counter32
+---r- lowpanOutCompOKs(18)           Counter32
+---r- lowpanOutFragReqds(19)          Counter32
+---r- lowpanOutFragFails(20)          Counter32
+---r- lowpanOutFragOKs(21)           Counter32
+---r- lowpanOutFragCreates(22)        Counter32
+---r- lowpanOutMeshHopLimitExceeds(23) Counter32
+---r- lowpanOutMeshNoRoutes(24)       Counter32
+---r- lowpanOutMeshRequests(25)       Counter32
+---r- lowpanOutMeshForwds(26)        Counter32
+---r- lowpanOutMeshTransmits(27)      Counter32
+---r- lowpanOutDiscards(28)          Counter32
+---r- lowpanOutTransmits(29)          Counter32
+---- lowpanIfStatsTable(2)
+---- lowpanIfStatsEntry(1) [ifIndex]
+---r- lowpanIfReasmTimeout(1)         Unsigned32
+---r- lowpanIfInReceives(2)           Counter32
+---r- lowpanIfInHdrErrors(3)          Counter32
+---r- lowpanIfInMeshReceives(4)       Counter32
+---r- lowpanIfInMeshForwds(5)         Counter32
+---r- lowpanIfInMeshDelivers(6)       Counter32
+---r- lowpanIfInReasmReqds(7)         Counter32
+---r- lowpanIfInReasmFails(8)         Counter32
+---r- lowpanIfInReasmOKs(9)           Counter32
+---r- lowpanIfInCompReqds(10)         Counter32
+---r- lowpanIfInCompFails(11)        Counter32
+---r- lowpanIfInCompOKs(12)          Counter32
+---r- lowpanIfInDiscards(13)         Counter32

```

```

|         +--r- lowpanIfInDelivers(14)           Counter32
|         +--r- lowpanIfOutRequests(15)          Counter32
|         +--r- lowpanIfOutCompReqds(16)         Counter32
|         +--r- lowpanIfOutCompFails(17)         Counter32
|         +--r- lowpanIfOutCompOKs(18)           Counter32
|         +--r- lowpanIfOutFragReqds(19)         Counter32
|         +--r- lowpanIfOutFragFails(20)         Counter32
|         +--r- lowpanIfOutFragOKs(21)           Counter32
|         +--r- lowpanIfOutFragCreates(22)        Counter32
|         +--r- lowpanIfOutMeshHopLimitExceeds(23) Counter32
|         +--r- lowpanIfOutMeshNoRoutes(24)       Counter32
|         +--r- lowpanIfOutMeshRequests(25)       Counter32
|         +--r- lowpanIfOutMeshForwds(26)         Counter32
|         +--r- lowpanIfOutMeshTransmits(27)      Counter32
|         +--r- lowpanIfOutDiscards(28)          Counter32
|         +--r- lowpanIfOutTransmits(29)         Counter32
+----- lowpanConformance(2)
+----- lowpanGroups(1)
|   +----- lowpanStatsGroup(1)
|   +----- lowpanStatsMeshGroup(2)
|   +----- lowpanIfStatsGroup(3)
|   +----- lowpanIfStatsMeshGroup(4)
+----- lowpanCompliances(2)
+----- lowpanCompliance(1)

```

Figure 2: Object Identifier Registration Tree

The counters defined in the LOWPAN-MIB module provide information about the 6LoWPAN datagrams received and transmitted and how they are processed in the 6LoWPAN layer. For link layers that use the 6LoWPAN dispatch byte as defined in [RFC4944] (e.g., IEEE 802.15.4), a 6LoWPAN datagram is a datagram with a dispatch byte matching the bit patterns 01xxxxxx, 10xxxxxx, or 11xxxxxx. Datagrams with a dispatch byte matching the bit pattern 00xxxxxx (NALP - not a LoWPAN frame) are not considered to be 6LoWPAN datagrams by this specification. Other radio technologies may use different mechanisms to identify 6LoWPAN datagrams (e.g., the BLUETOOTH Low-Energy Logical Link Control and Adaptation Protocol uses Channel Identifiers [IPV6-BTLE]).

The Case Diagram [CASE] in Figure 3 illustrates the conceptual relationships between the counters. Implementations may choose to implement the processing of 6LoWPAN datagrams in a different order.

The generic InDiscards and OutDiscards counters can be incremented anytime 6LoWPAN datagrams are discarded due to reasons not covered by the other more specific counters. For example, an implementation

discarding 6LoWPAN datagrams while all buffers are used for ongoing packet reassemblies will increment the relevant InDiscards counters for each discarded 6LoWPAN datagram.




Figure 3: Conceptual Relationship between LOWPAN-MIB Counters

The fragmentation-related counters have been modeled after the fragmentation-related counters of the IP-MIB [RFC4293]. The discard counters have been placed at the end of the input and output chains, but they can be bumped any time if a datagram is discarded for a reason not covered by the other counters.

The compression-related counters provide insights into compression requests and, in particular, compression-related failures. Note that the diagram is conceptual in the sense that compression happens after reassembly for incoming 6LoWPAN datagrams, and compression happens

before fragmentation for outgoing 6LoWPAN datagrams. Implementations may choose to implement things slightly differently. For example, implementations may decompress FRAG1 fragments as soon as they are received, not waiting for reassembly to complete.

The counters related to MESH header processing do not have an explicit discard counter. Implementations that do not support mesh forwarding MUST count the number of received 6LoWPAN datagrams with a MESH header (lowpanInMeshReceives), but they MUST NOT increment the lowpanInMeshReceives and lowpanInMeshDelivers counters if these 6LoWPAN datagrams are dropped.

## 5. Relationship to Other MIB Modules

The MIB module imports definitions from SNMPv2-SMI [RFC2578], SNMPv2-CONF [RFC2580], and IF-MIB [RFC2863].

## 6. Definitions

LOWPAN-MIB DEFINITIONS ::= BEGIN

IMPORTS

```
MODULE-IDENTITY, OBJECT-TYPE, Unsigned32, Counter32, mib-2
FROM SNMPv2-SMI                                -- RFC 2578
OBJECT-GROUP, MODULE-COMPLIANCE
FROM SNMPv2-CONF                                -- RFC 2580
ifIndex FROM IF-MIB;                            -- RFC 2863
```

lowpanMIB MODULE-IDENTITY

```
LAST-UPDATED "201410100000Z" -- October 10, 2014
```

ORGANIZATION

```
"IETF IPv6 over Networks of Resource-constrained Nodes
Working Group"
```

CONTACT-INFO

```
"WG Email: 6lo@ietf.org
WG Web: http://tools.ietf.org/wg/6lo/
```

```
Juergen Schoenwaelder
Jacobs University Bremen
Email: j.schoenwaelder@jacobs-university.de
```

```
Anuj Sehgal
Jacobs University Bremen
Email: s.anuj@jacobs-university.de
```

```
Tina Tsou
Huawei Technologies
Email: tina.tsou.zouting@huawei.com
```

Cathy Zhou  
Huawei Technologies  
Email: cathyzhou@huawei.com"

## DESCRIPTION

"The MIB module for monitoring nodes implementing the IPv6 over Low-Power Wireless Personal Area Networks (6LoWPAN) protocol.

Copyright (c) 2014 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

REVISION "201410100000Z" -- October 10, 2014

## DESCRIPTION

"Initial version, published as RFC 7388."

::= { mib-2 226 }

-- object definitions

lowpanNotifications OBJECT IDENTIFIER ::= { lowpanMIB 0 }  
lowpanObjects OBJECT IDENTIFIER ::= { lowpanMIB 1 }  
lowpanConformance OBJECT IDENTIFIER ::= { lowpanMIB 2 }

lowpanStats OBJECT IDENTIFIER ::= { lowpanObjects 1 }

lowpanReasmTimeout OBJECT-TYPE

SYNTAX Unsigned32

UNITS "seconds"

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The maximum number of seconds that received fragments are held while they are awaiting reassembly at this entity."

::= { lowpanStats 1 }

lowpanInReceives OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current



## DESCRIPTION

"The total number of 6LoWPAN datagrams received, including those received in error."

::= { lowpanStats 2 }

## lowpanInHdrErrors OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of received 6LoWPAN datagrams discarded due to errors in their headers, including unknown dispatch values."

::= { lowpanStats 3 }

## lowpanInMeshReceives OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of received 6LoWPAN datagrams with a MESH header."

::= { lowpanStats 4 }

## lowpanInMeshForwds OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of received 6LoWPAN datagrams requiring mesh forwarding."

::= { lowpanStats 5 }

## lowpanInMeshDelivers OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of received 6LoWPAN datagrams with a MESH header delivered to the local system."

::= { lowpanStats 6 }

## lowpanInReasmReqds OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of received 6LoWPAN fragments that needed to be reassembled. This includes both FRAG1 and FRAGN 6LoWPAN datagrams."

::= { lowpanStats 7 }

## lowpanInReasmFails OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of failures detected by the re-assembly algorithm (e.g., timeouts). Note that this is not necessarily a count of discarded 6LoWPAN fragments since implementations can lose track of the number of fragments by combining them as received."

::= { lowpanStats 8 }

## lowpanInReasmOKs OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of IPv6 packets successfully reassembled."

::= { lowpanStats 9 }

## lowpanInCompReqds OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of 6LoWPAN datagrams requiring header decompression."

::= { lowpanStats 10 }

## lowpanInCompFails OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of 6LoWPAN datagrams where header decompression failed (e.g., because the necessary context information was not available)."

::= { lowpanStats 11 }

```
lowpanInCompOKs OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The number of 6LoWPAN datagrams where header decompression
        was successful."
    ::= { lowpanStats 12 }

lowpanInDiscards OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The number of received 6LoWPAN datagrams that were
        discarded (e.g., for lack of buffer space) even though no
        problems were encountered to prevent their continued
        processing. Note that this counter does not include any
        datagrams discarded due to a reassembly failure or a
        compression failure."
    ::= { lowpanStats 13 }

lowpanInDelivers OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The total number of IPv6 packets successfully delivered
        to the IPv6 layer."
    ::= { lowpanStats 14 }

lowpanOutRequests OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The total number of IPv6 packets supplied by the IPv6
        layer."
    ::= { lowpanStats 15 }

lowpanOutCompReqds OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The total number of IPv6 packets for which header
        compression was attempted."
    ::= { lowpanStats 16 }
```

```
lowpanOutCompFails OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The total number of IPv6 packets for which header
        compression failed."
    ::= { lowpanStats 17 }

lowpanOutCompOKs OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The total number of IPv6 packets for which header
        compression was successful."
    ::= { lowpanStats 18 }

lowpanOutFragReqds OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The number of IPv6 packets that required fragmentation
        in order to be transmitted."
    ::= { lowpanStats 19 }

lowpanOutFragFails OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The number of IPv6 packets that have been discarded because
        fragmentation failed."
    ::= { lowpanStats 20 }

lowpanOutFragOKs OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The number of IPv6 packets that have been successfully
        fragmented."
    ::= { lowpanStats 21 }

lowpanOutFragCreates OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
```

STATUS current  
DESCRIPTION  
"The number of 6LoWPAN fragments that have been  
generated as a result of fragmentation. This includes  
both FRAG1 and FRAGN 6LoWPAN datagrams."  
::= { lowpanStats 22 }

lowpanOutMeshHopLimitExceeds OBJECT-TYPE

SYNTAX Counter32  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The number of 6LoWPAN datagrams with a MESH header that  
were dropped because the hop limit was exceeded."  
::= { lowpanStats 23 }

lowpanOutMeshNoRoutes OBJECT-TYPE

SYNTAX Counter32  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The number of 6LoWPAN datagrams with a MESH header that  
were dropped because there was no forwarding information  
available."  
::= { lowpanStats 24 }

lowpanOutMeshRequests OBJECT-TYPE

SYNTAX Counter32  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The number of 6LoWPAN datagrams requiring MESH header  
encapsulation."  
::= { lowpanStats 25 }

lowpanOutMeshForwds OBJECT-TYPE

SYNTAX Counter32  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The number of 6LoWPAN datagrams with a MESH header for  
which suitable forwarding information was available."  
::= { lowpanStats 26 }

lowpanOutMeshTransmits OBJECT-TYPE

SYNTAX Counter32  
MAX-ACCESS read-only  
STATUS current

## DESCRIPTION

"The number of 6LoWPAN datagrams with a MESH header created."

::= { lowpanStats 27 }

## lowpanOutDiscards OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of IPv6 packets that were discarded (e.g., for lack of buffer space) even though no problem was encountered to prevent their transmission to their destination."

::= { lowpanStats 28 }

## lowpanOutTransmits OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The total number of 6LoWPAN datagram that this entity supplied to the lower layers for transmission."

::= { lowpanStats 29 }

## lowpanIfStatsTable OBJECT-TYPE

SYNTAX SEQUENCE OF LowpanIfStatsEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"A table providing per-interface statistics."

::= { lowpanObjects 2 }

## lowpanIfStatsEntry OBJECT-TYPE

SYNTAX LowpanIfStatsEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"An entry providing statistics for a specific interface."

INDEX { ifIndex }

::= { lowpanIfStatsTable 1 }

## LowpanIfStatsEntry ::= SEQUENCE {

lowpanIfReasmTimeout Unsigned32,

lowpanIfInReceives Counter32,

lowpanIfInHdrErrors Counter32,

lowpanIfInMeshReceives Counter32,

lowpanIfInMeshForwds Counter32,

```

lowpanIfInMeshDelivers      Counter32,
lowpanIfInReasmReqds        Counter32,
lowpanIfInReasmFails        Counter32,
lowpanIfInReasmOKs          Counter32,
lowpanIfInCompReqds         Counter32,
lowpanIfInCompFails         Counter32,
lowpanIfInCompOKs           Counter32,
lowpanIfInDiscards          Counter32,
lowpanIfInDelivers          Counter32,
lowpanIfOutRequests         Counter32,
lowpanIfOutCompReqds        Counter32,
lowpanIfOutCompFails        Counter32,
lowpanIfOutCompOKs          Counter32,
lowpanIfOutFragReqds        Counter32,
lowpanIfOutFragFails        Counter32,
lowpanIfOutFragOKs          Counter32,
lowpanIfOutFragCreates      Counter32,
lowpanIfOutMeshHopLimitExceeds Counter32,
lowpanIfOutMeshNoRoutes     Counter32,
lowpanIfOutMeshRequests     Counter32,
lowpanIfOutMeshForwds       Counter32,
lowpanIfOutMeshTransmits    Counter32,
lowpanIfOutDiscards         Counter32,
lowpanIfOutTransmits        Counter32
}

lowpanIfReasmTimeout OBJECT-TYPE
    SYNTAX      Unsigned32
    UNITS       "seconds"
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "The maximum number of seconds that received fragments are
         held while they are awaiting reassembly at this interface."
    ::= { lowpanIfStatsEntry 1 }

lowpanIfInReceives OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "The total number of 6LoWPAN datagrams received on this
         interface, including those received in error."
    ::= { lowpanIfStatsEntry 2 }

lowpanIfInHdrErrors OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only

```

```
STATUS      current
DESCRIPTION
    "The number of 6LoWPAN datagrams received on this
    interface that were discarded due to errors in
    their headers, including unknown dispatch values."
::= { lowpanIfStatsEntry 3 }
```

lowpanIfInMeshReceives OBJECT-TYPE

```
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The number of 6LoWPAN datagrams received on this
    interface with a MESH header."
::= { lowpanIfStatsEntry 4 }
```

lowpanIfInMeshForwds OBJECT-TYPE

```
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The number of 6LoWPAN datagrams received on this
    interface requiring mesh forwarding."
::= { lowpanIfStatsEntry 5 }
```

lowpanIfInMeshDelivers OBJECT-TYPE

```
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The number of 6LoWPAN datagrams received on this
    interface with a MESH header delivered to the local
    system."
::= { lowpanIfStatsEntry 6 }
```

lowpanIfInReasmReqds OBJECT-TYPE

```
SYNTAX      Counter32
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The number of 6LoWPAN fragments received on this
    interface that needed to be reassembled. This
    includes both FRAG1 and FRAGN 6LoWPAN datagrams."
::= { lowpanIfStatsEntry 7 }
```

lowpanIfInReasmFails OBJECT-TYPE

```
SYNTAX      Counter32
MAX-ACCESS  read-only
```



```
STATUS          current
DESCRIPTION
    "The number of failures detected by the reassembly
    algorithm (e.g., timeouts) for datagrams received
    on this interface. Note that this is not necessarily
    a count of discarded 6LoWPAN fragments since
    implementations can lose track of the number
    of fragments by combining them as received."
::= { lowpanIfStatsEntry 8 }
```

```
lowpanIfInReasmOKs OBJECT-TYPE
    SYNTAX          Counter32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The number of IPv6 packets successfully reassembled
        from fragments received on this interface."
    ::= { lowpanIfStatsEntry 9 }
```

```
lowpanIfInCompReqds OBJECT-TYPE
    SYNTAX          Counter32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The number of 6LoWPAN datagrams received on this
        interface requiring header decompression."
    ::= { lowpanIfStatsEntry 10 }
```

```
lowpanIfInCompFails OBJECT-TYPE
    SYNTAX          Counter32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The number of 6LoWPAN datagrams received on this
        interface where header decompression failed (e.g.,
        because the necessary context information was
        not available)."
    ::= { lowpanIfStatsEntry 11 }
```

```
lowpanIfInCompOKs OBJECT-TYPE
    SYNTAX          Counter32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The number of 6LoWPAN datagrams received on this
        interface where header decompression was successful."
    ::= { lowpanIfStatsEntry 12 }
```

```
lowpanIfInDiscards OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The number of 6LoWPAN datagrams received on this
        interface that were discarded (e.g., for lack of buffer
        space) even though no problems were encountered to
        prevent their continued processing. Note that this
        counter does not include any datagrams discarded due
        to a reassembly failure or a compression failure."
    ::= { lowpanIfStatsEntry 13 }

lowpanIfInDelivers OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total number of IPv6 packets received on this
        interface that were successfully delivered to the
        IPv6 layer."
    ::= { lowpanIfStatsEntry 14 }

lowpanIfOutRequests OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total number of IPv6 packets supplied by the IPv6
        layer to be sent over this interface."
    ::= { lowpanIfStatsEntry 15 }

lowpanIfOutCompReqds OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The total number of IPv6 packets to be sent over
        this interface for which header compression was
        attempted."
    ::= { lowpanIfStatsEntry 16 }

lowpanIfOutCompFails OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS  read-only
    STATUS      current
```

## DESCRIPTION

"The total number of IPv6 packets to be sent over  
this interface for which header compression failed."

::= { lowpanIfStatsEntry 17 }

## lowpanIfOutCompOKs OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The total number of IPv6 packets to be sent over  
this interface for which header compression was  
successful."

::= { lowpanIfStatsEntry 18 }

## lowpanIfOutFragReqds OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of IPv6 packets to be sent over this  
interface that required fragmentation in order  
to be transmitted."

::= { lowpanIfStatsEntry 19 }

## lowpanIfOutFragFails OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of IPv6 packets to be sent over this  
interface that have been discarded because  
fragmentation failed."

::= { lowpanIfStatsEntry 20 }

## lowpanIfOutFragOKs OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of IPv6 packets to be sent over this  
interface that have been successfully fragmented."

::= { lowpanIfStatsEntry 21 }

## lowpanIfOutFragCreates OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of 6LoWPAN fragments that have been generated on this interface as a result of fragmentation. This includes both FRAG1 and FRAGN 6LoWPAN datagrams."

::= { lowpanIfStatsEntry 22 }

## lowpanIfOutMeshHopLimitExceeds OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of 6LoWPAN datagrams to be sent on this interface with a MESH header that were dropped because the hop limit was exceeded."

::= { lowpanIfStatsEntry 23 }

## lowpanIfOutMeshNoRoutes OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of 6LoWPAN datagrams to be sent on this interface with a MESH header that were dropped because there was no forwarding information available."

::= { lowpanIfStatsEntry 24 }

## lowpanIfOutMeshRequests OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of 6LoWPAN datagrams to be sent on this interface requiring MESH header encapsulation."

::= { lowpanIfStatsEntry 25 }

## lowpanIfOutMeshForwds OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The number of 6LoWPAN datagrams to be sent on this interface with a MESH header for which suitable forwarding information was available."

::= { lowpanIfStatsEntry 26 }

```
lowpanIfOutMeshTransmits OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The number of 6LoWPAN datagrams to be sent on this
         interface with a MESH header created."
    ::= { lowpanIfStatsEntry 27 }

lowpanIfOutDiscards OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The number of IPv6 packets to be sent over this
         interface that were discarded (e.g., for lack of buffer
         space) even though no problem was encountered to
         prevent their transmission to their destination."
    ::= { lowpanIfStatsEntry 28 }

lowpanIfOutTransmits OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The total number of 6LoWPAN datagrams to be sent on
         this interface that this entity supplied to the lower
         layers for transmission."
    ::= { lowpanIfStatsEntry 29 }

-- conformance definitions

lowpanGroups          OBJECT IDENTIFIER ::= { lowpanConformance 1 }
lowpanCompliances     OBJECT IDENTIFIER ::= { lowpanConformance 2 }

lowpanCompliance MODULE-COMPLIANCE
    STATUS       current
    DESCRIPTION
        "Compliance statement for systems that implement 6LoWPAN."
    MODULE      -- this module
    MANDATORY-GROUPS {
        lowpanStatsGroup
    }
    GROUP        lowpanStatsMeshGroup
    DESCRIPTION
        "This group is mandatory for implementations that process
         or forward 6LoWPAN datagrams with a MESH header."
    GROUP        lowpanIfStatsGroup
```

## DESCRIPTION

"This group is mandatory for implementations that expose per-interface statistics."

GROUP lowpanIfStatsMeshGroup

## DESCRIPTION

"This group is mandatory for implementations that expose per-interface statistics and that process or forward 6LoWPAN datagrams with a MESH header."

::= { lowpanCompliances 1 }

## lowpanStatsGroup OBJECT-GROUP

## OBJECTS {

lowpanReasmTimeout,  
lowpanInReceives,  
lowpanInHdrErrors,  
lowpanInMeshReceives,  
lowpanInReasmReqds,  
lowpanInReasmFails,  
lowpanInReasmOKs,  
lowpanInCompReqds,  
lowpanInCompFails,  
lowpanInCompOKs,  
lowpanInDiscards,  
lowpanInDelivers,  
lowpanOutRequests,  
lowpanOutCompReqds,  
lowpanOutCompFails,  
lowpanOutCompOKs,  
lowpanOutFragReqds,  
lowpanOutFragFails,  
lowpanOutFragOKs,  
lowpanOutFragCreates,  
lowpanOutDiscards,  
lowpanOutTransmits

}

STATUS current

## DESCRIPTION

"A collection of objects providing information and statistics about the processing of 6LoWPAN datagrams, excluding counters covering the processing of datagrams with a MESH header."

::= { lowpanGroups 1 }

## lowpanStatsMeshGroup OBJECT-GROUP

## OBJECTS {

lowpanInMeshForwds,  
lowpanInMeshDelivers,  
lowpanOutMeshHopLimitExceeds,

```
        lowpanOutMeshNoRoutes,
        lowpanOutMeshRequests,
        lowpanOutMeshForwds,
        lowpanOutMeshTransmits
    }
    STATUS          current
    DESCRIPTION
        "A collection of objects providing information and
        statistics about the processing of 6LoWPAN datagrams
        with a MESH header."
    ::= { lowpanGroups 2 }

lowpanIfStatsGroup OBJECT-GROUP
    OBJECTS {
        lowpanIfReasmTimeout,
        lowpanIfInReceives,
        lowpanIfInHdrErrors,
        lowpanIfInMeshReceives,
        lowpanIfInReasmReqds,
        lowpanIfInReasmFails,
        lowpanIfInReasmOKs,
        lowpanIfInCompReqds,
        lowpanIfInCompFails,
        lowpanIfInCompOKs,
        lowpanIfInDiscards,
        lowpanIfInDelivers,
        lowpanIfOutRequests,
        lowpanIfOutCompReqds,
        lowpanIfOutCompFails,
        lowpanIfOutCompOKs,
        lowpanIfOutFragReqds,
        lowpanIfOutFragFails,
        lowpanIfOutFragOKs,
        lowpanIfOutFragCreates,
        lowpanIfOutDiscards,
        lowpanIfOutTransmits
    }
    STATUS          current
    DESCRIPTION
        "A collection of objects providing per-interface
        information and statistics about the processing
        of 6LoWPAN datagrams, excluding counters covering
        the processing of datagrams with a MESH header."
    ::= { lowpanGroups 3 }
```

```
lowpanIfStatsMeshGroup OBJECT-GROUP
    OBJECTS {
        lowpanIfInMeshForwds,
        lowpanIfInMeshDelivers,
        lowpanIfOutMeshHopLimitExceeds,
        lowpanIfOutMeshNoRoutes,
        lowpanIfOutMeshRequests,
        lowpanIfOutMeshForwds,
        lowpanIfOutMeshTransmits
    }
    STATUS      current
    DESCRIPTION
        "A collection of objects providing per-interface
        information and statistics about the processing
        of 6LoWPAN datagrams with a MESH header."
    ::= { lowpanGroups 4 }
```

END

## 7. Security Considerations

There are no management objects defined in this MIB module that have a MAX-ACCESS clause of read-write and/or read-create. So, if this MIB module is implemented correctly, then there is no risk that an intruder can alter or create any management objects of this MIB module via direct SNMP SET operations.

Some of the readable objects in this MIB module (i.e., objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control even GET and/or NOTIFY access to these objects and possibly to even encrypt the values of these objects when sending them over the network via SNMP.

The read-only counters provide insights into the amount of 6LoWPAN traffic a node is receiving or transmitting. This might provide information regarding whether a device is regularly exchanging information with other devices or whether a device is mostly not participating in any communication (e.g., the device might be "easier" to take away unnoticed). The reassembly counters could be used to direct denial-of-service attacks on the reassembly mechanism.

SNMP versions prior to SNMPv3 did not include adequate security. Even if the network itself is secure (for example by using IPsec), even then, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.



It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [RFC3410], Section 8), including full support for the SNMPv3 cryptographic mechanisms (for authentication and privacy).

Further, deployment of SNMP versions prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

## 8. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER value recorded in the SMI Numbers registry:

Descriptor	OBJECT IDENTIFIER value
-----	-----
lowpanMIB	{ mib-2 226 }

## 9. References

### 9.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999, <<http://www.rfc-editor.org/info/rfc2578>>.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, RFC 2579, April 1999, <<http://www.rfc-editor.org/info/rfc2579>>.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, RFC 2580, April 1999, <<http://www.rfc-editor.org/info/rfc2580>>.
- [RFC2863] McCloghrie, K. and F. Kastenholtz, "The Interfaces Group MIB", RFC 2863, June 2000, <<http://www.rfc-editor.org/info/rfc2863>>.

- [RFC4944] Montenegro, G., Kushalnagar, N., Hui, J., and D. Culler, "Transmission of IPv6 Packets over IEEE 802.15.4 Networks", RFC 4944, September 2007, <<http://www.rfc-editor.org/info/rfc4944>>.

## 9.2. Informative References

- [CASE] Case, J. and C. Partridge, "Case Diagrams: A First Step to Diagrammed Management Information Bases", Computer Communications Review 19(1), January 1989.
- [IPV6-BTLE] Nieminen, J., Savolainen, T., Isomaki, M., Patil, B., Shelby, Z., and C. Gomez, "Transmission of IPv6 Packets over BLUETOOTH(R) Low Energy", Work in Progress, draft-ietf-6lo-btle-03, September 2014.
- [RFC0768] Postel, J., "User Datagram Protocol", STD 6, RFC 768, August 1980, <<http://www.rfc-editor.org/info/rfc768>>.
- [RFC2460] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", RFC 2460, December 1998, <<http://www.rfc-editor.org/info/rfc2460>>.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002, <<http://www.rfc-editor.org/info/rfc3410>>.
- [RFC4113] Fenner, B. and J. Flick, "Management Information Base for the User Datagram Protocol (UDP)", RFC 4113, June 2005, <<http://www.rfc-editor.org/info/rfc4113>>.
- [RFC4292] Haberman, B., "IP Forwarding Table MIB", RFC 4292, April 2006, <<http://www.rfc-editor.org/info/rfc4292>>.
- [RFC4293] Routhier, S., "Management Information Base for the Internet Protocol (IP)", RFC 4293, April 2006, <<http://www.rfc-editor.org/info/rfc4293>>.
- [RFC4443] Conta, A., Deering, S., and M. Gupta, "Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification", RFC 4443, March 2006, <<http://www.rfc-editor.org/info/rfc4443>>.
- [RFC7252] Shelby, Z., Hartke, K., and C. Bormann, "The Constrained Application Protocol (CoAP)", RFC 7252, June 2014, <<http://www.rfc-editor.org/info/rfc7252>>.

## Acknowledgements

This specification borrows heavily from the IP-MIB defined in [RFC4293].

Juergen Schoenwaelder and Anuj Sehgal were partly funded by Flamingo, a Network of Excellence project (ICT-318488) supported by the European Commission under its Seventh Framework Programme.

## Authors' Addresses

Juergen Schoenwaelder  
Jacobs University  
Campus Ring 1  
Bremen 28759  
Germany

EMail: j.schoenwaelder@jacobs-university.de

Anuj Sehgal  
Jacobs University  
Campus Ring 1  
Bremen 28759  
Germany

EMail: s.anuj@jacobs-university.de

Tina Tsou  
Huawei Technologies  
2330 Central Expressway  
Santa Clara CA 95050  
United States

EMail: tina.tsou.zouting@huawei.com

Cathy Zhou  
Huawei Technologies  
Bantian, Longgang District  
Shenzhen 518129  
China

EMail: cathyzhou@huawei.com

