

Internet Engineering Task Force (IETF)  
Request for Comments: 8115  
Category: Standards Track  
ISSN: 2070-1721

M. Boucadair  
Orange  
J. Qin  
Cisco  
T. Tsou  
Philips Lighting  
X. Deng  
The University of New South Wales  
March 2017

## DHCPv6 Option for IPv4-Embedded Multicast and Unicast IPv6 Prefixes

### Abstract

This document defines a Dynamic Host Configuration Protocol version 6 (DHCPv6) Option for multicast IPv4 service continuity solutions, which is used to carry the IPv6 prefixes to be used to build unicast and multicast IPv4-embedded IPv6 addresses.

### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 7841.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc8115>.

### Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	2
1.1. Requirements Language . . . . .	2
2. Terminology . . . . .	2
3. OPTION_V6_PREFIX64 DHCPv6 Option . . . . .	3
4. DHCPv6 Client Behavior . . . . .	5
5. Security Considerations . . . . .	5
6. IANA Considerations . . . . .	6
7. References . . . . .	6
7.1. Normative References . . . . .	6
7.2. Informative References . . . . .	6
Appendix A. Configuration Recommendations for DHCP Servers . . .	8
Acknowledgments . . . . .	8
Authors' Addresses . . . . .	9

## 1. Introduction

Several solutions (e.g., [RFC8114]) are proposed for the delivery of multicast services in the context of transition to IPv6. Even if these solutions may have different applicable use cases, they all use specific IPv6 addresses that embed IPv4 addresses, for both multicast group and source addresses.

This document defines a DHCPv6 option [RFC3315] that carries the IPv6 prefixes to be used for constructing these IPv4-embedded IPv6 addresses.

In particular, this option can be used in the context of Dual-Stack Lite (DS-Lite) [RFC6333], Stateless Address plus Port (A+P) [RFC6346], and other IPv4-IPv6 transition techniques.

## 1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

## 2. Terminology

This document makes use of the following terms:

IPv4-embedded IPv6 address: an IPv6 address that embeds a 32-bit-encoded IPv4 address [RFC6052]. An IPv4-embedded IPv6 address can be a unicast or a multicast address.

Prefix64: an IPv6 prefix used for synthesizing IPv4-embedded IPv6 addresses. A Prefix64 can be unicast or multicast.

Note: "64" is used as an abbreviation for IPv6-IPv4 interconnection.

ASM\_mPrefix64: a multicast Prefix64 that belongs to the Any-Source Multicast (ASM) range.

SSM\_mPrefix64: a multicast Prefix64 which belongs to the Source-Specific Multicast (SSM) [RFC4607] range.

uPrefix64: a unicast Prefix64 for building the IPv4-embedded IPv6 addresses of multicast sources in SSM mode.

### 3. OPTION\_V6\_PREFIX64 DHCPv6 Option

OPTION\_V6\_PREFIX64 (Figure 1) conveys the IPv6 prefix(es) to be used (e.g., by an mB4 [RFC8114]) to synthesize IPv4-embedded IPv6 addresses.




Figure 1: Option Format for OPTION\_V6\_PREFIX64

The fields of the option shown in Figure 1 are as follows:

option-code: OPTION\_V6\_PREFIX64 (see Section 6).

option-length: length of the option, in octets.

asm-length: the prefix length for the ASM IPv4-embedded prefix, as an 8-bit unsigned integer. This field represents the number of valid leading bits in the prefix. This field MUST be set to 96.

ASM\_mPrefix64: this field identifies the IPv6 multicast prefix to be used to synthesize the IPv4-embedded IPv6 addresses of the multicast groups in the ASM mode. The conveyed multicast IPv6 prefix MUST belong to the ASM range.

ssm-length: the prefix length for the SSM IPv4-embedded prefix, as an 8-bit unsigned integer. This field represents the number of valid leading bits in the prefix. This field MUST be set to 96.

SSM\_mPrefix64: this field identifies the IPv6 multicast prefix to be used to synthesize the IPv4-embedded IPv6 addresses of the multicast groups in SSM mode. The conveyed multicast IPv6 prefix MUST belong to the SSM range.

unicast-length: the prefix length for the IPv6 unicast prefix to be used to synthesize the IPv4-embedded IPv6 addresses of the multicast sources, as an 8-bit unsigned integer. As specified in [RFC6052], the unicast-length MUST be one of 32, 40, 48, 56, 64, or 96. This field represents the number of valid leading bits in the prefix.

uPrefix64: this field identifies the IPv6 unicast prefix to be used in SSM mode for constructing the IPv4-embedded IPv6 addresses representing the IPv4 multicast sources in the IPv6 domain. uPrefix64 may also be used to extract the IPv4 address from the received multicast data flows. It is a variable-size field with the length of the field defined by the unicast-length field and is rounded up to the nearest octet boundary. In this case, any additional padding bits must be zeroed. The address mapping MUST follow the guidelines documented in [RFC6052].

Multiple instances of OPTION\_V6\_PREFIX64 may be returned to a DHCPv6 client. Configuration recommendations for DHCP servers are listed in Appendix A.

Note that it was tempting to define three distinct DHCPv6 options, but that approach was not adopted because it has a side effect: the specification of a DHCPv6 option that could be used to discover unicast Prefix64s in environments where multicast is not enabled. Such a side effect conflicts with the recommendation to support the Well-Known DNS Name heuristic discovery-based method for unicast-only environments (Section 6 of [RFC7051]).

#### 4. DHCPv6 Client Behavior

To retrieve the IPv6 prefixes that will be used to synthesize unicast and multicast IPv4-embedded IPv6 addresses, the DHCPv6 client MUST include the `OPTION_V6_PREFIX64` code in its `OPTION_ORO`. If the DHCPv6 client receives more than one `OPTION_V6_PREFIX64` option from the DHCPv6 server:

- o If each enclosed IPv6 multicast prefix has a distinct scope [RFC7346], the client MUST select the appropriate IPv6 multicast prefix whose scope matches the IPv4 multicast address used to synthesize an IPv4-embedded IPv6 multicast address.
- o If at least two of the received options convey IPv6 multicast prefixes that have the same scope, the said options MUST be discarded.

If `asm-length`, `ssm-length` and `unicast-length` fields are all set to 0, the DHCPv6 client MUST behave as if `OPTION_V6_PREFIX64` had not been received in the response received from the DHCPv6 server.

If the `asm-length` field is non-null, the IPv6 prefix identified by `ASM_mPrefix64` is used to synthesize IPv4-embedded IPv6 multicast addresses in the ASM range. This is achieved by concatenating the `ASM_mPrefix64` and the IPv4 multicast address; the IPv4 multicast address is inserted in the last 32 bits of the IPv4-embedded IPv6 multicast address.

If the `ssm-length` field is non-null, the IPv6 prefix identified by `SSM_mPrefix64` is used to synthesize IPv4-embedded IPv6 multicast addresses in the SSM range. This is achieved by concatenating the `SSM_mPrefix64` and the IPv4 multicast address; the IPv4 multicast address is inserted in the last 32 bits of the IPv4-embedded IPv6 multicast address.

If the `unicast-length` field is non-null, the IPv6 prefix identified by `uPrefix64` is used to synthesize IPv4-embedded IPv6 unicast addresses as specified in [RFC6052].

#### 5. Security Considerations

The security considerations documented in [RFC3315] and [RFC6052] are to be considered.

## 6. IANA Considerations

IANA has assigned the following option code in the "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)" registry  
<<http://www.iana.org/assignments/dhcpv6-parameters>>:

Option Name	Value
-----	-----
OPTION_V6_PREFIX64	113

## 7. References

### 7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC3315] Droms, R., Ed., Bound, J., Volz, B., Lemon, T., Perkins, C., and M. Carney, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", RFC 3315, DOI 10.17487/RFC3315, July 2003, <<http://www.rfc-editor.org/info/rfc3315>>.
- [RFC4607] Holbrook, H. and B. Cain, "Source-Specific Multicast for IP", RFC 4607, DOI 10.17487/RFC4607, August 2006, <<http://www.rfc-editor.org/info/rfc4607>>.
- [RFC6052] Bao, C., Huitema, C., Bagnulo, M., Boucadair, M., and X. Li, "IPv6 Addressing of IPv4/IPv6 Translators", RFC 6052, DOI 10.17487/RFC6052, October 2010, <<http://www.rfc-editor.org/info/rfc6052>>.

### 7.2. Informative References

- [RFC2365] Meyer, D., "Administratively Scoped IP Multicast", BCP 23, RFC 2365, DOI 10.17487/RFC2365, July 1998, <<http://www.rfc-editor.org/info/rfc2365>>.
- [RFC6333] Durand, A., Droms, R., Woodyatt, J., and Y. Lee, "Dual-Stack Lite Broadband Deployments Following IPv4 Exhaustion", RFC 6333, DOI 10.17487/RFC6333, August 2011, <<http://www.rfc-editor.org/info/rfc6333>>.
- [RFC6346] Bush, R., Ed., "The Address plus Port (A+P) Approach to the IPv4 Address Shortage", RFC 6346, DOI 10.17487/RFC6346, August 2011, <<http://www.rfc-editor.org/info/rfc6346>>.

- [RFC7051] Korhonen, J., Ed. and T. Savolainen, Ed., "Analysis of Solution Proposals for Hosts to Learn NAT64 Prefix", RFC 7051, DOI 10.17487/RFC7051, November 2013, <<http://www.rfc-editor.org/info/rfc7051>>.
- [RFC7346] Droms, R., "IPv6 Multicast Address Scopes", RFC 7346, DOI 10.17487/RFC7346, August 2014, <<http://www.rfc-editor.org/info/rfc7346>>.
- [RFC8114] Boucadair, M., Qin, C., Jacquenet, C., Lee, Y., and Q. Wang, "Delivery of IPv4 Multicast Services to IPv4 Clients over an IPv6 Multicast Network", RFC 8114, DOI 10.17487/RFC8114, March 2017, <<http://www.rfc-editor.org/info/rfc8114>>.

## Appendix A. Configuration Recommendations for DHCP Servers

This appendix details a set of non-normative configuration recommendations:

- o DHCP servers supporting `OPTION_V6_PREFIX64` must be configured with `ASM_mPrefix64` or `SSM_mPrefix64`, and may be configured with both.
- o `uPrefix64` must also be configured when `SSM_mPrefix64` is provided.
- o `uPrefix64` may be configured when `ASM_mPrefix64` is provided.

Note that `uPrefix64` is not mandatory for the ASM case if, for example, a local address mapping algorithm is supported or the Well-Known Prefix (`64:ff9b::/96`) is used.

- o Both `ASM_mPrefix64` and `SSM_mPrefix64` may be configured and therefore be returned to a requesting DHCP client in the same `OPTION_V6_PREFIX64`. In particular, if both SSM and ASM modes are supported, `ASM_mPrefix64` and `SSM_mPrefix64` prefixes must be configured. For SSM deployments, both `SSM_mPrefix64` and `uPrefix64` must be configured.
- o When a multicast Prefix64 (`ASM_mPrefix64` or `SSM_mPrefix64`) is configured, the length of the prefix must be `/96`.
- o When distinct IPv6 multicast address scopes [RFC7346] are required to preserve the scope when translating IPv4 multicast addresses (Section 8 of [RFC2365]), each scope is configured as a separate `OPTION_V6_PREFIX64`. How DHCP servers are configured to separate multicast Prefix64 per scope is implementation specific and not covered by this document.
- o When scope preservation is not required, only one instance of `OPTION_V6_PREFIX64` is configured.

## Acknowledgments

Thanks to C. Jacquenet, S. Venaas, B. Volz, T. Taylor, R. Weber, R. Even, J. Sheng, T. Mrugalski, and T. Chown for their review.

Many thanks to I. Farrer and T. Lemon for the comments.



## Authors' Addresses

Mohamed Boucadair  
Orange  
Rennes 35000  
France

Email: mohamed.boucadair@orange.com

Jacni Qin  
Cisco  
Shanghai  
China

Email: jacni@jacni.com

Tina Tsou  
Philips Lighting  
United States of America

Email: tina.tsou@philips.com

Xiaohong Deng  
The University of New South Wales  
Sydney NSW 2052  
Australia

Email: dxhbupt@gmail.com

