

Internet Research Task Force (IRTF)  
Request for Comments: 9620  
Updates: 8280  
Category: Informational  
ISSN: 2070-1721

G. Grover  
N. ten Oever  
University of Amsterdam  
September 2024

## Guidelines for Human Rights Protocol and Architecture Considerations

### Abstract

This document sets guidelines for human rights considerations for developers working on network protocols and architectures, similar to the work done on the guidelines for privacy considerations (RFC 6973). This is an updated version of the guidelines for human rights considerations in RFC 8280.

This document is a product of the Human Right Protocol Considerations (HRPC) Research Group in the IRTF.

### Status of This Memo

This document is not an Internet Standards Track specification; it is published for informational purposes.

This document is a product of the Internet Research Task Force (IRTF). The IRTF publishes the results of Internet-related research and development activities. These results might not be suitable for deployment. This RFC represents the consensus of the Human Rights Protocol Considerations Research Group of the Internet Research Task Force (IRTF). Documents approved for publication by the IRSG are not candidates for any level of Internet Standard; see Section 2 of RFC 7841.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <https://www.rfc-editor.org/info/rfc9620>.

### Copyright Notice

Copyright (c) 2024 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

### Table of Contents

1. Introduction
2. Human Rights Threats
3. Conducting Human Rights Reviews
  - 3.1. Analyzing Internet-Drafts Based on Guidelines for Human Rights Considerations Model
  - 3.2. Analyzing Internet-Drafts Based on Their Perceived or Speculated Impact
  - 3.3. Expert Interviews
  - 3.4. Interviews with Impacted Persons and Communities
  - 3.5. Tracing Impacts of Implementations

## 4. Guidelines for Human Rights Considerations

- 4.1. Intermediaries
- 4.2. Connectivity
- 4.3. Reliability
- 4.4. Content Signals
- 4.5. Internationalization
- 4.6. Localization
- 4.7. Open Standards
- 4.8. Heterogeneity Support
- 4.9. Adaptability
- 4.10. Integrity
- 4.11. Authenticity
- 4.12. Confidentiality
- 4.13. Security
- 4.14. Privacy
- 4.15. Anonymity and Pseudonymity
  - 4.15.1. Pseudonymity
  - 4.15.2. Unlinkability
- 4.16. Censorship Resistance
- 4.17. Outcome Transparency
- 4.18. Accessibility
- 4.19. Decentralization
- 4.20. Remedy
- 4.21. Miscellaneous Considerations

## 5. Document Status

## 6. Security Considerations

## 7. IANA Considerations

## 8. Research Group Information

## 9. Informative References

## Acknowledgements

## Authors' Addresses

## 1. Introduction

This document outlines a set of human rights protocol considerations for protocol developers. It provides questions that engineers should ask themselves when developing or improving protocols if they want to understand how their decisions can potentially influence the exercise of human rights on the Internet. It should be noted that the impact of a protocol cannot solely be deduced from its design, but its usage and implementation should also be studied to form a full human rights impact assessment.

The questions are based on the research performed by the Human Rights Protocol Considerations (HRPC) Research Group, which has been documented before these considerations. The research establishes that human rights relate to standards and protocols and offers a common vocabulary of technical concepts that influence human rights and how these technical concepts can be combined to ensure that the Internet remains an enabling environment for human rights. With this, the contours of a model for developing human rights protocol considerations has taken shape.

This document is an iteration of the guidelines that can be found in [RFC8280]. The methods for conducting human rights reviews (Section 3.2) and the guidelines for human rights considerations (Section 3.3) in this document are being tested for relevance, accuracy, and validity [HR-RT]. The understanding of what human rights are is based on the "Universal Declaration of Human Rights" [UDHR] and subsequent treaties that jointly form the body of international human rights law [UNHR].

This document does not provide a detailed taxonomy of the nature of (potential) human rights violations, whether direct or indirect / long-term or short-term, that certain protocol choices might present. In part, it is because this is highly context-dependent and also

because this document aims to provide a practical set of guidelines. However, further research in this field would definitely benefit developers and implementers.

This informational document has consensus for publication from the Internet Research Task Force (IRTF) Human Right Protocol Considerations (HRPC) Research Group. It has been reviewed, tried, and tested by both the research group as well as researchers and practitioners from outside the research group. The research group acknowledges that the understanding of the impact of Internet protocols and architecture on society is a developing practice and is a body of research that is still ongoing. This document is not an IETF product and is not a standard.

## 2. Human Rights Threats

Threats to the exercise of human rights on the Internet come in many forms. Protocols and standards may harm or enable the right to freedom of expression; right to freedom of information; right to non-discrimination; right to equal protection; right to participate in cultural life, arts, and science; right to freedom of assembly and association; right to privacy; and right to security. An end user who is denied access to certain services or content may be unable to disclose vital information about the malpractices of a government or other authority. A person whose communications are monitored may be prevented or dissuaded from exercising their right to freedom of association or participate in political processes [Penney]. In a worst-case scenario, protocols that leak information can lead to physical danger. A realistic example to consider is when individuals perceived as threats to the state are subjected to torture, extra-judicial killing, or detention on the basis of information gathered by state agencies through the monitoring of network traffic.

This document presents several examples of how threats to human rights materialize on the Internet. This threat modeling is inspired by "Privacy Considerations for Internet Protocols" [RFC6973], which is based on security threat analysis. This method is a work in progress and by no means a perfect solution for assessing human rights risks in Internet protocols and systems. Certain specific human rights threats are indirectly considered in Internet protocols as part of the security considerations [RFC3552]; however, privacy considerations [RFC6973] or reviews, let alone human rights impact assessments of protocols, are neither standardized nor implemented.

Many threats, enablers, and risks are linked to different rights. This is not surprising if one takes into account that human rights are interrelated, interdependent, and indivisible. However, here we're not discussing all human rights because not all human rights are relevant to Information and Communication Technologies (ICTs) in general and to protocols and standards in particular [Orwat]:

The main source of the values of human rights is the \_International Bill of Human Rights\_ that is composed of the \_Universal Declaration of Human Rights\_ (UDHR) [UDHR] along with the \_International Covenant on Civil and Political Rights\_ (ICCPR) [ICCPR] and the \_International Covenant on Economic, Social and Cultural Rights\_ (ICESCR) [ICESCR]. In the light of several cases of Internet censorship, the UN Human Rights Council Resolution 20/8 was adopted in 2012, affirming that "...the same rights that people have offline must also be protected online..." [UNHRC2016]. In 2015, the \_Charter of Human Rights and Principles for the Internet\_ [IRP] was developed and released [Jorgensen]. According to these documents, some examples of human rights relevant for ICT systems are \_human dignity\_ (Art. 1 UDHR), \_non-discrimination\_ (Art. 2), \_rights to life, liberty and security\_ (Art. 3), \_freedom of opinion and expression\_ (Art. 19), \_freedom of

| assembly and association\_ (Art. 20), \_rights to equal protection,  
| legal remedy, fair trial, due process, presumed innocent\_ (Art.  
| 7-11), \_appropriate social and international order\_ (Art. 28),  
| \_participation in public affairs\_ (Art. 21), \_participation in  
| cultural life, protection of intellectual property\_ (Art. 27), and  
| \_privacy\_ (Art. 12).

A partial catalog of human rights related to ICTs, including economic rights, can be found in [Hill].

This is by no means an attempt to exclude specific rights or prioritize some rights over others.

### 3. Conducting Human Rights Reviews

Ideally, protocol developers and collaborators should incorporate human rights considerations into the design process itself (see Section 3.1 ("Analyzing Internet-Drafts Based on Guidelines for Human Rights Considerations Model")). This section provides guidance on how to conduct a human rights review, i.e., gauge the impact or potential impact of a protocol or standard on human rights.

Human rights reviews can be done by any participant and can take place at different stages of the development process of an Internet-Draft. Generally speaking, it is easier to influence the development of a technology at earlier stages than at later stages. This does not mean that reviews at Last Call are not relevant, but they are less likely to result in significant changes in the reviewed document.

Human rights reviews can be done by document authors, document shepherds, members of review teams, advocates, or impacted communities to influence the standards development process. IETF documents can benefit from people with different knowledge, perspectives, and backgrounds, especially since their implementations can impact many different communities as well.

Methods for analyzing technology for specific human rights impacts are still quite nascent. Currently, five methods have been explored by the human rights review team, often in conjunction with each other.

#### 3.1. Analyzing Internet-Drafts Based on Guidelines for Human Rights Considerations Model

This analysis of Internet-Drafts uses the model as described in Section 4. The outlined categories and questions can be used to review an Internet-Draft. The advantage of this is that it provides a known overview, and document authors can go back to this document as well as [RFC8280] to understand the background and the context.

#### 3.2. Analyzing Internet-Drafts Based on Their Perceived or Speculated Impact

When reviewing an Internet-Draft, specific human rights impacts can become apparent by doing a close reading of the draft and seeking to understand how it might affect networks or society. While less structured than the straight use of the human rights considerations model, this analysis may lead to new speculative understandings of links between human rights and protocols.

#### 3.3. Expert Interviews

Interviews with document authors, active members of the working group, or experts in the field can help explore the characteristics of the protocol and its effects. There are two main advantages to

this approach:

1. It allows the reviewer to gain a deeper understanding of the (intended) workings of the protocol.
2. It allows for the reviewer to start a discussion with experts or even document authors, which can help the review gain traction when it is published.

#### 3.4. Interviews with Impacted Persons and Communities

Protocols impact users of the Internet. Interviews can help the reviewer understand how protocols affect the people that use the protocols. Since human rights are best understood from the perspective of the rights-holder, this approach will improve the understanding of the real-world effects of the technology. At the same time, it can be hard to attribute specific changes to a particular protocol; this is of course even harder when a protocol has not been widely deployed.

#### 3.5. Tracing Impacts of Implementations

The reality of deployed protocols can be at odds with the expectations during the protocol design and development phase [RFC8980]. When a specification already has associated running code, the code can be analyzed either in an experimental setting or on the Internet where its impact can be observed. In contrast to reviewing the draft text, this approach can allow the reviewer to understand how the specifications work in practice and potentially what unknown or unexpected effects the technology has.

#### 4. Guidelines for Human Rights Considerations

This section provides guidance for document authors in the form of a questionnaire about protocols and how technical decisions can shape the exercise of human rights. The questionnaire may be useful at any point in the design process, particularly after the document authors have developed a high-level protocol model as described in [RFC4101]. These guidelines do not seek to replace any existing referenced specifications but, rather, contribute to them and look at the design process from a human rights perspective.

Protocols and Internet Standards might benefit from a documented discussion of potential human rights risks arising from potential misapplications of the protocol or technology described in the Request for Comments (RFC). This might be coupled with an Applicability Statement for that RFC.

Note that the guidance provided in this section does not recommend specific practices. The range of protocols developed in the IETF is too broad to make recommendations about particular uses of data or how human rights might be balanced against other design goals. However, by carefully considering the answers to the following questions, document authors should be able to produce a comprehensive analysis that can serve as the basis for discussion on whether the protocol adequately takes specific human rights threats into account. This guidance is meant to help the thought process of a human rights analysis; it does not provide specific directions for how to write a human rights considerations section (following the example set in [RFC6973]).

In considering these questions, authors will need to be aware of the potential of technical advances or the passage of time to undermine protections. In general, considerations of rights are likely to be more effective if they have a purpose and specific use cases rather than abstract, absolute goals.

Also note that while the section uses the word "protocol", the principles identified in these questions may be applicable to other types of solutions (extensions to existing protocols, architecture for solutions to specific problems, etc.).

#### 4.1. Intermediaries

Question(s): Does your protocol depend on or allow for protocol-specific functions at intermediary nodes?

Explanation: The end-to-end principle [Saltzer] holds that certain functions can and should be performed at "ends" of the network. [RFC1958] states that "in very general terms, the community believes that the goal is connectivity ... and the intelligence is end to end rather than hidden in the network". There are new opportunities for failure when a protocol exchange includes both endpoints and an intermediary, especially when the intermediary is not under control of either endpoint, or is even largely invisible to it, for instance, as with intercepting HTTPS proxies [HTTPS-interception]. This pattern also contributes to ossification because the intermediaries may impose protocol restrictions -- sometimes in violation of the specification -- that prevent the endpoints from using more modern protocols, as described in Section 9.3 of [RFC8446].

Note that intermediaries are distinct from services. In the former case, the third-party element is part of the protocol exchange; whereas in the latter, the endpoints communicate explicitly with the service. The client/server pattern provides clearer separation of responsibilities between elements than having an intermediary. However, even in client/server systems, it is often good practice to provide for end-to-end encryption between endpoints for protocol elements that are outside of the scope of the service, as in the design of Messaging Layer Security (MLS) [RFC9420].

Example: Encryption between the endpoints can be used to protect the protocol from interference by intermediaries. The encryption of transport layer information in QUIC [RFC9000] and of the TLS Server Name Indication (SNI) field [TLS-ESNI] are examples of this practice. One consequence of this is to limit the extent to which network operators can inspect traffic, requiring them to have control of the endpoints in order to monitor their behavior.

Impacts:

- \* Right to freedom of expression
- \* Right to freedom of assembly and association

#### 4.2. Connectivity

Questions(s): Is your protocol optimized for low-bandwidth and high-latency connections? Could your protocol also be developed in a stateless manner?

Considering the fact that network quality and conditions vary across geography and time, it is also important to design protocols such that they are reliable even on low-bandwidth and high-latency connections.

Impacts:

- \* Right to freedom of expression
- \* Right to freedom of assembly and association

#### 4.3. Reliability

Question(s): Is your protocol fault tolerant? Does it downgrade gracefully, i.e., with mechanisms for fallback and/or notice? Can your protocol resist malicious degradation attempts? Do you have a documented way to announce degradation? Do you have measures in place for recovery or partial healing from failure? Can your protocol maintain dependability and performance in the face of unanticipated changes or circumstances?

Explanation: Reliability and resiliency ensures that a protocol will execute its function consistently and resistant to error, as described, and will function without unexpected results. Measures for reliability in protocols assure users that their intended communication was successfully executed.

A system that is reliable degrades gracefully and will have a documented way to announce degradation. It will also have mechanisms to recover from failure gracefully and, if applicable, will allow for partial healing.

It is important here to draw a distinction between random degradation and malicious degradation. Some attacks against previous versions of TLS, for example, exploited TLS' ability to gracefully downgrade to non-secure cipher suites [FREAK] [Logjam]; from a functional perspective, this is useful, but from a security perspective, this can be disastrous.

For reliability, it is necessary that services notify the users if a delivery fails. In the case of real-time systems, in addition to the reliable delivery, the protocol needs to safeguard timeliness.

Example: In the modern IP stack structure, a reliable transport layer requires an indication that transport processing has successfully completed, such as given by TCP's ACK message [RFC9293]. Similarly, an application-layer protocol may require an application-specific acknowledgement that contains, among other things, a status code indicating the disposition of the request (see [RFC3724]).

Impacts:

- \* Right to freedom of expression
- \* Right to security

#### 4.4. Content Signals

Question(s): Does your protocol include explicit or implicit plaintext elements, in either the payload or the headers, that can be used for differential treatment? Is there a way to minimize leaking such data to network intermediaries? If not, is there a way for deployments of the protocol to make the differential treatment (including prioritization of certain traffic), if any, auditable for negative impacts on net neutrality?

Example: When network intermediaries are able to determine the type of content that a packet is carrying, then they can use that information to discriminate in favor of one type of content and against another. This impacts users' ability to send and receive the content of their choice.

As recommended in [RFC8558], protocol designers should avoid the construction of implicit signals of their content. In general, protocol designers should avoid adding explicit signals for intermediaries. In certain cases, it may be necessary to add such explicit signals, but designers should only do so when they provide

clear benefit to end users (see [RFC8890] for more on the priority of constituencies). In these cases, the implications of those signals for human rights should be documented.

Note that many protocols provide signals that are intended for endpoints that can be used as implicit signals by intermediaries for traffic discrimination, based on either the content (e.g., TCP port numbers) or the sender/receiver (IP addresses). Where possible, these should be protected from intermediaries by encryption. In many cases (e.g., IP addresses), these signals are difficult to remove; but in other cases, such as TLS Application Layer Protocol Negotiation [RFC7301], there are active efforts to protect this data [TLS-ESNI].

Impacts:

- \* Right to freedom of expression
- \* Right to non-discrimination
- \* Right to equal protection

#### 4.5. Internationalization

Question(s): Does your protocol or specification define text string elements, in the payload or headers, that have to be understood or entered by humans? Does your specification allow Unicode? If so, do you accept texts in one character set (which must be UTF-8) or several (which is dangerous for interoperability)? If charsets or encodings other than UTF-8 are allowed, does your specification mandate a proper tagging of the charset? Did you have a look at [RFC6365]?

Explanation: Internationalization refers to the practice of making protocols, standards, and implementations usable in different languages and scripts (see Section 4.6 ("Localization")). In the IETF, internationalization means to add or improve the handling of non-ASCII text in a protocol [RFC6365]. A different perspective, more appropriate to protocols that are designed for global use from the beginning, is the definition used by the World Wide Web Consortium (W3C) [W3CintDef]:

| Internationalization is the design and development of a product,  
| application or document content that enables easy localization for  
| target audiences that vary in culture, region, or language.

Many protocols that handle text only handle one charset (US-ASCII) or leave the question of what coded charset and encoding are used up to local guesswork (which leads, of course, to interoperability problems). If multiple charsets are permitted, they must be explicitly identified [RFC2277]. Adding non-ASCII text to a protocol allows the protocol to handle more scripts, hopefully representing users across the world. In today's world, that is normally best accomplished by allowing only Unicode encoded in UTF-8.

In current IETF practice [RFC2277], internationalization is aimed at user-facing strings, not protocol elements, such as the verbs used by some text-based protocols. (Do note that some strings are both content and protocol elements, such as identifiers.) Although this is reasonable practice for non-user visible elements, developers should provide full and equal support for all scripts and charsets in the user-facing features of protocols and for any content they carry.

Example: See Section 4.6 ("Localization").

Impacts:



- \* Right to freedom of expression
- \* Right to political participation
- \* Right to participate in cultural life, arts, and science

#### 4.6. Localization

Question(s): Does your protocol uphold the standards of internationalization? Have you made any concrete steps towards localizing your protocol for relevant audiences?

Explanation: "Localization refers to the adaptation of a product, application or document content to meet the language, cultural and other requirements of a specific target market (a 'locale')" [W3Cil8nDef]. For our purposes, it can be described as the practice of translating an implementation to make it functional in a specific language or for users in a specific locale (see Section 4.5 ("Internationalization")). Internationalization is related to localization, but they are not the same. Internationalization is a necessary precondition for localization.

Example: The Internet is a global medium, but many of its protocols and products are developed with certain audiences in mind that often share particular characteristics like knowing how to read and write in American Standard Code for Information Interchange (ASCII) and knowing English. This limits the ability of a large part of the world's online population from using the Internet in a way that is culturally and linguistically accessible. An example of a standard that has taken into account the view that individuals like to have access to data in their preferred language can be found in [RFC5646]. The document describes a way to label information with an identifier for the language in which it is written. And this allows information to be presented and accessed in more than one language.

Impacts:

- \* Right to non-discrimination
- \* Right to participate in cultural life, arts, and science
- \* Right to freedom of expression

#### 4.7. Open Standards

Question(s): Is your protocol fully documented in a way that it could be easily implemented, improved, built upon, and/or further developed? Do you depend on proprietary code for the implementation, running, or further development of your protocol? Does your protocol favor a particular proprietary specification over technically equivalent competing specification(s), for instance, by making any incorporated vendor specification "required" or "recommended" [RFC2026]? Do you normatively reference another standard that is behind a paywall (and could you do without it)? Are you aware of any patents that would prevent your standard from being fully implemented [RFC8179] [RFC6701]?

Explanation: The Internet was able to be developed into the global network of networks because of the existence of open, non-proprietary standards [Zittrain]. They are crucial for enabling interoperability. Yet, open standards are not explicitly defined within the IETF. On the subject, [RFC2026] states:

| Various national and international standards bodies, such as ANSI,  
| ISO, IEEE, and ITU-T, develop a variety of protocol and service

| specifications that are similar to Technical Specifications  
| defined here [at the IETF]. National and international groups  
| also publish "implementors' agreements" that are analogous to  
| Applicability Statements, capturing a body of implementation-  
| specific detail concerned with the practical application of their  
| standards. All of these are considered to be "open external  
| standards" for the purposes of the Internet Standards Process.

Similarly, [RFC3935] does not define open standards but does  
emphasize the importance of an "open process", i.e.:

| ... any interested person can participate in the work, know what  
| is being decided, and make [their] voice heard on the issue.

Open standards (and open source software) allow users to glean  
information about how the tools they are using work, including the  
tools' security and privacy properties. They additionally allow for  
permissionless innovation, which is important to maintain the freedom  
and ability to freely create and deploy new protocols on top of the  
communications constructs that currently exist. It is at the heart  
of the Internet as we know it, and to maintain its fundamentally open  
nature, we need to be mindful of the need for developing open  
standards.

All standards that need to be normatively implemented should be  
freely available and with reasonable protection for patent  
infringement claims so that they can also be implemented in open  
source or free software. Patents have often held back open  
standardization or been used against those deploying open standards,  
particularly in the domain of cryptography [Newegg]. An exemption of  
this is sometimes made when a standardized protocol normatively  
relies on specifications produced by others Standards Development  
Organizations (SDOs) that are not freely available. Patents in open  
standards or in normative references to other standards should have a  
patent disclosure [Note-well], royalty-free licensing  
[Patent-policy], or some other form of fair, reasonable, and non-  
discriminatory terms.

Example: [RFC6108] describes a system for providing critical end-user  
notifications to web browsers, which has been deployed by Comcast, an  
Internet Service Provider (ISP). Such a notification system is being  
used to provide near-immediate notifications to customers, such as to  
warn them that their traffic exhibits patterns that are indicative of  
malware or virus infection. There are other proprietary systems that  
can perform such notifications, but those systems utilize Deep Packet  
Inspection (DPI) technology. In contrast, that document describes a  
system that does not rely upon DPI and is instead based on open IETF  
standards and open source applications.

Impacts:

- \* Right to freedom of expression
- \* Right to participate in cultural life, arts, and science

#### 4.8. Heterogeneity Support

Question(s): Does your protocol support heterogeneity by design?  
Does your protocol allow for multiple types of hardware? Does your  
protocol allow for multiple types of application protocols? Is your  
protocol liberal in what it receives and handles? Will it remain  
usable and open if the context changes?

Explanation: The Internet is characterized by heterogeneity on many  
levels: devices, nodes, router scheduling algorithms, queue  
management mechanisms, routing protocols, levels of multiplexing,

protocol versions and implementations, and underlying link layers (e.g., point-to-point, multi-access links, wireless, Fiber Distributed Data Interface (FDDI), etc.) in the traffic mix and in the levels of congestion at different times and places. Moreover, as the Internet is composed of autonomous organizations and ISPs, each with their own separate policy concerns, there is a large heterogeneity of administrative domains and pricing structures. As a result, the heterogeneity principle proposed in [RFC1958] needs to be supported by design [FIArch].

Heterogeneity support in protocols can, thus, enable a wide range of devices and (by extension) users to participate on the network.

Example: Heterogeneity significantly contributed to the success of the Internet architecture [Zittrain]. There is a famous quote often attributed to Niels Bohr: "Prediction is very difficult, especially if it's about the future." This also holds true for future uses of the Internet architecture and infrastructure. Therefore, as a rule of thumb, it is important to -- as far as possible -- design your protocol for different devices and uses, especially at lower layers of the stack. However, if you choose not to do this, it could be relevant to document the reasoning for that.

Impacts:

- \* Right to freedom of expression
- \* Right to political participation

#### 4.9. Adaptability

Question(s): Is your protocol written in a modular fashion, and does it facilitate or hamper extensibility? In this sense, does your protocol impact permissionless innovation? (See Section 4.7 ("Open Standards").)

Explanation: Adaptability is closely interrelated with permissionless innovation: both maintain the freedom and ability to create and deploy new protocols on top of the communications constructs that currently exist. It is at the heart of the Internet as we know it, and to maintain its fundamentally open nature, we need to be mindful of the impact of protocols on maintaining or reducing permissionless innovation to ensure that the Internet can continue to develop.

Adaptability and permissionless innovation can be used to shape information networks as groups of users prefer. Furthermore, a precondition of adaptability is the ability of the people who can adapt the network to be able to know and understand the network. This is why adaptability and permissionless innovation are inherently connected to the right to education and the right to science as well as the right to freedom of assembly and association and the right to freedom of expression, since it allows the users of the network to determine how to assemble, collaborate, and express themselves.

Example: WebRTC generates audio and/or video data. WebRTC can be used in different locations by different parties; WebRTC's standard Application Programming Interfaces (APIs) are developed to support applications from different voice service providers. Multiple parties will have similar capabilities. In order to ensure that all parties can build upon existing standards, these need to be adaptable and allow for permissionless innovation.

Impacts:

- \* Right to education

- \* Right to science
- \* Right to freedom of expression
- \* Right to freedom of assembly and association

#### 4.10. Integrity

Question(s): Does your protocol maintain, assure, and/or verify the accuracy of payload data? Does your protocol maintain and assure the consistency of data? Does your protocol in any way allow for the data to be (intentionally or unintentionally) altered?

Explanation: Integrity refers to the maintenance and assurance of the accuracy and consistency of data to ensure it has not been (intentionally or unintentionally) altered.

Example: Integrity verification of data is important to prevent vulnerabilities and attacks from on-path attackers. These attacks happen when a third party (often for malicious reasons) intercepts a communication between two parties, inserting themselves in the middle and changing the content of the data. In practice, this looks as follows:

Alice wants to communicate with Bob. Alice sends a message to Bob, which Corinne intercepts and modifies. Bob cannot see that the data from Alice was altered by Corinne. Corinne intercepts and alters the communication as it is sent between Alice and Bob. Corinne is able to control the communication content.

Impacts:

- \* Right to freedom of expression
- \* Right to security

#### 4.11. Authenticity

Question(s): Do you have sufficient measures to confirm the truth of an attribute of a single piece of data or entity? Can the attributes get garbled along the way (see Section 4.13 ("Security"))? If relevant, have you implemented IPsec, DNS Security (DNSSEC), HTTPS, and other standard security best practices?

Explanation: Authenticity ensures that data does indeed come from the source it claims to come from. This is important to prevent certain attacks or unauthorized access and use of data.

At the same time, authentication should not be used as a way to prevent heterogeneity support, as is often done for vendor lock-in or digital rights management.

Example: Authentication of data is important to prevent vulnerabilities and attacks from on-path attackers. These attacks happen when a third party (often for malicious reasons) intercepts a communication between two parties, inserting themselves in the middle and posing as both parties. In practice, this looks as follows:

Alice wants to communicate with Bob. Alice sends data to Bob. Corinne intercepts the data sent to Bob. Corinne reads (and potentially alters) the message to Bob. Bob cannot see that the data did not come from Alice but from Corinne.

With proper authentication, the scenario would be as follows:

Alice wants to communicate with Bob. Alice sends data to Bob.

Corinne intercepts the data sent to Bob. Corinne reads and alters the message to Bob. Bob is unable to verify whether that the data came from Alice.

Impacts:

- \* Right to privacy
- \* Right to freedom of expression
- \* Right to security

#### 4.12. Confidentiality

Question(s): Does the protocol expose the transmitted data over the wire? Does the protocol expose information related to identifiers or data? If so, what does it reveal to each protocol entity (i.e., recipients, intermediaries, and enablers) [RFC6973]? What options exist for protocol implementers to choose to limit the information shared with each entity? What operational controls are available to limit the information shared with each entity?

What controls or consent mechanisms does the protocol define or require before personal data or identifiers are shared or exposed via the protocol? If no such mechanisms or controls are specified, is it expected that control and consent will be handled outside of the protocol?

Does the protocol provide ways for initiators to share different pieces of information with different recipients? If not, are there mechanisms that exist outside of the protocol to provide initiators with such control?

Does the protocol provide ways for initiators to limit the sharing or expressing of individuals' preferences to recipients or intermediaries with regard to the collection, use, or disclosure of their personal data? If not, are there mechanisms that exist outside of the protocol to provide users with such control? Is it expected that users will have relationships that govern the use of the information (contractual or otherwise) with those who operate these intermediaries? Does the protocol prefer encryption over cleartext operation?

Explanation: Confidentiality refers to keeping your data secret from unintended listeners [RFC3552]. The growth of the Internet depends on users having confidence that the network protects their personal data [RFC1984]. The possibility of pervasive monitoring and surveillance undermines users' trust and can be mitigated by ensuring confidentiality, i.e., passive attackers should gain little or no information from observation or inference of protocol activity [RFC7258] [RFC7624].

Example: Protocols that do not encrypt their payload make the entire content of the communication available to the idealized attacker along their path. Following the advice in [RFC3365], most such protocols have a secure variant that encrypts the payload for confidentiality, and these secure variants are seeing ever-wider deployment. A noteworthy exception is DNS [RFC1035], as DNSSEC [RFC4033] does not have confidentiality as a requirement. This implies that, in the absence of the use of more recent standards like DNS over TLS [RFC7858] or DNS over HTTPS [RFC8484], all DNS queries and answers generated by the activities of any protocol are available to the attacker. When store-and-forward protocols are used (e.g., SMTP [RFC5321]), intermediaries leave this data subject to observation by an attacker that has compromised these intermediaries, unless the data is encrypted end-to-end by the application-layer

protocol or the implementation uses an encrypted store for this data [RFC7624].

Impacts:

- \* Right to privacy
- \* Right to security

#### 4.13. Security

Question(s): Did you have a look at "Guidelines for Writing RFC Text on Security Considerations" [RFC3552]? Have you found any attacks that are somewhat related to your protocol/specification yet considered out of scope of your document? Would these attacks be pertinent to the human-rights-enabling features of the Internet (as described throughout this document)?

Explanation: Security is not a single monolithic property of a protocol or system but rather a series of related yet somewhat independent properties. Not all of these properties are required for every application. Since communications are carried out by systems and access to systems is through communications channels, security goals obviously interlock, but they can also be independently provided [RFC3552].

Typically, any protocol operating on the Internet can be the target of passive attacks (when the attacker can access and read packets on the network) and active attacks (when an attacker is capable of writing information to the network packets) [RFC3552].

Example: See [RFC3552].

Impacts:

- \* Right to freedom of expression
- \* Right to freedom of assembly and association
- \* Right to non-discrimination
- \* Right to security

#### 4.14. Privacy

Question(s): Did you have a look at the guidelines described in Section 7 of "Privacy Considerations for Internet Protocols" [RFC6973]? Does your protocol maintain the confidentiality of metadata? Could your protocol counter traffic analysis? Does your protocol adhere to data minimization principles? Does your document identify potentially sensitive data logged by your protocol and/or for how long that needs to be retained for technical reasons?

Explanation: Privacy refers to the right of an entity (normally a person), acting on its own behalf, to determine the degree to which it will interact with its environment, including the degree to which the entity is willing to share its personal information with others [RFC4949]. If a protocol provides insufficient privacy protection, it may have a negative impact on freedom of expression as users self-censor for fear of surveillance or find that they are unable to express themselves freely.

Example: See [RFC6973].

Impacts:

- \* Right to freedom of expression
- \* Right to privacy
- \* Right to non-discrimination

#### 4.15. Anonymity and Pseudonymity

Question(s): Does your protocol make use of identifiers? Are these identifiers persistent? Are they used across multiple contexts? Is it possible for the user to reset or rotate them without negatively impacting the operation of the protocol? Are they visible to others besides the protocol endpoints? Are they tied to real-world identities? Have you considered "Privacy Considerations for Internet Protocols" [RFC6973], especially Section 6.1.2?

Explanation: Most protocols depend on the use of some kind of identifier in order to correlate activity over time and space. For instance:

- \* IP addresses are used as an identity for the source and destination for IP datagrams.
- \* QUIC connection identifiers are used to correlate packets belonging to the same connection.
- \* HTTP uses cookies to correlate multiple HTTP requests from the same client.
- \* Email uses email addresses of the form example@example.com to identify senders and receivers.

In general, these identifiers serve a necessary function for protocol operations by allowing them to maintain continuity. However, they can also create privacy risks. There are two major ways in which those risks manifest:

- \* The identifier may itself reveal the user's identity in some way or be tied to an identifier that does, as is the case when E.164 (telephone) numbers are used as identifiers for instant messaging systems.
- \* While the identifier may not reveal the user's identity, it may make it possible to link enough of a user's behavior to threaten their privacy, as is the case with HTTP cookies.

Because identifiers are necessary for protocol operation, true anonymity is very difficult to achieve, but there are practices that promote user privacy even when identifiers are used.

Impacts:

- \* Right to non-discrimination
- \* Right to freedom of expression
- \* Right to political participation
- \* Right to freedom of assembly and association

##### 4.15.1. Pseudonymity

In general, user privacy is better preserved when identifiers are pseudonymous (not tied to a user's real-world identity).

Example: In the development of the IPv6 protocol, it was discussed to

embed a Media Access Control (MAC) address into unique IP addresses. This would make it possible for eavesdroppers and other information collectors to identify when different addresses used in different transactions actually correspond to the same node. This is why standardization efforts like "Temporary Address Extensions for Stateless Address Autoconfiguration in IPv6" [RFC8981] and MAC address randomization [MAC-ADDRESS-RANDOMIZATION] have been pursued.

Note that it is often attractive to try to create a pseudonym from a persistent identifier. This can be very difficult to do correctly in a way that does not allow for recovering the persistent identifiers.

Example: A common practice in web tracking is to "encrypt" email addresses by hashing them, thus allegedly making them "non-personally identifying". However, because hash functions are public operations, it is possible to do a dictionary search for candidate email addresses and recover the original address [Email-hashing].

#### 4.15.2. Unlinkability

Even true pseudonymous identifiers can present a privacy risk if they are used across a wide enough scope. User privacy is better preserved if identifiers have limited scope both in time and space.

Example: An example is the Dynamic Host Configuration Protocol (DHCP) where sending a persistent identifier as the client name was not mandatory but, in practice, done by many implementations before DHCP [RFC7844].

Example: Third-party cookies in HTTP allow trackers to correlate HTTP traffic across sites. This is the foundation of a whole ecosystem of web tracking. Increasingly, web browsers are restricting the use of third-party cookies in order to protect user privacy.

#### 4.16. Censorship Resistance

Question(s): Does your protocol architecture facilitate censorship? Does it include "choke points" that are easy to use for censorship? Does it expose identifiers that can be used to selectively block certain kinds of traffic? Could it be designed to be more censorship resistant? Does your protocol make it apparent or transparent when access to a resource is restricted and why it is restricted?

Explanation: Governments and service providers block or filter content or traffic, often without the knowledge of end users [RFC7754]. For a survey of censorship techniques employed across the world, see [RFC9505], which lays out protocol properties that have been exploited to censor access to information. Censorship resistance refers to the methods and measures to prevent Internet censorship.

Example: The current design of the Web has a number of architectural choke points where it is possible for censors to intervene. These include obtaining the control of the domain name itself, DNS blocking either at the protocol layer or at the resolver, IP address blocking, and blocking at the web server. There has been extensive work on content distribution systems, which are intended to be more censorship resistant; and some, such as BitTorrent, are in wide use. However, these systems may have inferior reliability and performance compared to the Web (e.g., they do not support active content on the server).

Example: Identifiers of content exposed within a protocol might be used to facilitate censorship by allowing the censor to determine which traffic to block. DNS queries, the "host" request header in an HTTP request, and the Server Name Indication (SNI) in a Transport



Layer Security (TLS) ClientHello are all examples of protocol elements that can travel in plaintext and be used by censors to identify what content a user is trying to access [RFC9505]. Protocol mechanisms such as Encrypted ClientHello [TLS-ESNI] or DNS over HTTPS [RFC8484] that encrypt metadata provide some level of resistance to this type of protocol inspection. Full traffic encryption systems, such as Tor <<https://torproject.org>>, can also be used by people to access otherwise censored resources.

Example: As noted above, one way to censor web traffic is to require the server to block it or require ISPs to block requests to the server. In HTTP, denial or restriction of access can be made apparent by the use of status code 451, which allows server operators and intermediaries to operate with greater transparency in circumstances where issues of law or public policy affect their operation [RFC7725]. If a protocol potentially enables censorship, protocol designers should strive towards creating error codes that capture different scenarios (e.g., blocked due to administrative policy, unavailable because of legal requirements, etc.) to minimize ambiguity for end users.

Impacts:

- \* Right to freedom of expression
- \* Right to political participation
- \* Right to participate in cultural life, arts, and science
- \* Right to freedom of assembly and association

#### 4.17. Outcome Transparency

Question(s): Are the intended and foreseen effects of your protocol documented and easily comprehensible? Have you described the central use case(s) for your protocol with a clear description of expected behavior and how it may, or may not, impact other protocols, implementations, user expectations, or behavior? Have you reviewed other protocols that solve similar problems, or made use of similar mechanisms, to see if there are lessons that can be learned from their use and misuse?

Explanation: Certain technical choices may have unintended consequences.

Example: Lack of authenticity may lead to lack of integrity and negative externalities; of which, spam is an example. Lack of data that could be used for billing and accounting can lead to so-called "free" arrangements that obscure the actual costs and distribution of the costs, for example, the barter arrangements that are commonly used for Internet interconnection, and the commercial exploitation of personal data for targeted advertising, which is the most common funding model for the so-called "free" services such as search engines and social networks. Unexpected outcomes might not be technical but rather architectural, social, or economic. Therefore, it is of importance to document the intended outcomes and other possible outcomes that have been considered.

Impacts:

- \* Right to freedom of expression
- \* Right to privacy
- \* Right to freedom of assembly and association

- \* Right to access to information

#### 4.18. Accessibility

Question(s): Is your protocol designed to provide an enabling environment for all? Have you looked at the W3C Web Accessibility Initiative for examples and guidance [W3CAccessibility]?

Explanation: Sometimes in the design of protocols, websites, web technologies, or web tools, barriers are created that exclude people from using the Web. The Internet should be designed to work for all people, whatever their hardware, software, language, culture, location, or physical or mental ability. When the Internet technologies meet this goal, it will be accessible to people with a diverse range of hearing, movement, sight, and cognitive ability [W3CAccessibility].

Example: The HTML protocol as defined in [HTML] specifically requires that every image must have an alt attribute (with a few exceptions) to ensure images are accessible for people who cannot themselves decipher non-text content in web pages.

Another example is the work done in the AVT and AVTCORE Working Groups in the IETF that enables text conversation in multimedia, text telephony, wireless multimedia, and video communications for sign language and lipreading (i.e., [RFC9071]).

Impacts:

- \* Right to non-discrimination
- \* Right to freedom of assembly and association
- \* Right to education
- \* Right to political participation

#### 4.19. Decentralization

Question(s): Can your protocol be implemented without a single point of control? If applicable, can your protocol be deployed in a federated manner? Does your protocol create additional centralized points of control?

Explanation: Decentralization is one of the central technical concepts of the architecture of the Internet and is embraced as such by the IETF [RFC3935]. It refers to the absence or minimization of centralized points of control, a feature that is assumed to make it easy for new users to join and new uses to unfold [Ziewitz]. It also reduces issues surrounding single points of failure and distributes the network such that it continues to function even if one or several nodes are disabled. With the commercialization of the Internet in the early 1990s, there has been a slow move away from decentralization, to the detriment of the technical benefits of having a decentralized Internet. For a more detailed discussion of this topic, please see [Arkko].

Example: The bits traveling the Internet are increasingly susceptible to monitoring and censorship from both governments and ISPs as well as third (malicious) parties. The ability to monitor and censor is further enabled by the increased centralization of the network that creates central infrastructure points that can be tapped into. The creation of peer-to-peer networks and the development of voice-over-IP protocols using peer-to-peer technology in combination with Distributed Hash Table (DHT) for scalability are examples of how protocols can preserve decentralization [Pouwelse].

Impacts:

- \* Right to freedom of expression
- \* Right to freedom of assembly and association

#### 4.20. Remedy

Question(s): Can your protocol facilitate a negatively impacted party's right to remedy without disproportionately impacting other parties' human rights, especially their right to privacy?

Explanation: Providing access to remedy by states and corporations is a part of the UN Guiding Principles on Business and Human Rights [UNGP]. Access to remedy may help victims of human rights violations in seeking justice or allow law enforcement agencies to identify a possible violator. However, current mechanisms in protocols that try to enable "attribution" to individuals impede the exercise of the right to privacy. The former UN Special Rapporteur for Freedom of Expression has also argued that anonymity is an inherent part of freedom of expression [Kaye]. Considering the potential adverse impact of attribution on the right to privacy and freedom of expression, enabling attribution on an individual level is most likely not consistent with human rights.

Example: Adding personally identifiable information to data streams as a means to enable the human right to remedy might help in identifying a violator of human rights and provide access to remedy, but this would disproportionately affect all users right to privacy, anonymous expression, and association. Furthermore, there are some recent advances in enabling abuse detection in end-to-end encrypted messaging systems, which also carry some risk to users' privacy [Messenger-franking] [Hecate].

Impacts:

- \* Right to remedy
- \* Right to security
- \* Right to privacy

#### 4.21. Miscellaneous Considerations

Question(s): Have you considered potential negative consequences (individual or societal) that your protocol or document might have?

Explanation: Publication of a particular RFC under a certain status has consequences. Publication as an Internet Standard as part of the Standards Track may signal to implementers that the specification has a certain level of maturity, operational experience, and consensus. Similarly, publication of a specification as an experimental document not part of the Standards Track would signal to the community that the document "may not be intended to be an Internet Standard, or it may be intended for eventual standardization but not yet ready" for wide deployment [RFC2026]. The extent of the deployment, and consequently its overall impact on end users, may depend on the document status presented in the RFC. See [RFC2026] and updates to it for a fuller explanation.

#### 5. Document Status

This research group document lays out best practices and guidelines for human rights reviews of network protocols, architectures, and other Internet-Drafts and RFCs.

## 6. Security Considerations

Article three of the "Universal Declaration of Human Rights" reads: "Everyone has the right to life, liberty and security of person" [UDHR]. This article underlines the importance of security and its interrelation with human life and liberty; but since human rights are indivisible, interrelated, and interdependent, security is also closely linked to other human rights and freedoms. This document seeks to strengthen human rights, freedoms, and security by relating and translating these concepts to concepts and practices as they are used in Internet protocol and architecture development. The aim of this is to secure human rights and thereby improve the sustainability, usability, and effectiveness of the network. The document seeks to achieve this by providing guidelines as done in Section 3 of this document.

## 7. IANA Considerations

This document has no IANA actions.

## 8. Research Group Information

The discussion list for the IRTF Human Rights Protocol Considerations Research Group is located at the e-mail address:  
<mailto:hrpc@ietf.org>.

Information on the group and information on how to subscribe to the list is at: <<https://www.irtf.org/mailman/listinfo/hrpc>>.

Archives of the list can be found at:  
<<https://mailarchive.ietf.org/arch/browse/hrpc/>>.

## 9. Informative References

[Arkko] Arkko, J., Trammell, B., Nottingham, M., Huitema, C., Thomson, M., Tantsura, J., and N. ten Oever, "Considerations on Internet Consolidation and the Internet Architecture", Work in Progress, Internet-Draft, draft-arkko-iab-internet-consolidation-02, 8 July 2019, <<https://datatracker.ietf.org/doc/html/draft-arkko-iab-internet-consolidation-02>>.

[Email-hashing] Acar, G., Englehardt, S., and A. Narayanan, "Four cents to deanonymize: Companies reverse hashed email addresses", April 2018, <<https://freedom-to-tinker.com/2018/04/09/four-cents-to-deanonymize-companies-reverse-hashed-email-addresses/>>.

[FIArch] Papadimitriou, D., Zahariadis, T., Martinez-Julia, P., Papafili, I., Morreale, V., Torelli, F., Sales, B., and P. Demeester, "Design Principles for the Future Internet Architecture", The Future Internet, pp. 55-67, DOI 10.1007/978-3-642-30241-1\_6, January 2012, <[https://link.springer.com/chapter/10.1007/978-3-642-30241-1\\_6](https://link.springer.com/chapter/10.1007/978-3-642-30241-1_6)>.

[FREAK] University of Michigan, "Tracking the FREAK Attack", Wayback Machine archive, March 2015, <<https://web.archive.org/web/20150304002021/https://freakattack.com/>>.

[Hecate] Issa, R., Alhaddad, N., and M. Varia, "Hecate, Abuse Reporting in Secure Messengers with Sealed Sender", 31st USENIX Security Symposium (USENIX Security 22), pp

- 2335-2352, August 2022,  
<<https://www.usenix.org/conference/usenixsecurity22/presentation/issa>>.
- [Hill] Hill, R., "Partial Catalog of Human Rights Related to ICT Activities", May 2014,  
<<http://www.apig.ch/UNIGE%20Catalog.pdf>>.
- [HR-RT] "IRTF-HRPC / reviews", commit 3f5fbff, December 2020,  
<<https://github.com/IRTF-HRPC/reviews>>.
- [HTML] WHATWG, "HTML Living Standard", August 2024,  
<<https://html.spec.whatwg.org/multipage/>>.
- [HTTPS-interception]  
Durumeric, Z., Ma, Z., Springall, D., Barnes, R., Sullivan, N., Bursztein, E., Bailey, M., Halderman, J., and V. Paxson, "The Security Impact of HTTPS Interception", NDSS Symposium 2017, DOI 10.14722/ndss.2017.23456, February 2017,  
<<https://doi.org/10.14722/ndss.2017.23456>>.
- [ICCPR] United Nations General Assembly, "International Covenant on Civil and Political Rights", December 1966,  
<<https://www.ohchr.org/en/instruments-mechanisms/instruments/international-covenant-civil-and-political-rights>>.
- [ICESCR] United Nations General Assembly, "International Covenant on Economic, Social and Cultural Rights", December 1966,  
<<https://www.ohchr.org/en/instruments-mechanisms/instruments/international-covenant-economic-social-and-cultural-rights>>.
- [IRP] Internet Rights and Principles Dynamic Coalition, "10 Internet Rights & Principles",  
<<https://internetrightsandprinciples.org/campaign/>>.
- [Jorgensen]  
Jrgensen, R. F., "An internet bill of rights", Research Handbook on Governance of the Internet, edited by Ian Brown. Cheltenham: Edward Elgar Publishing, DOI 10.4337/9781849805025.00022, April 2013,  
<<https://doi.org/10.4337/9781849805025.00022>>.
- [Kaye] Kaye, D., "Report of the Special Rapporteur on the Promotion and Protection of the Right to Freedom of Opinion and Expression, David Kaye", A/HRC/29/32, May 2015, <<https://digitallibrary.un.org/record/798709?v=pdf>>.
- [Logjam] Adrian, D., Bhargavan, K., Durumeric, Z., Gaudry, P., Green, M., Halderman, J., Heninger, N., Springall, D., Thom, E., Valenta, L., VanderSloot, B., Wustrow, E., Zanella-Bguelin, S., and P. Zimmerman, "Imperfect Forward Secrecy: How Diffie-Hellman Fails in Practice", CCS '15: Proceedings of the 22nd ACM SIGSAC Conference on Computer and Communications Security, pp 5-17, DOI 10.1145/2810103.2813707, October 2015,  
<<https://doi.org/10.1145/2810103.2813707>>.
- [MAC-ADDRESS-RANDOMIZATION]  
Ziga, J. C., Bernardos, C. J., Ed., and A. Andersdotter, "Randomized and Changing MAC Address State of Affairs", Work in Progress, Internet-Draft, draft-ietf-madinas-mac-address-randomization-15, 15 July 2024,  
<<https://datatracker.ietf.org/doc/html/draft-ietf-madinas->

mac-address-randomization-15>.

[Messenger-franking]

Grubbs, P., Lu, J., and T. Ristenpart, "Message Franking via Committing Authenticated Encryption", Cryptology ePrint Archive, Paper 2017/664, July 2017, <<https://eprint.iacr.org/2017/664>>.

[Newegg]

Mullin, J., "Newegg on trial: Mystery company TQP rewrites the history of encryption", Ars Technica, November 2013, <<https://arstechnica.com/tech-policy/2013/11/newegg-on-trial-mystery-company-tqp-re-writes-the-history-of-encryption/>>.

[Note-well]

IETF, "Note Well", <<https://www.ietf.org/about/note-well/>>.

[Orwat]

Orwat, C. and R. Bless, "Values and Networks: Steps Toward Exploring their Relationships", ACM SIGCOMM Computer Communication Review, vol. 46, no. 2, pp 25-31, DOI 10.1145/2935634.2935640, May 2016, <<https://doi.org/10.1145/2935634.2935640>>.

[Patent-policy]

Weitzner, D., "W3C Patent Policy", W3C Recommendation, February 2004, <<https://www.w3.org/Consortium/Patent-Policy-20040205/>>.

[Penney]

Penney, J., "Chilling Effects: Online Surveillance and Wikipedia Use", Berkeley Technology Law Journal, vol. 31, no. 1, pp 117-182, DOI 10.15779/Z38SS13, September 2016, <[https://papers.ssrn.com/sol3/papers.cfm?abstract\\_id=2769645](https://papers.ssrn.com/sol3/papers.cfm?abstract_id=2769645)>.

[Pouwelse]

Pouwelse, J., Ed., "Media without censorship (CensorFree) scenarios", Work in Progress, Internet-Draft, draft-pouwelse-censorfree-scenarios-02, 22 October 2012, <<https://datatracker.ietf.org/doc/html/draft-pouwelse-censorfree-scenarios-02>>.

[RFC1035]

Mockapetris, P., "Domain names - implementation and specification", STD 13, RFC 1035, DOI 10.17487/RFC1035, November 1987, <<https://www.rfc-editor.org/info/rfc1035>>.

[RFC1958]

Carpenter, B., Ed., "Architectural Principles of the Internet", RFC 1958, DOI 10.17487/RFC1958, June 1996, <<https://www.rfc-editor.org/info/rfc1958>>.

[RFC1984]

IAB and IESG, "IAB and IESG Statement on Cryptographic Technology and the Internet", BCP 200, RFC 1984, DOI 10.17487/RFC1984, August 1996, <<https://www.rfc-editor.org/info/rfc1984>>.

[RFC2026]

Bradner, S., "The Internet Standards Process -- Revision 3", BCP 9, RFC 2026, DOI 10.17487/RFC2026, October 1996, <<https://www.rfc-editor.org/info/rfc2026>>.

[RFC2277]

Alvestrand, H., "IETF Policy on Character Sets and Languages", BCP 18, RFC 2277, DOI 10.17487/RFC2277, January 1998, <<https://www.rfc-editor.org/info/rfc2277>>.

[RFC3365]

Schiller, J., "Strong Security Requirements for Internet Engineering Task Force Standard Protocols", BCP 61, RFC 3365, DOI 10.17487/RFC3365, August 2002, <<https://www.rfc-editor.org/info/rfc3365>>.

- [RFC3552] Rescorla, E. and B. Korver, "Guidelines for Writing RFC Text on Security Considerations", BCP 72, RFC 3552, DOI 10.17487/RFC3552, July 2003, <<https://www.rfc-editor.org/info/rfc3552>>.
- [RFC3724] Kempf, J., Ed., Austein, R., Ed., and IAB, "The Rise of the Middle and the Future of End-to-End: Reflections on the Evolution of the Internet Architecture", RFC 3724, DOI 10.17487/RFC3724, March 2004, <<https://www.rfc-editor.org/info/rfc3724>>.
- [RFC3935] Alvestrand, H., "A Mission Statement for the IETF", BCP 95, RFC 3935, DOI 10.17487/RFC3935, October 2004, <<https://www.rfc-editor.org/info/rfc3935>>.
- [RFC4033] Arends, R., Austein, R., Larson, M., Massey, D., and S. Rose, "DNS Security Introduction and Requirements", RFC 4033, DOI 10.17487/RFC4033, March 2005, <<https://www.rfc-editor.org/info/rfc4033>>.
- [RFC4101] Rescorla, E. and IAB, "Writing Protocol Models", RFC 4101, DOI 10.17487/RFC4101, June 2005, <<https://www.rfc-editor.org/info/rfc4101>>.
- [RFC4949] Shirey, R., "Internet Security Glossary, Version 2", FYI 36, RFC 4949, DOI 10.17487/RFC4949, August 2007, <<https://www.rfc-editor.org/info/rfc4949>>.
- [RFC5321] Klensin, J., "Simple Mail Transfer Protocol", RFC 5321, DOI 10.17487/RFC5321, October 2008, <<https://www.rfc-editor.org/info/rfc5321>>.
- [RFC5646] Phillips, A., Ed. and M. Davis, Ed., "Tags for Identifying Languages", BCP 47, RFC 5646, DOI 10.17487/RFC5646, September 2009, <<https://www.rfc-editor.org/info/rfc5646>>.
- [RFC6108] Chung, C., Kasyanov, A., Livingood, J., Mody, N., and B. Van Lieu, "Comcast's Web Notification System Design", RFC 6108, DOI 10.17487/RFC6108, February 2011, <<https://www.rfc-editor.org/info/rfc6108>>.
- [RFC6365] Hoffman, P. and J. Klensin, "Terminology Used in Internationalization in the IETF", BCP 166, RFC 6365, DOI 10.17487/RFC6365, September 2011, <<https://www.rfc-editor.org/info/rfc6365>>.
- [RFC6701] Farrel, A. and P. Resnick, "Sanctions Available for Application to Violators of IETF IPR Policy", RFC 6701, DOI 10.17487/RFC6701, August 2012, <<https://www.rfc-editor.org/info/rfc6701>>.
- [RFC6973] Cooper, A., Tschofenig, H., Aboba, B., Peterson, J., Morris, J., Hansen, M., and R. Smith, "Privacy Considerations for Internet Protocols", RFC 6973, DOI 10.17487/RFC6973, July 2013, <<https://www.rfc-editor.org/info/rfc6973>>.
- [RFC7258] Farrell, S. and H. Tschofenig, "Pervasive Monitoring Is an Attack", BCP 188, RFC 7258, DOI 10.17487/RFC7258, May 2014, <<https://www.rfc-editor.org/info/rfc7258>>.
- [RFC7301] Friedl, S., Popov, A., Langley, A., and E. Stephan, "Transport Layer Security (TLS) Application-Layer Protocol Negotiation Extension", RFC 7301, DOI 10.17487/RFC7301, July 2014, <<https://www.rfc-editor.org/info/rfc7301>>.

- [RFC7624] Barnes, R., Schneier, B., Jennings, C., Hardie, T., Trammell, B., Huitema, C., and D. Borkmann, "Confidentiality in the Face of Pervasive Surveillance: A Threat Model and Problem Statement", RFC 7624, DOI 10.17487/RFC7624, August 2015, <<https://www.rfc-editor.org/info/rfc7624>>.
- [RFC7725] Bray, T., "An HTTP Status Code to Report Legal Obstacles", RFC 7725, DOI 10.17487/RFC7725, February 2016, <<https://www.rfc-editor.org/info/rfc7725>>.
- [RFC7754] Barnes, R., Cooper, A., Kolkman, O., Thaler, D., and E. Nordmark, "Technical Considerations for Internet Service Blocking and Filtering", RFC 7754, DOI 10.17487/RFC7754, March 2016, <<https://www.rfc-editor.org/info/rfc7754>>.
- [RFC7844] Huitema, C., Mrugalski, T., and S. Krishnan, "Anonymity Profiles for DHCP Clients", RFC 7844, DOI 10.17487/RFC7844, May 2016, <<https://www.rfc-editor.org/info/rfc7844>>.
- [RFC7858] Hu, Z., Zhu, L., Heidemann, J., Mankin, A., Wessels, D., and P. Hoffman, "Specification for DNS over Transport Layer Security (TLS)", RFC 7858, DOI 10.17487/RFC7858, May 2016, <<https://www.rfc-editor.org/info/rfc7858>>.
- [RFC8179] Bradner, S. and J. Contreras, "Intellectual Property Rights in IETF Technology", BCP 79, RFC 8179, DOI 10.17487/RFC8179, May 2017, <<https://www.rfc-editor.org/info/rfc8179>>.
- [RFC8280] ten Oever, N. and C. Cath, "Research into Human Rights Protocol Considerations", RFC 8280, DOI 10.17487/RFC8280, October 2017, <<https://www.rfc-editor.org/info/rfc8280>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.
- [RFC8484] Hoffman, P. and P. McManus, "DNS Queries over HTTPS (DoH)", RFC 8484, DOI 10.17487/RFC8484, October 2018, <<https://www.rfc-editor.org/info/rfc8484>>.
- [RFC8558] Hardie, T., Ed., "Transport Protocol Path Signals", RFC 8558, DOI 10.17487/RFC8558, April 2019, <<https://www.rfc-editor.org/info/rfc8558>>.
- [RFC8890] Nottingham, M., "The Internet is for End Users", RFC 8890, DOI 10.17487/RFC8890, August 2020, <<https://www.rfc-editor.org/info/rfc8890>>.
- [RFC8980] Arkko, J. and T. Hardie, "Report from the IAB Workshop on Design Expectations vs. Deployment Reality in Protocol Development", RFC 8980, DOI 10.17487/RFC8980, February 2021, <<https://www.rfc-editor.org/info/rfc8980>>.
- [RFC8981] Gont, F., Krishnan, S., Narten, T., and R. Draves, "Temporary Address Extensions for Stateless Address Autoconfiguration in IPv6", RFC 8981, DOI 10.17487/RFC8981, February 2021, <<https://www.rfc-editor.org/info/rfc8981>>.
- [RFC9000] Iyengar, J., Ed. and M. Thomson, Ed., "QUIC: A UDP-Based Multiplexed and Secure Transport", RFC 9000, DOI 10.17487/RFC9000, May 2021,



- <<https://www.rfc-editor.org/info/rfc9000>>.
- [RFC9071] Hellstrm, G., "RTP-Mixer Formatting of Multiparty Real-Time Text", RFC 9071, DOI 10.17487/RFC9071, July 2021, <<https://www.rfc-editor.org/info/rfc9071>>.
- [RFC9293] Eddy, W., Ed., "Transmission Control Protocol (TCP)", STD 7, RFC 9293, DOI 10.17487/RFC9293, August 2022, <<https://www.rfc-editor.org/info/rfc9293>>.
- [RFC9420] Barnes, R., Beurdouche, B., Robert, R., Millican, J., Omara, E., and K. Cohn-Gordon, "The Messaging Layer Security (MLS) Protocol", RFC 9420, DOI 10.17487/RFC9420, July 2023, <<https://www.rfc-editor.org/info/rfc9420>>.
- [RFC9505] Hall, J. L., Aaron, M. D., Andersdotter, A., Jones, B., Feamster, N., and M. Knodel, "A Survey of Worldwide Censorship Techniques", RFC 9505, DOI 10.17487/RFC9505, November 2023, <<https://www.rfc-editor.org/info/rfc9505>>.
- [Saltzer] Saltzer, J. H., Reed, D. P., and D. D. Clark, "End-to-end arguments in system design", ACM Transactions on Computer Systems, vol. 2, no. 4, pp 277-288, DOI 10.1145/357401.357402, November 1984, <<https://doi.org/10.1145/357401.357402>>.
- [TLS-ESNI] Rescorla, E., Oku, K., Sullivan, N., and C. A. Wood, "TLS Encrypted Client Hello", Work in Progress, Internet-Draft, draft-ietf-tls-esni-20, 4 August 2024, <<https://datatracker.ietf.org/doc/html/draft-ietf-tls-esni-20>>.
- [UDHR] United Nations General Assembly, "Universal Declaration of Human Rights", December 1948, <<https://www.un.org/en/about-us/universal-declaration-of-human-rights>>.
- [UNGP] United Nations, "Guiding Principles on Business and Human Rights: Implementing the United Nations 'Protect, Respect and Remedy' Framework", January 2012, <<https://www.ohchr.org/en/publications/reference-publications/guiding-principles-business-and-human-rights>>.
- [UNHR] United Nations, "The Core International Human Rights Instruments and their monitoring bodies", <<https://www.ohchr.org/en/core-international-human-rights-instruments-and-their-monitoring-bodies>>.
- [UNHRC2016] United Nations Human Rights Council, "The promotion, protection and enjoyment of human rights on the Internet", A/HRC/32/L.20, June 2016, <<https://digitallibrary.un.org/record/845728?ln=en>>.
- [W3CAccessibility] W3C, "Accessibility", <<https://www.w3.org/standards/webdesign/accessibility>>.
- [W3Ci18nDef] Ishida, R. and S. Miller, "Localization vs. Internationalization", December 2005, <<https://www.w3.org/International/questions/qa-il8n.en>>.
- [Ziewitz] Ziewitz, M. and I. Brown, "A Prehistory of Internet Governance", Research Handbook on Governance of the Internet, edited by Ian Brown. Cheltenham: Edward Elgar

Publishing, DOI 10.4337/9781849805025.00008, April 2013,  
<<https://doi.org/10.4337/9781849805025.00008>>.

[Zittrain] Zittrain, J., "The Future of the Internet and How to Stop It", Yale University Press, 2008,  
<<https://dash.harvard.edu/handle/1/4455262>>.

#### Acknowledgements

Thanks to:

- \* Corinne Cath-Speth for work on [RFC8280].
- \* Reese Enghardt, Joe Hall, Avri Doria, Joey Salazar, Corinne Cath-Speth, Farzaneh Badii, Sandra Braman, Colin Perkins, John Curran, Eliot Lear, Mallory Knodel, Brian Trammell, Jane Coffin, Eric Rescorla, Sofa Celi, and the hrpc list for reviews and suggestions.
- \* Individuals who conducted human rights reviews for their work and feedback: Amelia Andersdotter, Shane Kerr, Beatrice Martini, Karan Saini, and Shivan Kaul Sahib.

#### Authors' Addresses

Gurshabad Grover  
Email: [gurshabad@cis-india.org](mailto:gurshabad@cis-india.org)

Niels ten Oever  
University of Amsterdam  
Email: [mail@nielstenoever.net](mailto:mail@nielstenoever.net)